

## < Exam Reference Sheet > - DSA8640

### Algebraic expressions

Usage	Explanation
<code>a + b</code>	sum of a and b
<code>a - b</code>	difference of a and b
<code>a * b</code>	product of a and b
<code>a / b</code>	quotient of a and b
<code>a ** b</code>	a to the b power
<code>a // b</code>	quotient from floor division of a and b
<code>a % b</code>	remainder of a / b

### Boolean expressions

Usage	Explanation
<code>a &lt; b</code>	a is smaller than b
<code>a &lt;= b</code>	a is smaller than or equal to b
<code>a &gt; b</code>	a is bigger than b
<code>a &gt;= b</code>	a is bigger than or equal to b
<code>a == b</code>	a is equal to b
<code>a != b</code>	a is not equal to b

### String operators, functions, and methods

Usage	Explanation
<code>x in s</code>	<code>x</code> is a substring of <code>s</code>
<code>x not in s</code>	<code>x</code> is not a substring of <code>s</code>
<code>s + t</code>	Concatenation of <code>s</code> and <code>t</code>
<code>s * n, n * s</code>	Concatenation of <code>n</code> copies of <code>s</code>
<code>s[i]</code>	Character at index <code>i</code> of <code>s</code>
<code>len(s)</code>	(function) Length of string <code>s</code>

`s[i:j]` : the slice of `s` starting at index `i` and ending **before** index `j`

`s[i:]` : the slice of `s` starting at index `i`

`s[:j]` : the slice of `s` ending **before** index `j`

Usage	Explanation
<code>s.capitalize()</code>	returns a copy of <code>s</code> with first character capitalized
<code>s.count(target)</code>	returns the number of occurrences of <code>target</code> in <code>s</code>
<code>s.find(target)</code>	returns the index of the first occurrence of <code>target</code> in <code>s</code>
<code>s.lower()</code>	returns lowercase copy of <code>s</code>
<code>s.upper()</code>	returns uppercase copy of <code>s</code>
<code>s.split(sep)</code>	returns list of substrings of <code>s</code> , delimited by <code>sep</code>

### List operators, functions, and methods

Usage	Explanation
<code>x in lst</code>	<code>x</code> is an item of <code>lst</code>
<code>x not in lst</code>	<code>x</code> is not an item of <code>lst</code>
<code>lst + lstB</code>	Concatenation of <code>lst</code> and <code>lstB</code>
<code>lst*n, n*lst</code>	Concatenation of <code>n</code> copies of <code>lst</code>
<code>lst[i]</code>	Item at index <code>i</code> of <code>lst</code>
<code>len(lst)</code>	Number of items in <code>lst</code>
<code>min(lst)</code>	Minimum item in <code>lst</code>
<code>max(lst)</code>	Maximum item in <code>lst</code>
<code>sum(lst)</code>	Sum of items in <code>lst</code>

Usage	Explanation
<code>lst.append(item)</code>	adds item to the end of <code>lst</code>
<code>lst.count(item)</code>	returns the number of times item occurs in <code>lst</code>
<code>lst.index(item)</code>	Returns index of (first occurrence of) item in <code>lst</code>
<code>lst.pop()</code>	Removes and returns the last item in <code>lst</code>
<code>lst.remove(item)</code>	Removes (the first occurrence of) item from <code>lst</code>
<code>lst.reverse()</code>	Reverses the order of items in <code>lst</code>
<code>lst.sort()</code>	Sorts the items of <code>lst</code> in increasing order

## Operator precedence

	Operator
	[...]
	<code>x[]</code>
	**
	+ <code>x</code> , - <code>x</code>
	*, /, //, %
	+, -
	in, not in
	<, >, <=, >=, ==, !=
	not <code>x</code>
	and
	or

higher precedence ↑

↓ lower precedence

24

## Import a module

```
import <module>
```

### One-way if statement syntax

```
if <condition>:  
    <indented code block>  
<non-indented statement>
```

### Two-way if statement syntax

```
if <condition>:  
    <indented code block 1>  
else:  
    <indented code block 2>  
<non-indented statement>
```

### Multi-way if statement syntax

```
If <condition>:  
    <indented code block 1>  
elif <condition2>:  
    <indented code block 2>  
else:  
    <indented code block 3>  
<non-indented statement>
```

### for loop syntax

```
for <variable> in <sequence>:  
    <indented code block >  
<non-indented code block>
```

### while loop syntax

```
while <condition>:  
    <indented code block>  
<non-indented statement>
```

### function definition syntax

```
def <function name> (<0 or more variables>):  
    <indented function body>
```

## range() function

- To iterate over the n numbers 0, 1, 2, ..., n-1  
for i in range(n):
- To iterate over the range j, j+1, j+2, ..., n-1  
for i in range(j, n):
- To iterate over the range with step c: j, j+c, j+2c, j+3c, ..., n-1  
for i in range(j, n, c):

## File modes

The file mode defines how the file will be accessed

Mode	Description
r	Reading (default)
w	Writing (if file exists, content is <b>wiped</b> )
a	Append (if file exists, writes are <b>appended</b> )
r+	Reading and Writing
t	Text (default)
b	Binary

## File methods

Usage	Description
<u>infile.read(n)</u>	Read <u>n</u> characters starting from <b>cursor</b> ; if fewer than <u>n</u> characters remain, read until the end of file
<u>infile.read()</u>	Read starting from <b>cursor</b> up to the end of the file
<u>infile.readline()</u>	Read starting from <b>cursor</b> up to, and including, the end of line character
<u>infile.readlines()</u>	Read starting from <b>cursor</b> up to the end of the file <b>and return list of lines</b>
<u>outfile.write(s)</u>	Write string <u>s</u> to file <u>outfile</u> starting from <b>cursor</b>
<u>infile.close(n)</u>	Close file <u>infile</u>

20

## format method of class str

```
print('{}'.format(<variable>))
```

## Dictionary methods

Operation	Explanation
d.items()	Returns a view of the (key, value) pairs in d
d.keys()	Returns a view of the keys of d
d.pop(key)	Removes the (key, value) pair with key key from d and returns the value
d.update(d2)	Adds the (key, value) pairs of dictionary d2 to d
d.values()	Returns a view of the values of d

## Module random

random.randrange() : takes a pair of integers a and b, and returns some number between a and b-1

random.uniform(): takes two numbers a and b, and returns a float number x such that  $a \leq x \leq b$

random.shuffle(): shuffles, or permutes, the objects in a sequence

random.choice(): allows us to choose an item from a container uniformly at random

random.sample(): takes an input the container and an integer k, and returns a list of k items in the container