Deep Generative Models

Ava Soleimany

MIT 6.S191

January 21, 2021

Which face is real?

A

B

C

Supervised vs unsupervised learning

Supervised Learning

Data: (x, y)
x is data, y is label

Goal: Learn function to map
$$x \rightarrow y$$

Examples: Classification, regression, object detection, semantic segmentation, etc.

Unsupervised Learning

Data: x
x is data, no labels!

Goal: Learn some *hidden* or *underlying structure* of the data

Examples: Clustering, feature or dimensionality reduction, etc.

MIT 6.S191

Supervised vs unsupervised learning

Supervised Learning

Data: (x, y)
x is data, y is label

Goal: Learn function to map
$$x \rightarrow y$$

Examples: Classification, regression, object detection, semantic segmentation, etc.

Unsupervised Learning

Data: x
x is data, no labels!

Goal: Learn the *hidden* or *underlying structure* of the data

Examples: Clustering, feature or dimensionality reduction, etc.

MIT 6.S191

Generative modeling

Goal: Take as input training samples from some distribution and learn a model that represents that distribution

Density Estimation



Sample Generation

Input samples

Training data $\sim P_{data}(x)$



Generated samples

Generated $\sim P_{model}(x)$

How can we learn $P_{model}(x)$ similar to $P_{data}(x)$?

MIT 6.S191

Why generative models? Debiasing

Capable of uncovering **underlying features** in a dataset

VS

Homogeneous skin color, pose

Diverse skin color, pose, illumination

How can we use this information to create fair and representative datasets?

6.S191 Lab

Why generative models? Outlier detection

- **Problem:** How can we detect when we encounter something new or rare?
- **Strategy:** Leverage generative models, detect outliers in the distribution
- Use outliers during training to improve even more!

95% of Driving Data:
(1) sunny, (2) highway, (3) straight road

Detect outliers to avoid unpredictable behavior when training

Edge Cases

Harsh Weather



Pedestrians

MIT 6.S191

Latent variable models

Autoencoders and Variational Autoencoders (VAEs)



Generative Adversarial Networks (GANs)



MIT 6.S191

What is a latent variable?

Myth of the Cave

What is a latent variable?

Can we learn the **true explanatory factors**, e.g. latent variables, from only observed data?

Autoencoders

MIT 6.S191

Autoencoders: background

Unsupervised approach for learning a **lower-dimensional** feature representation from unlabeled training data



Why do we care about a low-dimensional z?

"Encoder" learns mapping from the data, x, to a low-dimensional latent space, z

MIT 6.S191

Autoencoders: background

How can we learn this latent space?
Train the model to use these features to **reconstruct the original data**



"Decoder" learns mapping back from latent space, z,
to a reconstructed observation, $\hat{x}$

MIT 6.S191

Autoencoders: background

How can we learn this latent space?

Train the model to use these features to **reconstruct the original data**



$$\mathcal{L}(x, \hat{x}) = \|x - \hat{x}\|^2$$

Loss function doesn't use any labels!!

MIT 6.S191

Autoencoders: background

How can we learn this latent space?

Train the model to use these features to **reconstruct the original data**



$$\mathcal{L}(x, \hat{x}) = \|x - \hat{x}\|^2$$

Loss function doesn't use any labels!!

MIT 6.S191

Dimensionality of latent space → reconstruction quality

Autoencoding is a form of compression!
Smaller latent space will force a larger training bottleneck

2D latent space

5D latent space

Ground Truth

Autoencoders for representation learning

Bottleneck hidden layer forces network to learn a compressed latent representation

Reconstruction loss forces the latent representation to capture (or encode) as much "information" about the data as possible

Autoencoding = **Auto**matically **encoding** data

MIT 6.S191

Variational Autoencoders (VAEs)

MIT 6.S191

Traditional autoencoders



MIT 6.S191

VAEs: key difference with traditional autoencoder



MIT 6.S191

VAEs: key difference with traditional autoencoder



The VAE autoencoder learns the man and the variance of the laten variable

Variational autoencoders are a probabilistic twist on autoencoders!

Sample from the mean and standard deviation to compute latent sample

VAE optimization



Encoder computes: $q_\phi(\mathrm{z}|x)$ Decoder computes: $p_\theta(\mathrm{x}|z)$

Tries to learn the probability distribution of the latent variable z given the input x

MIT 6.S191

VAE optimization



$$\mathcal{L}(\phi, \theta, x) = (\text{reconstruction loss}) + (\text{regularization term})$$

New term

MIT 6.S191

VAE optimization



$$\mathcal{L}(\phi, \theta, x) = \text{(reconstruction loss)} + \text{(regularization term)}$$

MIT 6.S191

VAE optimization



$$\mathcal{L}(\phi, \theta, x) = \boxed{\text{(reconstruction loss)}} + \text{(regularization term)}$$

MIT 6.S191

VAE optimization



$$\mathcal{L}(\phi, \theta, x) = \text{(reconstruction loss)} + \boxed{\text{(regularization term)}}$$

MIT 6.S191

Priors on the latent distribution

$$D\left(q_\phi(z|x) \parallel p(z)\right)$$

Inferred latent distribution

Fixed prior on latent distribution



Common choice of prior – Normal Gaussian:

$$p(z) = \mathcal{N}(\mu = 0, \sigma^2 = 1)$$

- Encourages encodings to distribute encodings evenly around the center of the latent space
- Penalize the network when it tries to "cheat" by clustering points in specific regions (i.e., by memorizing the data)

Priors on the latent distribution

$$D\left(q_\phi(z|x) \parallel p(z)\right)$$

$$= -\frac{1}{2}\sum_{j=0}^{k-1}\left(\sigma_j + \mu_j^2 - 1 - \log\sigma_j\right)$$

KL-divergence between the two distributions



Common choice of prior – Normal Gaussian:

$$p(z) = \mathcal{N}(\mu = 0, \sigma^2 = 1)$$

- Encourages encodings to distribute encodings evenly around the center of the latent space
- Penalize the network when it tries to "cheat" by clustering points in specific regions (i.e., by memorizing the data)

Intuition on regularization and the Normal prior

What properties do we want to achieve from regularization?

1. **Continuity:** points that are close in latent space → similar content after decoding
2. **Completeness:** sampling from latent space → "meaningful" content after decoding



MIT 6.S191

Intuition on regularization and the Normal prior

1. **Continuity**: points that are close in latent space → similar content after decoding
2. **Completeness:** sampling from latent space → "meaningful" content after decoding

Encoding as a distribution does not guarantee these properties!

Small variances → Pointed distributions

Different means → Discontinuities

Not regularized

Normal prior → continuity + completeness

Center means
Regularize variances

Regularized

Remember that the loss function includes a reconstruction term and a regularization term

Intuition on regularization and the Normal prior

1. **Continuity**: points that are close in latent space → similar content after decoding
2. **Completeness:** sampling from latent space → "meaningful" content after decoding



Note that there is a trade-off between reconstruction and regularisation

Regularization with Normal prior helps enforce **information gradient** in the latent space.

VAE computation graph



Encoder computes: $q_\phi(\mathbf{z}|x)$

Decoder computes: $p_\theta(\mathbf{x}|z)$

$$\mathcal{L}(\phi, \theta, x) = \text{(reconstruction loss)} + \text{(regularization term)}$$

MIT 6.S191

VAE computation graph

Problem: We cannot backpropagate gradients through sampling layers!

The layers with stochastic variables, back propagation requires deterministic nodes, deterministic layers



Encoder computes: $q_\phi(\mathbf{z}|x)$

Decoder computes: $p_\theta(\mathbf{x}|z)$

$$\mathcal{L}(\phi, \theta, x) = \text{(reconstruction loss)} + \text{(regularization term)}$$

MIT 6.S191

Reparametrizing the sampling layer



Key Idea:

$$\cancel{z \sim \mathcal{N}(\mu, \sigma^2)}$$

Consider the sampled latent vector z as a sum of

- a fixed μ vector,
- and fixed σ vector, scaled by random constants drawn from the prior distribution

$$\Rightarrow z = \mu + \sigma \odot \varepsilon$$

where $\varepsilon \sim \mathcal{N}(0,1)$

MIT 6.S191

Reparametrizing the sampling layer



Original form

MIT 6.S191

Reparametrizing the sampling layer



Original form

Reparametrized form

MIT 6.S191

VAEs: Latent perturbation

Slowly increase or decrease a **single latent variable**
Keep all other variables fixed

Head pose

Different dimensions of z encodes **different interpretable latent features**

MIT 6.S191

VAEs: Latent perturbation



Ideally, we want latent variables that are uncorrelated with each other

Enforce diagonal prior on the latent variables to encourage independence

Disentanglement

Latent space disentanglement with β-VAEs

β-VAE loss:

$$\mathcal{L}(\theta, \phi; \mathbf{x}, \mathbf{z}, \beta) = \underbrace{\mathbb{E}_{q_\phi(\mathbf{z}|\mathbf{x})}[\log p_\theta(\mathbf{x}|\mathbf{z})]}_{\text{Reconstruction term}} - \boxed{\beta}\, \underbrace{D_{KL}(q_\phi(\mathbf{z}|\mathbf{x}) \parallel p(\mathbf{z}))}_{\text{Regularization term}}$$

β > 1: constrain latent bottleneck, encourage efficient latent encoding → disentanglement

Head rotation (azimuth)

Smile also changing!

Standard VAE (β = 1)



β-VAE (β = 250)

Smile relatively constant!

Why latent variable models? Debiasing

Capable of uncovering **underlying latent variables** in a dataset

VS

Homogeneous skin color, pose

Diverse skin color, pose, illumination

When the latent variables are well defined, and are independent, we can see if the training is biased as some regions will be underrepresented

How can we use latent distributions to create fair and representative datasets?

6.S191 Lab

VAE summary

1. Compress representation of world to something we can use to learn



MIT 6.S191

VAE summary

1. Compress representation of world to something we can use to learn
2. Reconstruction allows for unsupervised learning (no labels!)



MIT 6.S191

VAE summary

1. Compress representation of world to something we can use to learn
2. Reconstruction allows for unsupervised learning (no labels!)
3. Reparameterization trick to train end-to-end



MIT 6.S191

VAE summary

1. Compress representation of world to something we can use to learn
2. Reconstruction allows for unsupervised learning (no labels!)
3. Reparameterization trick to train end-to-end
4. Interpret hidden latent variables using perturbation



MIT 6.S191

VAE summary

1. Compress representation of world to something we can use to learn
2. Reconstruction allows for unsupervised learning (no labels!)
3. Reparameterization trick to train end-to-end
4. Interpret hidden latent variables using perturbation
5. Generating new examples



MIT 6.S191

Generative Adversarial Networks (GANs)

MIT 6.S191

What if we just want to sample?

Idea: don't explicitly model density, and instead just sample to generate new instances.

Problem: want to sample from complex distribution – can't do this directly!

Solution: sample from something simple (e.g., noise), learn a transformation to the data distribution.



MIT 6.S191

Generative Adversarial Networks (GANs)

Generative Adversarial Networks (GANs) are a way to make a generative model by having two neural networks compete with each other.

The **discriminator** tries to identify real data from fakes created by the generator.

The **generator** turns noise into an imitation of the data to try to trick the discriminator.



MIT 6.S191

Intuition behind GANs

Generator starts from noise to try to create an imitation of the data.



MIT 6.S191

Intuition behind GANs

Discriminator looks at both real data and fake data created by the generator.

Discriminator

Generator

Fake data

MIT 6.S191

Intuition behind GANs

Discriminator looks at both real data and fake data created by the generator.

Discriminator

Generator

Real data

Fake data

MIT 6.S191

Intuition behind GANs

Discriminator tries to predict what's real and what's fake.



MIT 6.S191

Intuition behind GANs

Discriminator tries to predict what's real and what's fake.



MIT 6.S191

Intuition behind GANs

Discriminator tries to predict what's real and what's fake.



MIT 6.S191

Intuition behind GANs

Discriminator tries to predict what's real and what's fake.



MIT 6.S191

Intuition behind GANs

Generator tries to improve its imitation of the data.



MIT 6.S191

Intuition behind GANs

Generator tries to improve its imitation of the data.



MIT 6.S191

Intuition behind GANs

Generator tries to improve its imitation of the data.



MIT 6.S191

Intuition behind GANs

Discriminator tries to predict what's real and what's fake.



MIT 6.S191

Intuition behind GANs

Discriminator tries to predict what's real and what's fake.



MIT 6.S191

Intuition behind GANs

Discriminator tries to predict what's real and what's fake.



MIT 6.S191

Intuition behind GANs

Discriminator tries to predict what's real and what's fake.



MIT 6.S191

Intuition behind GANs

Generator tries to improve its imitation of the data.



MIT 6.S191

Intuition behind GANs

Generator tries to improve its imitation of the data.



MIT 6.S191

Intuition behind GANs

Generator tries to improve its imitation of the data.



MIT 6.S191

Intuition behind GANs

Discriminator tries to identify real data from fakes created by the generator.
Generator tries to create imitations of data to trick the discriminator.



MIT 6.S191

Training GANs

D tries to identify the synthesized instances

G tries to synthesize fake instances that fool **D**



Training: adversarial objectives for **D** and **G**

Global optimum: G reproduces the true data distribution

Training GANs: loss function



D tries to identify the synthesized images

Discriminators output on generators output

Generators output

Distriminator estimate that a real instance is fake

$$\underbrace{\arg\max_{D}}\ \mathbb{E}_{\mathbf{z},\mathbf{x}}\Big[\ \underbrace{\log D(G(\mathbf{z}))}_{\textbf{Fake}} + \underbrace{\log\left(1 - D(\mathbf{x})\right)}_{\textbf{Real}}\ \Big]$$

Training GANs: loss function

G tries to synthesize fake images that fool **D**



$$\arg\min_{G} \mathbb{E}_{\mathbf{z},\mathbf{x}}[\, \log D(G(\mathbf{z})) + \log(1 - D(\mathbf{x}))\,]$$

Training GANs: loss function



G tries to synthesize fake images that fool the *best* **D**

$$\arg\min_{G}\max_{D}\ \mathbb{E}_{\mathbf{z},\mathbf{x}}[\ \log D(G(\mathbf{z})) + \log\left(1 - D(\mathbf{x})\right)\ ]$$

MIT 6.S191

Generating new data with GANs



After training, use generator network to create **new data** that's never been seen before.

GANs are distribution transformers



MIT 6.S191

GANs are distribution transformers



MIT 6.S191

GANs are distribution transformers



GANs: Recent Advances

MIT 6.S191

Progressive growing of GANs



MIT 6.S191

Karras+ *ICLR* 2018; Karras+ *arXiv* 2019.

Progressive growing of GANs: results

Karras+ *ICLR* 2018.

StyleGAN(2): progressive growing + style transfer





GANs for image synthesis: latest results

Karras+ *arXiv* 2019.

GANs for image synthesis: latest results

Karras+ *arXiv* 2019.

Conditional GANs

What if we want to control the nature of the output, by **conditioning** on a label?



MIT 6.S191

Conditional GANs and pix2pix: paired translation



The discriminator, D, classifies between fake and real **pairs**.
The generator, G, learns to fool the discriminator.

MIT 6.S191

Applications of paired translation

Labels to Street Scene



input output

MIT 6.S191

Paired translation: results

Map → Aerial View

input **output**

Aerial View → Map

input **output**

Paired translation: coloring from edges

MIT 6.S191

Isola+ *CVPR* 2017; Bertrand Gondouin, Twitter.

CycleGAN: domain transformation

CycleGAN learns transformations across domains with unpaired data.



Zhu+ *ICCV* 2017. 1/21/21

Distribution transformations

GANs:

Gaussian noise

$z \sim N(0,1)$



Gaussian noise → target data manifold

CycleGANs:



data manifold X → data manifold Y

MIT 6.S191

CycleGAN: transforming speech




Original (Amini)
Synthesized (Obama)
CANNYA
0:02.560
0:02.571

Deep Generative Modeling: Summary

Autoencoders and Variational Autoencoders (VAEs)

Learn lower-dimensional **latent space** and **sample** to generate input reconstructions



Generative Adversarial Networks (GANs)

Competing **generator** and **discriminator** networks



MIT 6.S191

6.S191: Introduction to Deep Learning

Lab 2: Computer Vision

Link to download labs:
http://introtodeeplearning.com#schedule

1. Open the lab in Google Colab
2. Start executing code blocks and filling in the #TODOs
3. Need help? Come to the class Gather.Town!