

Implementation and Analysis of a Web Request Pipelining Framework

For a degree of Master of Science in Computer Science
at Southern Connecticut State University

Sean P. Kenny

Thesis Advisor: Dr. Hrvoje Podnar

October 2012

Abstract

This project intends to improve upon the current HTTP based web request and response system utilized by modern web browsers and servers today. This improvement will be made possible through the creation of a software HTTP web request pipelining framework named OpenPipe. The OpenPipe framework will attempt to increase the perceived speed of web content delivery through the optimization of communication sequences that occur during a standard HTTP web request cycle. The OpenPipe framework will be provided as a PHP library for Apache based web servers, and a client side cross-browser JavaScript library. The existence of this library will allow for a greater level of transparency to web developers whom wish to provide advanced HTTP request pipelining to their web sites and web application in a more pluggable way, that can be extended to integrate with new and existing web based MVC frameworks. Once this library has been developed the final stage of this project will be to collect, analyze, and compare data for non-pipelined and pipelined web pages. The overall goal of this analysis will be to provide a clear picture of where the performance benefits occur when utilizing an HTTP request pipelining framework that OpenPipe provides.

To my daughters, Paige and Jocelyn - for inspiration I will cherish always.

*To my wife, Kim - who's selfless love, support, and encouragement has
allowed me to fulfill new dreams and goals I never would have been able to
imagine without her.*

Contents

1	Introduction	1
2	Implementation and Analysis Tools	6
2.1	Git	6
2.2	PHP	7
2.3	phpDocumentor	7
2.4	Apache	8
2.5	FireFox	8
2.6	CodeIgniter	9
2.7	Selenium	9
3	Test Applications	11
3.1	Static Sample App	11
3.2	Basic Pipeline	13
3.2.1	MVC Pipeline (PVC)	14
4	Architectural Components	16
4.1	Server components	16
4.2	Client components	17

5	Pipelets	19
5.1	The Root Pipelet	19
5.2	Nested Pipelets	22
5.3	Pipelet Priority	24
6	Class Interfaces	25
6.1	Output	26
6.2	Framework Adapter	28
7	Design Patterns	30
7.1	Strategy Pattern	30
7.2	Factory Pattern	31
8	Sequence Diagrams	33
8.1	Server	33
8.2	Client	35
9	Data Objects	39
9.1	Transmitted Data	39
10	Other Library Components	41
10.1	PHP Output Buffering	41
10.2	Dynamic JavaScript DOM Insertion	42
11	Methodology	44
11.1	Data Collection	44
11.2	Simulating Load	47
12	Results	48

13 Discussion	53
13.1 Expanded Output API	53
13.2 Minification	54
13.3 Addition of framework adapters	54
13.4 Language agnostic Apache server extension	55
14 Code Listings	56

List of Figures

1.1	Layers of the Open Systems Interconnection model (OSI model). Open-Pipe resides in the application level of the OSI model.	3
1.2	Comparison of a traditional HTTP web request with the operation of an HTTP web request Pipeline. A pipeline approach will deliver visible content sooner, as all parts of the document are delivered in parallel.	5
3.1	Feature rich OpenPipe sample application to illustrate nested pipelines . .	12
3.2	Basic OpenPipe sample application to illustrate a basic pipelines	13
3.3	OpenPipe adapter setup for CodeIgniter	15
4.1	Server side technology stack with OpenPipe components	17
4.2	Client side technology stack with OpenPipe components	18
5.1	Sample pipelet containing HTML, CSS, and JavaScript	19
5.2	Root pipelet HTML	20
5.3	Root pipelet layout	21
5.4	Nested Pipelets with a depth of 3	23
5.5	Sample pipelet containing HTML, CSS, and JavaScript	24
6.1	A generalization of the OpenPipe output object	26
6.2	A generalization of the OpenPipe adapter object	28

7.1	The strategy pattern utilized by OpenPipe for the main OpenPipe runner object	31
7.2	Instantiation and running of an OpenPipe.Runner object	31
7.3	The factory pattern utilized by OpenPipe	32
8.1	OpenPipe Runner sequence diagram	35
8.2	OpenPipe output sequence diagram	37
8.3	OpenPipe client side pipelet load calls	38
9.1	The client segment data object	40
10.1	PHP function that helps bypass PHP output buffering that blocks the HTTP pipelining of data to the client browser	42
10.2	JavaScript code segment that allows for reliable cross browser insertion of dynamic JavaScript code into the DOM	43
11.1	A selenium script that retrieves performance and timing data from websites	45
11.2	DOM performance timing data made available via JavaScript [5]	46
11.3	DOM performance timing data show as linear request [5]	47
12.1	Calculated response and load time in milliseconds. Data is based on timing data collected from automated browser runs via Selenium scripting.	50
12.2	OpenPipe column chart comparing non-piped vs. piped response times and total load times for plain HTML data	50
12.3	OpenPipe column chart comparing non-piped vs. piped response times and total load times when connecting to a local database system for data .	51
12.4	OpenPipe column chart comparing non-piped vs. piped response times and total load times when connecting to an external REST API for data . .	52

13.1 An explicit version of an OpenPipe output API	54
--	----

Chapter 1

Introduction

Modern web sites and web applications provide valuable information and services to an ever growing web audience. One of the most important requirements of web sites and web applications trying to deliver this important content is speed. Increased speed of a website can often determine an end user's perception of overall quality and value of a web-based service. Fast and responsive sites will be more likely to achieve higher monthly page views, adoption rates, and overall success

If speed is recognized as a critical factor for today's web then the current HTTP protocol used to deliver this web content should be examined as the source of a possible bottleneck when trying to deliver it. Web content has become increasingly more dynamic and interactive over the last ten years, and this current standard for web content delivery can be tailored for meeting the current pressures of the modern web.

Since the introduction of HTTP, web developers have built an ever-growing repertoire of tips and tricks to squeeze the most out of the HTTP-based web. These methods include, but are not limited to the following [9]:

- Use a content delivery network
- Add an Expires header (HTTP 1.1)

- Gzip components
- Put CSS at the top of the page
- Avoid CSS expressions
- Reduce DNS lookups
- Minify JS
- Avoid redirects
- Remove duplicate scripts
- Turn off ETags
- Make AJAX cacheable and small

Today's web sites and web applications employ many of these techniques to help deliver content to end-users in an efficient manner. HTTP Pipelining is another technique that could be employed alongside any of these methods to increase web performance.

The HTTP protocol is part of the application layer of the OSI model [see figure 1]. When an HTTP request is issued from a web browser for an initial HTML document, related elements such as images, JavaScript, and Cascading Style Sheet (CSS) are subsequently retrieved using additional HTTP requests. Therefore, the rendering of a single web page could involve many HTTP web requests. An HTTP pipeline is presented as a thin layer of application logic on top of HTTP which attempts to optimize the request cycle in a manner that allow pieces of a full web page to load and display independently. This added layer is developed as a software library containing both server-side and client-side application code.




Figure 1.1: Layers of the Open Systems Interconnection model (OSI model). OpenPipe resides in the application level of the OSI model.

The resulting framework processes, requests, and delivers responses in an optimized manner taking into account current HTTP limitations that are inherent to the overhead created by the connect and request style of communication. The result of this response optimization through a pipeline is an increase in perceived speed that is accomplished by displaying fully functional content as quickly as possible – even before the entire document is completely processed by the web server.

HTTP pipelining is inspired from traditional pipelining technologies utilized by today's modern CPU's, where an instruction's life cycle is broken into multiple stages. Instead of instructions, HTTP pipelining breaks the page generation process into several stages [see figure 1] which include [1]:

1. Request parsing: web server parses and sanity checks the HTTP request.

2. Data fetching: web server fetches data from storage tier.
3. Markup generation: web server generates HTML markup for the response.
4. Network transport: the response is transferred from web server to browser.
5. CSS downloading: browser downloads CSS required by the page.
6. DOM tree construction and CSS styling: browser constructs DOM tree of the document, and then applies CSS rules on it.
7. JavaScript downloading: browser downloads JavaScript resources referenced by the page.
8. JavaScript execution: browser executes JavaScript code of the page.




Figure 1.2: Comparison of a traditional HTTP web request with the operation of an HTTP web request Pipeline. A pipeline approach will deliver visible content sooner, as all parts of the document are delivered in parallel.

Chapter 2

Implementation and Analysis Tools

2.1 Git



The OpenPipe project makes use of Git to store the current codebase, examples, documentation, and research data. Git is a modern distributed revision control and source code management tool. Through utilizing Git, developers are free to checkout, and even branch the existing code base to meet current and future needs.

Git (a command line tool) is available with many Linux distributions, and is freely available to download and compile. Pre-built binary installers, and GUI interfaces exist for all major operating systems. The SSH URL for accessing this project via git is `git@github.com:polycoder/OpenPipe.git`. All fork requests can be placed by visiting [HTTPS://github.com/polycoder/OpenPipe](https://github.com/polycoder/OpenPipe).

2.2 PHP



The core server components of OpenPipe were all written with PHP 5.3. PHP is a general-purpose server-side scripting language originally designed for web development to produce dynamic web pages.

PHP can be deployed on most Web servers and as a standalone shell on almost every operating system and platform free of charge. PHP is installed on more than 20 million Web sites and 1 million Web servers [7]. These statistics make PHP a very good option to build and develop new web technologies and frameworks which will then be available to a large community of software developers.

2.3 phpDocumentor



OpenPipe uses phpDocumentor to generate all of the available PHP class documentation. phpDocumentor is a tool with which it is possible to generate documentation from your PHP source code using a standardized set of source code commenting conventions. With this documentation you can provide developers with more information regarding the functionality embedded within your source code. phpDocumentor is heavily inspired by the JavaDoc tool available with the Java SDK.

2.4 Apache



OpenPipe has been built and tested using the Apache HTTP server. OpenPipe is not limited to running on this architecture, and can theoretically be run on any web server that supplies integration with PHP.

Apache is a web server software notable for playing a key role in the initial growth of the World Wide Web. Apache is developed and maintained by an open community of developers under the Apache Software Foundation. Apache is available with many Linux distributions, and is freely available to download and compile. Prebuilt binary installers exist for all major operating systems.

Since April 1996 Apache has been the most popular HTTP server software in use. As of March 2012 Apache was estimated to serve 57.46% of all active websites and 65.24% of the top servers across all domains [8].

2.5 FireFox



All client side testing and analysis (manual and automated) of OpenPipe was performed using the FireFox web browser. FireFox supplies a very advanced toolset for profiling HTTP requests, viewing and editing HTML, and debugging JavaScript. FireFox

is freely available to download and compile. Prebuilt binary installers exist for all major operating systems.

2.6 Codelgniter



The OpenPipe framework that has currently been developed provides an adapter that interfaces with the Codelgniter framework. Using this adapter it is fairly straight forward and simple to convert an existing Codelgniter application to take advantage of OpenPipe HTTP request pipelining. Codelgniter is a powerful PHP framework with a very small footprint, built for PHP coders who need a simple and elegant toolkit to create full-featured web applications.

2.7 Selenium



Selenium automates browsers by providing a common API that is provided in the form of a, 'WebDriver'. WebDrivers exist for every major browser including:

1. Firefox

2. Chrome
3. Safari
4. Internet Explorer
5. Android
6. iOS

Selenium is primarily used for the automated testing of web applications, and is often used in conjunction with a unit testing framework. Selenium is however not limited to this set of tasks and can be extremely useful for other tasks such as performance testing and analysis. OpenPipe utilized Selenium to help clarify the performance gains and penalties when using the framework under different usage scenarios and server load. Utilizing Selenium it became trivial to automate web page loading, and record large datasets of performance data.

Chapter 3

Test Applications

3.1 Static Sample App

Before development on the server and client components was started a static web site was built using plain HTML and CSS [see figure 3.1] . This static site's main purpose is to provide a foundation for testing, while adding a clean visual experience that adequately illustrates the optimization of a pipelined HTML page. The main requirement for this static site was that it be composed of many individual components and page sections. OpenPipe is geared towards pages that load information that has many cross cutting concerns per request. The static sample application meets this requirement, and has various components that fall into the following defined sections:

1. Header

- (a) Navigation - main navigational links available to the user.

2. Main Content Area

- (a) Post Input - an input box used for submitting posts of various types.

- (b) Posts list - a listing of main posts that the user has received.
- (c) Post comments - each post contains a potential list of comments that have recorded.

3. Left Sidebar

- (a) Favorite - a sidebar item containing the areas most accessed by a user.
- (b) Apps - application currently installed by the user.
- (c) Groups - groups a user is a member of.
- (d) Friends - groupings of friends the user is related to.
- (e) Friends Search - A search input box for finding friends.
- (f) Friends Face-box - A graphical view of friends through their profile pictures.

4. Right Sidebar



Figure 3.1: Feature rich OpenPipe sample application to illustrate nested pipelines

The static application contains a diverse amount of sections. The resulting HTML, CSS, and JavaScript code created during this page creation was migrated to an MVC Based system that implements the OpenPipe Adapter interface.

3.2 Basic Pipeline

During the initial prototyping phase for OpenPipe a basic pipelined base site was built to illustrate the core components that are applied during the main pipeline process. The basic pipeline example is composed of one default layout, and three separate page pipelets [see figure 3.2].




Figure 3.2: Basic OpenPipe sample application to illustrate a basic pipelines

This simple design did not integrate with any existing PHP frameworks and relied on a very simple paradigm available in the PHP language called includes. Each pipelet being loaded is placed in an include file within a defined folder specified at runtime. The

root Pipelet layout is placed within the layout.php include file, which is also specified at runtime. This simple and effective OpenPipe application was used to verify and test all the components of the OpenPipe system including the client side JavaScript library.

3.2.1 MVC Pipeline (PVC)

The final stage in the development cycle was to implement an adapter for an existing PHP MVC framework. This adapter essentially retrofits the existing framework, and allows it to take advantage of HTTP pipelining provided by the OpenPipe framework.

The PHP MVC framework chosen to create an adapter for is named CodeIgniter. CodeIgniter is a lightweight open-source MVC framework, that is relatively simple to work with and extend.

Utilizing CodeIgniter's same system of controllers and views, a developer can easily convert any CodeIgniter page to an HTTP pipelined request. This is made possible by a simple series of installation steps illustrated in the provided sample application. The main index file ends up looking like figure 3.2.1, once the OpenPipe integration has taken place.


```

<?php
require_once(dirname(__FILE__).'../../../../../server/php/OpenPipe/Adapter/Pvc/
    CodeIgniter.php');
require_once(dirname(__FILE__).'../../../../../server/php/OpenPipe/Output/Piped
    .php');
require_once(dirname(__FILE__).'../../../../../server/php/OpenPipe/Output/
    Standard.php');
require_once(dirname(__FILE__).'../../../../../server/php/OpenPipe/Runner.php')
    ;

$openPipeAdapter = new OpenPipe_Adapter_Pvc_CodeIgniter(dirname(__FILE__))
    ;

if(isset($_GET['nopipe'])) {
    $openPipeOutput = new OpenPipe_Output_Standard();
} else {
    $openPipeOutput = new OpenPipe_Output_Piped('../../../../../../client/js');
}

```

Figure 3.3: OpenPipe adapter setup for CodeIgniter

Chapter 4

Architectural Components

4.1 Server components

The server is composed of four main layers:

1. **PHP** - The underlying scripting language. Run as a component of the web server.
2. **OpenPipe_Runner** - The main loop of an OpenPipe application. The runner orchestrates actions between the adapter being utilized, and the output that is generated.

```
//starting an openpipe runner
$openPipeRunner = new OpenPipe_Runner($openPipeAdapter,
    $openPipeOutput); $openPipeRunner->run(); //outputs openpipe
content
```

3. **OpenPipe_Adapter** - A pluggable interface which retrieves and returns pipelets components from the underlying web framework. An adapter can be used to interface pre-existing PHP application frameworks with OpenPipe, or whole new OpenPipe-centric application frameworks.

```
//loading an openpipe adapter
```

```
$openPipeAdapter = OpenPipe_Adapter_Pvc_CodeIgniter(dirname(__FILE__))  
);
```

4. **Framework** - The framework being utilized with the OpenPipe adapter. The framework normally provides core web application components such as database libraries, request routing, session handling, and form validation. The CodeIgniter MVC system is an example of framework.




Figure 4.1: Server side technology stack with OpenPipe components

4.2 Client components

The client is composed of three main layers:

1. **JavaScript** - The host environment (web browser) and core JavaScript libraries.
2. **Vendor Libraries** - OpenPipe makes use of two very popular, reliable, and lightweight cross-browser JavaScript frameworks.
 - (a) **Underscore.js** - A utility-belt library for JavaScript that provides functional programming support.
 - (b) **jQuery** - Provides simple and elegant client side scripting and manipulation of HTML DOM.
3. **OpenPipe** - A client side library which is responsible for receiving events from an OpenPipe based server. These events are processed and associated data for these events is loaded into the HTML DOM as HTML, CSS, and JavaScript.




Figure 4.2: Client side technology stack with OpenPipe components

Chapter 5

Pipelets

Every OpenPipe HTTP request cycle is composed of pipelets. A pipelets represents an atomic composition of HTML, CSS, and JavaScript [see figure 5] . A web page request can be composed of one to many pipelets.

```
<!-- a simple pipelet containing css, javascript, and html -->
<div pipelet-id="pipelet-1" ></div>
  <link rel="stylesheet" type="text/css" href="css/pipelet-1.css" />
  <script type="text/javascript" src="js/pipelet-1.js" ></script>
  <h1>Hello world!</h1>
</div>
```

Figure 5.1: Sample pipelet containing HTML, CSS, and JavaScript

5.1 The Root Pipelet

Every pipelined HTTP request contains at least one initial pipelet. This initial pipelet is known as the root pipelet, and is the source for extraction and retrieval for all other pipelets. The root pipelet is special because it defines the overall layout of the page, from which all pipelets will be loaded and placed into [see figure 5.1 and 5.1].

The root pipelet contains the root `<html />` element and its immediate children - `<head`

`/>` and `<body />` . Since the root pipelet defines the head section it is capable of setting extra page meta information through specialized head tags, and linking or including CSS and JavaScript shared between pipelets.

```
<html>
<head>
<title>Root Pipelet!</title>
<link rel="stylesheet" type="text/css" href="css/global.css" />
<script type="text/javascript" src="js/app.js" ></script>
</head>
<body>
<h1>Hello World!</h1>
<div pipelet-id="pipelet-1"></div>
<div pipelet-id="pipelet-2"></div>
</body>
</html>
```

Figure 5.2: Root pipelet HTML




Figure 5.3: Root pipelet layout

5.2 Nested Pipelets

Pipelets can be nested within other pipelets. This provides a mechanism to display content that contains n -levels of content depth, and allows for a great deal of flexibility when dealing with nested retrieval and display of data within a web page. Using nested pipelets the page being rendered can start to be divided into subcomponents, and those subcomponents can have more subcomponents of their own.

Figure 5.2 illustrates a nested pipelet page of depth 3. Each set of pipelets is loaded using a breadth first loading algorithm. So all the pipelets at depth n will be loaded and rendered before the system continues to load pipelets at depth $n+1$. Its also important to note that loading of JavaScript for all pipelets will be deferred until all pipelet content (HTML and CSS) has been loaded for the given depth.




Figure 5.4: Nested Pipelets with a depth of 3

5.3 Pipelet Priority

Pipelets that are part of the same depth can be prioritized explicitly using the `pipelet-priority` OpenPipe HTML attribute [see figure 5.3]. By default all pipelets are loaded in ascending alphanumeric order of the `pipelet_id` OpenPipe HTML attribute. The addition of an explicit `pipelet-priority` tag allows for a greater degree of control when loading pipelet components and, most importantly, allows for the developer to choose which pieces of the page should be loaded and transmitted first.

```
<!-- a root pipelet -->
<html>
<head>
<title>Root Pipelet!</title>
  <link rel="stylesheet" type="text/css" href="css/global.css" />
  <script type="text/javascript" src="js/app.js" ></script>
</head>
<body>
  <h1>Hello World!</h1>
  <div pipelet-id="pipelet-1"></div>
  <div pipelet-id="pipelet-2" pipelet-priority="1" ></div>
</body>
</html>
```

Figure 5.5: Sample pipelet containing HTML, CSS, and JavaScript

Chapter 6

Class Interfaces

OpenPipe defines core interfaces for pluggable components of the system. Through utilizing provided interfaces developers can contour and extend the framework to meet new and existing needs.

6.1 Output




Figure 6.1: A generalization of the OpenPipe output object

The output interface [see figure 6.1] defines how to conform to a set of output principles that allow for desired output functionality depending on the needs and capability of the client accessing an OpenPipe based web page. The output interface defines the following methods:

1. **bootstrap** - Allows implementor to setup and output any data before the content phase begins.
2. **preContent** - Called immediately before any content is to be outputted through the

associated content() method.

3. **output** - Called when content is ready for output - This content is already generated HTML string.
4. **phaseComplete** - Called when an output phase is complete. A phase represents a layer of data (each layer of data can contain n number of deeper layers).
5. **postContent** - Called immediately after all data has been sent for output.
6. **clean** - Allows implementor to do any final cleanup and output. This is the last step in the output process.

Out of the box the core OpenPipe library provides two output interface implementations:

1. **OpenPipe_Output_Piped** - Implementation of an OpenPipe output interface that sends data by way of an HTTP pipeline. This is done by loading the openpipe.js client library and associated libraries. The output handler handles extracting pipelet HTML data, and transmitting it as packed JSON object, which will be unpacked by the client openpipe.js library.
2. **OpenPipe_Output_Standard** - Implementation of an OpenPipe output interface that sends data as a standard HTML document. Content pieces are used to construct a complete HTML document, placing CSS and JavaScript in proper placement, and inject each content piece within a pipelet place holder on the server side. It's important to note that no javascript is required to complete output on the client web browser while using this output implementation.

This illustrates the power of decoupling the output system into an interface which is chosen at runtime based on the needs and capabilities of a given client receiving the

output information. Through the use of the same output interface the OpenPipe runner can transparently interface with JavaScript capable devices and non JavaScript capable devices such as web crawlers and bots without needing to alter any information retrieved from a corresponding framework interface.

6.2 Framework Adapter




Figure 6.2: A generalization of the OpenPipe adapter object

A framework's adapter [see figure 6.2] is a crucial component of the OpenPipe library that converts web requests into underlying framework routing requests. These routing requests result in output. The output for each request is returned by the framework adapter to the OpenPipe output interpreter where it is parsed for more web requests that need to be retrieved by the framework adapter. This process continues until all output is retrieved.

Chapter 7

Design Patterns

The OpenPipe library utilizes design patterns where appropriate to make the available components easier to comprehend from a conceptual level, and also easier to extend for future use. The patterns explained below were chosen to provide maximum flexibility to the underlying system when integrating with existing PHP web application systems and frameworks.

7.1 Strategy Pattern

OpenPipe uses the strategy design pattern to define families of objects that can be utilized by the `OpenPipe_Runner` class at runtime [see figure 7.1]. This helps effectively decouple the `OpenPipe_Runner` from rendering and output concerns. These two concerns can vary depending on:

1. The type of HTTP client accessing the web page (web browser, bot, crawler).
2. The type of framework that OpenPipe is using to access and render web page information (CodeIgniter, Zend Framework, CakePHP).




Figure 7.1: The strategy pattern utilized by OpenPipe for the main OpenPipe runner object

Another benefit of this design pattern implementation is that new adapters and output classes can be developed and utilized in the future. Once created they only need to be passed as parameters to the OpenPipeRunner class when it is instantiated [see figure 7.1].

```
//starting an openpipe runner
$openPipeRunner = new OpenPipe_Runner($openPipeAdapter, $openPipeOutput);
$openPipeRunner->run(); //outputs openpipe content
```

Figure 7.2: Instantiation and running of an OpenPipeRunner object

7.2 Factory Pattern

OpenPipe utilizes the factory design pattern to construct pipelets from output received from a framework adapter [see figure 7.2]. The factory receives raw HTML data and

current phase information. The factory then continues to parse embedded pipelet information from the HTML and return an array of Pipelets that conform to the OpenPipe_Pipelet_Interface




Figure 7.3: The factory pattern utilized by OpenPipe

Chapter 8

Sequence Diagrams

8.1 Server

Every open pipe request cycle is handle by a core class named `OpenPipe_Runner`. The runner is responsible for orchestration communication with a class that implements the `OpenPipe_Adapter` interface. This communication results in:

1. Notification of bootstrapping and cleanup stages in the request cycle.
2. Retrieval of the root pipelet content (layout).
3. Retrieval of nested pipelets within the root pipelet.

Once the `OpenPipe_Runner` class has received information from the `OpenPipe_Adapter` its passes any renderable content to a class that implements the `OpenPipe_Output` interface. The `OpenPipe_Output` class handles sending data to the client, and removes any special concerns for how this data is transmitted away from the `OpenPipe_Runner`.

The `OpenPipe_Runner` is also responsible for calling upon a `Pipelet_Factory` to build pipelets from content gathered from the `Pipelet_Adapter`. The `Pipelet_Factory` returns an

array of pipelets which contain information that can be sent to the `OpenPipe_Adapter` to gather the pipelet HTML and data, and then passed to the `OpenPipe_Output` class for rendering. The factory process is the main loop in the `OpenPipe_Runner` application.

All components of this process are pluggable and determined at runtime. The `OpenPipe_Runner` class depends only on the individual interfaces defined in the `OpenPipe` library, and utilizes specific design patterns such as the strategy and factory patterns to decouple it directly from any class instantiation.

The sequence diagram for a complete `OpenPipe` request is outlined in figure 8.1




Figure 8.1: OpenPipe Runner sequence diagram

8.2 Client

Once a request is handled and output is sent through an `OpenPipe_Output` class, this output must be interpreted and acted upon by the OpenPipe client library. The client

library is built entirely of JavaScript and contains the following API calls:

1. **init** - this is called during the main page layout initialization stage. It handles setting up the layout and initializing the client library so it can load additional segments.
2. **loadSegment** - this is the main method call, which handles loading pipelet data from the server and rendering it within a web browser. It accepts segment data, which are essentially predefined JSON objects.
3. **registerPhase** - called when a segment is loaded. If the segment part of a new phase then the phase is recorded as starting and any script received will be queued until this phases content (HTML and CSS) has been loaded and rendered.
4. **loadCss** - loads a given array of CSS elements (<link /> and <style /> tags). The CSS information is inserted directly into the <head /> section of the HTML document].
5. **loadHtml** - load a given HTML document into the layout's pipelet placeholder. The placeholder to insert content to is determined using the segments corresponding id.
6. **pushScripts** - pushes a segment's set of script tags (both inline and external) onto a stack for later retrieval. JavaScript is loaded at the end of each loading phase. This allows for content represented as HTML and CSS to be loaded and viewable first before any possibly long JavaScript execution takes place.
7. **phaseComplete** - marks a phase as complete. When a phase is marked complete all JavaScript queued from segments loaded during the same phase will be appended to the <head /> section of the HTML document and executed in the order received.

The sequence diagram for a complete OpenPipe client processing cycle is outlined in figure 8.2




Figure 8.2: OpenPipe output sequence diagram

```

<html>
<head>
  <title>OpenPipe Sample Page</title>
  <script type="text/javascript" src="js/libs/jquery.js"></script>
  <script type="text/javascript" src="js/libs/underscore.js"></script>
  <script type="text/javascript" src="js/openpipe.js"></script>
</head>
<body>
  <div id="container" ><!-- root layout data. --></div>
  <!-- followed by openpipe client request calls -->
  <script type="text/javascript">
    op.load({...});
  </script>
  <script type="text/javascript">
    op.load({'id':'pipelet1', 'html': '...', 'css': [], 'scripts': []});
  </script>
  <script type="text/javascript">
    op.load({'id':'pipelet2', 'html': '...', 'css': [], 'scripts': []});
  </script>
  <script type="text/javascript">
    op.load({'id':'pipelet3', 'html': '...', 'css': [], 'scripts': []});
  </script>
  <script type="text/javascript">
    op.phaseComplete(1); op.done();
  </script>
</body>
</html>

```

Figure 8.3: OpenPipe client side pipelet load calls

Chapter 9

Data Objects

9.1 Transmitted Data

Pipelet data is transmitted as JSON to the client. Each individual pipelet transmitted as JSON is referred to as a segment in the OpenPipe.js client library. A segment contains the following data elements [see figure 9.1]:

1. **ID** - the id of the pipelet the information in the segment pertains to.
2. **CSS** - an array of inline and external css HTML tags. This information is extracted from the server output and organized before transmission to the client as a segment.
3. **Scripts** - an array of inline and external script HTML tags. This information is extracted from the server output and organized before transmission to the client as a segment.
4. **HTML** - raw HTML data that is left after css and script data extraction.




Figure 9.1: The client segment data object

Chapter 10

Other Library Components

10.1 PHP Output Buffering

PHP has built in functionality which prevents output data from being transmitted to a client connection until a certain amount of data has been placed into an output buffer. This however is counter productive to the operation of OpenPipe since each pipelet needs to be transferred immediately after is ready for output. This allows for the illusion of page rendering speed. If the buffer was left in place PHP would not output the data in a continuous stream and the experience would be similar to non HTTP Pipelined pages.

To get around this issue OpenPipe utilizes a custom output utility class which provides an output function named `echoNow` [see figure 10.1]. `echoNow` performs similarly to the standard `echo` function in PHP, but it is output buffer aware. Every time the `echoNow` function is called it queries the current PHP output buffer size and pads the output string with as much data that is needed so that the buffer will be full and the output data will be sent immediately. Utilizing this function classes within the OpenPipe library to not need to individually carry the concern of output buffering and how to circumvent it.

```

/**
 * Highly reusable output method which echos data NOW - by NOW we mean in
 * an intelligent way that takes into account output buffering in PHP
 * as well as browser based deferred display of data (until data is of x
 * bytes) - Using this utility method one should not have to worry about
 * how
 * to immediately send data to an end client browser NOW
 * @param string $output the data to output NOW!
 * @param int|null $outputBufferSize the output buffer currently in use -if
 * a string is not of an output buffer length it will be padded to meet
 * the minimum buffer size - If not provided this value will be looked up
 * from the PHP ini configuration value
 * @param string $paddingCharacter the character to pad output with if the
 * buffer is larger than the data to output
 */
public static function echoNow($output, $outputBufferSize=null,
    $paddingCharacter = ' '){

    //if the output buffer is null, then attempt to get it from php ini
    if($outputBufferSize === null){
        $outputBufferSize = @ini_get('output_buffering');
        if($outputBufferSize == 'Off') $outputBufferSize = 0;
    }

    //now that we know the buffer check to see how much we need to pad the
    string that is to be outputted
    $bufferSpace = $outputBufferSize - strlen($output);
    if($bufferSpace > 0){
        $output = $output.str_repeat($paddingCharacter, $bufferSpace);
    }

    //echo the string (with possible padding), then flush!
    echo $output;
    flush();
}

```

Figure 10.1: PHP function that helps bypass PHP output buffering that blocks the HTTP pipelining of data to the client browser

10.2 Dynamic JavaScript DOM Insertion

Inserting JavaScript into an existing DOM document needs to be done in a slightly different way than just appending the raw JavaScript data to the current HTML document being loaded. To do this in a reliable and cross browser way the boiler plate DOM function,

'createElement', is used to create a new script tag. Once the script tag is created the type and source code attributes are set independently using the JSON data that is sent with a piplet's JavaScript component. The code that accomplishes the JavaScript insertion can be found in figure 10.2

```
var script = document.createElement('script');
script.type = jq_script.attr('type') || '';
script.src = jq_script.attr('src') || '';
$('body').append(script);
```

Figure 10.2: JavaScript code segment that allows for reliable cross browser insertion of dynamic JavaScript code into the DOM

Chapter 11

Methodology

11.1 Data Collection

To collect data a simple but powerful script [see figure 11.1] was developed utilizing the Selenium framework to automate the systematic retrieval of performance timing data for loaded web pages. The web page selected for data collection was the OpenPipe enabled static sample app previously illustrated [see figure 3.1]. Selenium was a perfect candidate for automated retrieval of data, because unlike other types of web request tools such as cURL or wget which just send and receive raw HTTP data, Selenium drives a physical web browser through the utilizing of underlying browser API systems. This means that data is loaded and processed exactly the same as when an end user accesses a given website. This includes web requests, web responses, loading and unloading of the DOM, and JavaScript execution. JavaScript execution was a crucial component in determining the load time for a OpenPipe enabled web page, since all data is unpacked and loaded in the browser via JavaScript after it has been received from the server.

```

#-----
# Script for recording performance timing of a given web page
# @author Sean Kenny <skenny214@gmail.com>
#-----
require 'pp'
require 'rubygems'
require 'csv'
require 'selenium-webdriver'

#get arguments
url = ARGV[0];
cycles = ARGV[1] || '5'
output_file = ARGV[2] || 'output.csv'

#open client driver for firefox
browser = Selenium::WebDriver.for :firefox

#open csv for writing output data
CSV.open(output_file, "w") do |csv|
  #for the amount of times the user wanted, get the page, get the
  #performance timing, and output to csv
  cycles.to_i.times do |i|
    browser.get url
    browser_timing = browser.execute_script("return window.performance.
      timing");
    openpipe_timing = browser.execute_script("return typeof(op) !== '
      undefined' ? op.performance.timing.segments : null");

    # calculate wait time in two ways - if not openpipe then just use
    #reponse start
    if(openpipe_timing == nil)
      browser_timing['responseWaitTime'] = browser_timing['responseStart']
        - browser_timing['requestStart']

    #if we have openpipe timing then the response wait time is for first
    #piece of actual content (assumed to be pipelet of first priority)
    else
      browser_timing['responseWaitTime'] = openpipe_timing[1] -
        browser_timing['requestStart']
    end

    browser_timing['totalLoadWaitTime'] = browser_timing['loadEventEnd'] -
      browser_timing['requestStart']

    sorted_timing_values = []
    browser_timing.keys.sort.each do |key|
      sorted_timing_values << browser_timing[key]
    end

    csv << browser_timing.keys.sort if i==0
    csv << sorted_timing_values
  end
end
end
end

browser.quit

```


Figure 11.1: A selenium script that retrieves performance and timing data from websites

Utilizing Selenium to load a web page also allowed for controlled access to performance timing information recorded by web browsers during each web request. This performance timing information can be found in the DOM javascript element, 'window.performance.timing'. The data structure for window.performance.timing can be seen in figure 11.1. To make the meaning of the data found within the window.performance.timing data structure more clear a visualization timeline that illustrates when the performance timing events occur can be seen in figure 11.3.

```
interface PerformanceTiming {
    readonly attribute unsigned long long navigationStart;
    readonly attribute unsigned long long unloadEventStart;
    readonly attribute unsigned long long unloadEventEnd;
    readonly attribute unsigned long long redirectStart;
    readonly attribute unsigned long long redirectEnd;
    readonly attribute unsigned long long fetchStart;
    readonly attribute unsigned long long domainLookupStart;
    readonly attribute unsigned long long domainLookupEnd;
    readonly attribute unsigned long long connectStart;
    readonly attribute unsigned long long connectEnd;
    readonly attribute unsigned long long secureConnectionStart;
    readonly attribute unsigned long long requestStart;
    readonly attribute unsigned long long responseStart;
    readonly attribute unsigned long long responseEnd;
    readonly attribute unsigned long long domLoading;
    readonly attribute unsigned long long domInteractive;
    readonly attribute unsigned long long domContentLoadedEventStart;
    readonly attribute unsigned long long domContentLoadedEventEnd;
    readonly attribute unsigned long long domComplete;
    readonly attribute unsigned long long loadEventStart;
    readonly attribute unsigned long long loadEventEnd;
};
```

Figure 11.2: DOM performance timing data made available via JavaScript [5]

Figure 11.3: DOM performance timing data show as linear request [5]



11.2 Simulating Load

One important characteristic to consider when developing a web based library is how it performs under load. The dimension of load that was considered when performance testing OpenPipe was the number of concurrent connections the server was able to process, and how this affected overall performance with and without the OpenPipe library outputting data through an HTTP data pipeline.

To achieve an accurate simulation of load the freely available and opensource tool named, 'Siege'. Siege is an HTTP load testing and benchmarking utility. It was designed to let web developers measure their code under duress, to see how it will stand up to load on the internet [6]. OpenPipe was tested while siege was run at concurrency levels 10, 25, 50, and 100.

Chapter 12

Results

Once the performance timing data was collected additional data points were calculated to clarify if any performance benefits could be found between a pipelined and non-pipelined version a webpage. This data was collected and laid out in a tabular format [see figure 12]. The columns in the presented table represent the following variables and formulas:

1. **Type** - Represents the type of external event that the server is issuing to complete the given web page request. Three types of web page requests were simulated:
 - (a) **Plain HTML** - The server does not connect to any external system. It simply renders and return HTML content. This HTML content also includes CSS and JavaScript.
 - (b) **Database** - The server creates a connection to a local database system and issues select queries over this connection to gather data. The data is not used in the display of the web page, but nevertheless this simulates the overhead necessary to connect to a local database system, loop through the data, and return a result.
 - (c) **Web Service** - The server create a connection to an external REST based

web service. For the purposes of these tests the server connect to the twitter REST API and issues REST based query commands. The data is not used in the display of the web page, but nevertheless this simulates the overhead necessary to connect to an external REST based system, loop through the data, and return a result.

2. **Load** - The ammount of load that is being put on the web server during the testing time. Load was simulated using the command line tool named, 'Siege'. The number presented in this column represents the total number of concurrent connection being issued from Siege during the tests.
3. **Response** - The initial response time for a non piped page. The formula for this data point is: $responseStart - requestStart$
4. **Response Piped** - The initial response time for a non piped page. This is calculated by recording the load time of the first piece of content within a pipelet (users sees something) and comparing that to the request start time. The formula for this data point is: $firstPipeletLoadTimeEnd - requestStart$
5. **Total Time** and **Total Time Piped** - The total time it took to the load the page, starting at request start and ending at the final DOM loaded event. The formula for this data point is: $loadEventEnd - requestStart$

Type	Load	Response	Response Piped	Total Time	Total Time Piped
<i>Plain HTML</i>	0	80.81632653	56.10204082	102.6122449	144.0408163
<i>Database</i>	0	149.0612245	74.14285714	166.5714286	127.6122449
<i>Web Service</i>	0	5144.959184	795.2244898	5164.77551	5103.959184
<i>Plain HTML</i>	10	141.9183673	90.51020408	187.4489796	172.3469388
<i>Database</i>	10	408.8367347	231.8979592	448.4081633	618.7142857
<i>Web Service</i>	10	5053.040816	767.5510204	5110.591837	5114.691837
<i>Plain HTML</i>	25	137.1836735	137.1836735	184.4285714	192.8163265
<i>Database</i>	25	2583.612245	939.6530612	2621.387755	2649.897959
<i>Web Service</i>	25	4872.367347	718.877551	4912.204082	5177.857143
<i>Plain HTML</i>	50	146.9591837	111.5306122	194	220.8979592
<i>Database</i>	50	6172.265306	2203.897959	6214.673469	6244.55102
<i>Web Service</i>	50	4791.755102	750.2857143	4848.040816	4790.081633
<i>Plain HTML</i>	100	149.2653061	102.7959184	192.8979592	195.3673469
<i>Database</i>	100	12139.69388	4530.346939	12217.28571	12878.77551
<i>Web Service</i>	100	4742.285714	741.6734694	4827.040816	4754.469388

Figure 12.1: Calculated response and load time in milliseconds. Data is based on timing data collected from automated browser runs via Selenium scripting.




Figure 12.2: OpenPipe column chart comparing non-piped vs. piped response times and total load times for plain HTML data




Figure 12.3: OpenPipe column chart comparing non-piped vs. piped response times and total load times when connecting to a local database system for data




Figure 12.4: OpenPipe column chart comparing non-piped vs. piped response times and total load times when connecting to an external REST API for data

Chapter 13

Discussion

13.1 Expanded Output API

Right now the OpenPipe system relies on an implicit layout output system that is integrated into a new or existing web framework. The API could be extended to provide a more explicit type of output system that may be useful in some scenarios that a developer may encounter. An example of an explicit API that could be developed can be found in figure 13.1

```

<?php
$layoutData = file_get_contents('layout.php');

$pipe = new OpenPipe_Output_Handle();
$pipe->sendLayout($layoutData);

$dbRecords = mysql_query('select * from facts');
$content = '';
foreach($dbRecords as $dbRecord){
    $content .= "<h1>User {$dbRecord['user_name']}

```

Figure 13.1: An explicit version of an OpenPipe output API

13.2 Minification

The OpenPipe output adapter could add another output step where JavaScript, CSS, and HTML code is minified. Minified code has all unnecessary characters removed from its content, without changing the functionality of the original program. Minification can play an important role in further optimizing the pipeline by reducing the overall size of individual pipelet components.

13.3 Addition of framework adapters

Out of the box OpenPipe allows for integration with the CodeIgniter MVC Framework. Utilizing the strategy design pattern it is possible to develop additional adapters that allow for integration with existing and future PHP frameworks. Some frameworks that would be next to integrate include:

1. Symfony

2. Zend Framework
3. CakePHP
4. Yii

13.4 Language agnostic Apache server extension

Currently the OpenPipe framework is limited to working with PHP based applications and websites. This is due to the fact that the entire server side implementation is built using the PHP language and is executed by the web server using additional modules like mod_php.

Web servers like apache provide application interfaces for developing server extensions. OpenPipe development could progress to include an embedded apache module that allows for integration with any web based applications utilizing any web scripting language. This would allow OpenPipe to integrate with tools such as Python, Ruby, and Perl.

Chapter 14

Code Listings

Listing 14.1: "OpenPipe/Runner.php"

```
1 <?php
2
3 require_once('Output/Util.php');
4 require_once('Adapter/Interface.php');
5 require_once('Pipelet/Factory.php');
6
7 /**
8  * A runner is the core object for any OpenPipe based application. A
9  *   runner is responsible for gathering output from an
10  *   OpenPipe_Adapter_Interface based
11  *   adapter and returning to the end client browser as piped data objects.
12  *   Before sending these piped based data objects this runner also ensures
13  *   that the
14  *   end client browser has been setup/instantiated appropriately by sending
15  *   the CORE OpenPipe front end JavaScript libraries and the CORE HTML
16  *   framework
17  *   Once constructed calling this object run() method will kickoff the
18  *   OpenPipe HTTP pipelining process
```

```

12 * @author Sean Kenny <skenny214@gmail.com>
13 * @package OpenPipe
14 * @license (c) 2011-2012 Sean Kenny, Southern Connecticut State University
    (SCSU).
15 * @version 1.0.0
16 */
17 class OpenPipe_Runner {
18
19     /**
20      * The OpenPipe_Adapter_Interface object that is used by this
        OpenPipe_Runner to gather pipelets and load individual pipelet data
21      * @var OpenPipe_Adapter_Interface
22      */
23     protected $frameworkAdapter;
24
25     /**
26      * The OpenPipe_Output_Interface object that is used by this
        OpenPipe_Runner to send output data to the browser
27      * @var OpenPipe_Output_Interface
28      */
29     protected $output;
30
31
32
33     /**
34      * Constructs an OpenPipe_Runner object that communicated with the given
        OpenPipe_Adapter_Interface based object
35      * @param OpenPipe_Adapter_Interface $frameworkAdapter
36      * @param OpenPipe_Output_Interface $output
37      */

```

```

38 public function __construct(OpenPipe_Adapter_Interface $frameworkAdapter
    , OpenPipe_Output_Interface $output){
39     $this->frameworkAdapter = $frameworkAdapter;
40     $this->output = $output;
41 }
42
43
44 /**
45  * Is responsible for the ENTIRE OpenPipe HTTP pipelining lifecycle -
    handle all bootstrapping, base client library loading, output
    gathering, output transmission, Script, and shutdown
46 */
47 public function run(){
48     $this->bootstrap();
49     $this->output->preContent();
50
51     //ask the framework for the root output layer (the layout!). This
    contains the starting point for all pipelets to get recognized and
    loaded from
52     $layout = $this->frameworkAdapter->getOutput();
53     $this->output->content($layout);
54
55     $phase = 0;
56     $pipelets= OpenPipe_Pipelet_Factory::buildFromHtml($layout, $phase);
57     $pipeletsQueue = array();
58
59     while(!empty($pipelets)){
60
61         $currentPipelet = array_shift($pipelets);
62
63         $this->frameworkAdapter->getOutput($currentPipelet);

```

```

64     $this->output->content($currentPipelet);
65
66
67     //add pipelets contained within the current pipelet to the the
        pipelet queue - the pipelet queue will get loaded as part of the
        next phase
68     $pipeletsQueue = array_merge($pipeletsQueue,
        OpenPipe_Pipelet_Factory::buildFromHtml($currentPipelet->
        getOutput(), $phase+1));
69
70     //once the current pipelets have been completed. Check the queue. If
        the queue is not empty then move batch to the pipelets array for
        processing, and mark the current pahse complete
71     if(empty($pipelets)){
72         $pipelets = $pipeletsQueue;
73         $pipeletsQueue = array();
74
75         $this->output->phaseComplete(++$phase);
76
77     }
78
79 }
80
81 $this->output->postContent();
82 $this->clean();
83 }
84
85
86
87
88 /**

```

```

89  * Performs bootstrapping of OpenPipe runner object and calls the
    injected OpenPipe_Adapter_Interface bootstrap() method at the very
    end
90  */
91  protected function bootstrap(){
92      $this->frameworkAdapter->bootstrap();
93      $this->output->bootstrap();
94  }
95
96  /**
97  * Performs Script of OpenPipe runner object and calls the injected
    OpenPipe_Adapter_Interface clean() method at the very end
98  */
99  protected function clean(){
100      $this->frameworkAdapter->clean();
101      $this->output->clean();
102  }
103
104
105
106 }

```

Listing 14.2: "OpenPipe/Pipelet/Interface.php"

```

1  <?php
2
3  /**
4  * An interface defining a pipelet. A pipelet is an atomic entity with an
    pipe based HTML layout. A pipelet is essentially a piece of content
    that is loaded
5  * in a priority based sequential fashion and outputted immediately to the
    end client browser, without having to wait for other pipelets or sub

```

```

    pipelets to be
6 * loaded as well. A pipelet's main purposed is to deliver content in
    modular packages that increase the, 'perceived', load time of an HTML
    based PHP application.
7 * A pipelet at its core has an ID, phase, and output.
8 * - An id is derived either from the parent layout of parent pipelet. The
    id is used to identify and load content from a PHP OpenPipe adapter (
    OpenPipe_Adapter_Interface)
9 * - A phase is used to determine the timing and priority of a pipelet when
    it is received by an end client browser
10 * - The output is any data gathered from the OpenPipe adapter (utilizing
    the pipelet id). This data is subsequently piped to an end client
    browser
11 * @author Sean Kenny <skenny214@gmail.com>
12 * @package OpenPipe_Pipelet
13 * @license (c) 2011-2012 Sean Kenny, Southern Connecticut State University
    (SCSU).
14 * @version 1.0.0
15 */
16 interface OpenPipe_Pipelet_Interface{
17
18     /**
19      * Sets the id of the pipelet (used to determine what content to gather
        from a Pipe Adapter)
20      * @param string $id a unique identifier for the pipelet that will
        signify importance to the client adapter and allow data to be looked
        up/generated accordingly
21      */
22     function setId($id);
23
24     /**

```

```

25  * Returns the current set pipelet id
26  */
27  function getId();
28
29
30  /**
31  * Sets the phase of the pipelet (used to determine loading priorities
    and sequences)
32  * @param int/string phase to set - Lower numbers are higher priority
    (1), than higher numbers (999)
33  */
34  function setPhase($phase);
35
36  /**
37  * Return the current set phase number
38  */
39  function getPhase();
40
41
42  /**
43  * Set the output that has been gathered for this pipelet from a
    Pipelet_Adapter
44  * @param string $output the output string that has been generated/
    gathered for this given pipelet
45  */
46  function setOutput($output);
47
48
49  /**
50  * Return the output that is currently set for the pipelet
51  */

```



```

52     function getOutput();
53
54 }

```

Listing 14.3: "OpenPipe/Pipelet/Abstract.php"

```

1  <?php
2
3  require_once('Interface.php');
4
5  /**
6   * Abstract implementation of the OpenPipe_Pipelet_Interface. Provided
       basic bindings for all methods defined in the interface.
7   * @author Sean Kenny <skenny214@gmail.com>
8   * @package OpenPipe_Pipelet
9   * @license (c) 2011-2012 Sean Kenny, Southern Connecticut State University
       (SCSU).
10  * @version 1.0.0
11  */
12  abstract class OpenPipe_Pipelet_Abstract implements
       OpenPipe_Pipelet_Interface {
13
14      /**
15       * The unique identifier for this pipelet - that distinguishes it from
       all others.
16       * @var string
17       */
18      protected $id;
19
20      /**
21       * The numbered phase of the pipelet to signify priority low-to-high
22       * @var string

```

```

23     */
24     protected $phase;
25
26
27     /**
28      * The output that is potentially gathered and piped as output for
29      * this pipelet
30      * @var string
31      */
32     protected $output;
33
34     /**
35      * Sets the id of the pipelet (used to determine what content to gather
36      * from a Pipe Adapter)
37      * @param string $id a unique identifier for the pipelet that will
38      * signify importance to the client adapter and allow data to be looked
39      * up/generated accordingly
40      */
41     public function setId($id){
42         $this->id = $id;
43     }
44
45     /**
46      * Returns the current set pipelet id
47      */
48     public function getId(){
49         return $this->id;
50     }

```

```

50  /**
51  * Sets the phase of the pipelet (used to determine loading priorities
    and sequences)
52  * @param int/string $phase to set - Lower numbers are higher priority
    (1), than higher numbers (999)
53  */
54  public function setPhase($phase){
55      $this->phase = $phase;
56  }
57
58  /**
59  * Return the current set phase number
60  */
61  public function getPhase(){
62      return $this->phase;
63  }
64
65
66  /**
67  * Set the output that has been gathered for this pipelet from a
    Pipelet_Adapter
68  * @param string $output the output string that has been generated/
    gathered for this given pipelet
69  */
70  public function setOutput($output){
71      $this->output = $output;
72  }
73
74  /**
75  * Return the output that is currently set for the pipelet
76  */

```

```

77     public function getOutput(){
78         return $this->output;
79     }
80
81
82 }

```

Listing 14.4: "OpenPipe/Pipelet/Base.php"

```

1  <?php
2
3  require_once('Abstract.php');
4
5  /**
6   * Provided a basic extension off of the OpenPipe_Pipelet_Abstract
       convenience implementation
7   * @author Sean Kenny <skenny214@gmail.com>
8   * @package OpenPipe_Pipelet
9   * @license (c) 2011-2012 Sean Kenny, Southern Connecticut State University
       (SCSU).
10  * @version 1.0.0
11  */
12  class OpenPipe_Pipelet_Base extends OpenPipe_Pipelet_Abstract{
13
14
15      /**
16       * Builds the object
17       * @param string $id the identifier for the pipelet
18       * @param int/string $phase the phase for the pipelet
19       * @return OpenPipe_Pipelet_Base new instance
20       */
21      public function __construct($id, $phase){

```

```

22     $this->setId($id);
23     $this->setPhase($phase);
24 }
25 }

```

Listing 14.5: "OpenPipe/Pipelet/Factory.php"

```

1 <?php
2
3 require_once('Base.php');
4
5 /**
6  * Generated pipelets using factory based methods
7  * @author Sean Kenny <skenny214@gmail.com>
8  * @package OpenPipe_Pipelet
9  * @license (c) 2011-2012 Sean Kenny, Southern Connecticut State University
10     (SCSU).
11  * @version 1.0.0
12  */
13
14 class OpenPipe_Pipelet_Factory{
15
16     /**
17      * Extracts an array of pipelets from an given HTML document (represented
18      * as s string)
19      * @param string $html An html document represented via string
20      * @param int/string $phase The current phase of the pipelet loading
21      * process - This is assigned to any loaded pipelets extracted from the
22      * first html string parameter
23      * @return array all pipelets extracted from the HTML input and
24      * instantiated as OpenPipe_Pipelet_Base objects
25      */
26
27 }

```

```

21 public static function buildFromHtml($html, $phase){
22
23     //pipelet containers
24     $pipelets = array();
25     $pipeletGroups = array();
26
27     //setup regex to find pipelets - all pipelets need to specify at least
        a pipelet-id attribute
28     preg_match_all('/<.*?pipelet-id.*?>/', $html, $matches, PREG_SET_ORDER
        );
29
30     //for all matches extract the pipelet to its appropriate group
31     foreach($matches as $match){
32         //reset match arrays
33         $pipeletIdMatch = array();
34         $pipeletPriorityMatch = array();
35
36         //extract pipelet attributes into corresponding match arrays
37         preg_match('/pipelet-id\\=(\\'.*?\\'|".*?")/', $match[0],
            $pipeletIdMatch);
38         preg_match('/pipelet-priority\\=(\\'.*?\\'|".*?")/', $match[0],
            $pipeletPriorityMatch);
39
40         //assign matches to local variables
41         $pipeletId = trim(@$pipeletIdMatch[1], '\\\'"');
42         $pipeletPriority = trim(@$pipeletPriorityMatch[1], '\\\'"');;
43         if(empty($pipeletPriority)) $pipeletPriority = 0;
44
45         //construct a pipelet based on extracted information, and place in
            proper group
46         if(!empty($pipeletId)){

```

```

47         $pipeletGroups[$pipeletPriority][$pipeletId] = new
           OpenPipe_Pipelet_Base($pipeletId, $phase);
48     }
49 }
50
51     //sort each groups array by pipelet id
52     foreach($pipeletGroups as $key => $pipeletGroup){
53         ksort($pipeletGroups[$key]);
54     }
55     //now that all groups are accounted for sort by priority
56     krsort($pipeletGroups);
57
58
59     //flatten all the segments to a single array
60     foreach($pipeletGroups as $pipeletGroup){
61         foreach($pipeletGroup as $pipelet){
62             $pipelets[] = $pipelet;
63         }
64     }
65
66     return $pipelets;
67 }
68
69 }

```

Listing 14.6: "OpenPipe/Output/Interface.php"

```

1 <?php
2
3 /**
4  * An interface defining the output mechanism for OpenPipe. This
      abstraction allows for the implementing class to handle individual

```

```

    pipelet output appropriately
5 * @author Sean Kenny <skenny214@gmail.com>
6 * @package OpenPipe_Pipelet
7 * @license (c) 2011-2012 Sean Kenny, Southern Connecticut State University
    (SCSU).
8 * @version 1.0.0
9 */
10 interface OpenPipe_Output_Interface {
11
12     /**
13      * Allow implementor to setup/output any data before the content phase
14      * begins
15      */
16     public function bootstrap();
17
18     /**
19      * Called immediately before any content is to be outputted via the
20      * associated content() method
21      */
22     public function preContent();
23
24     /**
25      * Called when content is ready for output - This content is already
26      * generated HTML string
27      * @param string $content html data
28      */
29     public function content($content);
30
31     /**

```



```

31  * Called when an output phase is complete -A phase represents a layer of
    data (each layer of data can contain n number of deeper layers)
32  * @param int $phase the number of the phase to mark complete
33  */
34  public function phaseComplete($phase);
35
36
37  /**
38  * Called immediately after all data has been sent for output
39  */
40  public function postContent();
41
42
43  /**
44  * Allows implementor to do any final cleanup/output - last step in the
    output process
45  */
46  public function clean();
47
48  }

```

Listing 14.7: "OpenPipe/Output/Piped.php"

```

1  <?php
2
3  require_once('Interface.php');
4  require_once('Util.php');
5
6  /**
7  * Implementation of an OpenPipe output interface that sends data via an
    HTTP pipeline.
8  * This is done by loading the openpipe.js client library and associated

```

```

    libraries.
9  * The output handler handles extracting pipelet html data, and
    transmitting it as packed JSON object -
10 * which will be unpacked by the client openpipe.js library
11 * @author Sean Kenny <skenny214@gmail.com>
12 * @package OpenPipe_Output
13 * @license (c) 2011-2012 Sean Kenny, Southern Connecticut State University
    (SCSU).
14 * @version 1.0.0
15 */
16 class OpenPipe_Output_Piped implements OpenPipe_Output_Interface {
17
18     /**
19      * the web path where the client openpipejs library will reside
20      * @var string the
21      */
22     protected $jsPath;
23
24
25     /**
26      * Builds an Piped output object
27      * @param string $jsPath the web path to the openpipejs client library
28      */
29     public function __construct($jsPath){
30         $this->jsPath = $jsPath;
31     }
32
33
34     /**
35      * Sends an initial string of output to force php and the browser to
        display piped output immediately

```

```

36  */
37  public function bootstrap(){
38      //set a 1024 newline - this forces soutput to the browser to start
39      echo str_repeat(" ",1024);
40      flush();
41  }
42
43
44  /**
45   * Outputs the framework for an HTTP Pipeline HTML document - this is
         essentially html and Javascript libraries - Note the html is unclosed
         (no ending body and html tags)
46  */
47  public function preContent(){
48      $header = "<!DOCTYPE HTML>\n<html><head>";
49      $header .= "<script type='text/javascript' src='{ $this->jsPath }/libs/";
         jquery.js' ></script>";
50      $header .= "<script type='text/javascript' src='{ $this->jsPath }/libs/";
         underscore.js'></script>";
51      $header .= "<script type='text/javascript' src='{ $this->jsPath }/";
         openpipe.js'></script>";
52      $header .= "<script type='text/javascript' >op.init();</script>";
53      $header .= ' </head><body><div pipelet-id="op-container"></div>';
54
55      OpenPipe_Output_Util::echoNow($header);
56  }
57
58
59
60  /**
61   * Extracts and outputs data in an openpipe.js friendly way

```

```

62  * @param string $content the content to be piped immediately - If CSS/JS
    is contained within the content this will be extracted and handled
    automatically
63  */
64  public function content($content){
65
66      if(is_string($content)){
67          $id = 'op-container';
68          $html = $content;
69      }else{
70          $id = $content->getId();
71          $html = $content->getOutput();
72      }
73
74      $css = array_merge(OpenPipe_Output_Util::extractLinkTags($html),
        OpenPipe_Output_Util::extractStyleTags($html));
75      $js = OpenPipe_Output_Util::extractScriptTags($html);
76
77      $html = str_replace("'", "\\'", $html);
78      $css = json_encode($css);
79      $js = json_encode($js);
80
81
82      OpenPipe_Output_Util::echoJsNow("op.load({'id': '$id', 'html': '$html
        ', 'css': $css, 'scripts': $js});");
83  }
84
85
86  /**
87  * Handles a phase complete signal by sending the openpipejs
    phaseComplete command to the client browser

```

```

88  * @param int $phase the number of the phase that has been completed
89  */
90  public function phaseComplete($phase){
91      OpenPipe_Output_Util::echoJsNow("op.phaseComplete($phase);");
92  }
93
94
95  /**
96  * Outputs the closing framework elements for an HTTP Pipeline HTML
97  * document - sends shutdown (done) method for client library and close
98  * initially open body and html tags
99  */
100 public function postContent(){
101     OpenPipe_Output_Util::echoJsNow('op.done();');
102     OpenPipe_Output_Util::echoNow('</body></html>');
103 }
104
105 /**
106 * This handler is always fresh and so clean clean
107 */
108 public function clean(){
109     //we're all clean!
110 }
111
112
113 }

```

Listing 14.8: "OpenPipe/Output/Standard.php"

```
1 <?php
```

```

2
3 require_once('Interface.php');
4 require_once('Util.php');
5
6 /**
7  * Implementation of an OpenPipe output interface that sends data as a
8   * standard HTML document
9  * Content pieces are used to construct a complete HTML document, placing
10   * CSS and JavaScript in proper
11   * placement, and inject each content piece within a pipelet place holder
12   * on the server side. It's
13   * important to note that no javascript is required to complete output on
14   * the client web browser while
15   * utilizing this output implementation
16   * @author Sean Kenny <skenny214@gmail.com>
17   * @package OpenPipe_Output
18   * @license (c) 2011-2012 Sean Kenny, Southern Connecticut State University
19   * (SCSU).
20   * @version 1.0.0
21 */
22 class OpenPipe_Output_Standard implements OpenPipe_Output_Interface {
23
24     /**
25      * linear array of style tags extracted from content and stored as string
26      * data
27      * @var array
28      */
29     protected $styles;
30
31     /**
32      * linear array of link tags extracted from content and stored as string

```

```

        data
27    * @var array
28    */
29    protected $links;
30
31    /**
32     * linear array of script tags extracted from content and stored as
33     * string data
34     * @var array
35     */
36    protected $scripts;
37
38    /**
39     * main html content stored as string and injected piece by piece as new
40     * content becomes available
41     * @var string
42     */
43    protected $content;
44
45    /**
46     * Setup all the variables that will be needed to generate proper output
47     */
48    public function bootstrap(){
49        $this->styles = array();
50        $this->links = array();
51        $this->scripts = array();
52        $this->content = '';
53    }
54

```

```

55  /**
56  * because standard output does not send any output until the end (clean
    method) - This method is not needed
57  */
58  public function preContent(){
59      //nothing to do for standard based output
60  }
61
62
63  /**
64  * takes content and builds an complete html document piece by piece
65  * @param string/OpenPipe_Pipelet_Interface $content the html content
    that will have data extracted and assigned for final output
66  */
67  public function content($content){
68      if(is_string($content)){
69          $id = '';
70          $html = $content;
71      }else{
72          $id = $content->getId();
73          $html = $content->getOutput();
74      }
75
76      //get the link, style, and script tages in each content section
77      $this->styles = array_merge($this->styles, OpenPipe_Output_Util::
    extractStyleTags($html));
78      $this->links = array_merge($this->links, OpenPipe_Output_Util::
    extractLinkTags($html));
79      $this->scripts = array_merge($this->scripts, OpenPipe_Output_Util::
    extractScriptTags($html));
80

```



```

81     $this->injectHtml($id, $html);
82 }
83
84
85 /**
86  * because standard output does not send any output until the end (clean
87   method) - This method is not needed
88  * @param int phase not needed
89  */
90 public function phaseComplete($phase){
91     //nothing to do for standard based output
92 }
93
94 /**
95  * because standard output does not send any output until the end (clean
96   method) - This method is not needed
97  */
98 public function postContent(){
99     //nothing to do for standard based output
100 }
101
102 /**
103  * Takes all of the gathered output and send the final html document as
104   part of this last step
105  */
106 public function clean(){
107     $finalOutput = "<!DOCTYPE HTML>\n<html><head>";
108
109     //put the collected scripts before body close

```

```

109     foreach($this->links as $link){
110         $finalOutput .= $link;
111     }
112
113     //put the collected styles in the head;
114     foreach($this->styles as $style){
115         $finalOutput .= $style;
116     }
117
118     $finalOutput .= '</head><body>';
119     $finalOutput .= $this->content;
120
121
122     //put the collected scripts before body close
123     foreach($this->scripts as $script){
124         $finalOutput .= $script;
125     }
126
127     $finalOutput .= '</body></html>';
128
129     echo $finalOutput;
130 }
131
132
133
134 /**
135 * Attempts to inject the given html data into the currently recorded
136 data - The point of injection is determined by the id provided
137 * @param string $pipeletId the identifier for the pipelet that will have
138 html content injected within it
139 * @param string $html the content that will be injected into the current

```

```

        gathered output
138 */
139 protected function injectHtml($pipeletId, $html){
140
141     //if the content is currently empty, no injection needs to take place.
        Just set as the content root
142     if($this->content == ''){
143         $this->content = $html;
144
145         //if we have content, find the injection point and perform the string
        replacement with a regex
146     }else{
147         $this->content = preg_replace("/(<.*?pipelet-id=(?:\"$pipeletId\"|'
            $pipeletId').*?>)/ms", "\\1 $html", $this->content);
148     }
149 }
150
151
152 }

```

Listing 14.9: "OpenPipe/Output/Util.php"

```

1 <?php
2
3 /**
4  * Utility object which provides reusable output based services for HTTP
        Pipeline based systems
5  * @author Sean Kenny <skenny214@gmail.com>
6  * @package OpenPipe_Output
7  * @license (c) 2011-2012 Sean Kenny, Southern Connecticut State University
        (SCSU).
8  * @version 1.0.0

```

```

9 */
10 class OpenPipe_Output_Util {
11
12     /**
13      * Given an html string extract the link information from the raw data
14      * and return
15      * @param string $html the html string to extract script tags from
16      * @return array strings containing link tags found within the html
17      * string
18      */
19     public static function extractLinkTags(&$html){
20         preg_match_all('/<link.*?\>/ms', $html, $matches, PREG_SET_ORDER);
21         $html = preg_replace('/<link.*?\>/ms', '', $html);
22
23         $links = array();
24         foreach($matches as $match){
25             $links[] = $match[0];
26         }
27
28         return $links;
29     }
30
31     /**
32      * Given an html string extract the style information from the raw data
33      * and return
34      * @param string $html the html string to extract style tags from
35      * @return array strings containing style tags found within the html
36      * string
37      */
38     public static function extractStyleTags(&$html){

```

```

36     preg_match_all('/<style.*?>.*?<\/style>/ms', $html, $matches,
37         PREG_SET_ORDER);
38
39     $html = preg_replace('/<style.*?>.*?<\/style>/ms', '', $html);
40
41     $styles = array();
42     foreach($matches as $match){
43         $styles[] = $match[0];
44     }
45
46     return $styles;
47 }
48
49 /**
50  * Given an html string extract the information from the raw data and
51  * return
52  * @param string $html the html string to extract script tags from
53  * @return array strings containing script tags found within the html
54  * string
55  */
56
57 public static function extractScriptTags(&$html){
58     preg_match_all('/<script.*?>.*?<\/script>/ms', $html, $matches,
59         PREG_SET_ORDER);
60
61     $html = preg_replace('/<script.*?>.*?<\/script>/ms', '', $html);
62
63     $scripts = array();
64     foreach($matches as $match){
65         $scripts[] = $match[0];
66     }
67
68     return $scripts;

```

```

63 }
64
65
66
67
68 /**
69  * Outputs javascript data in piped format - Piped format implies
        minimized and able to be placed in a pipe JavaScript array
70  * @param string $output the output data (javascript) to be wrapped in a
        javascript tagged and echoed immediately
71  * @param boolean $wrapTags wrap the output in a script opening and
        closing tag
72  * @param int/null $outputBufferSize the size of the buffer currently in
        use - used to determine how much passing must be used for output to
        skip buffering
73  * @param string $paddingCharacter the character that will be used if
        padding must occur
74  */
75 public static function echoJsNow($output, $wrapTags=true,
        $outputBufferSize=null, $paddingCharacter=' '){
76     $output = str_replace("\n", '', $output);
77     if($wrapTags === true) $output = '<script type="text/javascript" >'.
        $output.'</script>';
78
79     self::echoNow($output, $outputBufferSize, $paddingCharacter);
80 }
81
82
83 /**
84  * Highly reusable output method which echos data NOW - by NOW we mean in
        an intelligent way that takes into account output buffering in PHP

```

```

85  * as well as browser based deferred display of data (until data is of x
      bytes) - Using this utility method one should not have to worry about
      how
86  * to immediately send data to an end client browser NOW
87  * @param string $output the data to output NOW!
88  * @param int/null $outputBufferSize the output buffer currently in use -
      if a string is not of an output buffer length it will be padded to
      meet the minimum buffer size - If not provided this value will be
      looked up from the PHP ini configuration value
89  * @param string $paddingCharacter the character to pad output with if
      the buffer is larger than the data to output
90  */
91  public static function echoNow($output, $outputBufferSize=null,
      $paddingCharacter = ' '){
92
93      //if the output buffer is null, then attempt to get it from php ini
94      if($outputBufferSize === null){
95          $outputBufferSize = @ini_get('output_buffering');
96          if($outputBufferSize == 'Off') $outputBufferSize = 0;
97      }
98
99      //now that we know the buffer check to see how much we need to pad the
      string that is to be outputted
100  $bufferSpace = $outputBufferSize - strlen($output);
101  if($bufferSpace > 0){
102      $output = $output.str_repeat($paddingCharacter, $bufferSpace);
103  }
104
105  //echo the string (with possible padding), then flush!
106  echo $output;
107  flush();

```

```
108     }
109
110 }
```

Listing 14.10: "OpenPipe/Adapter/Interface.php"

```
1 <?php
2
3 /**
4  * An interface defining an adapter which bridges php based applications
5  * with OpenPipe. OpenPipe will call the adapter to load layouts and
6  * pipelets.
7  * In essence the adapter is responsible for making sure that the php based
8  * application is instantiated, bootstrapped, and run appropriately to
9  * obtain
10 * the request element (either layout or pipelet)
11 * @author Sean Kenny <skenny214@gmail.com>
12 * @package OpenPipe_Adapter
13 * @license (c) 2011-2012 Sean Kenny, Southern Connecticut State University
14 * (SCSU).
15 * @version 1.0.0
16 */
17 interface OpenPipe_Adapter_Interface {
18
19     /**
20      * return output from the php application for immediate piping
21      * @param OpenPipe_Pipelet_Interface $pipelet a pipelet which supplies
22      * information on
23      * @return mixed implementors are free to return what they will
24      */
25     function getOutput(OpenPipe_Pipelet_Interface $pipelet = null);
26 }
```



```

21  /**
22  * called once during the initialization of an OpenPipe runner
23  */
24  function bootstrap();
25
26  /**
27  * called once during the shut down of an OpenPipe runner
28  */
29  function clean();
30 }

```

Listing 14.11: "OpenPipe/Adapter/Abstract.php"

```

1  <?php
2
3  require_once('Interface.php');
4
5  /**
6  * Represents an abstract OpenPipe adapter. As an abstract class it
   provides basic services for obtaining the layout (root object for
   pipelets), and generating
7  * output for pipelets that are requested. Any object which extends this
   class will implement the getLayout() and getContent() methods. This
   abstract class will
8  * handle the details in regards to buffering output and sending it back to
   the requesting object.
9  * @author Sean Kenny <skenny214@gmail.com>
10 * @package OpenPipe_Adapter
11 * @license (c) 2011-2012 Sean Kenny, Southern Connecticut State University
   (SCSU).
12 * @version 1.0.0
13 */

```

```

14 abstract class OpenPipe_Adapter_Abstract implements
    OpenPipe_Adapter_Interface{
15
16     /**
17     * Returns output for the given pipelet - Output is web content (html,
        css, javascript) - If Pipelet is null then the layout is generated.
18     * @param OpenPipe_Pipelet_Interface/null $pipelet if not specified then
        the adapter will generate the pipelet layout by default
19     * @return string/OpenPipe_Pipelet_Interface given string output either
        generated for layout or a OpenPipe_Pipelet_Interface with output set
20     */
21     public function getOutput(OpenPipe_Pipelet_Interface $pipelet = null){
22
23         ob_start();
24
25         if($pipelet === null){
26             $this->getLayout();
27         }else{
28             $this->getContent($pipelet);
29
30         }
31
32         $output = ob_get_contents();
33         ob_end_clean();
34
35
36         if($pipelet !== null){
37             $pipelet->setOutput($output);
38             return $pipelet;
39         }else{
40             return $output;

```

```

41     }
42
43 }
44
45
46 /**
47  * Method should return the layout for the given web request
48  * @return string the root layout for all pipelets to be derived from
49  */
50 abstract protected function getLayout();
51
52 /**
53  * Method should return the layout for the given web request
54  * @param OpenPipe_Pipelet_Interface $pipelet the pipelet to get content
55  *      from
56  * @return string the root layout for all pipelets to be derived from
57  */
58 abstract protected function getContent(OpenPipe_Pipelet_Interface
59     $pipelet);
60
61 /**
62  * This abstract class does not provided any bootstrapping logic
63  */
64 public function bootstrap(){ }
65
66 /**
67  * This abstract class does not provided any clean logic
68  */
69 public function clean(){ }

```

70 }

Listing 14.12: "OpenPipe/Adapter/Basic.php"

```
1 <?php
2
3 require_once('Abstract.php');
4
5 /**
6  * A basic adapter which provides an implementation of the abstract adapter
7  * class. It simply loads layouts and pipelets from known directories
8  * given during
9  * the constructor process
10 * @author Sean Kenny <skenny214@gmail.com>
11 * @package OpenPipe_Adapter
12 * @license (c) 2011-2012 Sean Kenny, Southern Connecticut State University
13 * (SCSU).
14 * @version 1.0.0
15 */
16 class OpenPipe_Adapter_Basic extends OpenPipe_Adapter_Abstract {
17
18     /**
19      * The full path to the layouts php files that will be loaded by this
20      * adapter
21      * @var string
22      */
23     public $layoutsPath;
24
25     /**
26      * The full path to the pipelets php files that will be loaded by this
27      * adapter
28      * @var string
```

```

24     */
25     public $pipeletsPath;
26
27     /**
28      * Constructs a new Basic pipe adapter
29      * @param string $layoutsPath the full path to the layouts php file that
        will be loaded by this adapter
30      * @param string $pipeletsPath the full path to the pipelet php files
        that will be loaded by this adapter
31     */
32     public function __construct($layoutsPath, $pipeletsPath){
33         $this->layoutsPath = $layoutsPath;
34         $this->pipeletsPath = $pipeletsPath;
35     }
36
37     /**
38      * loads a php layout via include()
39      * @param string $id the id of the layout to be used - An id is the
        filename without the php extension - For example default.php would be
        default
40      * @return void
41     */
42     protected function getLayout($id='default'){
43         include($this->layoutsPath.'/'.$id.'.php');
44     }
45
46     /**
47      * loads a php pipelet via include()
48      * @param OpenPipe_Pipelet_Interface $pipelet the pipelet to load content
        for
49      * @return void

```

```

50  */
51  protected function getContent(OpenPipe_Pipelet_Interface $pipelet){
52      include($this->pipeletsPath.'/' . $pipelet->getId() . '.php');
53  }
54
55  }

```

Listing 14.13: "OpenPipe/Adapter/Pvc/CodeIgniter.php"

```

1  <?php
2
3  require_once(dirname(__FILE__).'../Abstract.php');
4
5  //declare global variables that CodeIgniter 2 needs to function. This will
   be called on before including code igniter files
6  $BM; $CFG; $UNI;
7
8
9  /**
10 * A PMVC adapter which provides an implementation of for CodeIgniter 2.x
   applications to take advantage of piped output
11 * @author Sean Kenny <skenny214@gmail.com>
12 * @package OpenPipe_Adapter
13 * @license (c) 2011-2012 Sean Kenny, Southern Connecticut State University
   (SCSU).
14 * @version 1.0.0
15 */
16 class OpenPipe_Adapter_Pvc_CodeIgniter extends OpenPipe_Adapter_Abstract {
17
18     /**
19      * The root path of the currently active CodeIgniter application
20      * @var string

```

```

21  */
22  protected $appRootPath;
23
24
25  /**
26   * The file name within the $appRootPath that bootstraps and runs a
      CodeIgniter application
27   * @var string
28   */
29  protected $indexFileName;
30
31  /**
32   * Constructs a new CodeIgniter pipe adapter
33   * @param string $appRootPath the root path of the currently active
      CodeIgniter application
34   * @param string $indexFileName the file name within the $appRootPath
      that bootstraps and runs a CodeIgniter application
35   * @return OpenPipe_Adapter_Pvc_CodeIgniter new instance of this object
36   */
37  public function __construct($appRootPath, $indexFileName='index.pipe.php
      '){
38      $this->appRootPath = rtrim($appRootPath, '/');
39      $this->indexFileName = $indexFileName;
40  }
41
42  /**
43   * loads a php layout by starting the code igniter index file
44   */
45  protected function getLayout(){
46      global $BM, $CFG, $UNI;
47      include($this->appRootPath.'/'. $this->indexFileName);

```

```

48
49 }
50
51 /**
52  * loads a php pipelet via CodeIgniter controller - being sure to play
    nice with output class
53  * @param OpenPipe_Pipelet_Interface $pipelet the pipelet to be used.
54  */
55 protected function getContent(OpenPipe_Pipelet_Interface $pipelet){
56     global $BM, $CFG, $UNI;
57
58     $CI = &get_instance();
59     $CI->output->set_output('');
60
61     call_user_func_array(array($CI, $pipelet->getId()), array());
62
63     $CI->output->_display();
64 }
65
66 }

```

Listing 14.14: "openpipe.js"

```

1 //      OpenPipe.js 1.0.0
2 //      (c) 2011-2012 Sean Kenny, Southern Connecticut State University (
    SCSU).
3 //      OpenPipe is freely distributable under the MIT license.
4
5 (function() {
6
7     //debug vars - for timing
8     var isDebug = (document.location.search.indexOf('debug=true') != -1);

```



```

9   var debugInitTime;
10  var debugDoneTime;
11  var debugLastSegmentLoadTime;
12
13
14  // Establish the root object, 'window' in the browser, or 'global' on
    the server.
15  var root = this;
16
17  // Save the previous value of the 'op' variable.
18  var previousOpenPipe = root.op;
19
20  var isFirstSegment = true;
21
22  var lastPhase = 0;
23  var phases = [];
24  var scripts = [];
25
26
27  var op = {};
28
29  //if this is debug then record performance statistics
30  if(isDebug === true){
31      op.performance = {};
32      op.performance.timing = {};
33      op.performance.timing.segments = [];
34  }
35
36  //init the OpenPipe client - hide pipelets initally (no FLOCs)
37  op.init = function(){
38      //record times for logging

```

```

39     if(isDebug === true){
40         debugInitTime = new Date().getTime();
41         debugLastSegmentLoadTime = debugInitTime;
42     }
43
44     $("*[pipelet-loading-indicator]").append('<div class="op-loading">
45         loading</div>');
46     $("*[pipelet-auto-show='true']").hide();
47 };
48
49 //load a given segment object into the pipelined document
50 op.load = function(segment){
51     this.loadSegment(segment);
52
53     //record times and output to the log
54     if(isDebug === true){
55         var debugCurrentSegmentLoadTime = new Date().getTime();
56         op.performance.timing.segments.push(debugCurrentSegmentLoadTime);
57         console.log('SEGMENT "' + segment.id + '" LOAD TIME: ' + (
58             debugCurrentSegmentLoadTime - debugLastSegmentLoadTime));
59         console.log('TIME UNTIL SEGMENT: ' + (debugCurrentSegmentLoadTime -
60             debugInitTime));
61         debugLastSegmentLoadTime = debugCurrentSegmentLoadTime;
62     }
63 };
64
65 //register a given phase from a segment
66 op.registerPhase = function(phase){
67     if(typeof(phase) == 'undefined') phase = 0;
68     if(typeof(phases[phase]) == 'undefined') phases[phase] = phase;

```

```

67     };
68
69     //mark a phase complete. A completed phase has its deferred JavaScript
        elemetns loaded (and consequently run)
70     op.phaseComplete = function(phase){
71         lastPhase = phase;
72         this.loadScripts(phase);
73     };
74
75
76     //mark the pipeline as completed. For all the phases mark complete if
        not already done (load all JavaScript for any phases where complete
        notification was not sent)
77     op.done = function(){
78         var that = this;
79         _.each(phases, function(phase){
80             if(phase > lastPhase) that.phaseComplete(phase);
81         });
82
83         if(isDebug === true){
84             debugDoneTime = new Date().getTime();
85             console.log('TOTAL LOAD TIME: '+(debugDoneTime-debugInitTime));
86         }
87
88     };
89
90
91
92     //load an pipeline segment. A segment contains an id (element to load on
        page), css, html and JavaScript. The id is found, css is loaded,
        html is loaded , and JavaScript is queued until the end of the

```

```

    segments phase
93 op.loadSegment = function(segment){
94     if(isFirstSegment === true){
95         isFirstSegment = false;
96         $("*[pipelet-loading-indicator]").hide();
97     }
98
99     this.registerPhase(segment.phase);
100
101     if(typeof(segment.css) != 'undefined') this.loadCss(segment.css);
102     if(typeof(segment.html) != 'undefined') this.loadHtml(segment.html,
        segment.id);
103     $("*[pipelet-id='"+segment.id+"'").show();
104
105     if(typeof(segment.scripts) != 'undefined') this.pushScripts(segment.
        scripts, segment.phase);
106 };
107
108
109
110 //load html into the given #id'ed element by appending
111 op.loadHtml = function(html, id){
112     if(typeof(id) == 'undefined') id = 'content';
113
114     $("*[pipelet-id='"+id+"'").append(html);
115 };
116
117 //load css into the head of the documents
118 op.loadCss = function(css){
119
120     var that = this;

```

```

121     _ .each(css, function(css_item){
122         $('head').append(css_item);
123     });
124
125
126 };
127
128
129
130 //push a set of script blocks onto a phase of the pipeline cycle. Once
    the phase is marked complete all the scripts in that phase will be
    loaded (and executed)
131 op.pushScripts = function(scripts, phase){
132
133     var that = this;
134     _ .each(scripts, function(script){
135         that.pushScript(script, phase);
136     });
137
138 };
139
140 //push a single script block onto a phase of the pipeline cycle. Once
    the phase is marked complete all the script in that pahse will be
    loaded (and execueted)
141 op.pushScript = function(script, phase){
142     if(typeof(phase) == 'undefined') phase=lastPhase+1;
143     if(typeof(scripts[phase]) == 'undefined') scripts[phase] = [];
144     scripts[phase].push(script);
145 };
146
147 //loads all the pusheds script for a given phase

```

```

148 op.loadScripts = function(phase){
149     var that = this;
150     _.each(scripts[phase], function(script_item){
151         jq_script = $(script_item);
152
153         //if this is an external javascript then we make a new dom object to
154         house it from the string data
155         if(typeof(jq_script.src) != 'undefined'){
156             var script = document.createElement('script');
157             script.type = jq_script.attr('type') || '';
158             script.src = jq_script.attr('src') || '';
159             $('body').append(script);
160
161             //if this was just an internal javascript append to body and jquery
162             will execute it
163         } else {
164             $('body').append(script_item);
165         }
166     });
167
168     //set the root open pipe object
169     root['op'] = op;
170
171
172
173 }).call(this);

```

Bibliography

- [1] "BigPipe: Pipelining web pages for high performance", Facebook, June 2010. [Online] Available: <http://www.facebook.com/notes/facebook-engineering/bigpipe-pipelining-web-pages-for-high-performance/389414033919> [Retrieved December 2010]
- [2] "Part of Hypertext Transfer Protocol – HTTP/1.1 – 8 - Connections" [Online] Available: <http://www.w3.org/Protocols/rfc2616/rfc2616-sec8.html> [Retrieved December 2010]
- [3] "Optimizing Page Load Time", Aaron Hopkins [Online] Available: http://www.die.net/musings/page_load_time/ [Retrieved December 2010]
- [4] "What is HTTP pipelining", Darin Fisher [Online] Available: <http://www.mozilla.org/projects/netlib/http/pipelining-faq.html> [Retrieved December 2010]
- [5] "Navigation Timing", Editor's Draft July 16th, 2012 [Online] Available: dvcs.w3.org/hg/webperf/raw-file/tip/specs/NavigationTiming/Overview.html
- [6] "Siege Home", January 30, 2012 [Online] Available: www.joedog.org/siege-home
- [7] "PHP" [Online] Available: <http://en.wikipedia.org/wiki/PHP>
- [8] "March 2012 Web Server Survey" [Online] Available: <http://news.netcraft.com/archives/2012/03/05/march-2012-web-server-survey.html>

[9] Steve Souders, High Performance Websites, Oreilly Media, September 2007

[10] Steve Souders, Even Faster Web Sites: Performance Best Practices for Web Developers, Oreilly Media, June 2009