

	INITIAL SURVEY	FINAL SURVEY
MV "RC Gemini"	Inner roads 9.2	Wharf 212
	06 05 2026 - 14:20 h	11 05 2026 - 07 15 h
	0,10 m. waves	0,20 m. waves
IMO NO. 9452610 FLAG: Marshalllesse BUILD: 2008	Wind force 01	Wind force 02
DRAUGHT SURVEY CERTIFICATE	No tide flow	Flood tide >1knot
PGUA/DS/142/26	Weather: Sunny	Weather: Sunny
DRAUGHT	INITIAL	FINAL
Forward port	4,7500 m	12,6700 m
Forward starboard	4,7800 m	12,6100 m
Forward mean	4,7650 m	12,6400 m
Stern correction	-0,0884 m	-0,0273 m
Draught forward (corrected to fore perpendicular)	4,6766 m	12,6127 m
Midship port	5,6400 m	12,9100 m
Midship starboard	5,6900 m	12,8000 m
Midship mean	5,6650 m	12,8550 m
Midship correction	-0,0190 m	-0,0190 m
Draught midship (corrected to midship perpendicular)	5,6460 m	12,8360 m
Aft port	6,6900 m	12,9200 m
Aft starboard	6,7000 m	12,8200 m
Aft mean	6,6950 m	12,8700 m
Stern correction	0,0905 m	-0,0059 m
Draught after (corrected to after perpendicular)	6,7855 m	12,8641 m
Kell correction	0,0190 m	0,0190 m
Waterplane coefficient correction for hull deflexion	0,0086 m	-0,0141 m
Means of means corrected for deflexion:	5,6758 m	12,7975 m
True trim	BY STERN 2,11 m	BY STERN 0,25 m
Heel (angle & in cm)	S 000 ° 5,00 cm	P 000 ° 11,00 cm
Hull deflexion:	HOGGING 8,50 cm	SAGGING 9,76 cm
DISPLACEMENTS	INITIAL	FINAL
Displacement in salt water	33 123,0 t	80.616,6 t
First trim correction	-443,1 t	26,8 t
Second trim correction	40,1 t	0,3 t
Displacement corrected for trim	32 719,9 t	80 643,6 t
Water density	1,01950	1,01950
Displacement corrected for density	32 544,4 t	80 210,9 t
Deductibles (fresh water, oils, etc.)	18 191,7 t	2 107,2 t
Displacement corrected for deductibles	14.352,6 t	78.103,7 t
Light Ship	13.699,8 t	
Calculated constant	679,5 t	
Anchor + chain	26,7 t	0,0 t
Total cargo loaded on board as per draught survey		63724,4 t
Loading terminals: CG, B1, CT, IT, RO, .	TPC	63,3 t/cm
Cargo: Soybean meal in bulk	MTC +0.5	912,5 t/cm
Paranaguá, Br - Brazil. May 11th, 2026	MTC -0.5	872,5 t/cm
Total cargo loaded on board as per shore scales		63.656,520 t
Total cargo loaded on board as per draught survey		63.724,387 t
Surplus	67,867 t	0,11 %

Remarks: 1) Due to huge hull deflexion in hogging on initial draft survey and sagging on final draft survey, it was applied the waterplane area coefficient correction for the deflexion formula as per UNECE/Energy/19/1992. 2) According to the Master/Chief Officer usual constant would amount to 450 t.

Standard Brazil Marine Surveys & Services Ltda.
José Antonio Machado Gomes Pereira / Armando do R. A. Araujo Junior
Licensed Marine Officer / Marine Surveyor / 375460MM

Master/Ch.Off: 63.728.832 t 72,312 t 0,11 %
Customs: 63.731.924 t 75,404 t 0,12 %

Master/Ch.Off: