

MV "Orpheus"		INITIAL SURVEY		FINAL SURVEY	
		Inner roads 9.1		Wharf 214	
		14.05.2026 - 10:00 h		20.05.2026 - 17:40 h	
		0.15 m. waves		0.15 m. waves	
IMO NO. 9646675	FLAG: Liberian	BUILD: 2017			
DRAUGHT SURVEY CERTIFICATE				Ebb tide, < 1knot	
PGUA/DS/150/26				Weather: Fine	
				Weather: Overcast	
DRAUGHT				INITIAL	
Forward port				5.0400 m	
Forward starboard				5.0600 m	
Forward mean				5.0500 m	
Stem correction				-0.0152 m	
Draught forward (corrected to fore perpendicular)				5.0348 m	
Midship port				6.0600 m	
Midship starboard				6.1400 m	
Midship mean				6.1000 m	
Midship correction				0.0000 m	
Draught midship (corrected to midship perpendicular)				6.1000 m	
Aft port				7.2700 m	
Aft starboard				7.2900 m	
Aft mean				7.2800 m	
Stern correction				0.1176 m	
Draught after (corrected to after perpendicular)				7.3976 m	
Kell correction				0.0000 m	
Waterplane coefficient correction for hull deflexion				0.0120 m	
Means of means corrected for deflexion:				6.1411 m	
True trim				BY STERN 2.36 m	
Heel (angle & in cm)				S 0.14 ° 8.00 cm	
Hull deflexion:				HOGGING 11.62 cm	
DISPLACEMENTS				INITIAL	
Displacement in salt water				35,982.1 t	
First trim correction				-483.5 t	
Second trim correction				45.2 t	
Displacement corrected for trim				35,543.7 t	
Water density				1.01950	
Displacement corrected for density				35,353.0 t	
Deductibles (fresh water, oils, etc.)				21,401.5 t	
Displacement corrected for deductibles				13,951.6 t	
Light Ship				13,539.6 t	
Calculated constant				445.9 t	
Anchor + chain				33.9 t	
Total cargo loaded on board as per draught survey				0.0 t	
				60733.4 t	
Loading terminals: CO, RO, .				TPC	62.2 t/cm
Cargo: Soybean meal in bulk				MTC +0.5	889.8 t*cm
Paranaguá, Br - Brazil. May 20th, 2026				MTC -0.5	854.7 t*cm
Total cargo loaded on board as per shore scales				60,481.090 t	
Total cargo loaded on board as per draught survey				60,733.423 t	
Surplus				252.333 t 0.42 %	

Remarks: 1) Due to huge hull deflexion in hogging on initial draft survey, it was applied the waterplane area coefficient correction for the deflexion formula as per UN/ECE/Energy/19/1992. 2) According to the Master/Chief Officer usual constant would amount to 550 t.

Standard Brazil Marine Surveys & Services Ltda.

José Antonio Machado Gomes Pereira / Marcelo Fernandes Alves Junior

Licensed Marine Officer / Marine Surveyor / 374460MM

Master/Ch. Off: 60,779.555 t

298.465 t

0.49 %

Charterers: 60,747.335 t

266.245 t

0.44 %

