


Problem List

DescriptionEditorialSolutionsSubmissions

Given the head of a linked list and an integer val, remove all the nodes of the linked list that has Node.val == val, and return the new head.

Example 1:



Input: head = [1,2,6,3,4,5,6], val = 6
Output: [1,2,3,4,5]

Example 2:

Input: head = [], val = 1
Output: []

Example 3:

Input: head = [7,7,7,7], val = 7
Output: []

Constraints:

- The number of nodes in the list is in the range [0, 10⁴].
- 1 <= Node.val <= 50
- 0 <= val <= 50

8.9K8544 Online

Code

C++Auto

1/**

SavedLn 14, Col 25

TestcaseTest Result

AcceptedRuntime: 0 ms

Case 1Case 2Case 3

Input

head =
[]

val =
1

Output

[]

Expected

[]


Contribute a testcase

Problem List

DescriptionEditorialSolutionsSubmissions

Given the head of a linked list and an integer val, remove all the nodes of the linked list that has Node.val == val, and return the new head.

Example 1:



Input: head = [1,2,6,3,4,5,6], val = 6
Output: [1,2,3,4,5]

Example 2:

Input: head = [], val = 1
Output: []

Example 3:

Input: head = [7,7,7,7], val = 7
Output: []

Constraints:

- The number of nodes in the list is in the range [0, 10⁴].
- 1 <= Node.val <= 50
- 0 <= val <= 50

8.9K8544 Online

Code

C++Auto

1/**

SavedLn 14, Col 25

TestcaseTest Result

AcceptedRuntime: 0 ms

Case 1Case 2Case 3

Input

head =
[1,2,6,3,4,5,6]

val =
6

Output

[1,2,3,4,5]

Expected

[1,2,3,4,5]

Contribute a testcase