

```
mysql> CREATE FUNCTION customerlevel(p_CREDITLIMIT INT)
-> RETURNS VARCHAR(10)
-> DETERMINISTIC
-> BEGIN
-> DECLARE lvl VARCHAR(10);
-> IF p_CREDITLIMIT>50000 THEN
-> SET lvl='platinum';
-> ELSEIF (p_CREDITLIMIT<=50000 AND p_CREDITLIMIT>=10000) THEN
-> SET lvl='Gold';
-> ELSEIF p_CREDITLIMIT<10000 THEN
-> SET lvl='Silver';
-> END IF;
-> RETURN(lvl);
-> END
-> //
```

Query OK, 0 rows affected (0.484 sec)

```
mysql> SELECT cname, customerlevel(p_CREDITLIMIT) AS Customer_Level
-> FROM customer
-> ORDER BY cname;
-> DELIMITER //
```

cname	Customer_Level
Anu	Gold
Kiran	Silver
Priya	Gold
Rahul	Gold
Ravi	platinum
Sita	Silver

6 rows in set (0.025 sec)

```
mysql> DELIMITER //
mysql> CREATE PROCEDURE factorial(IN n INT, OUT fact INT)
-> BEGIN
-> IF n = 1 THEN
-> SET fact := 1;
-> ELSE
-> CALL factorial(n - 1, fact);
-> SET fact := n * fact;
-> END IF;
-> END //
```

```
mysql> DELIMITER ;
mysql> CALL factorial(5, @fact);
Query OK, 0 rows affected (0.338 sec)
```

```
mysql>
mysql> SELECT @fact AS Factorial;
+-----+
| Factorial |
```

120

1 row in set (0.007 sec)