

```
sravya@Sravya1955:~/os$ mkdir fifo_project
sravya@Sravya1955:~/os$ cd fifo_project
sravya@Sravya1955:~/os/fifo_project$ pwd
/home/sravya/os/fifo_project
```

```
GNU nano 7.2
#include <stdio.h>
#include <stdlib.h>
#include <string.h>
#include <fcntl.h>
#include <unistd.h>
#include <sys/stat.h>

#define FIF01 "client_to_server"
#define FIF02 "server_to_client"
#define SIZE 100

int main() {
    char message[SIZE];

    mkfifo(FIF01, 0666);
    mkfifo(FIF02, 0666);

    printf("Server waiting for client...\n");

    int read_fd = open(FIF01, O_RDONLY);
    int write_fd = open(FIF02, O_WRONLY);

    while (1) {
        memset(message, 0, SIZE);

        read(read_fd, message, SIZE);

        if (strcmp(message, "exit") == 0)
            break;

        printf("Client: %s\n", message);

        printf("Server response: ");
        fgets(message, SIZE, stdin);
        message[strcspn(message, "\n")] = '\0';

        write(write_fd, message, strlen(message) + 1);
```

```
        if (strcmp(message, "exit") == 0)
            break;
    }

    close(read_fd);
    close(write_fd);

    unlink(FIFO1);
    unlink(FIFO2);

    printf("Server terminated.\n");

    return 0;
}
```

```
sravya@Sravya1955:~/os/fifo_project$ nano server.c
sravya@Sravya1955:~/os/fifo_project$ cd fifo_project
-bash: cd: fifo_project: No such file or directory
sravya@Sravya1955:~/os/fifo_project$ gcc server.c -o server
sravya@Sravya1955:~/os/fifo_project$ ls
server  server.c
```

```
GNU nano 7.2
#include <stdio.h>
#include <stdlib.h>
#include <string.h>
#include <fcntl.h>
#include <unistd.h>

#define FIFO1 "client_to_server"
#define FIFO2 "server_to_client"
#define SIZE 100

int main() {
    char message[SIZE];

    int write_fd = open(FIFO1, O_WRONLY);
    int read_fd = open(FIFO2, O_RDONLY);

    while (1) {
        printf("Enter message: ");
        fgets(message, SIZE, stdin);

        message[strcspn(message, "\n")] = '\0';

        write(write_fd, message, strlen(message) + 1);

        if (strcmp(message, "exit") == 0)
            break;

        memset(message, 0, SIZE);

        read(read_fd, message, SIZE);

        printf("Server: %s\n", message);

        if (strcmp(message, "exit") == 0)
            break;
    }
}
```

```
sravya@Sravya1955:~$ cd ~/os
sravya@Sravya1955:~/os$ cd ~/os/fifo_project
sravya@Sravya1955:~/os/fifo_project$ ./client
-bash: ./client: No such file or directory
sravya@Sravya1955:~/os/fifo_project$ gcc client.c -o client
sravya@Sravya1955:~/os/fifo_project$ ./client
Enter message: hello
Server:
Enter message:
```

```
sravya@Sravya1955:~/os/fifo_project$ ./server
Server waiting for client...
```

```
Client: hello
Server response:
```