```c
#include <stdio.h>
#include <unistd.h>
#include <signal.h>

int main() {
    sigset_t set;

    sigemptyset(&set);
    sigaddset(&set, SIGINT);

    sigprocmask(SIG_BLOCK, &set, NULL);
    printf("SIGINT blocked for 5 seconds. Press Ctrl+C.\n");

    sleep(5);

    sigprocmask(SIG_UNBLOCK, &set, NULL);
    printf("SIGINT unblocked.\n");

    return 0;
}
```

```
  GNU nano 7.2
#include <stdio.h>
#include <unistd.h>
#include <signal.h>
#include <sys/wait.h>

int main() {
    pid_t pid = fork();

    if (pid < 0) {
        perror("fork");
        return 1;
    }

    if (pid == 0) {
        printf("Child running: PID %d\n", getpid());
        for (int i = 1; i <= 10; i++) {
            printf("Working: %d\n", i);
            sleep(1);
        }
        return 0;
    }

    sleep(2);
    printf("Stopping child...\n");
    kill(pid, SIGSTOP);

    sleep(2);
    printf("Resuming child...\n");
    kill(pid, SIGCONT);

    waitpid(pid, NULL, 0);
    printf("Child completed.\n");

    return 0;
}
```

```
sravya@Sravya1955:~$ cd ~/os
sravya@Sravya1955:~/os$ nano q17a.c
sravya@Sravya1955:~/os$ gcc q17a.c -o q17a
sravya@Sravya1955:~/os$ ./q17a
SIGINT blocked for 5 seconds. Press Ctrl+C.
SIGINT unblocked.
sravya@Sravya1955:~/os$ nano q17b.c
sravya@Sravya1955:~/os$ gcc q17b.c -o q17b
sravya@Sravya1955:~/os$ ./q17b
Child running: PID 1294
Working: 1
Working: 2
Stopping child...
Resuming child...
Working: 3
Working: 4
Working: 5
Working: 6
Working: 7
Working: 8
Working: 9
Working: 10
Child completed.
sravya@Sravya1955:~/os$
```