```
  GNU nano 7.2
#include <stdio.h>
#include <string.h>

int main() {
    char input[100];

    while (1) {
        printf("> ");
        fflush(stdout);

        if (fgets(input, sizeof(input), stdin) == NULL)
            break;

        input[strcspn(input, "\n")] = '\0';

        if (strcmp(input, "exit") == 0) {
            printf("Exit\n");
            break;
        }

        printf("Processed input: %s\n", input);
    }

    return 0;
}
```

```
  GNU nano 7.2
CC = gcc
CFLAGS = -Wall -Wextra
TARGET = q24a

all: $(TARGET)

$(TARGET): q24a.c
        $(CC) $(CFLAGS) q24a.c -o $(TARGET)

clean:
        rm -f $(TARGET)
```

```
  GNU nano 7.2
# Question 24 - Command Processing

## Description
A C program that reads user input and processes it
until the user enters exit.

## Requirements
- GCC compiler
- Linux or Ubuntu

## Compilation
make

## Execution
./q24a

## Cleanup
make clean
```

```
  GNU nano 7.2
#!/bin/bash

set -e

gcc -Wall -Wextra q24a.c -o q24a

output=$(printf 'hello\ntest\nexit\n' | ./q24a)

echo "$output"

echo "$output" | grep -q "Processed input: hello"
echo "$output" | grep -q "Processed input: test"
echo "$output" | grep -q "Exit"

echo "All tests passed successfully."
```

```
sravya@Sravya1955:~/os$ nano test_q24.sh
sravya@Sravya1955:~/os$ chmod +x test_q24.sh
sravya@Sravya1955:~/os$ ./test_q24.sh
> Processed input: hello
> Processed input: test
> Exit
All tests passed successfully.
sravya@Sravya1955:~/os$ gcc -Wall -Wextra q24a.c -o q24a
sravya@Sravya1955:~/os$ ./q24a
> hello
Processed input: hello
> text
Processed input: text
> exit
Exit
```