```
  GNU nano 7.2
#include <stdio.h>
#include <fcntl.h>
#include <unistd.h>
#include <string.h>

int main() {
    int fd = open("append.txt",
                  O_WRONLY | O_CREAT | O_APPEND, 0644);

    if (fd < 0) {
        perror("append.txt");
        return 1;
    }

    const char *message = "New appended line\n";

    ssize_t n = write(fd, message, strlen(message));

    if (n < 0)
        perror("write");

    close(fd);

    return n < 0;
}
```

```
  GNU nano 7.2
#include <stdio.h>
#include <fcntl.h>
#include <unistd.h>

int main() {
    int fd = open("error.txt",
                  O_WRONLY | O_CREAT | O_TRUNC, 0644);

    if (fd < 0) {
        perror("error.txt");
        return 1;
    }

    if (dup2(fd, STDERR_FILENO) < 0) {
        close(fd);
        return 1;
    }

    close(fd);

    fprintf(stderr, "This is a test error message\n");
    fprintf(stderr, "Error stream redirected successfully\n");

    return 0;
}
```

```
Output saved successfully
sravya@Sravya1955:~/os$ nano q14a.c
sravya@Sravya1955:~/os$ gcc q14a.c -o q14a
sravya@Sravya1955:~/os$ echo "Original line" > append.txt
sravya@Sravya1955:~/os$ ./q14a
sravya@Sravya1955:~/os$ cat append.txt
Original line
New appended line
sravya@Sravya1955:~/os$ nano q14b.c
sravya@Sravya1955:~/os$ gcc q14b.c -o q14b
sravya@Sravya1955:~/os$ ./q14b
sravya@Sravya1955:~/os$ cat error.txt
This is a test error message
Error stream redirected successfully
sravya@Sravya1955:~/os$
```