

```

#include <stdio.h>
#include <stdlib.h>
#include <fcntl.h>
#include <unistd.h>

int main()
{
    int src, dest;
    char buffer[1024];
    ssize_t bytes;

    src = open("source.txt", O_RDONLY);

    if (src < 0)
    {
        perror("Cannot open source file");
        return 1;
    }

    dest = open("destination.txt", O_WRONLY | O_CREAT | O_TRUNC, 0644);

    if (dest < 0)
    {
        perror("Cannot create destination file");
        close(src);
        return 1;
    }

    while ((bytes = read(src, buffer, sizeof(buffer))) > 0)
    {
        write(dest, buffer, bytes);
    }

    close(src);
    close(dest);

    printf("File copied successfully.\n");
}

```

```

GNU nano 7.2
Hello!
This is Operating Systems Lab.
Learning system calls in Linux.

```

```

sravya@Sravya1955:~/os$ ls
MyProject  exec  filecopy.c  os.c  os1.2.c  os1.c  os14.c  os2.c  os4.c  os6.c  os8.c  test.txt
destination.txt  filecopy  os  os1.1.c  os1.3.c  os1.xc  os15.c  os3.c  os5.c  os7.c  source.txt

```

```
destination.txt filecopy OS OS1.1.C OS1.3.C  
sravya@Sravya1955:~/os$ gcc filecopy.c -o filecopy  
sravya@Sravya1955:~/os$ ./filecopy  
File copied successfully.
```

```
sravya@Sravya1955:~/os$ cat destination.txt  
Hello!  
This is Operating Systems Lab.  
Learning system calls in Linux.
```