

# System Design

---

## Lecture 09

# Overview

---

**Design I:** System decomposition

1. Overview of System Design
2. Identify Design Goals
3. Design Initial Subsystem Decomposition

**Design II:** Refine subsystem decomposition

**Design III:** Object-level design

# Design is Difficult

There are two ways of constructing a software design (Tony Hoare):

One way is to make it **so simple** that there are obviously no deficiencies


The other way is to make it **so complicated** that there are no obvious deficiencies.”



Sir **Antony Hoare**, \*1934

- Quicksort
- Hoare logic for verification

# The activities of system design.




# The Scope of System Design

Bridge the gap  
between a problem and an  
existing system in a  
manageable way


How?

Use Divide & Conquer:


- 1) Identify design goals
- 2) Model the new system design as a set of subsystems
- 3-8) Address the major design goals.



# System Design: Eight Issues



# Analysis Sources: Requirements and System Model



# Why is Design so Difficult?

---

**Analysis:** Focuses on the application domain

**Design:** Focuses on the solution domain

**The solution domain is changing very rapidly**

- Halftime knowledge in software engineering: About 3-5 years
- Cost of hardware rapidly sinking
- Design knowledge is a moving target

**Design window:** Time in which design decisions have to be made.



# System Design Concepts

---

## Subsystems

**Coupling:** dependency between two subsystems

**Cohesion:** dependencies within a subsystem

Desire LOW coupling and HIGH cohesion

## Refinement

Layering

Partitions

## Software Architecture Patterns

Repository

Model/View/Controller

Client/Server

Peer-To-Peer

3-Tier (4-Tier)

Pipe and Filter

# Coupling and Cohesion

---

**Goal:** Reduction of *complexity while change occurs*

Cohesion measures the dependence among classes

**High cohesion:** The classes in the subsystem perform similar tasks and are related to each other (via associations)

**Low cohesion:** Lots of miscellaneous and auxiliary classes, no associations

Coupling measures dependencies between subsystems


**High coupling:** Changes to one subsystem will have high impact on the other subsystem (change of model, massive recompilation, etc.)

**Low coupling:** A change in one subsystem does not affect any other subsystem


# Coupling and Cohesion

**Coupling** is a measure of the **interdependence** among **components** in a computer program.


Low coupling is desired




uncoupled



Loosely coupled



Highly coupled



# Content coupling

```
void f() {  
  // block X  
  ....  
  goto Y;  
  .....  
  // block Z  
  ...  
  goto X;  
  ....  
  // block Y  
  .....  
  goto Z;  
}
```

```
class X {  
  void mX(Y y) {  
    ...  
    // change fY value  
    y.fY = ...;  
    ...  
  }  
}
```

```
class Y {  
  public int fY;  
  void mY() {  
    // change fY value  
    ...  
    // use fY value  
  }  
}
```

## Content coupling:

Content coupling exists between two modules, if they share code, e.g. a branch from one module into another module.


# Control coupling

```
class X {  
    void mX(Y y) {  
        ...  
        y.mY(flag);  
        ...  
    }  
}
```

```
class Y {  
    void mY(int flag) {  
        if (flag >= LIMIT_A) {  
            ... // block A  
        }  
        else if (flag < LIMIT_B) {  
            ... // block B  
        } else { ... }  
    }  
}
```

**Control coupling:**  
Control coupling exists between two modules, if data from one module is used to direct the order of instructions execution in another.

# Common coupling



## Common coupling:

Two modules are common coupled, if they **share data** through some **global data** items.

# Stamp coupling

```
class X {  
    void mX(MyList commonRepr) {  
        ...  
        // accesses only 2nd element  
        dataForX = commonRepr.get(2);  
        ...  
    }  
}
```

```
class Y {  
    void mY(MyList commonRepr) {  
        // accesses only 4th element  
        dataForY = commonRepr.get(4);  
    }  
}
```

**Stamp coupling:**  
Two modules are stamp coupled, if they communicate using a composite data.

# Data coupling

```
class X {  
    void mX() {  
        ...  
        Y yObject;  
        ....  
        yObject.mY(iVar, dVar, sVar);  
    }  
}
```


**Data coupling:** Two modules are data coupled, if they **communicate through parameter.**

```
class Y {  
    void mY(int iPar, double dPar, String sPar) {  
        // ...  
    }  
}
```



# Cohesion

**Cohesion** is a measure of the **strength of association** of the elements within a component.



# Coincidental Cohesion

```
class GodModule {  
    void accessPrinter() {  
        // many variables  
        // many Lines of Code  
    }  
    void drawChart() {  
        // many variables  
        // many Lines of Code  
    }  
    void connectToDatabase() {  
        // many variables  
        // many Lines of Code  
    }  
}
```

**Coincidental cohesion:** A module is said to have coincidental cohesion, if it performs a **set of tasks that relate to each other very loosely**, if at all.


Function A	
Function B	Function C
Function D	Function E

Parts unrelated

# Logical Cohesion

```
class InputReader {
    char[] getInput(int flag) {
        if(flag == 1)
            getInputFromFile();
        else
            if(flag == 2)
                getInputFromDatabase();
            else .....
    }
    char[] getInputFromFile() {
        // many variables
        // many Lines of Code
    }
    char[] getInputFromDatabase() {
        // many variables
        // many Lines of Code
    }
    char[] getInputFromKeyboard() {...}
}
```

**Logical cohesion:** A module is said to be logically cohesive, if **all elements** of the module perform **similar operations**.



# Temporal Cohesion

```
class Initializer {  
    void initAll() {  
        initDatabase();  
        initNetwork();  
    }  
    void initNetwork() {  
        // many variables  
        // many Lines of Code  
    }  
    void initDatabase() {  
        // many variables  
        // many Lines of Code  
    }  
}
```

**Temporal cohesion:** When a module contains functions that are related by the fact that all the functions must be executed in the same time span

Time T0

Time T0 + X

Time T0 + 2X

Related by time

# Procedural Cohesion

```
class Initializer {  
    void initAll() {  
        initDatabase();  
        initNetwork();  
    }  
    void initNetwork() {  
        // many variables  
        // many Lines of Code  
    }  
    void initDatabase() {  
        // many variables  
        // many Lines of Code  
    }  
}
```

**Procedural cohesion:** A module is said to possess procedural cohesion, if the **set of functions of the module are all part of a procedure** (algorithm) in which certain sequence of steps have to be carried out for achieving an objective.

Function A


Function B

Function C

# Communication Cohesion


```
class Person {  
    Table[] personalData;  
  
    getName(){return personalData[0];}  
    getCustomerInfo(){return personalData[1];}  
    getEmployeeInfo(){return personalData[2];}  
}
```

**Communicational cohesion:** A module is said to have communication cohesion, if all functions of the module refer to or update the same data structure



# Sequential Cohesion

```
class TravelAgent {  
    void reserveTrip(location) {  
        date = reserveTicket(location);  
        address = reserveHotel(date);  
        taxi = reserveTaxi(address, date);  
    }  
    String reserveTicket(String location) {  
        // many variables  
        // many Lines of Code  
    }  
    String reserveHotel(String date) {  
        // many variables  
        // many Lines of Code  
    }  
    int reserveTaxi(String address, String date) {  
        // many variables  
        // many Lines of Code  
    }  
}
```



**Sequential cohesion:** A module is said to possess sequential cohesion, if the elements of a module form the parts of sequence, where the output from one element of the sequence is input to the next.

# Functional Cohesion

```
class TravelAgent {
    AirlineAgent airlineCompany;
    HotelAgent hotelCompany;
    TaxiAgent taxiCompany;

    void scheduleTrip(location) {
        date = airlineCompany.reserve(location);
        hotel = hotelCompany.reserve(dates);
        taxi = taxiCompany.reserve(hotel);
    }
}

class AirlineAgent{
    String reserve(String location){
        // ...
    }
}

class HotelAgent{
    String reserve(String date){
        // ...
    }
}

}
.....
```

**Functional cohesion:**  
Functional cohesion is said to exist, **if different elements of a module cooperate to achieve a single function.**

Function A: part 1


Function A : part 2

Function A : part 3




# High Coupling

Alternative 1: Direct access to the Database subsystem subject to change




# Coupling Reduced


Alternative 2: Storage subsystem more stable



# Decision tracking system: Low Cohesion



# Better Conesion obtained by dividing 1 subsystem into 2



# Partitions and Layers

---

Partitioning and layering are techniques to achieve low coupling.

A large system is usually decomposed into subsystems using both layers and partitions.

**A *partition*** vertically divides system into several independent (or weakly-coupled) subsystems that provide services *on the same level of abstraction*.

**A *layer*** is a subsystem that provides services to a layer *at a higher level of abstraction*

A layer can only depend on lower layers

A layer has no knowledge of higher layers

# Properties of Subsystems: Layers and Partitions

---

A **layer** is a subsystem that provides a service to another subsystem with the following restrictions:

- A layer only depends on services from lower layers

- A layer has no knowledge of higher layers

A layer can be divided horizontally into several independent subsystems called **partitions**

- Partitions provide services to other partitions on the same layer

- Partitions are also called “weakly coupled” subsystems.

# Relationships between Subsystems

Two major types of **Layer relationships**

Layer A **“depends on”** Layer B (compile time dependency)

Example: Build dependencies (make, ant, maven)

Layer A **“calls”** Layer B (runtime dependency)

Example: A web browser calls a web server

Can the client and server layers run on the same machine?

Yes, they are layers, not processor nodes


Mapping of layers to processors is decided during the  
Software/hardware mapping!

## **Partition relationship**

The subsystems have mutual knowledge about each other

A calls services in B; B calls services in A (**Peer-to-Peer**)

# Example of a Subsystem Decomposition





# How the Analysis Models Influence System Design

Nonfunctional requirements =>

**Activity 1:** Design Goals Definition

Functional model =>

**Activity 2:** System decomposition (Selection of subsystems based on functional requirements, cohesion, and coupling)

Object model =>

**Activity 4:** Hardware/software mapping

**Activity 5:** Persistent data management

Dynamic model =>

**Activity 3:** Concurrency

**Activity 6:** Global resource handling

**Activity 7:** Software control

Subsystem Decomposition

**Activity 8:** Boundary conditions

# Sharpen the Design Goals

---

## Location-based input

- Input depends on user location

- Input depends on the direction where the user looks (“egocentric systems”)

## Multi-modal input

- The input comes from more than one input device

## Dynamic connection

- Contracts are only valid for a limited time

- Is there a possibility of further generalizations?

- Example: location can be seen as a special case of context

- User preference is part of the context


- Interpretation of commands depends on context

# Example of Design Goals

- Reliability
- Modifiability
- Maintainability
- Understandability
- Adaptability
- Reusability
- Efficiency
- Portability
- Traceability of requirements
- Fault tolerance
- Backward-compatibility
- Cost-effectiveness
- Robustness
- High-performance

- Good documentation
- Well-defined interfaces
- User-friendliness
- Reuse of components
- Rapid development
- Minimum number of errors
- Readability
- Ease of learning
- Ease of remembering
- Ease of use
- Increased productivity
- Low-cost
- Flexibility

# Stakeholders have different Design Goals



# Typical Design Trade-offs

---

Functionality v. Usability

Cost v. Robustness

Efficiency v. Portability

Rapid development v. Functionality

Cost v. Reusability

Backward Compatibility v. Readability

# Summary

---

## System Design

- Reduces the gap between requirements and the (virtual) machine

- Decomposes the overall system into manageable parts

## Design Goals Definition

- Describes and prioritizes the qualities that are important for the system

- Defines the value system against which options are evaluated

---

Thank You