# **Modeling with UML**

Lecture 4

#### **UML Basic Notation Summary**

UML provides a wide variety of notations for modeling many aspects of software systems


we concentrated on a few notations:

Functional model: Use case diagram


Object model: Class diagram

Dynamic model: Sequence diagrams, activity diagram,


statechart




Use case diagrams represent the functionality of the system from user's point of view



Use case diagrams represent the functionality of the system from user's point of view



Use case diagrams represent the functionality of the system from user's point of view




#### Review of Class Diagrams

+ getHour():Integer


+ destroy()

+ setDeliverable(Delv:String)+ getDeliverable():String

#### **Project** - Name: String - Desc: String - StartDate: Date + create():Project + setName(Name:String) + getString():String + setDesc(Desc:String) + getDesc():String **Activity** + setStartDate(StartDate:Date) - Number: Integer + getStartDate():Date - Desc: String + destroy() - StartDate: Date - Hours:Integer - Deliverable:String + create():Activity + setNumber(Number:Integer) + getNumber():Integer + setDesc(Desc:String) + getDesc():String + setStartDate(StartDate:Date) + getStartDate():Date + setHour(Hour:Integer)




#### Review of Class Diagrams




Class diagrams represent the structure of the system

# Aggregation


#### **Aggregation**



#### **Composition**




#### Inheritance



Inheritance is another special case of an association denoting a "kind-of" hierarchy for describing taxonomies

#### Code Generation from UML to Java I



```
public class Component{ }

public class Leaf extends Component{ }

public class Composite extends Component{
   private Collection<Component> components;
   ...
}
```


#### Where are we?

- ✓ What is UML?
- ✓ Review functional modeling
  - √ Use case diagram
- ✓ Review object modeling
  - ✓ Class diagram
- Review dynamic modeling
  - Sequence diagram

State chart diagram

Activity diagram

### Sequence diagram: Basic Notation



Sequence diagrams represent the behavior of a system as messages ("interactions") between *different objects*.

### Lifeline and Execution Specification


- A **lifeline** represents an individual participant (or object) in the interaction
- A lifeline is shown using a symbol that consists of a rectangle forming its "head" followed by a vertical line (which may be dashed) that represents the lifetime of the participant
- An **execution specification** specifies a behavior or interaction within the lifeline
- An execution specification is represented as a thin rectangle on the lifeline.


### Messages

Define a particular communication between lifelines of an interaction

raising a signal
invoking an operation
creating or destroying an instance
Specify (implicitly) sender and receiver
are shown as a line from the sender to the receiver
Form of line and arrowhead reflect message
properties

# Message Types





Represents behavior of a single object with interesting dynamic behavior.

### **UML** Activity Diagrams


An activity diagram is a special case of a state chart diagram

The states are activities ("functions")

An activity diagram is useful to depict the workflow in a system.




#### Activity Diagrams allow to model Decisions



#### Activity Diagrams can model Concurrency


Synchronization of multiple activities

Splitting the flow of control into multiple threads



# Activities

Activities may be grouped into swimlanes to denote the object or subsystem that implements the activities.



### Domain Modeling

Why? —The goal of domain modeling is to understand how system-to-be will work

Requirements analysis determined how users will interact with system-to-be (external behavior)

**Domain modeling** determines how **elements** of system-tobe interact (internal behavior) to produce the external behavior

#### Domain Modeling

How? —We do domain modeling based on sources:


Knowledge of how system-to-be is supposed to behave (from requirements analysis, e.g., use cases)


- Studying the work domain (or, problem domain)
- Knowledge base of software designs
- Developer's past experience with software design

#### Use Cases vs. Domain Model


In use case analysis, we consider the system as a "black box"

In domain analysis, we consider the system as a "transparent box"






# Example: ATM Machine




(b)




(a)

#### Building Domain Model from Use Cases

Step 1: Identifying the boundary concepts



Step 2: Identifying the internal concepts



#### Thank You