Patch Size in a Small Vision Transformer

Samuel Collins - Ph.D. Student, Department of Cyber-Physical Systems, Clark Atlanta University
samuel.collins@students.cau.edu

Computer Vision - Lab Assignment 6: Vision Transformers (ViT)

Instructor: Dr. Kishor Datta Gupta

Date: 2026-10-16

Repository: https://github.com/srcollins785/Samuel_Collins_ViT_Patch_Size

---

Summary

Smaller patches won here, by a modest margin, and not by being cheaper. The 4x4 model reached 38.1% validation accuracy against 34.8% for 8x8 (a gap of 3.3 points), and it was ahead in 5 of 5 seeds, by 2.5 points on average (range 0.3 to 3.6). The 4x4 model computes 14.6 times as many attention-score entries per head and layer, yet its measured training time was 5.2 s against 5.2 s: at this scale the cost is not set by the attention map. Absolute accuracy is low for both (below 40 percent), as expected of a tiny ViT trained from scratch for five epochs.

A two-block ViT (width 64, four heads, feed-forward width 128) was trained from scratch on a stratified 10,000-image subset of CIFAR-10 with 2,000 separate validation images, for 5 epochs, once with 4x4 patches and once with 8x8 patches. The split, seed, preprocessing, optimizer, batch size, epoch budget and every width, depth and head count were identical; only the patch size differed. The official test split was never loaded. Total training time was 10.5 s on Apple M4 Max (mps).

Every table, figure and number in this report was generated from the saved run files by `scripts/generate_report.py`; none was typed by hand. `scripts/validate_results.py` audits those files, including that the two run configurations differ in the patch size and in no other field.

1. Data and configuration

The images are not in the repository (the brief forbids submitting dataset downloads). `scripts/build_cifar_split.py` rebuilds the same split from the committed indices, and both runs recorded the same checksum, which the audit checks. All settings below are identical for the two runs except the patch size.

Item	Value
Dataset	CIFAR-10 official training split (50,000 images), native 32 x 32 RGB
Training subset	10,000 images, 1,000 per class
Validation subset	2,000 images, 200 per class, disjoint from training
Test split	never loaded; kept out of model selection
Seed	42
Split checksum	`0a7a9f92ecec1aac...` (SHA-256 over both index lists)
Split indices	`data/split_indices.json` (committed)
Normalization	per-channel mean [0.4915, 0.4817, 0.4465], std [0.248, 0.2447, 0.2626], from the training subset only
Augmentation	none
Optimizer	Adam, learning rate 0.0003, betas (0.9, 0.999), no weight decay
Batch size	64 (157 batches per epoch)
Epochs	5
Dropout	0.1 in attention, MLP and embeddings; off at evaluation
Loss	`CrossEntropyLoss` on raw logits (log-softmax is inside the loss; no second softmax)
Hardware	Apple M4 Max, device `mps`, macOS-26.6.2-arm64-arm-64bit
Libraries	Python 3.12.13, torch 2.14.0, torchvision 0.29.0, numpy 2.5.3



Sixteen labeled training examples.

2. The model

The model follows Dosovitskiy et al. (2021) at the sizes the brief fixes: non-overlapping patches, one shared linear projection to width 64, a learnable class token, learned position embeddings, two pre-norm encoder blocks (LayerNorm, four-head self-attention, residual; LayerNorm, MLP of width 128 with GELU,

residual), a final LayerNorm and a linear head to 10 logits. The encoder is written out by hand (`src/vit_patch_size/model.py`) so the attention weights are available; `tests/test_model.py` checks it against `nn.MultiheadAttention` with identical weights, so it is verified, not trusted.

2.1 Tensor shapes

Shapes below were recorded from a real forward pass, not derived from constructor arguments. B is the batch size.

Stage	4x4 patches	8x8 patches
Images	(B, 3, 32, 32)	(B, 3, 32, 32)
Flattened non-overlapping patches	(B, 64, 48)	(B, 16, 192)
Projected tokens (shared linear layer)	(B, 64, 64)	(B, 16, 64)
With class token	(B, 65, 64)	(B, 17, 64)
With position embedding	(B, 65, 64)	(B, 17, 64)
Encoder output (2 blocks)	(B, 65, 64)	(B, 17, 64)
Class-token representation	(B, 64)	(B, 64)
Logits	(B, 10)	(B, 10)

With P x P patches on a 32 x 32 image, the number of patch tokens is N = (32/P)^2 and the total including the class token is L = N + 1. For P = 4, N = (32/4)^2 = 64 and L = 65. For P = 8, N = (32/8)^2 = 16 and L = 17. Each flattened patch has 3 x P x P values: 48 for 4x4 and 192 for 8x8.

2.2 Queries, keys and values

Each token t is multiplied by three learned matrices to give a query q = W_Q t, a key k = W_K t and a value v = W_V t. The query and key decide *where to look*: the score of token i for token j is the dot product q_i . k_j, a similarity (large when the two vectors point the same way). Scores are divided by the square root of the key dimension, for stable gradients, and passed through a softmax along j, giving non-negative weights that sum to 1. The value decides *what is passed on*: the output for token i is the weight-weighted sum of every token's value vector. Four heads repeat this in four 16-dimensional subspaces and an output projection mixes the results (lecture L2, slides 21-35).

A worked example with three value vectors (the values and the scores [2, 4, 4] for query 1 are the lecture L1 example):

	weights	**weighted sum of v1=[0,0,0], v2=[1,4,0], v3=[1,3,1.5]**
softmax of raw scores	[0.063, 0.468, 0.468]	[0.937, 3.278, 0.702]
softmax of scores / sqrt(3) (what the model does)	[0.136, 0.432, 0.432]	[0.864, 3.024, 0.648]

The lecture slide rounds the softmax to [0.0, 0.5, 0.5], which gives [2.0, 7.0, 1.5]; the exact values are above. Token 1 gets almost no weight because its key matches the query worst, so the output is nearly an even blend of v2 and v3. The slide's last summary row reads [2.0, 7.0, 1.0] where its own step gives 1.5, so this report does not reuse that row. `tests/test_model.py` asserts these exact numbers.

2.3 Why positions are needed, and why there is no causal mask

Self-attention is permutation-equivariant: the weights depend only on token content, so without extra information the patches are an unordered set and a shuffled image looks the same as the original. The learned position embedding, added to each token, is what tells the model where a patch came from. This is tested rather than assumed: with the embedding zeroed, shuffling an image's patches leaves the logits unchanged, and with a non-zero embedding it does not (`test_position_embedding_breaks_permutation_symmetry`).

Image classification has no left-to-right generation order, so nothing should be hidden: every patch may attend to every patch, in both directions. A causal mask (future positions set to minus infinity before the softmax) belongs to the transformer *decoder* (lecture L2, decoder slide); the ViT uses only the encoder. With a causal mask the class token, at position 0, could attend to nothing but itself. `tests/test_model.py` checks that attention above the diagonal is non-zero and that changing only the last patch changes the class output.


3. The 4x4 model: training and evidence

Trained from scratch for 5 epochs with the brief's starting configuration (Adam, learning rate 3e-4, batch size 64), unchanged. Validation ran with dropout disabled (`model.eval()`) and no gradient updates (`torch.no_grad()`); a test checks that evaluation changes no parameter.

Final validation accuracy 38.1%, validation loss 1.6728, **75,082 parameters**, **training runtime 5.2 s** (training and validation, 5 epochs, mps). Chance is 10%.

epoch	train loss*	train acc*	train acc (eval mode)	val loss	val acc	seconds
1	2.0622	24.8%	26.6%	1.9839	26.1%	1.31
2	1.8926	30.1%	34.0%	1.8153	32.0%	1.01
3	1.7826	34.0%	37.7%	1.7260	36.4%	0.96
4	1.7090	36.2%	38.6%	1.6969	36.8%	0.98
5	1.6682	38.2%	40.3%	1.6728	38.1%	0.95

* Running mean over the epoch's batches, measured with dropout active while the weights were changing. The 'eval mode' column scores the whole training subset after the epoch with dropout off, and is not included in the seconds.



4x4 model: training and validation loss and accuracy per epoch.

Eight fixed validation examples (one per class for eight classes, chosen from the seed and the labels alone - never from a model's predictions - so both models are shown the same images). 6 of the 8 are misclassified, so mistakes are shown.




4x4 model on the eight fixed validation examples.

#	true	predicted	confidence	correct
1	airplane	dog	0.40	no
2	automobile	truck	0.50	no
3	bird	deer	0.32	no
4	deer	dog	0.27	no
5	frog	deer	0.37	no
6	horse	bird	0.28	no
7	ship	ship	0.63	yes
8	truck	truck	0.44	yes

4. Controlled patch-size comparison

The 8x8 model was trained from scratch with the same split, preprocessing, seed, embedding width, depth, heads, feed-forward width, optimizer settings, batch size and epoch budget. `scripts/validate_results.py` diffs the two saved configurations and fails unless `patch_size` is the only field that differs. Both models also see the same batches in the same order: the loader's shuffle is seeded on the CPU, independent of device.

patch	N	L	parameters	val acc	val loss	train acc (eval mode)	runtime
4x4	64	65	75,082	38.1%	1.6728	40.3%	5.2 s
8x8	16	17	81,226	34.8%	1.7584	38.5%	5.2 s



Both learning curves: training (dashed) and validation (solid) loss and accuracy.



8x8 model on the same eight fixed validation examples.

#	true	4x4 predicted	8x8 predicted
1	airplane	dog	dog
2	automobile	truck	truck
3	bird	deer	deer
4	deer	dog	bird
5	frog	deer	deer
6	horse	bird	horse
7	ship	ship	ship
8	truck	truck	truck

4.1 What changed in the parameters

Only two shapes depend on the patch size. The patch projection maps 3 x P x P inputs to 64, so it grows from 3,136 to 12,352 parameters; the position embedding has one 64-vector per token, so it shrinks from 4,160 to 1,088. The projection grows by more than the embedding shrinks, so **the 8x8 model has more parameters (81,226 against 75,082) despite four times fewer tokens**: each patch carries four times the pixels.

Component	4x4	8x8
Patch projection (3 P^2 x 64 + 64)	3,136	12,352
Class token	64	64
Position embedding (L x 64)	4,160	1,088
Two encoder blocks	66,944	66,944
Final LayerNorm and head	778	778
Total	**75,082**	**81,226**

4.2 Attention cost

Each head in each layer scores every token against every token, an L x L map with L^2 entries. This is the count the brief asks for; the last column multiplies it by 4 heads and 2 layers.

patch	N = (32/P)^2	L = N + 1	L^2 entries per head and layer	entries, 4 heads x 2 layers
4x4	64	65	4,225	33,800
8x8	16	17	289	2,312

The 4x4 model computes 4,225 / 289 = **14.6 times** as many score entries. Its measured training time was 1.00 times the 8x8 model's, not 14.6.

4.3 Why the count does not predict runtime or memory

L^2 counts one thing: entries of the score matrix. Total time and memory also include work that scales with the number of tokens, not its square (the patch projection, both LayerNorms, the QKV and output projections, the MLP, the residual adds - all linear in L), work that does not depend on L at all (the batch transfer, the optimizer update of all parameters, kernel launches, Python overhead). Memory likewise holds parameters, Adam's two moment buffers and every per-token activation saved for backward, not only the L x L maps. Two measurements (`scripts/run_timing.py`, median of 100 optimizer steps at batch size 64 after warm-up) show the effect directly:

device	step ms 4x4	step ms 8x8	step ratio	scores+softmax ms 4x4	scores+softmax ms 8x8	scores ratio
CPU	22.85	12.08	1.89x	0.680	0.429	1.58x
MPS	5.12	5.35	0.96x	0.247	0.176	1.40x

On the CPU the whole training step costs 1.89 times as much at 4x4, and the isolated score-and-softmax computation 1.58 times - both far below 14.6, because at width 64 and 16 dimensions per head these matrices are tiny and most time goes to per-token and fixed work. On the GPU (`mps`) the step ratio is 0.96: the two patch sizes cost the same, consistent with a step dominated by fixed per-step overhead rather than arithmetic. I did not profile the GPU kernels, so the overhead explanation is an inference from these ratios, not a measurement of the cause.


Memory (GPU allocator, batch size 64, each model measured in a fresh process; `scripts/run_timing.py`) tells the same story from another angle. The parameters, Adam's moment buffers and the input batch occupy almost the same memory for both models. The activations kept for the backward pass differ by 5.4 times, not 14.6, because the score and softmax tensors are only some of what is saved: every token also has its embeddings, normalized copies, QKV projections, MLP activations and dropout masks. This is the memory held after one forward pass, not a measured peak across the backward pass and optimizer step.

quantity	4x4	8x8	ratio
Parameters + Adam state + input batch (MB)	1.69	1.76	0.96x
Activations the autograd graph keeps for backward (MB)	66.2	12.4	5.35x
One (B, heads, L, L) attention-map tensor (MB)	4.33	0.30	14.62x

4.4 Is the accuracy gap more than seed noise?

A single accuracy on 2,000 validation images has a binomial standard error of about 1.1 points, so the graded 3.3-point gap is only about 3.1 standard errors on its own. I therefore repeated both patch sizes at 5 seeds on the same split (`scripts/run_supplementary.py`; the seed changes the initial weights, batch order and dropout masks). The seed-42 pair reproduces the graded runs exactly. This is supplementary; the graded comparison is the seed-42 pair.

seed	4x4 val acc	8x8 val acc	difference (points)
42	38.1%	34.8%	3.3
43	39.5%	35.9%	3.6
44	38.2%	36.0%	2.3
45	35.8%	35.5%	0.3
46	39.1%	35.9%	3.3
mean (sd)	38.1% (1.5)	35.6% (0.5)	2.5 (1.4)




Final validation accuracy by seed, both patch sizes.

The 4x4 model is ahead in 5 of 5 seeds, by 2.5 points on average, but the smallest margin is only 0.3 points, and 5 seeds cannot rule out an occasional reversal.

4.5 Where the models differ

The models are right together and wrong together more often than not: both correct on 508 of 2,000 validation images, both wrong on 1,050, only 4x4 correct on 254, only 8x8 correct on 188. The largest per-class difference is **dog**: 65% at 4x4 against 44% at 8x8, 43 of the 200 dog images.



Per-class validation accuracy for both models (seed 42).

5. Analysis

Performance. The 4x4 model finished at 38.1% validation accuracy and the 8x8 model at 34.8%, with validation loss 1.673 against 1.758. One pair is thin evidence, since one accuracy carries about 1.1 points of sampling error, but across 5 seeds 4x4 led every time, by 2.5 points on average. The advantage concentrated in particular classes: dog accuracy was 65% against 44%. Most examples behave alike: both models were right on 508 images and wrong on 1,050 of 2,000, and they split on the remainder (254 only 4x4, 188 only 8x8). Smaller patches did not buy accuracy with time: runtimes were 5.2 s and 5.2 s, within the run-to-run noise of about a second, although 4x4 scores 14.6 times as many attention entries. The cost of the larger map is real but invisible at this scale.

Global attention and position. A convolution sees a small neighborhood, and distant pixels meet only after many layers; lecture L2 counts O(n/k) layers for kernel size k, against O(1) for self-attention. Here every one of the 65 or 17 tokens attends to all others in the first block. A convolution also shares weights across positions, which builds in translation equivariance; a ViT has no such prior. Attention alone ignores order, so the position embedding is what lets the model use where a patch is; a test confirmed that without it, shuffling patches changes nothing.

Poor absolute performance. Both models are far from converged: training accuracy scored in evaluation mode was 40.3% for 4x4, barely above its validation accuracy, and the curves were still falling at epoch five. That is underfitting, not overfitting. A ViT lacks a CNN's built-in locality, so it must learn such structure from data, and the lecture attributes ViT's success to pretraining on hundreds of millions of images; this model saw ten thousand, briefly. The experiment ran no CNN, one dataset, one tiny budget, so it says nothing about CNNs or transformers being better in general.

Swin for dense tasks. Three separate ideas help. Windowed attention cuts cost: on a 3,136-token map (56 x 56, a 224-pixel image with 4x4 patches), global attention needs 9,834,496 entries per head, while 7 x 7 windows need 153,664, 64 times fewer; that is arithmetic, not a measurement. Shifted windows restore communication, because tokens in different windows interact in alternate layers. Patch merging builds multiscale features, giving the detector or segmenter the coarse-to-fine maps a flat coarse-patch ViT lacks; lecture L2 has the four stages shrink a 224-pixel input to 56, 28, 14 and 7 tokens per side, the resolutions of ResNet-style backbones. Small objects need fine patches, and windows make fine patches affordable.

Next experiment. Train both patch sizes for many more epochs, with early stopping on validation, alongside a parameter-matched small CNN under the same protocol and several seeds. That would show whether the patch-size gap persists at convergence and give the missing CNN reference. Comparing the patch sizes at several equal optimizer-step budgets would also separate slower convergence from a genuinely lower ceiling at 8x8.

6. Limitations and honest notes

- **Weak absolute accuracy.** Both models sit well under 50%, as the brief anticipates. Nothing here was tuned to raise them.
- **Runtime is noisy.** Across the 5 replicated seeds the 4x4 run took 4.9-5.1 s and the 8x8 run 5.1-5.4 s. Differences under about a second are not resolvable, so no claim here depends on which patch size was faster, only on neither being many times faster. Accuracies and predictions reproduce bit for bit on rerun; wall-clock time does not.
- **One split, two sizes, small validation set.** The split is fixed, so seed variation excludes split-to-split variation. The seed replication addresses initialization and batch order only.
- **Training metrics.** The 'train' columns are running means with dropout on; the 'eval mode' column is the like-for-like comparison with validation.
- **Fixed examples** are chosen before any model is trained, from the seed and labels, so they are not selected to show errors. They happen to include both correct and incorrect predictions.
- **Compute option not used.** The full 10,000 / 2,000 / 5-epoch protocol ran in seconds, so the reduced option was unnecessary.
- **Choices the brief left open**: dropout 0.1, pre-norm blocks, GELU, learned position embeddings, trunc-normal(0.02) initialization, per-channel normalization from the training subset, no augmentation. All recorded in `configuration.yaml` and identical across the two runs.
- **Lecture slides.** Two slips in lecture L1's attention example are noted in section 2.2; this report uses exact values.

7. Reproduction and sources

```
python3.12 -m venv .venv
.venv/bin/python -m pip install -r requirements.txt
.venv/bin/python scripts/run_all.py
```

`run_all.py` runs the tests, rebuilds the split, trains both models, runs the seed replication and timing, audits the results, writes `configuration.yaml`, builds this report and the executed notebook, and stops at the first failure. `--skip-training` rebuilds the documents only.

Sources. No code was copied from another repository; the model is written from the papers below.

- Dosovitskiy et al. *An Image is Worth 16x16 Words: Transformers for Image Recognition at Scale.* ICLR 2021 (architecture, class token, learned position embeddings).
- Vaswani et al. *Attention Is All You Need.* NeurIPS 2017 (scaled dot-product attention, multi-head attention, residual and LayerNorm structure).
- Liu et al. *Swin Transformer: Hierarchical Vision Transformer Using Shifted Windows.* ICCV 2021 (windows, shifting, patch merging).
- Krizhevsky. *Learning Multiple Layers of Features from Tiny Images.* 2009 (CIFAR-10).
- Kingma and Ba. *Adam: A Method for Stochastic Optimization.* ICLR 2015.
- PyTorch `nn.MultiheadAttention` documentation: used only as a test oracle for the hand-written attention, not in the model.
- Course lectures: **L1** `VisionTransformers_Details.pdf` (ViT and Swin; cites Dosovitskiy et al. and Liu et al.) and **L2** `visiontransformers.pdf` (UCSD CSE 252D, SP24, Chandraker et al.; cites Alammar's *The Illustrated Transformer*).