tmvar, x, y, f, m, n variables

covar, c coercion variables

 $\begin{array}{c} datacon, \ K \\ const, \ T, \ F \end{array}$ 

index, i indices

```
role, R
                                                                                                          Role
                                           ::=
                                                    Nom
                                                    Rep
                                                    R_1 \cap R_2
                                                                                    S
relflag, \ \rho
                                                                                                          relevance flag
constraint, \phi
                                                                                                          props
                                                    a \sim_{A/R} b
                                                                                    S
                                                    (\phi)
                                                                                    S
                                                    \phi\{b/x\}
                                                                                    S
                                                    |\phi|
                                                                                    S
                                                    a \sim_R b
tm, a, b, v, w, A, B
                                                                                                          types and kinds
                                                    \lambda^{\rho}x:A/R.b
                                                                                    \mathsf{bind}\ x\ \mathsf{in}\ b
                                                    \lambda^{R,\rho}x.b
                                                                                    \mathsf{bind}\ x\ \mathsf{in}\ b
                                                    a b^{R,\rho}
                                                    F
                                                                                    \mathsf{bind}\ x\ \mathsf{in}\ B
                                                    \Pi^{\rho}x:A/R\to B
                                                    a \triangleright_R \gamma
                                                    \forall c : \phi.B
                                                                                    bind c in B
                                                    \Lambda c : \phi . b
                                                                                    \mathsf{bind}\ c\ \mathsf{in}\ b
                                                    \Lambda c.b
                                                                                    \mathsf{bind}\ c\ \mathsf{in}\ b
                                                    a[\gamma]
                                                    ifPath R a' a b_1 b_2
                                                    \mathbf{match}\ a\ \mathbf{with}\ brs
                                                    \operatorname{\mathbf{sub}} R a
                                                                                    S
                                                    a\{b/x\}
                                                                                    S
                                                    a
                                                                                    S
                                                    a\{\gamma/c\}
                                                                                    S
                                                                                    S
                                                    (a)
                                                                                    S
                                                                                                              parsing precedence is hard
                                                                                    S
                                                    |a|_R
                                                                                    S
                                                    Int
                                                                                    S
                                                    Bool
                                                                                    S
                                                    Nat
                                                                                    S
                                                    Vec
                                                                                    S
                                                    0
                                                    S
                                                                                    S
```

```
S
                                 True
                                                                          S
                                 \mathbf{Fix}
                                                                          S
                                 \mathbf{Age}
                                                                          S
                                 a \rightarrow b
                                 \phi \Rightarrow A
                                                                          S
                                                                          S
                                 a b
                                                                          S
                                 \lambda x.a
                                                                          S
                                 \lambda x : A.a
                                                                          S
                                 \forall x: A/R \to B
                                 if \phi then a else b
                                                                          S
brs
                     ::=
                                                                                                       case branches
                                 none
                                 K \Rightarrow a; brs
                                 brs\{a/x\}
                                                                          S
                                 brs\{\gamma/c\}
                                                                          S
                                                                          S
                                 (brs)
co, \gamma
                                                                                                       explicit coercions
                                 \mathbf{red}\;a\;b
                                 \mathbf{refl}\;a
                                 (a \models \mid_{\gamma} b)
                                 \mathbf{sym}\,\gamma
                                 \gamma_1; \gamma_2
                                 \operatorname{sub} \gamma
                                 \Pi^{R,\rho}x\!:\!\gamma_1.\gamma_2
                                                                          bind x in \gamma_2
                                \lambda^{R,\rho} x : \gamma_1 \cdot \gamma_2
\gamma_1 \cdot \gamma_2^{R,\rho}
                                                                          bind x in \gamma_2
                                 \mathbf{piFst}\,\gamma
                                 \mathbf{cpiFst}\,\gamma
                                 \mathbf{isoSnd}\,\gamma
                                 \gamma_1@\gamma_2
                                 \forall c: \gamma_1.\gamma_3
                                                                          bind c in \gamma_3
                                 \lambda c: \gamma_1.\gamma_3@\gamma_4
                                                                          bind c in \gamma_3
                                 \gamma(\gamma_1,\gamma_2)
                                 \gamma@(\gamma_1 \sim \gamma_2)
                                 \gamma_1 \triangleright_R \gamma_2
                                 \gamma_1 \sim_A \gamma_2
                                 conv \phi_1 \sim_{\gamma} \phi_2
                                 \mathbf{eta}\,a
                                 left \gamma \gamma'
                                 \mathbf{right}\,\gamma\,\gamma'
                                                                          S
                                 (\gamma)
                                                                          S
                                 \gamma
```

```
\gamma\{a/x\}
                                                                         S
role\_context,\ \Omega
                                    ::=
                                                                                role_contexts
                                             Ø
                                            \Omega, x:R
                                             (\Omega)
                                                                          Μ
                                             \Omega
                                                                          Μ
sig\_sort
                                    ::=
                                                                                signature classifier
                                            :A/R
                                             \sim a:A/R
                                                                                binding classifier
sort
                                             \mathbf{Tm}\,A\,R
                                             \mathbf{Co}\,\phi
context, \Gamma
                                    ::=
                                                                                contexts
                                             Ø
                                            \Gamma, x : A/R
                                            \Gamma, c: \phi
                                            \Gamma\{b/x\}
                                                                          Μ
                                            \Gamma\{\gamma/c\} \\ \Gamma, \Gamma'
                                                                          Μ
                                                                          Μ
                                             |\Gamma|
                                                                          М
                                             (\Gamma)
                                                                          Μ
                                             Γ
                                                                          Μ
sig, \Sigma
                                    ::=
                                                                                signatures
                                            \Sigma \cup \{Fsig\_sort\}
                                            \Sigma_0
                                                                          Μ
                                             \Sigma_1
                                                                          Μ
                                             |\Sigma|
                                                                          Μ
available\_props,\ \Delta
                                             Ø
                                             \Delta, c
                                            \widetilde{\Gamma}
                                                                          Μ
                                             (\Delta)
                                                                          Μ
terminals
                                             \leftrightarrow
                                             \Leftrightarrow
                                             min
```

```
\in
                                         \not\in
                                         \Leftarrow
                                         Λ
                                         \neq
                                         \triangleright
                                          ok
                                         fv
                                         dom
                                         \sim
                                         \simeq
                                         \mathbf{fst}
                                         \operatorname{snd}
                                         |\Rightarrow|
                                        \vdash_=
                                         \mathbf{refl_2}
                                         ++
formula, \psi
                              ::=
                                        judgement
                                         x:A/R\in\Gamma
                                         x:R^{'}\in\Omega
                                         c:\phi\,\in\,\Gamma
                                         \textit{F sig\_sort} \, \in \, \Sigma
                                         K:T\Gamma\in\Sigma
                                         x \in \Delta
                                         c \in \Delta
                                         c \, \mathbf{not} \, \mathbf{relevant} \, \in \, \gamma
                                         x \not\in \mathsf{fv} a
```

```
x \not\in \operatorname{dom} \Gamma
                                  uniq(\Omega)
                                  c \not\in \operatorname{dom} \Gamma
                                  T \not\in \operatorname{dom} \Sigma
                                  F \not\in \operatorname{dom} \Sigma
                                  a = b
                                  \phi_1 = \phi_2
                                  \Gamma_1 = \Gamma_2
                                  \gamma_1 = \gamma_2
                                  \neg \psi
                                  \psi_1 \wedge \psi_2
                                  \psi_1 \vee \psi_2
                                  \psi_1 \Rightarrow \psi_2
                                  c:(a:A\sim b:B)\in\Gamma
                                                                                 suppress lc hypothesis generated by Ott
JSubRole
                                  R_1 \leq R_2
                                                                                 Subroling judgement
JPath
                         ::=
                                  Path_R \ a = F
                                                                                 Type headed by constant (partial function)
JValue
                         ::=
                                  \mathsf{Value}_R\ A
                                                                                 values
JValue\,Type
                                  ValueType_R A
                                                                                 Types with head forms (erased language)
J consistent \\
                         ::=
                                  \mathsf{consistent}_R\ ab
                                                                                 (erased) types do not differ in their heads
Jerased
                                  \Omega \vDash a : R
JChk
                                 (\rho = +) \lor (x \not\in \mathsf{fv}\ A)
                                                                                irrelevant argument check
Jpar
                            \begin{array}{c|c} & \Omega \vDash a \Rightarrow_R b \\ & \Omega \vdash a \Rightarrow_R^* b \\ & \Omega \vdash a \Leftrightarrow_R b \end{array} 
                                                                                 parallel reduction (implicit language)
                                                                                 multistep parallel reduction
                                                                                 parallel reduction to a common term
Jbeta
                           | \qquad \models a > b/R \\ | \qquad \models a \leadsto b/R
                                                                                 primitive reductions on erased terms
                                                                                 single-step head reduction for implicit language
```

```
\models a \leadsto^* b/R
                                                                    multistep reduction
Jett
                       ::=
                                                                    Prop wellformedness
                               \Gamma \vDash \phi \  \, \mathsf{ok}
                              \Gamma \vDash \overset{\cdot}{a} : A/R
                                                                    typing
                              \Gamma; \Delta \vDash \phi_1 \equiv \phi_2
                                                                    prop equality
                              \Gamma; \Delta \vDash a \equiv b : A/R
                                                                    definitional equality
                               \vDash \Gamma
                                                                    context\ well formedness
Jsig
                       ::=
                              \models \Sigma
                                                                    signature wellformedness
Jann
                       ::=
                               \Gamma \vdash \phi \  \, \mathsf{ok}
                                                                    prop wellformedness
                              \Gamma \vdash a : A/R
                                                                    typing
                              \Gamma; \Delta \vdash \gamma : \phi_1 \sim \phi_2
                                                                    coercion between props
                              \Gamma; \Delta \vdash \gamma : A \sim_R B
                                                                    coercion between types
                              \vdash \Gamma
                                                                    context wellformedness
                              \vdash \Sigma
                                                                    signature wellformedness
Jred
                               \Gamma \vdash a \leadsto b/R
                                                                    single-step, weak head reduction to values for annotated lang
judgement
                       ::=
                               JSubRole
                               JPath
                               JValue
                               JValue\,Type
                               J consistent
                               Jerased
                               JChk
                               Jpar
                               Jbeta
                               Jett
                               Jsig
                               Jann
                               Jred
user\_syntax
                       ::=
                               tmvar
                               covar
                               data con
                               const
                               index
                               role
```

 $\begin{array}{c} \textit{relflag} \\ \textit{constraint} \end{array}$ 

 $egin{array}{c|c} tm \\ brs \\ co \\ role\_context \\ sig\_sort \\ sort \\ context \\ sig \\ available\_props \\ terminals \\ formula \end{array}$ 

## $R_1 \le R_2$ Subroling judgement

 $\mathsf{Path}_R \ a = F$  Type headed by constant (partial function)

$$F \sim a: A/R_1 \in \Sigma_0$$
 $\neg (R_1 \leq R)$ 
 $Path_R F = F$ 
 $Path_R a = F$ 
 $Path_R (a b'^{R_1,\rho}) = F$ 
 $Path_R a = F$ 
 $Path_R a = F$ 
 $Path_R (a[ullet]) = F$ 
 $Path_R (a[ullet]) = F$ 

 $Value_R A$  values

$$\begin{array}{c|c} \overline{\operatorname{Value}_R \, \star} & \operatorname{Value\_STAR} \\ \hline \\ \overline{\operatorname{Value}_R \, \Pi^\rho x \colon A/R_1 \to B} & \operatorname{Value\_PI} \\ \hline \\ \overline{\operatorname{Value}_R \, \forall c \colon \phi.B} & \operatorname{Value\_CPI} \\ \hline \\ \overline{\operatorname{Value}_R \, \lambda^+ x \colon A/R_1.a} & \operatorname{Value\_ABSREL} \\ \hline \\ \overline{\operatorname{Value}_R \, \lambda^{R_1,+} x.a} & \operatorname{Value\_UABSREL} \\ \hline \\ \overline{\operatorname{Value}_R \, \lambda^{R_1,+} x.a} & \operatorname{Value\_UABSIRREL} \\ \hline \\ \overline{\operatorname{Value}_R \, \lambda^{R_1,-} x.a} & \operatorname{Value\_UABSIRREL} \\ \hline \\ \overline{\operatorname{Value}_R \, \Lambda c \colon \phi.a} & \operatorname{Value\_CABS} \\ \hline \\ \overline{\operatorname{Value}_R \, \Lambda c.a} & \operatorname{Value\_UCABS} \\ \hline \\ \hline \end{array}$$

$$\frac{\mathsf{Path}_R \ a = F}{\mathsf{Value}_R \ a} \quad \mathsf{VALUE\_PATH}$$

 $ValueType_R A$ Types with head forms (erased language)

$$\overline{\mathsf{ValueType}_R \, \star} \quad \mathtt{VALUE\_TYPE\_STAR}$$

$$\overline{\mathsf{ValueType}_R\ \Pi^{
ho}x\!:\!A/R_1 o B}$$
 VALUE\_TYPE\_PI

$$\overline{\mathsf{ValueType}_R \; \forall c \!:\! \phi.B} \quad \text{VALUE\_TYPE\_CPI}$$

$$\mathsf{Path}_R\ A = F$$

$$\mathsf{Value}_R\ A$$

 $\frac{\mathsf{Value}_R\ A}{\mathsf{Value}\mathsf{Type}_R\ A}\quad \mathsf{VALUE\_TYPE\_PATH}$ 

 $\mathsf{consistent}_R\ ab$ (erased) types do not differ in their heads

 $\frac{}{\mathsf{consistent}_R \star \star}$  Consistent\_A\_Star

CONSISTENT\_A\_PI  $\overline{\mathsf{consistent}_{R'} \; (\Pi^{\rho} x_1 \colon\! A_1/R \to B_1) (\Pi^{\rho} x_2 \colon\! A_2/R \to B_2)}$ 

CONSISTENT\_A\_CPI  $\overline{\mathsf{consistent}_R \; (\forall c_1 \colon \phi_1.A_1)(\forall c_2 \colon \phi_2.A_2)}$ 

$$\mathsf{Path}_R \ a_1 = F$$

$$\mathsf{Path}_R \ a_2 = F$$

 $\frac{\mathsf{Path}_R \ a_2 = F}{\mathsf{consistent}_R \ a_1 a_2} \quad \text{Consistent\_A\_PATH}$ 

 $\frac{\neg \mathsf{ValueType}_R\ a}{\mathsf{consistent}_R\ ab}\quad \text{Consistent\_A\_STEP\_L}$ 

 $|\Omega \vDash a : R|$ 

$$\frac{uniq(\Omega)}{\Omega \vDash \Box : R} \quad \text{ERASED\_A\_BULLET}$$

$$\overline{\Omega \vDash \Box : R}$$

$$\Omega \vDash \star : R$$

 $\frac{uniq(\Omega)}{\Omega \vDash \star : R} \quad \text{ERASED\_A\_STAR}$ 

 $uniq(\Omega)$ 

 $x:R\in\Omega$ 

$$R \leq R_1$$

 $\frac{R \le R_1}{\Omega \models x : R_1} \quad \text{ERASED_A_VAR}$ 

$$\frac{\Omega, x : R_1 \vDash a : R}{\Omega \vDash (\lambda^{R_1, \rho} x. a) : R} \quad \text{ERASED\_A\_ABS}$$

$$\Omega \vDash a : R$$

$$\Omega \vDash b : R_1$$

 $\frac{1}{\Omega \vDash (a \ b^{R_1,\rho}) : R} \quad \text{ERASED\_A\_APP}$ 

$$\Omega \vDash A : R_1$$

$$\Omega. x : R_1 \vDash B : R$$

$$\frac{\Omega, x : R_1 \vDash B : R}{\Omega \vDash (\Pi^{\rho} x : A / R_1 \to B) : R} \quad \text{ERASED\_A\_PI}$$

$$\begin{array}{c} \Omega \vDash a : R_1 \\ \Omega \vDash b : R_1 \\ \Omega \vDash A : R_1 \\ \Omega \vDash B : R \\ \hline \Omega \vDash (\forall c : a \sim_{A/R_1} b.B) : R \end{array} \end{array}$$
 ERASED\_A\_CPI 
$$\begin{array}{c} \Omega \vDash b : R \\ \hline \Omega \vDash (\forall c : b) : R \\ \hline \Omega \vDash ((Ac.b) : R \end{array} \end{array} = \text{ERASED_A_CABS} \\ \hline \frac{\Omega \vDash a : R}{\Omega \vDash (Ac.b) : R} = \text{ERASED_A_CAPP} \\ \hline \frac{\Omega \vDash a : R}{\Omega \vDash (a [\bullet]) : R} = \text{ERASED_A_CAPP} \\ \hline \frac{uniq(\Omega)}{P} = a : A/R \in \Sigma_0 \\ \Omega \vDash r : R_1 \\ D \vDash F : R_1 \\ \hline R \Rightarrow a : A/R' \in \Sigma_0 \\ \Omega \vDash a : R \\ \Omega \vDash b_1 : R_1 \\ \Omega \vDash b_2 : R_1 \\ \hline \Omega \vDash (i \text{FPath } R F \ a \ b_1 \ b_2) : R_1 \end{array} = \text{ERASED_A_FAM}$$
 ERASED\_A\_FAM} 
$$\begin{array}{c} F \sim a_0 : A/R' \in \Sigma_0 \\ \Omega \vDash a : R \\ \Omega \vDash b : R_1 \\ \hline \Omega \vDash a : R \\ \hline \Omega \vDash a : R \\ \hline \Omega \vDash a \Rightarrow_R a \\ \hline A \Leftrightarrow b \end{array} = \text{ERASED_A_FAM}$$
 ERASED\_A\_FAM} 
$$\begin{array}{c} F \Rightarrow a : A/R \in \Sigma_0 \\ \hline \Omega \vDash a : R \\ \hline \Omega \vDash a \Rightarrow_R a \\ \hline \Omega \vDash a \Rightarrow_R a' \\ \hline \Omega \vDash A \Rightarrow_R A \land A' \\ \hline \Omega \vDash A \Rightarrow_R A \land A' \\ \hline \Omega \vDash A \Rightarrow_R A \land A' \\ \hline \Omega \vDash A \Rightarrow_R A \land A' \\ \hline \Omega \vDash A \Rightarrow_R A \land A' \\ \hline \Omega \vDash A \Rightarrow_R A \land A' \\ \hline \Omega \vDash A \Rightarrow_R A \land A' \\ \hline \Omega \vDash A \Rightarrow_R A \land A' \\ \hline \Omega \vDash A \Rightarrow_R A \land A' \\ \hline \Omega \vDash A \Rightarrow_R A \land A' \\ \hline \Omega \vDash A \Rightarrow_R A \land A' \\ \hline \Omega \vDash A \Rightarrow_R A \land A' \\ \hline \Omega \vDash A \Rightarrow_R A \land A' \\ \hline \Omega \vDash A \Rightarrow_R A \land A' \\ \hline \Omega \vDash A \Rightarrow_R A \land A' \\ \hline \Omega \vDash A \Rightarrow_R A \land A' \\ \hline \Omega \vDash A \Rightarrow_R A \Rightarrow_R A \succeq A$$

$$\begin{array}{c} \Omega \vDash A \Rightarrow_{R_1} A' \\ \Omega \vDash a \Rightarrow_{R_1} b' \\ \Omega \vDash b \Rightarrow_{R_1} b' \\ \Omega \vDash b \Rightarrow_{R_1} b' \\ \hline \Omega \vDash b \Rightarrow_{R_1} a' \\ \hline PAR_{-} A = \sum_{n=1}^{N_1} PAR_{-} A = \sum_{n=1}^{N_1}$$

$$\begin{array}{ll} \operatorname{Path}_R \ a = F \\ \hline \models \operatorname{\mathbf{ifPath}} R \ F \ a \ b_1 \ b_2 > b_1/R_0 \end{array} \quad \text{Beta\_PatternTrue} \\ F \ \sim a_0 : A/R' \in \Sigma_0 \\ \operatorname{Value}_R \ a \\ \hline \neg (\operatorname{Path}_R \ a = F) \\ \hline \models \operatorname{\mathbf{ifPath}} R \ F \ a \ b_1 \ b_2 > b_2/R_0 \end{array} \quad \text{Beta\_PatternFalse}$$

 $\models a \leadsto b/R$  single-step head reduction for implicit language

$$\begin{array}{c} \models a \leadsto a'/R_1 \\ \hline \models \lambda^{R,-}x.a \leadsto \lambda^{R,-}x.a'/R_1 \end{array} \quad \text{E\_ABSTERM} \\ \\ \frac{\models a \leadsto a'/R_1}{\models a \ b^{R,\rho} \leadsto a' \ b^{R,\rho}/R_1} \quad \text{E\_APPLEFT} \\ \\ \frac{\models a \leadsto a'/R}{\models a [\bullet] \leadsto a'[\bullet]/R} \quad \text{E\_CAPPLEFT} \\ \\ \frac{\models a \leadsto a'/R}{\models a \bowtie a'/R} \\ \hline \models if \textbf{Path} \ R \ F \ a \ b_1 \ b_2 \leadsto if \textbf{Path} \ R \ F \ a' \ b_1 \ b_2/R_0} \\ \\ \frac{\models a \gt b/R}{\models a \leadsto b/R} \quad \text{E\_PRIM} \end{array}$$

 $\models a \leadsto^* b/R$  multistep reduction

 $\Gamma \vDash \phi$  ok Prop wellformedness

$$\begin{array}{l} \Gamma \vDash a : A/R \\ \Gamma \vDash b : A/R \\ \hline \Gamma \vDash A : \star/R \\ \hline \Gamma \vDash a \sim_{A/R} b \text{ ok} \end{array} \quad \text{E-Wff}$$

 $\Gamma \vDash a : A/R$  typing

$$\begin{array}{ll} R_1 \leq R_2 \\ \hline \Gamma \vDash a : A/R_1 \\ \hline \Gamma \vDash a : A/R_2 \end{array} \quad \text{E\_SubRole} \\ \\ \frac{\vDash \Gamma}{\Gamma \vDash \star : \star/R} \quad \text{E\_STAR} \\ \\ \vDash \Gamma \\ \hline \frac{x : A/R \in \Gamma}{\Gamma \vDash x : A/R} \quad \text{E\_VAR} \\ \\ \Gamma, x : A/R \vDash B : \star/R' \\ \hline \Gamma \vDash A : \star/R \\ \hline \Gamma \vDash \Pi^{\rho}x : A/R \to B : \star/R' \end{array} \quad \text{E\_PI} \\ \end{array}$$

$$\begin{array}{c} \Gamma, x : A/R \vDash a : B/R' \\ \Gamma \vDash A : */R \\ (\rho = +) \lor (x \notin \exists v \ a) \\ \hline \Gamma \vDash \lambda^R \cdot \varphi_{R} \cdot x : \Pi(rx : A/R \rightarrow B)/R' \\ \hline \Gamma \vDash b : \Pi^+ x : A/R \rightarrow B/R' \\ \hline \Gamma \vDash b : \Pi^+ x : A/R \rightarrow B/R' \\ \hline \Gamma \vDash b : \Pi^- x : A/R \rightarrow B/R' \\ \hline \Gamma \vDash b : \Pi^- x : A/R \rightarrow B/R' \\ \hline \Gamma \vDash b : B \cap x : A/R \rightarrow B/R' \\ \hline \Gamma \vDash b : B \cap x : A/R \rightarrow B/R' \\ \hline \Gamma \vDash a : A/R \\ \hline \Gamma \vDash b : B \cap x : B\{a/x\}/R' \\ \hline \Gamma \vDash a : A/R \\ \hline \Gamma \vDash b : B : */Rep \\ \hline \Gamma \vDash B : */R \\ \hline \Gamma \vDash b : B : */R \\ \hline \Gamma \vDash a : B/R \\ \hline \Gamma \vDash a : A/R \\ \hline \Gamma \vDash a : B/R_0 \\ \hline \Gamma \vDash a : A/R \\ \hline \Gamma \vDash a : B/R_0 \\ \hline \Gamma \Rightarrow a : A/R \\ \hline C \Rightarrow A : A/R \\$$

$$\frac{\Gamma \vDash A_1 \sim_{B/R} A_2 \text{ ok}}{\Gamma; \Delta \vDash A_1 \sim_{A/R} A_2 \equiv A_1 \sim_{B/R} A_2} \quad \text{E_IsoConv}$$

$$\frac{\Gamma; \Delta \vDash \forall c : (a_1 \sim_{A/R_1} a_2).B_1 \equiv \forall c : (b_1 \sim_{B/R_2} b_2).B_2 : \star/R'}{\Gamma; \Delta \vDash a_1 \sim_{A/R_1} a_2 \equiv b_1 \sim_{B/R_2} b_2} \quad \text{E_CPiFst}$$

 $\Gamma; \Delta \vDash a \equiv b : A/R$  definitional equality

$$\begin{array}{c} \models \Gamma \\ c: (a \sim_{A/R} b) \in \Gamma \\ c \in \Delta \\ \hline \Gamma; \Delta \models a \equiv b: A/R \\ \hline \Gamma; \Delta \models a \equiv a: A/R \\ \hline \Gamma; \Delta \models a \equiv a: A/R \\ \hline \Gamma; \Delta \models a \equiv b: A/R \\ \hline \Gamma; \Delta \models a \equiv b: A/R \\ \hline \Gamma; \Delta \models a \equiv b: A/R \\ \hline \Gamma; \Delta \models a \equiv b: A/R \\ \hline \Gamma; \Delta \models a \equiv b: A/R \\ \hline \Gamma; \Delta \models a \equiv b: A/R \\ \hline \Gamma; \Delta \models a \equiv b: A/R \\ \hline \Gamma; \Delta \models a \equiv b: A/R \\ \hline \Gamma; \Delta \models a \equiv b: A/R \\ \hline \Gamma; \Delta \models a \equiv b: A/R_1 \\ \hline R_1 \leq R_2 \\ \hline \Gamma; \Delta \models a \equiv b: A/R_2 \\ \hline \Gamma; \Delta \models a \equiv b: A/R_2 \\ \hline \Gamma; \Delta \models a \equiv b: A/R_2 \\ \hline \Gamma; \Delta \models a \equiv b: A/R_2 \\ \hline \Gamma; \Delta \models a \equiv b: A/R_2 \\ \hline \Gamma; \Delta \models a \equiv b: A/R_2 \\ \hline \Gamma; \Delta \models a \equiv b: A/R_2 \\ \hline \Gamma; \Delta \models a \equiv b: A/R_2 \\ \hline \Gamma; \Delta \models a \equiv b: A/R_2 \\ \hline \Gamma; \Delta \models a_1 : B/R \\ \hline \Gamma; \Delta \models a_1 : B/R \\ \hline \Gamma; \Delta \models a_1 : B/R \\ \hline \Gamma; A_1 : A/R \\ \hline E.APPCONG \\ \hline E.APPCONG$$

```
\Gamma; \Delta \vDash a_1 \sim_{A_1/R} b_1 \equiv a_2 \sim_{A_2/R} b_2
                    \Gamma, c: a_1 \sim_{A_1/R} b_1; \Delta \vDash A \equiv B: \star/R'
                    \Gamma \vDash a_1 \sim_{A_1/R} b_1 ok
                    \Gamma \vDash \forall c : a_1 \sim_{A_1/R} b_1 . A : \star/R'
                   \Gamma \vDash \forall c : a_2 \sim_{A_2/R} b_2.B : \star/R'
                                                                                                                    E_CPICONG
   \overline{\Gamma; \Delta \vDash \forall c : a_1 \sim_{A_1/R} b_1.A \equiv \forall c : a_2 \sim_{A_2/R} b_2.B : \star/R'}
                             \Gamma, c: \phi_1; \Delta \vDash a \equiv b: B/R
                             \Gamma \vDash \phi_1 ok
                                                                                                 E_CABSCONG
                 \Gamma; \Delta \vDash (\Lambda c.a) \equiv (\Lambda c.b) : \forall c : \phi_1.B/R
               \Gamma; \Delta \vDash a_1 \equiv b_1 : (\forall c : (a \sim_{A/R} b).B)/R'
               \frac{\Gamma; \widetilde{\Gamma} \vDash a \equiv b : A/R}{\Gamma; \Delta \vDash a_1[\bullet] \equiv b_1[\bullet] : (B\{\bullet/c\})/R'} \quad \text{E\_CAPPCONG}
\Gamma; \Delta \vDash \forall c : (a_1 \sim_{A/R} a_2).B_1 \equiv \forall c : (a'_1 \sim_{A'/R'} a'_2).B_2 : \star/R_0
\Gamma; \widetilde{\Gamma} \vDash a_1 \equiv a_2 : A/R
\Gamma; \widetilde{\Gamma} \vDash a_1' \equiv a_2' : A'/R'
                                                                                                                              E_CPiSnd
                        \Gamma; \Delta \vDash B_1\{\bullet/c\} \equiv B_2\{\bullet/c\} : \star/R_0
                              \Gamma; \Delta \vDash a \equiv b : A/R
                             \frac{\Gamma; \Delta \vDash a \sim_{A/R} b \equiv a' \sim_{A'/R'} b'}{\Gamma; \Delta \vDash a' \equiv b' : A'/R'} \quad \text{E\_CAST}
                                   \Gamma; \Delta \vDash a \equiv b : A/R
                                   \Gamma; \widetilde{\Gamma} \vDash A \equiv B : \star / \mathbf{Rep}
                                  \frac{\Gamma \models B : \star / R}{\Gamma; \Delta \models a \equiv b : B / R} \quad \text{E\_EQCONV}
                          \frac{\Gamma; \Delta \vDash a \sim_{A/R_1} b \equiv a' \sim_{A'/R_1} b'}{\Gamma; \Delta \vDash A \equiv A' : \star / R_1} \quad \text{E\_ISOSND}
                                   F \sim a_0 : A_0/R' \in \Sigma_0
                                   \Gamma; \Delta \vDash a \equiv a' : A/R
                                   \Gamma; \Delta \vDash b_1 \equiv b_1' : B/R_0
                                   \Gamma; \Delta \vDash b_2 \equiv b_2' : B/R_0
                                                                                                                     E_PatCong
 \overline{\Gamma;\Delta\vDash\mathbf{ifPath}\,R\,F\;a\;b_1\;b_2\equiv\mathbf{ifPath}\,R\,F\;a'\;b_1'\;b_2':B/R_0}
                 \mathsf{Path}_{R'}\ a = F
                 Path_{R'} \ a' = F
                 \Gamma \vDash a : \Pi^+ x : A/R_1 \to B/R'
                 \Gamma \vDash b : A/R_1
                 \Gamma \vDash a' : \Pi^+ x : A/R_1 \to B/R'
                 \Gamma \vDash b' : A/R_1
                 \Gamma: \Delta \vDash a \ b^{R_1,+} \equiv a' \ b'^{R_1,+} : B\{b/x\}/R'
                \Gamma; \widetilde{\Gamma} \vDash B\{b/x\} \equiv B\{b'/x\} : \star/R_0
                    \Gamma; \Delta \vdash a \equiv a' : \Pi^+ x : A/R_1 \to B/R'
                                                                                                       E_LEFTRel
```

$$\begin{array}{l} \operatorname{Path}_{R'} \ a = F \\ \operatorname{Path}_{R'} \ a' = F \\ \Gamma \vDash a : \Pi^-x : A/R_1 \to B/R' \\ \Gamma \vDash b : A/R_1 \\ \Gamma \vDash a' : \Pi^-x : A/R_1 \to B/R' \\ \Gamma \vDash b' : A/R_1 \\ \Gamma \colon \Delta \vDash a \ \square^{R_1,-} \equiv a' \ \square^{R_1,-} : B\{b/x\}/R' \\ \Gamma \colon \widetilde{\Gamma} \vDash B\{b/x\} \equiv B\{b'/x\} : \star/R_0 \\ \hline \Gamma \colon \Delta \vDash a \equiv a' : \Pi^-x : A/R_1 \to B/R' \\ \hline \Gamma \colon \Delta \vDash a \equiv a' : \Pi^-x : A/R_1 \to B/R' \\ \hline \operatorname{Path}_{R'} \ a' = F \\ \operatorname{Path}_{R'} \ a' = F \\ \Gamma \vDash a : \Pi^+x : A/R_1 \to B/R' \\ \Gamma \vDash b' : A/R_1 \\ \Gamma \colon \Delta \vDash a \ b^{R_1,+} \equiv a' \ b'^{R_1,+} : B\{b/x\}/R' \\ \hline \Gamma \colon \widetilde{\Gamma} \vDash B\{b/x\} \equiv B\{b'/x\} : \star/R_0 \\ \hline \Gamma \colon \Delta \vDash b \equiv b' : A/R_1 \\ \hline \Gamma \colon \Delta \vDash b \equiv b' : A/R_1 \\ \hline \Gamma \colon \Delta \vDash b \equiv b' : A/R_1 \\ \hline \Gamma \colon \Delta \vDash b \equiv b' : A/R_1 \\ \hline \Gamma \colon \Delta \vDash a : \forall c : (a_1 \sim_{A/R_1} a_2) . B/R' \\ \Gamma \vDash a' : \forall c : (a_1 \sim_{A/R_1} a_2) . B/R' \\ \hline \Gamma \colon \Delta \vDash a \equiv a' : \forall c : (a_1 \sim_{A/R_1} a_2) . B/R' \\ \hline \Gamma \colon \Delta \vDash a \equiv a' : \forall c : (a_1 \sim_{A/R_1} a_2) . B/R' \\ \hline \Gamma \colon \Delta \vDash a \equiv a' : \forall c : (a_1 \sim_{A/R_1} a_2) . B/R' \\ \hline \Gamma \colon \Delta \vDash a \equiv a' : \forall c : (a_1 \sim_{A/R_1} a_2) . B/R' \\ \hline \Gamma \colon \Delta \vDash a \equiv a' : \forall c : (a_1 \sim_{A/R_1} a_2) . B/R' \\ \hline \end{array} \quad \text{E-CLEFT}$$

## $\models \Gamma$ context wellformedness

## $\models \Sigma$ signature wellformedness

$$\begin{array}{cc} & \overline{\Longrightarrow} & \mathrm{Sig\_Empty} \\ & \vDash \Sigma \\ & \varnothing \vDash a : A/R' \\ & F \not \in \mathsf{dom} \, \Sigma \\ & \vDash \Sigma \cup \{F \sim a : A/R'\} \end{array}$$
 Sig\\_ConsAx

 $\Gamma \vdash \phi$  ok prop wellformedness

$$\begin{split} &\Gamma \vdash a : A/R \\ &\Gamma \vdash b : B/R \\ &\frac{|A|_R = |B|_R}{\Gamma \vdash a \sim_{A/R} b \text{ ok}} \quad \text{An\_Wff} \end{split}$$

 $\Gamma \vdash a : A/R$  typing

$$\frac{\vdash \Gamma}{\Gamma \vdash \star : \star / R} \quad \text{An\_Star}$$

$$\vdash \Gamma$$

$$\frac{x : A/R \in \Gamma}{\Gamma \vdash x : A/R} \quad \text{An\_VAR}$$

$$\frac{\Gamma, x : A/R \vdash B : \star / R'}{\Gamma \vdash A : \star / R} \quad \text{An\_PI}$$

$$\frac{\Gamma \vdash A : \star / R}{\Gamma \vdash \Pi^{\rho} x : A/R \rightarrow B : \star / R'} \quad \text{An\_PI}$$

$$\frac{\Gamma \vdash A : \star / R}{\Gamma \vdash \Pi^{\rho} x : A/R \rightarrow B : \star / R'} \quad \text{An\_ABS}$$

$$\frac{\Gamma \vdash A : \star / R}{\Gamma \vdash \lambda^{\rho} x : A/R \land a : (\Pi^{\rho} x : A/R \rightarrow B) / R'} \quad \text{An\_ABS}$$

$$\frac{\Gamma \vdash b : (\Pi^{\rho} x : A/R \rightarrow B) / R'}{\Gamma \vdash b : a : A/R} \quad \text{An\_APP}$$

$$\frac{\Gamma \vdash a : A/R}{\Gamma \vdash b : a : A/R} \quad \text{An\_APP}$$

$$\frac{\Gamma \vdash a : A/R}{\Gamma \vdash B : \star / R} \quad \text{An\_CONV}$$

$$\frac{\Gamma \vdash \alpha : A/R}{\Gamma \vdash B : \star / R} \quad \text{An\_CONV}$$

$$\frac{\Gamma \vdash \phi \text{ ok}}{\Gamma \vdash B : \star / R} \quad \text{An\_CONV}$$

$$\frac{\Gamma \vdash \phi \text{ ok}}{\Gamma \vdash \forall c : \phi . B : \star / R} \quad \text{An\_CPI}$$

$$\frac{\Gamma \vdash \phi \text{ ok}}{\Gamma \vdash \Delta c : \phi . a : (\forall c : \phi . B) / R} \quad \text{An\_CABS}$$

$$\frac{\Gamma \vdash a_1 : (\forall c : a \sim_{A_1/R} b . B) / R'}{\Gamma \vdash A_1 : (\forall c : a \sim_{A_1/R} b . B) / R'} \quad \text{An\_CAPP}$$

$$\frac{\Gamma \vdash a_1 : (\forall c : a \sim_{A_1/R} b . B) / R'}{\Gamma \vdash a_1 : (\gamma : a \sim_{R} b} \quad \text{An\_CAPP}$$

$$\frac{\Gamma \vdash a_1 : (\forall c : a \sim_{A_1/R} b . B) / R'}{\Gamma \vdash a_1 : A/R_1} \quad \text{An\_CAPP}$$

$$\frac{\Gamma \vdash a_1 : (\forall c : a \sim_{A_1/R} b . B) / R'}{\Gamma \vdash a_1 : A/R_1} \quad \text{An\_FAM}$$

$$\frac{R_1 \le R_2}{\Gamma \vdash a : A/R_1} \quad \text{An\_FAM}$$

$$\frac{R_1 \le R_2}{\Gamma \vdash a : A/R_1} \quad \text{An\_SubRole}$$

 $\Gamma; \Delta \vdash \gamma : \phi_1 \sim \phi_2$ 

coercion between props

```
\Gamma; \Delta \vdash \gamma_1 : A_1 \sim_R A_2
                                                                         \Gamma; \Delta \vdash \gamma_2 : B_1 \sim_R B_2
                                                                         \Gamma \vdash A_1 \sim_{A/R} B_1 ok
                                  \frac{\Gamma \vdash A_2 \sim_{A/R} B_2 \text{ ok}}{\Gamma; \Delta \vdash (\gamma_1 \sim_A \gamma_2) : (A_1 \sim_{A/R} B_1) \sim (A_2 \sim_{A/R} B_2)} \quad \text{An\_PropCong}
                                                          \frac{\Gamma; \Delta \vdash \gamma : \forall c : \phi_1.A_2 \sim_R \forall c : \phi_2.B_2}{\Gamma; \Delta \vdash \mathbf{cpiFst} \ \gamma : \phi_1 \sim \phi_2} \quad \text{An\_CPiFst}
                                                                           \frac{\Gamma; \Delta \vdash \gamma : \phi_1 \sim \phi_2}{\Gamma; \Delta \vdash \mathbf{sym} \ \gamma : \phi_2 \sim \phi_1} \quad \text{An_IsoSym}
                                                                               \Gamma; \Delta \vdash \gamma : A \sim_R B
                                                                               \Gamma \vdash a_1 \sim_{A/R} a_2 ok
                                                                               \Gamma \vdash a_1' \sim_{B/R} a_2' ok
       |a_{1}|_{R} = |a'_{1}|_{R} 
|a_{2}|_{R} = |a'_{2}|_{R} 
|a_{2}|_{R} = |a'_{2}|_{R} 
\Gamma; \Delta \vdash \mathbf{conv} \ (a_{1} \sim_{A/R} a_{2}) \sim_{\gamma} (a'_{1} \sim_{B/R} a'_{2}) : (a_{1} \sim_{A/R} a_{2}) \sim (a'_{1} \sim_{B/R} a'_{2}) 
An_IsoConv
\Gamma; \Delta \vdash \gamma : A \sim_R B
                                                          coercion between types
                                                                                      \vdash \Gamma
                                                                                      c: a \sim_{A/R} b \in \Gamma
                                                                                      \frac{c \in \Delta}{\Gamma; \Delta \vdash c : a \sim_R b} \quad \text{An\_Assn}
                                                                                \frac{\Gamma \vdash a : A/R}{\Gamma ; \Delta \vdash \mathbf{refl} \; a : a \sim_R a} \quad \text{An\_Refl}
                                                                                \Gamma \vdash a : A/R
                                                                                \Gamma \vdash b : B/R
                                                                                |a|_R = |b|_R
                                                                     \frac{\Gamma; \widetilde{\Gamma} \vdash \gamma : A \sim_R B}{\Gamma; \Delta \vdash (a \models \mid_{\gamma} b) : a \sim_R b} \quad \text{An\_EraseEQ}
                                                                                      \Gamma \vdash b : B/R
                                                                                      \Gamma \vdash a : A/R
                                                                                      \Gamma; \widetilde{\Gamma} \vdash \gamma_1 : B \sim_R A
                                                                                 \frac{\Gamma; \Delta \vdash \gamma : b \sim_R a}{\Gamma; \Delta \vdash \mathbf{sym} \ \gamma : a \sim_R b} \quad \text{An\_Sym}
                                                                                 \Gamma; \Delta \vdash \gamma_1 : a \sim_R a_1
                                                                                 \Gamma; \Delta \vdash \gamma_2 : a_1 \sim_R b
                                                                                 \Gamma \vdash a : A/R
                                                                                 \Gamma \vdash a_1 : A_1/R
                                                                            \frac{\Gamma; \widetilde{\Gamma} \vdash \gamma_3 : A \sim_R A_1}{\Gamma; \Delta \vdash (\gamma_1; \gamma_2) : a \sim_R b} \quad \text{An\_Trans}
                                                                                     \Gamma \vdash a_1 : B_0/R
                                                                                      \Gamma \vdash a_2 : B_1/R
                                                                                      |B_0|_R = |B_1|_R
                                                                          \frac{\models |a_1|_R > |a_2|_R/R}{\Gamma; \Delta \vdash \mathbf{red} \ a_1 \ a_2 : a_1 \sim_R \ a_2} \quad \text{An\_Beta}
```

```
\Gamma; \Delta \vdash \gamma_1 : A_1 \sim_{R'} A_2
                                            \Gamma, x: A_1/R; \Delta \vdash \gamma_2: B_1 \sim_{R'} B_2
                                            B_3 = B_2\{x \triangleright_{R'} \operatorname{sym} \gamma_1/x\}
                                            \Gamma \vdash \Pi^{\rho} x : A_1/R \rightarrow B_1 : \star/R'
                                            \Gamma \vdash \Pi^{\rho} x : A_1/R \rightarrow B_2 : \star/R'
                                            \Gamma \vdash \Pi^{\rho} x : A_2/R \rightarrow B_3 : \star/R'
                                            R \leq R'
                                                                                                                                                       An_PiCong
         \overline{\Gamma; \Delta \vdash \Pi^{R,\rho} x : \gamma_1.\gamma_2 : (\Pi^{\rho} x : A_1/R \to B_1) \sim_{R'} (\Pi^{\rho} x : A_2/R \to B_3)}
                                           \Gamma; \Delta \vdash \gamma_1 : A_1 \sim_R A_2
                                           \Gamma, x: A_1/R; \Delta \vdash \gamma_2: b_1 \sim_{R'} b_2
                                           b_3 = b_2\{x \triangleright_{R'} \operatorname{sym} \gamma_1/x\}
                                           \Gamma \vdash A_1 : \star / R
                                           \Gamma \vdash A_2 : \star / R
                                           (\rho = +) \lor (x \not\in \mathsf{fv} \mid b_1 \mid_{R'})
                                            (\rho = +) \lor (x \not\in \mathsf{fv} \mid b_3 \mid_{R'})
                                           \Gamma \vdash (\lambda^{\rho} x : A_1/R.b_2) : B/R'
                                           R \leq R'
                                                                                                                                              An_AbsCong
              \overline{\Gamma; \Delta \vdash (\lambda^{R,\rho}x : \gamma_1.\gamma_2) : (\lambda^{\rho}x : A_1/R.b_1) \sim_{R'} (\lambda^{\rho}x : A_2/R.b_3)}
                                                     \Gamma; \Delta \vdash \gamma_1 : a_1 \sim_{R'} b_1
                                                     \Gamma; \Delta \vdash \gamma_2 : a_2 \sim_R b_2
                                                     \Gamma \vdash a_1 \ a_2^{R,\rho} : A/R'
                                                     \Gamma \vdash b_1 \ b_2^{R,\rho} : B/R'
                                   \frac{\Gamma; \widetilde{\Gamma} \vdash \gamma_3 : A \sim_{R'} B}{\Gamma; \Delta \vdash \gamma_1 \ \gamma_2^{R,\rho} : a_1 \ a_2^{R,\rho} \sim_{R'} b_1 \ b_2^{R,\rho}} \quad \text{An\_AppCong}
                          \Gamma; \Delta \vdash \gamma: \Pi^{\rho}x: A_1/R \to B_1 \sim_{R'} \Pi^{\rho}x: A_2/R \to B_2
                                                                                                                                            An_PiFst
                                                   \Gamma; \Delta \vdash \mathbf{piFst} \gamma : A_1 \sim_R A_2
                          \Gamma; \Delta \vdash \gamma_1 : \Pi^{\rho} x : A_1/R \to B_1 \sim_{R'} \Pi^{\rho} x : A_2/R \to B_2
                          \Gamma; \Delta \vdash \gamma_2 : a_1 \sim_R a_2
                          \Gamma \vdash a_1 : A_1/R
                          \Gamma \vdash a_2 : A_2/R
                                                                                                                                             An_PiSnd
                                     \Gamma; \Delta \vdash \gamma_1@\gamma_2 : \overline{B_1\{a_1/x\} \sim_{R'} B_2\{a_2/x\}}
                                   \Gamma; \Delta \vdash \gamma_1 : a_1 \sim_{A_1/R} b_1 \sim a_2 \sim_{A_2/R} b_2
                                   \Gamma, c: a_1 \sim_{A_1/R} b_1; \Delta \vdash \gamma_3: B_1 \sim_{R'} B_2
                                   B_3 = B_2\{c \triangleright_{R'} \operatorname{\mathbf{sym}} \gamma_1/c\}
                                   \Gamma \vdash \forall c : a_1 \sim_{A_1/R} b_1 . B_1 : \star / R'
                                   \Gamma \vdash \forall c : a_2 \sim_{A_2/R} b_2.B_3 : \star/R'
                                   \Gamma \vdash \forall c : a_1 \sim_{A_1/R} b_1.B_2 : \star/R'
                                                                                                                                                      An_CPiCong
      \overline{\Gamma; \Delta \vdash (\forall c : \gamma_1.\gamma_3) : (\forall c : a_1 \sim_{A_1/R} b_1.B_1) \sim_R (\forall c : a_2 \sim_{A_2/R} b_2.B_3)}
                      \Gamma; \Delta \vdash \gamma_1 : b_0 \sim_{A_1/R} b_1 \sim b_2 \sim_{A_2/R} b_3
                      \Gamma, c: b_0 \sim_{A_1/R} b_1; \Delta \vdash \gamma_3: a_1 \sim_{R'} a_2
                      a_3 = a_2 \{c \triangleright_{R'} \operatorname{\mathbf{sym}} \gamma_1/c\}
                      \Gamma \vdash (\Lambda c : b_0 \sim_{A_1/R} b_1.a_1) : \forall c : b_0 \sim_{A_1/R} b_1.B_1/R'
                      \Gamma \vdash (\Lambda c : b_0 \sim_{A_1/R} b_1.a_2) : B/R'
                      \Gamma \vdash (\Lambda c : b_2 \sim_{A_2/R} b_3.a_3) : \forall c : b_2 \sim_{A_2/R} b_3.B_2/R'
                      \Gamma; \Gamma \vdash \gamma_4 : \forall c : b_0 \sim_{A_1/R} b_1.B_1 \sim_{R'} \forall c : \phi_2.B_2
                                                                                                                                                         An_CABSCONG
\Gamma; \Delta \vdash (\lambda c : \gamma_1.\gamma_3@\gamma_4) : (\Lambda c : b_0 \sim_{A_1/R} b_1.a_1) \sim_{R'} (\Lambda c : b_2 \sim_{A_2/R} b_3.a_3)
```

$$\begin{array}{c} \Gamma; \Delta \vdash \gamma_{1} : a_{1} \sim_{R} b_{1} \\ \Gamma; \widetilde{\Gamma} \vdash \gamma_{2} : a_{2} \sim_{R'} b_{2} \\ \Gamma; \widetilde{\Gamma} \vdash \gamma_{3} : a_{3} \sim_{R'} b_{3} \\ \Gamma \vdash a_{1}[\gamma_{2}] : A/R \\ \Gamma \vdash b_{1}[\gamma_{3}] : B/R \\ \Gamma; \widetilde{\Gamma} \vdash \gamma_{4} : A \sim_{R} B \\ \hline \Gamma; \Delta \vdash \gamma_{1}(\gamma_{2}, \gamma_{3}) : a_{1}[\gamma_{2}] \sim_{R} b_{1}[\gamma_{3}] \end{array} \quad \text{An\_CAPPCong} \\ \Gamma; \Delta \vdash \gamma_{1} : (\forall c_{1} : a \sim_{A/R} a'.B_{1}) \sim_{R_{0}} (\forall c_{2} : b \sim_{B/R'} b'.B_{2}) \\ \Gamma; \widetilde{\Gamma} \vdash \gamma_{2} : a \sim_{R} a' \\ \Gamma; \widetilde{\Gamma} \vdash \gamma_{3} : b \sim_{R'} b' \\ \hline \Gamma; \Delta \vdash \gamma_{1} @ (\gamma_{2} \sim \gamma_{3}) : B_{1}\{\gamma_{2}/c_{1}\} \sim_{R_{0}} B_{2}\{\gamma_{3}/c_{2}\} \\ \hline \Gamma; \Delta \vdash \gamma_{1} : a \sim_{R_{1}} a' \\ \hline \Gamma; \Delta \vdash \gamma_{2} : a \sim_{A/R_{1}} a' \sim b \sim_{B/R_{1}} b' \\ \hline \Gamma; \Delta \vdash \gamma_{1} \rhd_{R_{1}} \gamma_{2} : b \sim_{R_{1}} b' \\ \hline \Gamma; \Delta \vdash \gamma : (a \sim_{A/R} a') \sim (b \sim_{B/R} b') \\ \hline \Gamma; \Delta \vdash \mathbf{isoSnd} \gamma : A \sim_{R} B \\ \hline \Gamma; \Delta \vdash \gamma : a \sim_{R_{1}} b \\ \hline \Gamma; \Delta \vdash \mathbf{sub} \gamma : a \sim_{R_{2}} b \\ \hline \Lambda_{N\_SUB} \end{array} \quad \text{An\_Sub}$$

 $\vdash \Gamma$  context wellformedness

 $\vdash \Sigma$  signature wellformedness

 $\Gamma \vdash a \leadsto b/R$  single-step, weak head reduction to values for annotated language

$$\frac{\Gamma \vdash a \leadsto a'/R_1}{\Gamma \vdash a \ b^{R,\rho} \leadsto a' \ b^{R,\rho}/R_1} \quad \text{An_Appleft}$$
 
$$\frac{\text{Value}_R \ (\lambda^\rho x \colon A/R.w)}{\Gamma \vdash (\lambda^\rho x \colon A/R.w) \ a^{R,\rho} \leadsto w\{a/x\}/R} \quad \text{An_Appabs}$$

$$\frac{\Gamma \vdash a \leadsto a'/R}{\Gamma \vdash a[\gamma] \leadsto a'[\gamma]/R} \quad \text{An\_CAPPLEFT}$$

$$\overline{\Gamma \vdash (\Lambda c : \phi. b)[\gamma] \leadsto b\{\gamma/c\}/R} \quad \text{An\_CAPPCABS}$$

$$\frac{\Gamma \vdash A : \star/R}{\Gamma \vdash A : \star/R} \quad \Gamma, x : A/R \vdash b \leadsto b'/R_1 \quad \text{An\_ABSTERM}$$

$$\frac{\Gamma \vdash (\lambda^- x : A/R.b) \leadsto (\lambda^- x : A/R.b')/R_1}{\Gamma \vdash (\lambda^- x : A/R.b) \leadsto (\lambda^- x : A/R.b')/R_1} \quad \text{An\_ABSTERM}$$

$$\frac{F \sim a : A/R \in \Sigma_1}{\Gamma \vdash F \leadsto a/R} \quad \text{An\_AXIOM}$$

$$\frac{\Gamma \vdash a \leadsto a'/R}{\Gamma \vdash a \bowtie_{R_1} \gamma \leadsto a' \bowtie_{R_1} \gamma/R} \quad \text{An\_CONVTERM}$$

$$\frac{\text{Value}_R \ v}{\Gamma \vdash (v \bowtie_{R_2} \gamma_1) \bowtie_{R_2} \gamma_2 \leadsto v \bowtie_{R_2} (\gamma_1; \gamma_2)/R} \quad \text{An\_COMBINE}$$

$$\text{Value}_R \ v$$

$$\Gamma; \widetilde{\Gamma} \vdash \gamma : \Pi^\rho x_1 : A_1/R \to B_1 \leadsto_{R'} \Pi^\rho x_2 : A_2/R \to B_2$$

$$b' = b \bowtie_{R'} \text{sym} (\text{piFst} \gamma)$$

$$\gamma' = \gamma@(b') \models_{(\text{piFst} \gamma)} b)$$

$$\Gamma \vdash (v \bowtie_{R'} \gamma) \ b^{R,\rho} \leadsto ((v \ b'^{R,\rho}) \bowtie_{R'} \gamma')/R} \quad \text{An\_PUSH}$$

$$\text{Value}_R \ v$$

$$\Gamma; \widetilde{\Gamma} \vdash \gamma : \forall c_1 : a_1 \leadsto_{B_1/R} b_1.A_1 \leadsto_{R'} \forall c_2 : a_2 \leadsto_{B_2/R} b_2.A_2$$

$$\gamma_1' = \gamma_1 \bowtie_{R'} \text{sym} (\text{cpiFst} \gamma)$$

$$\gamma' = \gamma@(\gamma_1' \leadsto \gamma_1)$$

$$\Gamma \vdash (v \bowtie_{R'} \gamma)[\gamma_1] \leadsto ((v[\gamma_1']) \bowtie_{R'} \gamma')/R$$

$$\text{Definition rules:} \qquad 162 \ \text{good} \qquad 0 \ \text{bad}$$

0 bad

Definition rule clauses: 517 good