

$tnvar, x, y, f, m, n$	variables
$covar, c$	coercion variables
$datacon, K$	
$const, T, F$	
$index, i$	indices

$relflag, \rho$	$::=$ $ $ $+$ $ $ $-$ $ $ $app_rho \nu$ S $ $ (ρ) S	relevance flag
$appflag, \nu$	$::=$ $ $ R $ $ ρ	applicative flag
$role, R$	$::=$ $ $ Nom $ $ Rep $ $ $R_1 \cap R_2$ S $ $ param $R_1 R_2$ S $ $ $app_role \nu$ S $ $ (R) S	Role
$constraint, \phi$	$::=$ $ $ $a \sim_{A/R} b$ $ $ (ϕ) S $ $ $\phi\{b/x\}$ S $ $ $ \phi $ S $ $ $a \sim_R b$ S	props
$tm, a, b, p, v, w, A, B, C$	$::=$ $ $ \star $ $ x $ $ $\lambda^\rho x:A.b$ bind x in b $ $ $\lambda^\rho x.b$ bind x in b $ $ $a \ b^\nu$ $ $ $\Pi^\rho x:A \rightarrow B$ bind x in B $ $ $\Lambda c:\phi.b$ bind c in b $ $ $\Lambda c.b$ bind c in b $ $ $a[\gamma]$ $ $ $\forall c:\phi.B$ bind c in B $ $ $a \triangleright_R \gamma$ $ $ F $ $ \square $ $ $\text{case}_R a \text{ of } F \rightarrow b_1 \parallel - \rightarrow b_2$ $ $ K $ $ match a with brs $ $ sub $R a$ $ $ $a\{b/x\}$ S $ $ $a\{\gamma/c\}$ S $ $ $a\{b/x\}$ S $ $ $a\{\gamma/c\}$ S	types and kinds

		a	S	
		a	S	
		(a)	S	
		a	S	parsing precedence is hard
		$ a _R$	S	
		Int	S	
		Bool	S	
		Nat	S	
		Vec	S	
		0	S	
		S	S	
		True	S	
		Fix	S	
		Age	S	
		$a \rightarrow b$	S	
		$\phi \Rightarrow A$	S	
		$a \ b$	S	
		$\lambda x. a$	S	
		$\lambda x : A. a$	S	
		$\forall x : A \rightarrow B$	S	
		if ϕ then a else b	S	
brs	$::=$			case branches
		none		
		$K \Rightarrow a; brs$		
		$brs\{a/x\}$	S	
		$brs\{\gamma/c\}$	S	
		(brs)	S	
co, γ	$::=$			explicit coercions
		•		
		c		
		red $a \ b$		
		refl a		
		$(a \models_\gamma b)$		
		sym γ		
		$\gamma_1; \gamma_2$		
		sub γ		
		$\Pi^{R,\rho} x : \gamma_1. \gamma_2$	bind x in γ_2	
		$\lambda^{R,\rho} x : \gamma_1. \gamma_2$	bind x in γ_2	
		$\gamma_1 \ \gamma_2^{R,\rho}$		
		piFst γ		
		cpiFst γ		
		isoSnd γ		
		$\gamma_1 @ \gamma_2$		
		$\forall c : \gamma_1. \gamma_3$	bind c in γ_3	

			\emptyset	
			$\Sigma \cup \{F : sig_sort\}$	
			Σ_0	M
			Σ_1	M
			$ \Sigma $	M
$available_props, \Delta$	$::=$		\emptyset	
			Δ, c	
			$\tilde{\Gamma}$	M
			(Δ)	M
$terminals$	$::=$		\leftrightarrow	
			\Leftrightarrow	
			\longrightarrow	
			min	
			\equiv	
			\forall	
			\in	
			\notin	
			\Leftarrow	
			\Rightarrow	
			\Rightarrow^*	
			\rightarrow	
			Λ	
			\square	
			\vdash	
			\vdash	
			\models	
			\models	
			\neq	
			\triangleright	
			ok	
			$-$	
			\rightsquigarrow	
			\rightsquigarrow^*	
			\rightsquigarrow	
			\emptyset	
			\circ	
			fv	
			dom	
			\sim	
			$\langle \rangle$	
			$ $	

	<div> <div>•</div> <div>fst</div> <div>snd</div> <div>as</div> <div>\Rightarrow</div> <div>$\vdash_{=}$</div> <div>refl₂</div> <div>$++$</div> <div>{</div> <div>}</div> </div>	
<i>formula, ψ</i>	<div> $::=$ <div> <div><i>judgement</i></div> <div>$x : A \in \Gamma$</div> <div>$x : R \in \Omega$</div> <div>$c : \phi \in \Gamma$</div> <div>$F : sig_sort \in \Sigma$</div> <div>$x \in \Delta$</div> <div>$c \in \Delta$</div> <div>$c \text{ not relevant} \in \gamma$</div> <div>$x \notin fva$</div> <div>$x \notin \text{dom } \Gamma$</div> <div>$uniq \ \Gamma$</div> <div>$uniq(\Omega)$</div> <div>$c \notin \text{dom } \Gamma$</div> <div>$T \notin \text{dom } \Sigma$</div> <div>$F \notin \text{dom } \Sigma$</div> <div>$R_1 = R_2$</div> <div>$a = b$</div> <div>$\phi_1 = \phi_2$</div> <div>$\Gamma_1 = \Gamma_2$</div> <div>$\gamma_1 = \gamma_2$</div> <div>$\neg \psi$</div> <div>$\psi_1 \wedge \psi_2$</div> <div>$\psi_1 \vee \psi_2$</div> <div>$\psi_1 \Rightarrow \psi_2$</div> <div>$(\psi)$</div> <div>$\psi$</div> <div>$c : (a : A \sim b : B) \in \Gamma$</div> </div> </div>	suppress lc hypothesis generated by Ott
<i>JSubRole</i>	<div> $::=$ <div> <div>$R_1 \leq R_2$</div> </div> </div>	Subroling judgement
<i>JPath</i>	<div> $::=$ <div> <div>$\text{Path } a = F@Rs$</div> </div> </div>	Type headed by constant (partial function)

$JCasePath$	$::=$ $ \quad \text{CasePath}_R \ a = F$	Type headed by constant (role-sensitive part)
$JPatCtx$	$::=$ $ \quad \Omega; \Gamma \vdash p :_F B \Rightarrow A$	Contexts generated by a pattern (variables bound)
$JMatchSubst$	$::=$ $ \quad \text{match } a_1 \text{ with } p \rightarrow b_1 = b_2$	match and substitute
$JValuePath$	$::=$ $ \quad \text{ValuePath } a = F$	Type headed by constant (role-sensitive part)
$JApplyArgs$	$::=$ $ \quad \text{apply args } a \text{ to } b \mapsto b'$	apply arguments of a (headed by a constant)
$JValue$	$::=$ $ \quad \text{Value}_R \ A$	values
$JValueType$	$::=$ $ \quad \text{ValueType}_R \ A$	Types with head forms (erased language)
$Jconsistent$	$::=$ $ \quad \text{consistent}_R \ a \ b$	(erased) types do not differ in their heads
$Jroleing$	$::=$ $ \quad \Omega \vdash a : R$	Roleing judgment
$JChk$	$::=$ $ \quad (\rho = +) \vee (x \notin \text{fv } A)$	irrelevant argument check
$Jpar$	$::=$ $ \quad \Omega \vdash a \Rightarrow_R b$ $ \quad \Omega \vdash a \Rightarrow_R^* b$ $ \quad \Omega \vdash a \Leftrightarrow_R b$	parallel reduction (implicit language) multistep parallel reduction parallel reduction to a common term
$Jbeta$	$::=$ $ \quad \vdash a > b/R$ $ \quad \vdash a \rightsquigarrow b/R$ $ \quad \vdash a \rightsquigarrow^* b/R$	primitive reductions on erased terms single-step head reduction for implicit language multistep reduction
$JBranchTyping$	$::=$ $ \quad \Gamma \vdash \text{case}_R \ a : A \text{ of } b : B \Rightarrow C \mid C'$	Branch Typing (aligning the types of case)
$Jett$	$::=$ $ \quad \Gamma \vdash \phi \text{ ok}$ $ \quad \Gamma \vdash a : A$ $ \quad \Gamma; \Delta \vdash \phi_1 \equiv \phi_2$	Prop wellformedness typing prop equality

		$\Gamma; \Delta \models a \equiv b : A/R$	definitional equality
		$\models \Gamma$	context wellformedness
$Jsig$	$::=$		
		$\models \Sigma$	signature wellformedness
$Jann$	$::=$		
		$\Gamma \vdash \phi \text{ ok}$	prop wellformedness
		$\Gamma \vdash a : A/R$	typing
		$\Gamma; \Delta \vdash \gamma : \phi_1 \sim \phi_2$	coercion between props
		$\Gamma; \Delta \vdash \gamma : A \sim_R B$	coercion between types
		$\vdash \Gamma$	context wellformedness
$Jred$	$::=$		
		$\Gamma \vdash a \rightsquigarrow b/R$	single-step, weak head reduction to values for annotated lang
$judgement$	$::=$		
		$JSubRole$	
		$JPath$	
		$JCasePath$	
		$JPatCtx$	
		$JMatchSubst$	
		$JValuePath$	
		$JApplyArgs$	
		$JValue$	
		$JValueType$	
		$Jconsistent$	
		$Jroleing$	
		$Jchk$	
		$Jpar$	
		$Jbeta$	
		$JBranchTyping$	
		$Jett$	
		$Jsig$	
		$Jann$	
		$Jred$	
$user_syntax$	$::=$		
		$tmvar$	
		$covar$	
		$datacon$	
		$const$	
		$index$	
		$relflag$	
		$appflag$	
		$role$	
		$constraint$	

tm
 brs
 co
 $role_context$
 $roles$
 sig_sort
 $sort$
 $context$
 sig
 $available_props$
 $terminals$
 $formula$

$R_1 \leq R_2$ Subroling judgement

$$\begin{array}{c}
\overline{\mathbf{Nom} \leq R} \quad \text{NOMBOT} \\
\overline{R \leq \mathbf{Rep}} \quad \text{REPTOP} \\
\overline{R \leq R} \quad \text{REFL} \\
\frac{R_1 \leq R_2 \quad R_2 \leq R_3}{R_1 \leq R_3} \quad \text{TRANS}
\end{array}$$

$\text{Path } a = F@Rs$ Type headed by constant (partial function)

$$\begin{array}{c}
\frac{F : A@Rs \in \Sigma_0}{\text{Path } F = F@Rs} \quad \text{PATH_ABSCONST} \\
\frac{F : p \sim a : A/R_1@Rs \in \Sigma_0}{\text{Path } F = F@Rs} \quad \text{PATH_CONST} \\
\frac{\text{Path } a = F@R_1, Rs}{\text{Path } (a \ b'^{R_1}) = F@Rs} \quad \text{PATH_APP} \\
\frac{\text{Path } a = F@Rs}{\text{Path } (a \ \square^-) = F@Rs} \quad \text{PATH_IAPP} \\
\frac{\text{Path } a = F@Rs}{\text{Path } (a[\bullet]) = F@Rs} \quad \text{PATH_CAPP}
\end{array}$$

$\text{CasePath}_R a = F$ Type headed by constant (role-sensitive partial function used in case)

$$\begin{array}{c}
\frac{F : A@Rs \in \Sigma_0}{\text{CasePath}_R F = F} \quad \text{CASEPATH_ABSCONST} \\
\frac{F : p \sim a : A/R_1@Rs \in \Sigma_0 \quad \neg(R_1 \leq R)}{\text{CasePath}_R F = F} \quad \text{CASEPATH_CONST} \\
\frac{\text{CasePath}_R a = F}{\text{CasePath}_R (a \ b'^{\rho}) = F} \quad \text{CASEPATH_APP} \\
\frac{\text{CasePath}_R a = F}{\text{CasePath}_R (a[\bullet]) = F} \quad \text{CASEPATH_CAPP}
\end{array}$$

$\boxed{\Omega; \Gamma \vdash p :_F B \Rightarrow A}$ Contexts generated by a pattern (variables bound by the pattern)

$$\begin{array}{c}
\frac{}{\emptyset; \emptyset \vdash F :_F A \Rightarrow A} \text{PATCTX_CONST} \\
\frac{\Omega; \Gamma \vdash p :_F \Pi^+ x : A' \rightarrow A \Rightarrow B}{\Omega, x : R; \Gamma, x : A' \vdash p \ x^R :_F A \Rightarrow B} \text{PATCTX_PIREL} \\
\frac{\Omega; \Gamma \vdash p :_F \Pi^- x : A' \rightarrow A \Rightarrow B}{\Omega; \Gamma, x : A' \vdash p \ \square^- :_F A \Rightarrow B} \text{PATCTX_PIIRR} \\
\frac{\Omega; \Gamma \vdash p :_F \forall c : \phi. A \Rightarrow B}{\Omega; \Gamma, c : \phi \vdash p[\bullet] :_F A \Rightarrow B} \text{PATCTX_CPI}
\end{array}$$

$\boxed{\text{match } a_1 \text{ with } p \rightarrow b_1 = b_2}$ match and substitute

$$\begin{array}{c}
\frac{}{\text{match } F \text{ with } F \rightarrow b = b} \text{MATCHSUBST_CONST} \\
\frac{\text{match } a_1 \text{ with } a_2 \rightarrow b_1 = b_2}{\text{match } (a_1 \ a^R) \text{ with } (a_2 \ x^R) \rightarrow b_1 = (b_2\{a/x\})} \text{MATCHSUBST_APPRELR} \\
\frac{\text{match } a_1 \text{ with } a_2 \rightarrow b_1 = b_2}{\text{match } (a_1 \ \square^-) \text{ with } (a_2 \ \square^-) \rightarrow b_1 = b_2} \text{MATCHSUBST_APPIRREL} \\
\frac{\text{match } a_1 \text{ with } a_2 \rightarrow b_1 = b_2}{\text{match } (a_1[\bullet]) \text{ with } (a_2[\bullet]) \rightarrow b_1 = b_2} \text{MATCHSUBST_CAPP}
\end{array}$$

$\boxed{\text{ValuePath } a = F}$ Type headed by constant (role-sensitive partial function used in value)

$$\begin{array}{c}
\frac{F : A@Rs \in \Sigma_0}{\text{ValuePath } F = F} \text{VALUEPATH_ABSCONST} \\
\frac{F : p \sim a : A/R_1@Rs \in \Sigma_0}{\text{ValuePath } F = F} \text{VALUEPATH_CONST} \\
\frac{\text{ValuePath } a = F}{\text{ValuePath } (a \ b'^\nu) = F} \text{VALUEPATH_APP} \\
\frac{\text{ValuePath } a = F}{\text{ValuePath } (a[\bullet]) = F} \text{VALUEPATH_CAPP}
\end{array}$$

$\boxed{\text{apply args } a \text{ to } b \mapsto b'}$ apply arguments of a (headed by a constant) to b

$$\begin{array}{c}
\frac{}{\text{apply args } F \text{ to } b \mapsto b} \text{APPLYARGS_CONST} \\
\frac{\text{apply args } a \text{ to } b \mapsto b'}{\text{apply args } a \ a'^\rho \text{ to } b \mapsto b' \ a'^\rho} \text{APPLYARGS_APP} \\
\frac{\text{apply args } a \text{ to } b \mapsto b'}{\text{apply args } a[\bullet] \text{ to } b \mapsto b'[\bullet]} \text{APPLYARGS_CAPP}
\end{array}$$

$\boxed{\text{Value}_R \ A}$ values

$$\begin{array}{c}
\frac{}{\text{Value}_R \ \star} \text{VALUE_STAR} \\
\frac{}{\text{Value}_R \ \Pi^\rho x : A \rightarrow B} \text{VALUE_PI} \\
\frac{}{\text{Value}_R \ \forall c : \phi. B} \text{VALUE_CPI}
\end{array}$$

$$\frac{}{\text{Value}_R \lambda^+ x : A. a} \quad \text{VALUE_ABSREL}$$

$$\frac{}{\text{Value}_R \lambda^+ x. a} \quad \text{VALUE_UABSREL}$$

$$\frac{\text{Value}_R a}{\text{Value}_R \lambda^- x. a} \quad \text{VALUE_UABSIRREL}$$

$$\frac{}{\text{Value}_R \Lambda c : \phi. a} \quad \text{VALUE_CABS}$$

$$\frac{}{\text{Value}_R \Lambda c. a} \quad \text{VALUE_UCABS}$$

$$\frac{\text{ValuePath } a = F \quad F : A @ R s \in \Sigma_0}{\text{Value}_R a} \quad \text{VALUE_CONST}$$

$$\frac{\text{ValuePath } a = F \quad F : p \sim b : A / R_1 @ R s \in \Sigma_0 \quad \neg(\text{match } a \text{ with } p \rightarrow \square = \square)}{\text{Value}_R a} \quad \text{VALUE_PATH}$$

$$\frac{\text{ValuePath } a = F \quad F : p \sim b : A / R_1 @ R s \in \Sigma_0 \quad \text{match } a \text{ with } p \rightarrow \square = \square \quad \neg(R_1 \leq R)}{\text{Value}_R a} \quad \text{VALUE_PATHMATCH}$$

$\boxed{\text{ValueType}_R A}$ Types with head forms (erased language)

$$\frac{}{\text{ValueType}_R \star} \quad \text{VALUE_TYPE_STAR}$$

$$\frac{}{\text{ValueType}_R \Pi^\rho x : A \rightarrow B} \quad \text{VALUE_TYPE_PI}$$

$$\frac{}{\text{ValueType}_R \forall c : \phi. B} \quad \text{VALUE_TYPE_CPI}$$

$$\frac{\text{ValuePath } a = F}{\text{ValueType}_R a} \quad \text{VALUE_TYPE_VALUEPATH}$$

$\boxed{\text{consistent}_R a \ b}$ (erased) types do not differ in their heads

$$\frac{}{\text{consistent}_R \star \star} \quad \text{CONSISTENT_A_STAR}$$

$$\frac{}{\text{consistent}_{R'} (\Pi^\rho x_1 : A_1 \rightarrow B_1) (\Pi^\rho x_2 : A_2 \rightarrow B_2)} \quad \text{CONSISTENT_A_PI}$$

$$\frac{}{\text{consistent}_R (\forall c_1 : \phi_1. A_1) (\forall c_2 : \phi_2. A_2)} \quad \text{CONSISTENT_A_CPI}$$

$$\frac{\text{ValuePath } a_1 = F \quad \text{ValuePath } a_2 = F}{\text{consistent}_R a_1 \ a_2} \quad \text{CONSISTENT_A_VALUEPATH}$$

$$\frac{\neg \text{ValueType}_R b}{\text{consistent}_R a \ b} \quad \text{CONSISTENT_A_STEP_R}$$

$$\frac{\neg \text{ValueType}_R a}{\text{consistent}_R a \ b} \quad \text{CONSISTENT_A_STEP_L}$$

$\boxed{\Omega \models a : R}$ Roleing judgment

$$\frac{\text{uniq}(\Omega)}{\Omega \models \square : R} \quad \text{ROLE_A_BULLET}$$

$$\frac{\text{uniq}(\Omega)}{\Omega \models \star : R} \quad \text{ROLE_A_STAR}$$

$$\frac{\begin{array}{c} \text{uniq}(\Omega) \\ x : R \in \Omega \\ R \leq R_1 \end{array}}{\Omega \models x : R_1} \quad \text{ROLE_A_VAR}$$

$$\frac{\Omega, x : \mathbf{Nom} \models a : R}{\Omega \models (\lambda^\rho x. a) : R} \quad \text{ROLE_A_ABS}$$

$$\frac{\begin{array}{c} \Omega \models a : R \\ \Omega \models b : \mathbf{Nom} \end{array}}{\Omega \models (a \ b^\rho) : R} \quad \text{ROLE_A_APP}$$

$$\frac{\begin{array}{c} \Omega \models a : R \\ \text{Path } a = F @_{R_1}, Rs \\ \Omega \models b : R_1 \end{array}}{\Omega \models a \ b^{R_1} : R} \quad \text{ROLE_A_TAPP}$$

$$\frac{\begin{array}{c} \Omega \models A : R \\ \Omega, x : \mathbf{Nom} \models B : R \end{array}}{\Omega \models (\Pi^\rho x : A \rightarrow B) : R} \quad \text{ROLE_A_PI}$$

$$\frac{\begin{array}{c} \Omega \models a : R_1 \\ \Omega \models b : R_1 \\ \Omega \models A : R_0 \\ \Omega \models B : R \end{array}}{\Omega \models (\forall c : a \sim_{A/R_1} b. B) : R} \quad \text{ROLE_A_CPI}$$

$$\frac{\Omega \models b : R}{\Omega \models (\Lambda c. b) : R} \quad \text{ROLE_A_CABS}$$

$$\frac{\Omega \models a : R}{\Omega \models (a[\bullet]) : R} \quad \text{ROLE_A_CAPP}$$

$$\frac{\begin{array}{c} \text{uniq}(\Omega) \\ F : A @ Rs \in \Sigma_0 \end{array}}{\Omega \models F : R} \quad \text{ROLE_A_CONST}$$

$$\frac{\begin{array}{c} \text{uniq}(\Omega) \\ F : p \sim a : A / R @ Rs \in \Sigma_0 \end{array}}{\Omega \models F : R_1} \quad \text{ROLE_A_FAM}$$

$$\frac{\begin{array}{c} \Omega \models a : R \\ \Omega \models b_1 : R_1 \\ \Omega \models b_2 : R_1 \end{array}}{\Omega \models \text{case}_R a \text{ of } F \rightarrow b_1 \parallel - \rightarrow b_2 : R_1} \quad \text{ROLE_A_PATTERN}$$

$\boxed{(\rho = +) \vee (x \notin \text{fv } A)}$ irrelevant argument check

$$\overline{(\rho = +) \vee (x \notin \text{fv } A)} \quad \text{RHO_REL}$$

$$\frac{x \notin \text{fv} A}{(- = +) \vee (x \notin \text{fv} A)} \quad \text{RHO_IRRREL}$$

$\boxed{\Omega \models a \Rightarrow_R b}$ parallel reduction (implicit language)

$$\frac{\Omega \models a : R}{\Omega \models a \Rightarrow_R a} \quad \text{PAR_REFL}$$

$$\frac{\begin{array}{l} \Omega \models a \Rightarrow_R (\lambda^\rho x. a') \\ \Omega \models b \Rightarrow_{\text{Nom}} b' \end{array}}{\Omega \models a \ b^\rho \Rightarrow_R a' \{b'/x\}} \quad \text{PAR_BETA}$$

$$\frac{\begin{array}{l} \Omega \models a \Rightarrow_R a' \\ \Omega \models b \Rightarrow_{\text{Nom}} b' \end{array}}{\Omega \models a \ b^\rho \Rightarrow_R a' \ b'^\rho} \quad \text{PAR_APP}$$

$$\frac{\Omega \models a \Rightarrow_R (\Lambda c. a')}{\Omega \models a[\bullet] \Rightarrow_R a' \{\bullet/c\}} \quad \text{PAR_CBETA}$$

$$\frac{\Omega \models a \Rightarrow_R a'}{\Omega \models a[\bullet] \Rightarrow_R a'[\bullet]} \quad \text{PAR_CAPP}$$

$$\frac{\Omega, x : \text{Nom} \models a \Rightarrow_R a'}{\Omega \models \lambda^\rho x. a \Rightarrow_R \lambda^\rho x. a'} \quad \text{PAR_ABS}$$

$$\frac{\begin{array}{l} \Omega \models A \Rightarrow_R A' \\ \Omega, x : \text{Nom} \models B \Rightarrow_R B' \end{array}}{\Omega \models \Pi^\rho x : A \rightarrow B \Rightarrow_R \Pi^\rho x : A' \rightarrow B'} \quad \text{PAR_PI}$$

$$\frac{\Omega \models a \Rightarrow_R a'}{\Omega \models \Lambda c. a \Rightarrow_R \Lambda c. a'} \quad \text{PAR_CABS}$$

$$\frac{\begin{array}{l} \Omega \models A \Rightarrow_{R_0} A' \\ \Omega \models a \Rightarrow_{R_1} a' \\ \Omega \models b \Rightarrow_{R_1} b' \\ \Omega \models B \Rightarrow_R B' \end{array}}{\Omega \models \forall c : a \sim_{A/R_1} b. B \Rightarrow_R \forall c : a' \sim_{A'/R_1} b'. B'} \quad \text{PAR_CPI}$$

$$F : p \sim b : A/R_1 @ R_s \in \Sigma_0$$

$$\Omega \models a : R$$

$$\text{match } a \text{ with } p \rightarrow b = b'$$

$$R_1 \leq R$$

$$\text{uniq}(\Omega)$$

$$\frac{}{\Omega \models a \Rightarrow_R b'} \quad \text{PAR_AXIOM}$$

$$\Omega \models a \Rightarrow_R a'$$

$$\Omega \models b_1 \Rightarrow_{R_0} b'_1$$

$$\Omega \models b_2 \Rightarrow_{R_0} b'_2$$

$$\frac{}{\Omega \models (\text{case}_R a \text{ of } F \rightarrow b_1 \parallel - \rightarrow b_2) \Rightarrow_{R_0} (\text{case}_R a' \text{ of } F \rightarrow b'_1 \parallel - \rightarrow b'_2)} \quad \text{PAR_PATTERN}$$

$$\Omega \models a \Rightarrow_R a'$$

$$\Omega \models b_1 \Rightarrow_{R_0} b'_1$$

$$\Omega \models b_2 \Rightarrow_{R_0} b'_2$$

$$\text{CasePath}_R a' = F$$

$$\text{apply args } a' \text{ to } b'_1 \mapsto b$$

$$\frac{}{\Omega \models (\text{case}_R a \text{ of } F \rightarrow b_1 \parallel - \rightarrow b_2) \Rightarrow_{R_0} b[\bullet]} \quad \text{PAR_PATTERNTRUE}$$

$$\begin{array}{c}
\Omega \models a \Rightarrow_R a' \\
\Omega \models b_1 \Rightarrow_{R_0} b'_1 \\
\Omega \models b_2 \Rightarrow_{R_0} b'_2 \\
\text{Value}_R a' \\
\neg(\text{CasePath}_R a' = F) \\
\hline
\Omega \models (\text{case}_R a \text{ of } F \rightarrow b_1 \parallel - \rightarrow b_2) \Rightarrow_{R_0} b'_2
\end{array}
\quad \text{PAR_PATTERNFALSE}$$

$$\boxed{\Omega \models a \Rightarrow_R^* b} \quad \text{multistep parallel reduction}$$

$$\begin{array}{c}
\overline{\Omega \models a \Rightarrow_R^* a} \quad \text{MP_REFL} \\
\\
\frac{\Omega \models a \Rightarrow_R b \quad \Omega \models b \Rightarrow_R^* a'}{\Omega \models a \Rightarrow_R^* a'} \quad \text{MP_STEP}
\end{array}$$

$$\boxed{\Omega \models a \Leftrightarrow_R b} \quad \text{parallel reduction to a common term}$$

$$\frac{\Omega \models a_1 \Rightarrow_R^* b \quad \Omega \models a_2 \Rightarrow_R^* b}{\Omega \models a_1 \Leftrightarrow_R a_2} \quad \text{JOIN}$$

$$\boxed{\models a > b/R} \quad \text{primitive reductions on erased terms}$$

$$\begin{array}{c}
\frac{\text{Value}_{R_1} (\lambda^\rho x.v)}{\models (\lambda^\rho x.v) \ b^\rho > v\{b/x\}/R_1} \quad \text{BETA_APPAbs} \\
\\
\frac{}{\models (\Lambda c.a')[\bullet] > a'\{\bullet/c\}/R} \quad \text{BETA_CAPPCAbs} \\
\\
\frac{F : p \sim b : A/R_1 @ Rs \in \Sigma_0 \quad \text{match } a \text{ with } p \rightarrow b = b' \quad R_1 \leq R}{\models a > b'/R} \quad \text{BETA_AXIOM}
\end{array}$$

$$\begin{array}{c}
\frac{\text{CasePath}_R a = F \quad \text{apply args } a \text{ to } b_1 \mapsto b'_1}{\models \text{case}_R a \text{ of } F \rightarrow b_1 \parallel - \rightarrow b_2 > b'_1[\bullet]/R_0} \quad \text{BETA_PATTERNTRUE} \\
\\
\frac{\text{Value}_R a \quad \neg(\text{CasePath}_R a = F)}{\models \text{case}_R a \text{ of } F \rightarrow b_1 \parallel - \rightarrow b_2 > b_2/R_0} \quad \text{BETA_PATTERNFALSE}
\end{array}$$

$$\boxed{\models a \rightsquigarrow b/R} \quad \text{single-step head reduction for implicit language}$$

$$\begin{array}{c}
\frac{\models a \rightsquigarrow a'/R_1}{\models \lambda^- x.a \rightsquigarrow \lambda^- x.a'/R_1} \quad \text{E_ABSTERM} \\
\\
\frac{\models a \rightsquigarrow a'/R_1}{\models a \ b^\rho \rightsquigarrow a' \ b^\rho/R_1} \quad \text{E_APPLEFT} \\
\\
\frac{\models a \rightsquigarrow a'/R}{\models a[\bullet] \rightsquigarrow a'[\bullet]/R} \quad \text{E_CAPPLEFT} \\
\\
\frac{\models a \rightsquigarrow a'/R}{\models \text{case}_R a \text{ of } F \rightarrow b_1 \parallel - \rightarrow b_2 \rightsquigarrow \text{case}_R a' \text{ of } F \rightarrow b_1 \parallel - \rightarrow b_2/R_0} \quad \text{E_PATTERN} \\
\\
\frac{\models a > b/R}{\models a \rightsquigarrow b/R} \quad \text{E_PRIM}
\end{array}$$

$\boxed{\vdash a \rightsquigarrow^* b/R}$ multistep reduction

$$\frac{}{\vdash a \rightsquigarrow^* a/R} \text{ EQUAL}$$

$$\frac{\vdash a \rightsquigarrow b/R \quad \vdash b \rightsquigarrow^* a'/R}{\vdash a \rightsquigarrow^* a'/R} \text{ STEP}$$

$\boxed{\Gamma \vdash \text{case}_R a : A \text{ of } b : B \Rightarrow C \mid C'}$ Branch Typing (aligning the types of case)

$$\frac{\text{uniq } \Gamma \quad \text{lc_tm } C}{\Gamma \vdash \text{case}_R a : A \text{ of } b : A \Rightarrow \forall c : (a \sim_{A/R} b). C \mid C} \text{ BRANCH_TYPING_BASE}$$

$$\frac{\Gamma, x : A \vdash \text{case}_R a : A_1 \text{ of } b \ x^+ : B \Rightarrow C \mid C'}{\Gamma \vdash \text{case}_R a : A_1 \text{ of } b : \Pi^+ x : A \rightarrow B \Rightarrow \Pi^+ x : A \rightarrow C \mid C'} \text{ BRANCH_TYPING_PIREL}$$

$$\frac{\Gamma, x : A \vdash \text{case}_R a : A_1 \text{ of } b \ \square^- : B \Rightarrow C \mid C'}{\Gamma \vdash \text{case}_R a : A_1 \text{ of } b : \Pi^- x : A \rightarrow B \Rightarrow \Pi^- x : A \rightarrow C \mid C'} \text{ BRANCH_TYPING_PIIRREL}$$

$$\frac{\Gamma, c : \phi \vdash \text{case}_R a : A \text{ of } b[\bullet] : B \Rightarrow C \mid C'}{\Gamma \vdash \text{case}_R a : A \text{ of } b : \forall c : \phi. B \Rightarrow \forall c : \phi. C \mid C'} \text{ BRANCH_TYPING_CPI}$$

$\boxed{\Gamma \vdash \phi \text{ ok}}$ Prop wellformedness

$$\frac{\Gamma \vdash a : A \quad \Gamma \vdash b : A \quad \Gamma \vdash A : \star}{\Gamma \vdash a \sim_{A/R} b \text{ ok}} \text{ E_WFF}$$

$\boxed{\Gamma \vdash a : A}$ typing

$$\frac{\vdash \Gamma}{\Gamma \vdash \star : \star} \text{ E_STAR}$$

$$\frac{\vdash \Gamma \quad x : A \in \Gamma}{\Gamma \vdash x : A} \text{ E_VAR}$$

$$\frac{\Gamma, x : A \vdash B : \star \quad \Gamma \vdash A : \star}{\Gamma \vdash \Pi^\rho x : A \rightarrow B : \star} \text{ E_PI}$$

$$\frac{\Gamma, x : A \vdash a : B \quad \Gamma \vdash A : \star \quad (\rho = +) \vee (x \notin \text{fv } a)}{\Gamma \vdash \lambda^\rho x. a : (\Pi^\rho x : A \rightarrow B)} \text{ E_ABS}$$

$$\frac{\Gamma \vdash b : \Pi^+ x : A \rightarrow B \quad \Gamma \vdash a : A}{\Gamma \vdash b \ a^+ : B\{a/x\}} \text{ E_APP}$$

$$\frac{\Gamma \vdash b : \Pi^+ x : A \rightarrow B \quad \Gamma \vdash a : A}{\Gamma \vdash b \ a^R : B\{a/x\}} \text{ E_TAPP}$$

$$\begin{array}{c}
\frac{\Gamma \models b : \Pi^- x : A \rightarrow B \quad \Gamma \models a : A}{\Gamma \models b \square^- : B\{a/x\}} \quad \text{E_IAPP} \\
\\
\frac{\Gamma \models a : A \quad \Gamma; \tilde{\Gamma} \models A \equiv B : \star / \mathbf{Rep} \quad \Gamma \models B : \star}{\Gamma \models a : B} \quad \text{E_CONV} \\
\\
\frac{\Gamma, c : \phi \models B : \star \quad \Gamma \models \phi \text{ ok}}{\Gamma \models \forall c : \phi. B : \star} \quad \text{E_CPI} \\
\\
\frac{\Gamma, c : \phi \models a : B \quad \Gamma \models \phi \text{ ok}}{\Gamma \models \Lambda c. a : \forall c : \phi. B} \quad \text{E_CABS} \\
\\
\frac{\Gamma \models a_1 : \forall c : (a \sim_{A/R} b). B_1 \quad \Gamma; \tilde{\Gamma} \models a \equiv b : A/R}{\Gamma \models a_1[\bullet] : B_1\{\bullet/c\}} \quad \text{E_CAPP} \\
\\
\frac{\models \Gamma \quad F : A @ Rs \in \Sigma_0 \quad \emptyset \models A : \star}{\Gamma \models F : A} \quad \text{E_CONST} \\
\\
\frac{\models \Gamma \quad F : p \sim a : A/R_1 @ Rs \in \Sigma_0}{\Gamma \models F : A} \quad \text{E_FAM}
\end{array}$$

$$\frac{\Gamma \models a : A \quad \Gamma \models F : A_1 \quad \Gamma \models b_1 : B \quad \Gamma \models b_2 : C \quad \Gamma \models \text{case}_R a : A \text{ of } F : A_1 \Rightarrow B \mid C}{\Gamma \models \text{case}_R a \text{ of } F \rightarrow b_1 \parallel - \rightarrow b_2 : C} \quad \text{E_CASE}$$

$\boxed{\Gamma; \Delta \models \phi_1 \equiv \phi_2}$ prop equality

$$\frac{\Gamma; \Delta \models A_1 \equiv A_2 : A/R \quad \Gamma; \Delta \models B_1 \equiv B_2 : A/R}{\Gamma; \Delta \models A_1 \sim_{A/R} B_1 \equiv A_2 \sim_{A/R} B_2} \quad \text{E_PROP CONG}$$

$$\frac{\Gamma; \Delta \models A \equiv B : \star / R_0 \quad \Gamma \models A_1 \sim_{A/R} A_2 \text{ ok} \quad \Gamma \models A_1 \sim_{B/R} A_2 \text{ ok}}{\Gamma; \Delta \models A_1 \sim_{A/R} A_2 \equiv A_1 \sim_{B/R} A_2} \quad \text{E_ISO CONV}$$

$$\frac{\Gamma; \Delta \models \forall c : (a_1 \sim_{A/R_1} a_2). B_1 \equiv \forall c : (b_1 \sim_{B/R_2} b_2). B_2 : \star / R'}{\Gamma; \Delta \models a_1 \sim_{A/R_1} a_2 \equiv b_1 \sim_{B/R_2} b_2} \quad \text{E_CPI FST}$$

$\boxed{\Gamma; \Delta \models a \equiv b : A/R}$ definitional equality

$$\frac{\models \Gamma \quad c : (a \sim_{A/R} b) \in \Gamma \quad c \in \Delta}{\Gamma; \Delta \models a \equiv b : A/R} \quad \text{E_ASSN}$$

$$\begin{array}{c}
\frac{\Gamma \models a : A}{\Gamma; \Delta \models a \equiv a : A/R} \quad \text{E_REFL} \\
\frac{\Gamma; \Delta \models b \equiv a : A/R}{\Gamma; \Delta \models a \equiv b : A/R} \quad \text{E_SYM} \\
\frac{\Gamma; \Delta \models a \equiv a_1 : A/R \quad \Gamma; \Delta \models a_1 \equiv b : A/R}{\Gamma; \Delta \models a \equiv b : A/R} \quad \text{E_TRANS} \\
\frac{\Gamma; \Delta \models a \equiv b : A/R_1 \quad R_1 \leq R_2}{\Gamma; \Delta \models a \equiv b : A/R_2} \quad \text{E_SUB} \\
\frac{\Gamma \models a_1 : B \quad \Gamma \models a_2 : B \quad \models a_1 > a_2/R}{\Gamma; \Delta \models a_1 \equiv a_2 : B/R} \quad \text{E_BETA} \\
\frac{\Gamma; \Delta \models A_1 \equiv A_2 : \star/R' \quad \Gamma, x : A_1; \Delta \models B_1 \equiv B_2 : \star/R' \quad \Gamma \models A_1 : \star \quad \Gamma \models \Pi^\rho x : A_1 \rightarrow B_1 : \star \quad \Gamma \models \Pi^\rho x : A_2 \rightarrow B_2 : \star}{\Gamma; \Delta \models (\Pi^\rho x : A_1 \rightarrow B_1) \equiv (\Pi^\rho x : A_2 \rightarrow B_2) : \star/R'} \quad \text{E_PICONG} \\
\frac{\Gamma, x : A_1; \Delta \models b_1 \equiv b_2 : B/R' \quad \Gamma \models A_1 : \star \quad (\rho = +) \vee (x \notin \text{fv } b_1) \quad (\rho = +) \vee (x \notin \text{fv } b_2)}{\Gamma; \Delta \models (\lambda^\rho x. b_1) \equiv (\lambda^\rho x. b_2) : (\Pi^\rho x : A_1 \rightarrow B)/R'} \quad \text{E_ABSCONG} \\
\frac{\Gamma; \Delta \models a_1 \equiv b_1 : (\Pi^+ x : A \rightarrow B)/R' \quad \Gamma; \Delta \models a_2 \equiv b_2 : A/\mathbf{Nom}}{\Gamma; \Delta \models a_1 \ a_2^+ \equiv b_1 \ b_2^+ : (B\{a_2/x\})/R'} \quad \text{E_APPCONG} \\
\frac{\Gamma; \Delta \models a_1 \equiv b_1 : (\Pi^+ x : A \rightarrow B)/R' \quad \Gamma; \Delta \models a_2 \equiv b_2 : A/\mathbf{param } R \ R'}{\Gamma; \Delta \models a_1 \ a_2^R \equiv b_1 \ b_2^R : (B\{a_2/x\})/R'} \quad \text{E_TAPPCONG} \\
\frac{\Gamma; \Delta \models a_1 \equiv b_1 : (\Pi^- x : A \rightarrow B)/R' \quad \Gamma \models a : A}{\Gamma; \Delta \models a_1 \ \Box^- \equiv b_1 \ \Box^- : (B\{a/x\})/R'} \quad \text{E_IAPPCONG} \\
\frac{\Gamma; \Delta \models \Pi^\rho x : A_1 \rightarrow B_1 \equiv \Pi^\rho x : A_2 \rightarrow B_2 : \star/R'}{\Gamma; \Delta \models A_1 \equiv A_2 : \star/R'} \quad \text{E_PIFST} \\
\frac{\Gamma; \Delta \models \Pi^\rho x : A_1 \rightarrow B_1 \equiv \Pi^\rho x : A_2 \rightarrow B_2 : \star/R' \quad \Gamma; \Delta \models a_1 \equiv a_2 : A_1/R'}{\Gamma; \Delta \models B_1\{a_1/x\} \equiv B_2\{a_2/x\} : \star/R'} \quad \text{E_PISND} \\
\frac{\Gamma; \Delta \models a_1 \sim_{A_1/R} b_1 \equiv a_2 \sim_{A_2/R} b_2 \quad \Gamma, c : a_1 \sim_{A_1/R} b_1; \Delta \models A \equiv B : \star/R' \quad \Gamma \models a_1 \sim_{A_1/R} b_1 \ \text{ok} \quad \Gamma \models \forall c : a_1 \sim_{A_1/R} b_1. A : \star \quad \Gamma \models \forall c : a_2 \sim_{A_2/R} b_2. B : \star}{\Gamma; \Delta \models \forall c : a_1 \sim_{A_1/R} b_1. A \equiv \forall c : a_2 \sim_{A_2/R} b_2. B : \star/R'} \quad \text{E_CPICONG}
\end{array}$$

$$\begin{array}{c}
\frac{\Gamma, c : \phi_1; \Delta \models a \equiv b : B/R \quad \Gamma \models \phi_1 \text{ ok}}{\Gamma; \Delta \models (\Lambda c. a) \equiv (\Lambda c. b) : \forall c : \phi_1. B/R} \text{E_CABS_CONG} \\
\\
\frac{\Gamma; \Delta \models a_1 \equiv b_1 : (\forall c : (a \sim_{A/R} b). B)/R' \quad \Gamma; \tilde{\Gamma} \models a \equiv b : A/\mathbf{param} R R'}{\Gamma; \Delta \models a_1[\bullet] \equiv b_1[\bullet] : (B\{\bullet/c\})/R'} \text{E_CAPP_CONG} \\
\\
\frac{\Gamma; \Delta \models \forall c : (a_1 \sim_{A/R} a_2). B_1 \equiv \forall c : (a'_1 \sim_{A'/R'} a'_2). B_2 : \star/R_0 \quad \Gamma; \tilde{\Gamma} \models a_1 \equiv a_2 : A/\mathbf{param} R R_0 \quad \Gamma; \tilde{\Gamma} \models a'_1 \equiv a'_2 : A'/\mathbf{param} R' R_0}{\Gamma; \Delta \models B_1\{\bullet/c\} \equiv B_2\{\bullet/c\} : \star/R_0} \text{E_CPI_SND} \\
\\
\frac{\Gamma; \Delta \models a \equiv b : A/R \quad \Gamma; \Delta \models a \sim_{A/R} b \equiv a' \sim_{A'/R'} b'}{\Gamma; \Delta \models a' \equiv b' : A'/R'} \text{E_CAST} \\
\\
\frac{\Gamma; \Delta \models a \equiv b : A/R \quad \Gamma; \tilde{\Gamma} \models A \equiv B : \star/\mathbf{Rep} \quad \Gamma \models B : \star}{\Gamma; \Delta \models a \equiv b : B/R} \text{E_EQ_CONV} \\
\\
\frac{\Gamma; \Delta \models a \sim_{A/R_1} b \equiv a' \sim_{A'/R_1} b'}{\Gamma; \Delta \models A \equiv A' : \star/\mathbf{Rep}} \text{E_ISO_SND} \\
\\
\frac{\Gamma; \Delta \models a \equiv a' : A/R \quad \Gamma; \Delta \models b_1 \equiv b'_1 : B/R_0 \quad \Gamma; \Delta \models b_2 \equiv b'_2 : B/R_0}{\Gamma; \Delta \models \text{case}_R a \text{ of } F \rightarrow b_1 \parallel - \rightarrow b_2 \equiv \text{case}_R a' \text{ of } F \rightarrow b'_1 \parallel - \rightarrow b'_2 : B/R_0} \text{E_PAT_CONG} \\
\\
\frac{\text{ValuePath } a = F \quad \text{ValuePath } a' = F \quad \Gamma \models a : \Pi^+ x : A \rightarrow B \quad \Gamma \models b : A \quad \Gamma \models a' : \Pi^+ x : A \rightarrow B \quad \Gamma \models b' : A \quad \Gamma; \Delta \models a \ b^{R_1} \equiv a' \ b'^{R_1} : B\{b/x\}/R' \quad \Gamma; \tilde{\Gamma} \models B\{b/x\} \equiv B\{b'/x\} : \star/R'}{\Gamma; \Delta \models a \equiv a' : \Pi^+ x : A \rightarrow B/R'} \text{E_LEFT_REL} \\
\\
\frac{\text{ValuePath } a = F \quad \text{ValuePath } a' = F \quad \Gamma \models a : \Pi^- x : A \rightarrow B \quad \Gamma \models b : A \quad \Gamma \models a' : \Pi^- x : A \rightarrow B \quad \Gamma \models b' : A \quad \Gamma; \Delta \models a \ \square^- \equiv a' \ \square^- : B\{b/x\}/R' \quad \Gamma; \tilde{\Gamma} \models B\{b/x\} \equiv B\{b'/x\} : \star/R_0}{\Gamma; \Delta \models a \equiv a' : \Pi^- x : A \rightarrow B/R'} \text{E_LEFT_IRREL}
\end{array}$$

$$\begin{array}{c}
\text{ValuePath } a = F \\
\text{ValuePath } a' = F \\
\Gamma \models a : \Pi^+ x : A \rightarrow B \\
\Gamma \models b : A \\
\Gamma \models a' : \Pi^+ x : A \rightarrow B \\
\Gamma \models b' : A \\
\Gamma; \Delta \models a \ b^+ \equiv a' \ b'^+ : B\{b/x\}/R' \\
\Gamma; \tilde{\Gamma} \models B\{b/x\} \equiv B\{b'/x\} : \star/R_0 \\
\hline
\Gamma; \Delta \models b \equiv b' : A/\mathbf{param} \ R_1 \ R' \quad \text{E_RIGHT} \\
\\
\text{ValuePath } a = F \\
\text{ValuePath } a' = F \\
\Gamma \models a : \forall c : (a_1 \sim_{A/R_1} a_2). B \\
\Gamma \models a' : \forall c : (a_1 \sim_{A/R_1} a_2). B \\
\Gamma; \tilde{\Gamma} \models a_1 \equiv a_2 : A/R' \\
\Gamma; \Delta \models a[\bullet] \equiv a'[\bullet] : B\{\bullet/c\}/R' \\
\hline
\Gamma; \Delta \models a \equiv a' : \forall c : (a_1 \sim_{A/R_1} a_2). B/R' \quad \text{E_LEFT}
\end{array}$$

$\boxed{\models \Gamma}$ context wellformedness

$$\begin{array}{c}
\overline{\models \emptyset} \quad \text{E_EMPTY} \\
\\
\begin{array}{c}
\models \Gamma \\
\Gamma \models A : \star \\
x \notin \text{dom } \Gamma \\
\hline
\models \Gamma, x : A \quad \text{E_CONSTM}
\end{array} \\
\\
\begin{array}{c}
\models \Gamma \\
\Gamma \models \phi \text{ ok} \\
c \notin \text{dom } \Gamma \\
\hline
\models \Gamma, c : \phi \quad \text{E_CONSCo}
\end{array}
\end{array}$$

$\boxed{\models \Sigma}$ signature wellformedness

$$\begin{array}{c}
\overline{\models \emptyset} \quad \text{SIG_EMPTY} \\
\\
\begin{array}{c}
\models \Sigma \\
\emptyset \models A : \star \\
F \notin \text{dom } \Sigma \\
\hline
\models \Sigma \cup \{F : A@Rs\} \quad \text{SIG_CONSTCONST}
\end{array} \\
\\
\begin{array}{c}
\models \Sigma \\
F \notin \text{dom } \Sigma \\
\emptyset \models A : \star \\
\Omega; \Gamma \models p :_F B \Rightarrow A \\
\Gamma \models a : B \\
\Omega \models a : \mathbf{Rep} \\
\hline
\models \Sigma \cup \{F : p \sim a : A/R@\mathbf{range} \ \Omega\} \quad \text{SIG_CONSAx}
\end{array}
\end{array}$$

$\boxed{\Gamma \vdash \phi \text{ ok}}$ prop wellformedness

$\boxed{\Gamma \vdash a : A/R}$ typing

$\boxed{\Gamma; \Delta \vdash \gamma : \phi_1 \sim \phi_2}$ coercion between props

$\boxed{\Gamma; \Delta \vdash \gamma : A \sim_R B}$ coercion between types

$\boxed{\vdash \Gamma}$ context wellformedness

$\boxed{\Gamma \vdash a \rightsquigarrow b/R}$ single-step, weak head reduction to values for annotated language

Definition rules: 145 good 0 bad

Definition rule clauses: 407 good 0 bad