



## **AP<sup>®</sup> Physics C: Mechanics 2010 Scoring Guidelines**

### **The College Board**

The College Board is a not-for-profit membership association whose mission is to connect students to college success and opportunity. Founded in 1900, the College Board is composed of more than 5,700 schools, colleges, universities and other educational organizations. Each year, the College Board serves seven million students and their parents, 23,000 high schools, and 3,800 colleges through major programs and services in college readiness, college admission, guidance, assessment, financial aid and enrollment. Among its widely recognized programs are the SAT<sup>®</sup>, the PSAT/NMSQT<sup>®</sup>, the Advanced Placement Program<sup>®</sup> (AP<sup>®</sup>), SpringBoard<sup>®</sup> and ACCUPLACER<sup>®</sup>. The College Board is committed to the principles of excellence and equity, and that commitment is embodied in all of its programs, services, activities and concerns.

© 2010 The College Board. College Board, ACCUPLACER, Advanced Placement Program, AP, AP Central, SAT, SpringBoard and the acorn logo are registered trademarks of the College Board. Admitted Class Evaluation Service is a trademark owned by the College Board. PSAT/NMSQT is a registered trademark of the College Board and National Merit Scholarship Corporation. All other products and services may be trademarks of their respective owners. Permission to use copyrighted College Board materials may be requested online at: [www.collegeboard.com/inquiry/cbpermit.html](http://www.collegeboard.com/inquiry/cbpermit.html).

**Visit the College Board on the Web: [www.collegeboard.com](http://www.collegeboard.com).**

**AP Central is the official online home for the AP Program: [apcentral.collegeboard.com](http://apcentral.collegeboard.com).**

# AP<sup>®</sup> PHYSICS

## 2010 SCORING GUIDELINES

### General Notes

1. The solutions contain the most common method of solving the free-response questions and the allocation of points for the solution. Some also contain a common alternate solution. Other methods of solution also receive appropriate credit for correct work.
2. Generally, double penalty for errors is avoided. For example, if an incorrect answer to part (a) is correctly substituted into an otherwise correct solution to part (b), full credit will usually be awarded. One exception to this may be cases when the numerical answer to a later part should be easily recognized as wrong — for example, a speed faster than the speed of light in vacuum.
3. Implicit statements of concepts normally receive credit. For example, if use of the equation expressing a particular concept is worth 1 point and a student's solution contains the application of that equation to the problem but the student does not write the basic equation, the point is still awarded. However, when students are asked to derive an expression it is normally expected that they will begin by writing one or more fundamental equations, such as those given on the AP Physics Exam equation sheets. For a description of the use of such terms as “derive” and “calculate” on the exams and what is expected for each, see “The Free-Response Sections — Student Presentation” in the *AP Physics Course Description*.
4. The scoring guidelines typically show numerical results using the value  $g = 9.8 \text{ m/s}^2$ , but use of  $10 \text{ m/s}^2$  is of course also acceptable. Solutions usually show numerical answers using both values when they are significantly different.
5. Strict rules regarding significant digits are usually not applied to numerical answers. However, in some cases answers containing too many digits may be penalized. In general, two to four significant digits are acceptable. Numerical answers that differ from the published answer due to differences in rounding throughout the question typically receive full credit. Exceptions to these guidelines usually occur when rounding makes a difference in obtaining a reasonable answer. For example, suppose a solution requires subtracting two numbers that should have five significant figures and that differ starting with the fourth digit (e.g., 20.295 and 20.278). Rounding to three digits will lose the accuracy required to determine the difference in the numbers, and some credit may be lost.

# AP<sup>®</sup> PHYSICS C: MECHANICS 2010 SCORING GUIDELINES

## Question 1

15 points total

Distribution  
of points

(a) 2 points

Starting with Newton's second law:

$$F_{\text{net}} = mg - Cv^2 = ma$$

For correctly indicating that at terminal velocity ( $v = v_T$ ), the net force and acceleration are zero

1 point

$$mg - Cv_T^2 = 0$$

For a correct relationship between  $v_T$  and  $m$


1 point

$$v_T^2 = \frac{g}{C}m$$

(b)

(i) 4 points

Mass of the stack of filters, $m$ (kg)	$1.12 \times 10^{-3}$	$2.04 \times 10^{-3}$	$2.96 \times 10^{-3}$	$4.18 \times 10^{-3}$	$5.10 \times 10^{-3}$
Terminal speed, $v_T$ (m/s)	0.51	0.62	0.82	0.92	1.06
$v_T^2$ ( $\text{m}^2/\text{s}^2$ )	0.26	0.38	0.67	0.85	1.12



**AP<sup>®</sup> PHYSICS C: MECHANICS  
2010 SCORING GUIDELINES**

**Question 1 (continued)**

**Distribution  
of points**

(b) (i) (continued)

For recording in the table a row of calculated data points that involve only  $v_T$  or a combination of  $v_T$  and  $g$  1 point

For graphing  $v_T^2$  (or the equivalent) on the vertical axis to obtain a linear graph 1 point

For including an appropriate linear scale on both axes 1 point

For drawing a reasonable best-fit straight line 1 point

Note: Correct graphs of  $v_T$  versus  $\sqrt{m}$  are given credit provided the quantities being plotted are clearly indicated.

(ii) 3 points

For a correct calculation of the slope, using points on the student's best-fit line (not points from the data table) 1 point

Using the example graph shown:

$$\text{slope} = \frac{(0.95 - 0.30) \text{ m}^2/\text{s}^2}{[(4.4 - 1.4) \times 10^{-3}] \text{ kg}} = 217 \text{ m}^2/\text{kg} \cdot \text{s}^2$$

For a correct expression relating the slope to  $C$  1 point

$$\text{slope} = 217 \text{ m}^2/\text{kg} \cdot \text{s}^2 = \frac{g}{C}$$


$$C = \frac{g}{\text{Slope}} = \frac{9.8 \text{ m/s}^2}{217 \text{ m}^2/\text{kg} \cdot \text{s}^2}$$

For correct units on  $C$  1 point

$$C = 0.045 \text{ kg/m} \quad (0.046 \text{ kg/m using } g = 10 \text{ m/s}^2)$$

(c)

(i) 3 points



For a graph that starts at the origin with an initial positive slope 1 point

For a graph that is concave down throughout 1 point

**AP<sup>®</sup> PHYSICS C: MECHANICS  
2010 SCORING GUIDELINES**

**Question 1 (continued)**

**Distribution  
of points**

For labeling  $v_T$  and  $T$  at a point where the slope of the graph approaches zero

1 point

(c) (continued)

(ii) 1 point

For a verbal statement that clearly indicates the distance  $Y$  is the area under the curve between times  $t = 0$  and  $t = T$

1 point

Or an equivalent statement referring to the area under the curve when the  $v$  versus  $t$  graph ends at  $T$

Or an equivalent mathematical expression with limits:  $Y = \int_0^T v(t) dt$

(d) 2 points

For a correct indication that the mechanical energy dissipated is the change in mechanical energy during the time the stack falls a distance  $y$

1 point

$$\Delta E = (U_{final} + K_{final}) - (U_{initial} + K_{initial}) \quad \left( \text{or } \Delta E = \int_0^y C v^2 dy \right)$$

$$\Delta E = \Delta U + \Delta K$$

For correct substitutions of  $y$ ,  $m$ , and  $v_T$

1 point

$$\Delta U = -mgy$$

$$\Delta K = \frac{1}{2}mv_T^2$$

$$\Delta E = \frac{1}{2}mv_T^2 - mgy \quad (\text{or any equation with an additional negative sign that has the correct relative signs for potential and kinetic energies})$$


**AP<sup>®</sup> PHYSICS C: MECHANICS  
2010 SCORING GUIDELINES**

**Question 2**

**15 points total**

**Distribution  
of points**

(a) 3 points



For each correct force for which the vector is drawn with the correct direction, label and point of application, 1 point was awarded.  
One earned point was deducted if any components or extraneous forces are present.

3 points

(b) 5 points

Starting with Newton's second law (linear form):

$$F_{net} = Ma$$

For expressing  $F_{net}$  in terms of gravitational and frictional forces

1 point

For including the correct component of the weight

1 point

$$Mg \sin \theta - F_f = Ma$$

$$\tau = I\alpha$$

For correct substitution of torque into Newton's second law (angular form)

1 point

$$RF_f = I\alpha$$

$$RF_f = (2/5)MR^2\alpha$$

For the correct relationship between angular and linear acceleration (either explicitly stated or used in the calculation)

1 point

$$\alpha = a/R$$

$$RF_f = (2/5)MR^2(a/R)$$

Solving for  $Ma$

$$Ma = (5/2)F_f$$

Substituting into the linear equation above

$$Mg \sin \theta - F_f = (5/2)F_f$$

$$F_f = (2/7)Mg \sin \theta = (2/7)(6.0 \text{ kg})(9.8 \text{ m/s}^2)(\sin 30^\circ)$$

For the correct value of  $F_f$

1 point

$$F_f = 8.4 \text{ N}$$

Notes: Credit is awarded for solutions that use the value of  $v$  calculated in (c) to calculate acceleration and, from there, the value of the frictional force.  
If  $Mg \cos \theta$  is used, the point was awarded for a value of 14.5 N.

**AP<sup>®</sup> PHYSICS C: MECHANICS  
2010 SCORING GUIDELINES**

**Question 2 (continued)**

**Distribution  
of points**

(c) 3 points

For an expression of conservation of energy

1 point

For including gravitational potential energy, translational kinetic energy and rotational kinetic energy in a correct energy equation or statement

1 point

$$Mg\Delta h = \frac{1}{2}Mv^2 + \frac{1}{2}I\omega^2$$

$$Mgd \sin \theta = \frac{1}{2}Mv^2 + \frac{1}{2}\left(\frac{2}{5}MR^2\right)\omega^2$$

$$\omega = v/R$$

$$Mgd \sin \theta = \frac{1}{2}Mv^2 + \frac{1}{5}Mv^2 = \frac{7}{10}Mv^2$$

$$v = \sqrt{(10/7)gd \sin \theta} = \sqrt{(10/7)(9.8 \text{ m/s}^2)(4.0 \text{ m})(\sin 30^\circ)}$$

For a correct numerical answer

1 point

$$v = 5.3 \text{ m/s}$$

*Alternate solution (kinematics method)*

*Alternate points*

*For determination of the linear acceleration in terms of mass and frictional force*

*1 point*

$a = 5F_f/2M$  from work shown in part (b)

$$a = 5(8.4 \text{ N})/2(6.0 \text{ kg}) = 3.5 \text{ m/s}^2$$

*For a correct substitution into an appropriate kinematics equation using  $v_0 = 0$*

*1 point*

$$v^2 = v_0^2 + 2ad = 2ad$$

$$v = \sqrt{2ad} = \sqrt{(2)(3.5 \text{ m/s}^2)(4.0 \text{ m})}$$

*For a correct numerical answer*

*1 point*

$$v = 5.3 \text{ m/s}$$

(d) 3 points

For a correct statement of conservation of momentum

1 point

$$M_i v_i = M_f v_f$$

$$v_f = (M_i/M_f)v_i$$

For correctly equating  $v_i$  with the horizontal component of the ball as it leaves the roof

1 point

For setting  $M_f$  equal to the total mass of the ball and the wagon/box

1 point

$$v_f = (M_i/M_f)v \cos \theta = [(6.0 \text{ kg})/(18.0 \text{ kg})](5.3 \text{ m/s}^2) \cos 30^\circ$$

$$v_f = 1.5 \text{ m/s}$$

Units 1 point

For correct units in at least two of the parts (b), (c) and (d)

1 point

**AP<sup>®</sup> PHYSICS C: MECHANICS  
2010 SCORING GUIDELINES**

**Question 3**

**15 points total**

**Distribution  
of points**

(a) 4 points

For a correct relationship between velocity and acceleration

1 point

$$v = \int a(t) dt \quad \text{OR} \quad v = \int_0^t a(t) dt \quad \text{OR} \quad \frac{dv}{dt} = a$$

For a correct substitution of the expression for acceleration into the integral relationship

1 point

$$v = \int \left( a_{\max} \sin \frac{\pi t}{T} \right) dt \quad \text{OR} \quad v = \int_0^t \left( a_{\max} \sin \frac{\pi t}{T} \right) dt \quad (0 < t < T)$$

For a correct evaluation of the integral, with an integration constant or correct limits

1 point

$$v = -\frac{a_{\max} T}{\pi} \cos \frac{\pi t}{T} + C \quad \text{OR} \quad v = -\frac{a_{\max} T}{\pi} \cos \frac{\pi t}{T} \Big|_0^t \quad (0 < t < T)$$

For a correct determination of the integration constant or evaluation between the limits

1 point

$$v(0) = -\frac{a_{\max} T}{\pi} + C = 0 \Rightarrow C = \frac{a_{\max} T}{\pi} \quad \text{OR} \quad v = -\frac{a_{\max} T}{\pi} \left( \cos \frac{\pi t}{T} - 1 \right) \quad (0 < t < T)$$

$$v = \frac{a_{\max} T}{\pi} \left( 1 - \cos \frac{\pi t}{T} \right) \quad (0 < t < T)$$

(b) 2 points

For indicating that the work done by the net force is equal to the change in kinetic energy

1 point

$$W = \frac{1}{2} m (v_f^2 - v_i^2)$$

For a correct substitution of velocity from (a) into the work-energy expression

1 point

$$v_f = v_T = \frac{a_{\max} T}{\pi} (1 - \cos \pi) = \frac{2a_{\max} T}{\pi}$$

$$v_i = v_0 = \frac{a_{\max} T}{\pi} (1 - \cos 0) = 0$$

$$W = \frac{1}{2} m \left( \frac{2a_{\max} T}{\pi} \right)^2$$

$$W = \frac{2ma_{\max}^2 T^2}{\pi^2}$$

*Alternate solution (integral form)*

*Alternate points*

$$W = \int F \cdot dx$$

*For a correct substitution of the expression for force into the integral*

*1 point*

$$W = \int m a_{\max} \sin \frac{\pi t}{T} dx$$

*For a correct expression for dx in terms of time*

*1 point*



**AP<sup>®</sup> PHYSICS C: MECHANICS**  
**2010 SCORING GUIDELINES**

**Question 3 (continued)**

**Distribution  
of points**

(b) (continued)

$$W = \int_0^T m a_{\max} \sin \frac{\pi t}{T} \left( \frac{a_{\max} T}{\pi} \left( 1 - \cos \frac{\pi t}{T} \right) \right) dt$$

$$W = \frac{m a_{\max}^2 T}{\pi} \int_0^T \left( \sin \frac{\pi t}{T} - \left( \sin \frac{\pi t}{T} \cos \frac{\pi t}{T} \right) \right) dt$$

$$W = \frac{m a_{\max}^2 T}{\pi} \int_0^T \left( \sin \frac{\pi t}{T} - \frac{1}{2} \sin \frac{2\pi t}{T} \right) dt$$

$$W = \frac{m a_{\max}^2 T^2}{\pi^2} \left( -\cos \frac{\pi t}{T} - \frac{1}{4} \cos \frac{2\pi t}{T} \right) \Big|_0^T$$

$$W = \frac{2 m a_{\max}^2 T^2}{\pi^2}$$

(c) 1 point

Starting with Newton's second law:

$$F_{\text{net}} = F_{\text{rope}} - mg \sin \theta = ma$$

At terminal velocity, the net force and acceleration are zero:

$$F_{\text{rope}} - mg \sin \theta = 0$$

For a correct expression for the force

$$F_{\text{rope}} = mg \sin \theta$$

1 point

(d) 2 points

$$J = \int F dt$$

For a correct substitution of force into the impulse-time relationship

1 point

$$J = m a_{\max} \int_0^T \sin \frac{\pi t}{T} dt$$

$$J = \frac{m a_{\max} T}{\pi} \left( -\cos \frac{\pi t}{T} \right) \Big|_0^T$$

For evaluation at the limits of integration

1 point

$$J = \frac{m a_{\max} T}{\pi} [-\cos \pi + \cos 0]$$

$$J = \frac{2 m a_{\max} T}{\pi}$$

Alternate solution (impulse-momentum)

Alternate points

$$J = \Delta p = mv_T$$

**AP<sup>®</sup> PHYSICS C: MECHANICS**  
**2010 SCORING GUIDELINES**

**Question 3 (continued)**

**Distribution  
of points**

(d) (continued)

*For a correct substitution of the velocity*

*1 point*

$$J = \frac{ma_{\max}T}{\pi} \left( 1 - \cos \frac{\pi t}{T} \right)$$

*For setting  $t = T$*

*1 point*


$$J = \frac{ma_{\max}T}{\pi} (1 - \cos \pi)$$

$$J = \frac{2ma_{\max}T}{\pi}$$

(e) 6 points

$$F_1 = mg \sin \theta + ma_{\max} \sin \left( \frac{\pi t}{T} \right) \quad (0 < t < T)$$

$$F_2 = mg \sin \theta + ma_{\max} e^{-\pi t/2T}$$



For a graph labeled  $F_1$ :

for starting at  $mg \sin \theta$

1 point

for half a sine wave with a maximum at  $\sim T/2$

1 point

for returning to original starting point at  $t = T$

1 point

for a horizontal line at the original starting point for  $t > T$

1 point

For a graph labeled  $F_2$ :

for starting on the vertical axis at a point above the starting point of  $F_1$  (if there is no  $F_1$  graph, this point was awarded if the  $F_2$  graph starts above  $mg \sin \theta$ )

1 point

for an exponential decay graph

1 point