Beyond the 11% Threshold: Sub-Threshold Eavesdropper Detection via Sentinel-Correlation Fingerprinting in the BB84 Protocol

Sree Charan Desu
IIIT - Andhra Pradesh
sreecharan309@gmail.com

March 22, 2026

Abstract

Recent implementations of Quantum Key Distribution (QKD) rely primarily on a static scalar threshold for the Quantum Bit Error Rate (QBER), traditionally abandoning keys where QBER exceeds 11%. This static approach ignores the temporal dimensions of error distributions. In this paper, we propose an Adversarial Error-Classification Engine (*AECE*) driven by a Sentinel Qubit stream. By analyzing the temporal and spatial correlation of errors across the quantum channel, we generate a highly accurate "Error Fingerprint" to detect sub-threshold Eve presence. Our approach yields complete computational resilience against structured channel spoofing and increases the functional Secure Key Rate (SKR) by over 30% in simulated noisy quantum environments. We demonstrate that static scalar constraints are fundamentally insufficient to maximize throughput without sacrificing unconditional security.

1 Introduction

The BB84 protocol established the mathematical proofs for unconditional security through the foundational principle of quantum state disturbance [1]. While theoretically bulletproof, practical deployments are challenged by inevitable hardware imperfections, polarization drift, and photon decoherence. Typically, the total scalar Quantum Bit Error Rate (QBER) acts as the single abort parameter for cryptographic operations. When the threshold limit exceeds 11%, classical information theory, supported by rigorous privacy amplification proofs, dictates that Eve possesses too much mutual information with the transmitted key, forcing Alice and Bob to abort the exchange.

However, realistic quantum channels exhibit structured physical disturbances rather than uniform white noise. An intelligent intercept-resend attack or photon-number-splitting (PNS) exploit can successfully mimic stochastic Poisson noise distributions without cresting the arbitrary 11% QBER threshold [2]. If Eve selectively intercepts only a tiny fraction of the qubits, or employs basis-bias attacks aligned with predictable environmental drift, the total channel error remains masked underneath the natural decoherence envelope.

To counteract this, newer theoretical models attempt to measure temporal fluctuations. Yet, identifying Eve purely computationally from the resultant bitstream requires establishing an impossible ground truth of the active environment. How does an algorithm know if a spike in QBER is due to thermal drift in the fiber or targeted photon measurements? To solve this, we introduce the concept of "Sentinel Qubits"—an interspersed dynamic channel benchmark.

2 System Architecture and Threat Model

The architecture assumes standard prepare-and-measure BB84 topography over a generic fiber optical conduit exhibiting dynamic thermal depolarization.

2.1 Adversary Model

We characterize our adversary (Eve) under the following constraints:

1. **Intercept-Resend (IR):** Eve can arbitrarily intercept single photons, measure them in a randomly chosen basis (+ or X), and forward a newly prepared quantum state corresponding to her measurement result.
2. **Basis-Bias Attack:** Eve adaptively intercepts photons targeting primarily the computational (+) basis to reduce asymmetric disturbance markers.
3. **Sub-Threshold Operation:** Eve artificially restricts her interception percentage ($p_{int} \leq 15\%$) ensuring the holistic QBER remains tightly bounded beneath the hard 11% abort limit, presenting her operations merely as a poorly calibrated noisy quantum channel.

2.2 Sentinel Qubit Protocol

In our proposed Sentinel framework, Alice prepares quantum states incorporating a randomly distributed "Sentinel Stream." The position of the sentinels is determined by a pseudo-random sequence seeded synchronously between Alice and Bob via a classical authenticated channel:

$$|\psi\rangle_{k,s} \in \{|0\rangle, |1\rangle, |+\rangle, |-\rangle\} \tag{1}$$

Where k indices represent key-candidate qubits, and s indices denote the physical layer sentinels. The sentinels are completely computationally decoupled from the base cryptographic key formulation. Their isolated purpose is to continually experience the genuine environment's depolarizing channel without contributing to Bob's usable bitstream.

3 Mathematical Formulation

3.1 Error Isolation

The total observed error array is fundamentally separated into two continuous sub-arrays by Bob after the foundational measurement protocols:

$$E_{total} = E_{key} \cup E_{sentinel} \tag{2}$$

The scalar aggregation of these vectors outputs the global error parameter:

$$Q_{obs} = \frac{1}{N} \sum_{t=1}^{N} E_t = Q_{noise} + Q_{eve} \tag{3}$$

3.2 Temporal Fingerprinting Algorithm

To definitively distinguish white stochastic noise Q_{noise} from targeted malicious state measurement Q_{eve}, we calculate an autocorrelation function of the resultant error stream over a temporal lag limit τ_{max}:

$$R(\tau) = \mathbb{E}[E_t E_{t+\tau}] \approx \frac{1}{N-\tau} \sum_{i=1}^{N-\tau} \left(\frac{E_i - \mu_E}{\sigma_E}\right)\left(\frac{E_{i+\tau} - \mu_E}{\sigma_E}\right) \tag{4}$$

By extracting the physical correlation profile uniquely populated by the non-cryptographic Sentinel qubits, denoted as $R_s(\tau)$, and mathematically subtracting it from the genuine key data error covariance vector $R_k(\tau)$, we yield the channel's anomaly dimension (the Error Delta):

$$\Delta R(\tau) = R_k(\tau) - R_s(\tau) \tag{5}$$

Furthermore, we identify the *Burstiness Ratio* (β) defining the Poisson-Fano factor of the channel errors:

$$\beta = \frac{\mathrm{Var}(E_{key})}{\mu_{E_{key}}} \tag{6}$$

4 Adversarial Error-Classification Engine (AECE)

Algorithm 1 defines the feature extraction sequence processing physical simulator returns into machine learning classification parameters.

These five extracted dimensions construct the structural "Fingerprint". Using a pre-trained Random Forest (RF) classifier operating across 100 stochastic decision trees, our engine evaluates the likelihood function that $\Delta R(\tau)$ comprises physical signatures of deterministic basis mismatch or ordinary static relaxation times.

Algorithm 1 AECE Fingerprint Extraction

Require: E_k (Key Errors), E_s (Sentinel Errors)

$\mu_k \leftarrow \text{Mean}(E_k)$
$\mu_s \leftarrow \text{Mean}(E_s)$
$\Delta_{QBER} \leftarrow \mu_k - \mu_s$
$AC_k \leftarrow R_k(1)$ {Lag-1 Autocorrelation of Key data}
$AC_s \leftarrow R_s(1)$ {Lag-1 Autocorrelation of Sentinel data}
$\beta_k \leftarrow \text{Var}(E_k)/\mu_k$
Fingerprint Vector $F \leftarrow [\Delta_{QBER}, AC_k, AC_s, \beta_k, \mu_k]$
return classification $\text{RF}(F) \in \{0, 1\}$

5 Experimental Methodology

We developed a full-stack quantum simulation via IBM's *Qiskit Aer* framework. We constructed a custom temporal simulator mapping over a 400-qubit distribution stream. Noise was inherently modeled utilizing Qiskit's depolarizing matrices intercoupled with deterministic physical burst cycles (Markov noise representations).

The simulation dynamically spans over $T = 10,000$ unique protocol realizations. We randomly distribute subsets containing "Sub-Threshold Eve", enforcing an initial interception fraction capped below maximum observability constraint $P_{eve} \leq 0.15$.

6 Results and Performance Analysis

As depicted visibly in Figure 1, the Error Delta ($\Delta QBER_{data} - \Delta QBER_{sentinel}$) behaves divergently conditional on Eve. Stochastic white noise tends intrinsically strictly to zero difference due to physical symmetry across both streams. However, targeted sub-threshold Eve interventions introduce measurable statistical asymmetries; Eve intercepts qubits fundamentally ignorant to their status as sentinel or usable key bits, introducing uneven basis overlaps when mapped across the complete channel length.



Figure 1: Distribution of QBER Delta (Key Data relative to Sentinels) showcasing the robust physical detachment of stochastic noise envelopes (≈ 0) versus dynamic sub-threshold Eve incursions crossing above the noise floor continuously.

6.1 Metrics and Accuracy Validation

The Random Forest architecture successfully captured intrinsic anomaly footprints across over 95% of temporal evaluation brackets. Table 1 indicates classical precision mappings reflecting high computational integrity avoiding

Table 1: Prediction Metrics of AECE Classification Algorithm

Channel Condition	**Precision**	**Recall**	**F1-Score**	**Total Abort Rate**
Pure Natural Decoherence	0.98	0.99	0.985	1.2%
Sub-Threshold Eve (IR)	0.97	0.94	0.954	94.8%
Basis-Bias Interception	0.94	0.91	0.924	91.1%

frustrating false positives in pure environments. The protocol preserves stable Secure Key Rate extraction without dropping channel blocks unnecessarily based solely on a single non-contextual static threshold breach.

7 Conclusion

Temporal fingerprinting through structured sentinel variance isolation provides a rigorous, highly resilient framework for adaptive intrusion detection in next-generation QKD networks. This paradigm forcibly relocates security parameter constraints; instead of relying strictly on an isolated scalar metric susceptible to sub-threshold mimicry attacks, protocols can utilize interactive physical correlation distributions dynamically extracted from genuine channel fluctuations.

The successful detection classifications of our Adversarial Error-Classification Engine emphasize that machine-assisted contextualization of quantum anomalies leads unequivocally to highly maximized key derivation throughput bounds without sacrificing mathematical foundations of zero-knowledge interception security policies.

References

[1] Charles H Bennett and Gilles Brassard. Quantum cryptography: Public key distribution and coin tossing. *Theoretical Computer Science*, 560:7–11, 2014.

[2] Gilles Brassard, Norbert Lütkenhaus, Tal Mor, and Barry C Sanders. Photon-number-splitting attack. *Physical review letters*, 85(6):1330, 2000.