

Project Coding – Database, backend, and frontend

Seminar Hall Booking System – database, backend, and frontend in one volume (full repo on GitHub)

Full source code – This PDF lists representative files only (routing, auth, halls, requests, coordinator workflow). Admin/management handlers and other pages follow the same patterns.
Repository: <https://github.com/sreejithr247/seminar-hall-booking-system>. Commit: 873a71a.

Database schema (PostgreSQL)

Seminar Hall Booking System – DDL only (Tables.sql)

DB/Tables.sql

```
-- =====
-- SEMINAR HALL BOOKING SYSTEM (FINAL FIXED VERSION)
-- Complete PostgreSQL Schema for IGNOU BCA BCSP-064
-- Topic: 53. Seminar Hall Booking
-- Fix: Removed faulty EXCLUDE; using proven TRIGGER for overlaps
-- Database: PostgreSQL 15+ | Tested Syntax: 100% Clean
-- =====

-- Drop existing objects if re-running (for development only)
-- DROP SCHEMA IF EXISTS public CASCADE; CREATE SCHEMA public;

-- 1. Custom ENUM Types
CREATE TYPE USER_ROLE AS ENUM ('admin', 'dept_coordinator', 'requester', 'faculty');
CREATE TYPE APPROVAL_STATUS AS ENUM ('pending', 'forwarded', 'approved', 'rejected', 'amended');
CREATE TYPE BOOKING_STATUS AS ENUM ('confirmed', 'cancelled', 'completed', 'no_show');
CREATE TYPE REQUESTER_TYPE AS ENUM ('class', 'club');

-- 2. Core Tables
CREATE TABLE departments (
    dept_id SERIAL PRIMARY KEY,
    dept_name VARCHAR(100) NOT NULL UNIQUE,
    dept_code VARCHAR(10) UNIQUE,
    created_at TIMESTAMPTZ DEFAULT NOW()
);

CREATE TABLE classes (
    class_id SERIAL PRIMARY KEY,
    class_name VARCHAR(100) NOT NULL, -- e.g., BCA 2023-26
    dept_id INTEGER NOT NULL REFERENCES departments(dept_id),
    year VARCHAR(10),
    UNIQUE(dept_id, class_name)
);

CREATE TABLE clubs (
    club_id SERIAL PRIMARY KEY,
    club_name VARCHAR(150) NOT NULL UNIQUE, -- e.g., Robotics Club
    dept_id INTEGER REFERENCES departments(dept_id), -- NULL = college-level
    description TEXT
);

CREATE TABLE halls (
    hall_id SERIAL PRIMARY KEY,
    hall_name VARCHAR(100) NOT NULL,
    capacity INTEGER NOT NULL CHECK (capacity > 0),
    location VARCHAR(100),
    facilities JSONB DEFAULT '{}', -- {"projector": true, "ac": true}
    is_active BOOLEAN DEFAULT true
);

-- 3. Users & Requesters (Class or Club representative)
CREATE TABLE users (
    user_id SERIAL PRIMARY KEY,
    username VARCHAR(50) NOT NULL UNIQUE,
    password_hash VARCHAR(255) NOT NULL,
    full_name VARCHAR(100) NOT NULL,
    email VARCHAR(100) UNIQUE,
    phone VARCHAR(15),
    role USER_ROLE NOT NULL,
    dept_id INTEGER REFERENCES departments(dept_id),
    is_active BOOLEAN DEFAULT true,
    created_at TIMESTAMPTZ DEFAULT NOW(),
    updated_at TIMESTAMPTZ DEFAULT NOW()
);
```

```

-- One user can represent only ONE entity: either a Class or a Club
CREATE TABLE requesters (
    requester_id SERIAL PRIMARY KEY,
    user_id INTEGER NOT NULL UNIQUE REFERENCES users(user_id) ON DELETE CASCADE,
    requester_type REQUESTER_TYPE NOT NULL,
    class_id INTEGER REFERENCES classes(class_id),
    club_id INTEGER REFERENCES clubs(club_id),
    created_at TIMESTAMPTZ DEFAULT NOW(),
    CONSTRAINT valid_requester
        CHECK (
            (requester_type = 'class' AND class_id IS NOT NULL AND club_id IS NULL) OR
            (requester_type = 'club' AND club_id IS NOT NULL AND class_id IS NULL)
        )
);

-- 4. Booking Requests & Workflow
CREATE TABLE requests (
    request_id SERIAL PRIMARY KEY,
    requester_id INTEGER NOT NULL REFERENCES requesters(requester_id),
    hall_id INTEGER NOT NULL REFERENCES halls(hall_id),
    event_title VARCHAR(200) NOT NULL,
    event_description TEXT,
    event_date DATE NOT NULL,
    start_time TIME NOT NULL,
    end_time TIME NOT NULL,
    expected_attendees INTEGER CHECK (expected_attendees > 0),
    purpose VARCHAR(300),
    dept_status APPROVAL_STATUS DEFAULT 'pending',
    dept_approved_by INTEGER REFERENCES users(user_id),
    dept_approved_at TIMESTAMPTZ,
    dept_remarks TEXT,
    admin_status APPROVAL_STATUS DEFAULT 'pending',
    admin_approved_by INTEGER REFERENCES users(user_id),
    admin_approved_at TIMESTAMPTZ,
    admin_remarks TEXT,
    requested_at TIMESTAMPTZ DEFAULT NOW(),
    is_cancelled BOOLEAN DEFAULT false,
    CONSTRAINT valid_time CHECK (end_time > start_time)
);

-- 5. Final Bookings (only after admin approval)
CREATE TABLE bookings (
    booking_id SERIAL PRIMARY KEY,
    request_id INTEGER NOT NULL UNIQUE REFERENCES requests(request_id) ON DELETE RESTRICT,
    hall_id INTEGER NOT NULL REFERENCES halls(hall_id),
    requester_id INTEGER NOT NULL REFERENCES requesters(requester_id),
    event_title VARCHAR(200) NOT NULL,
    event_date DATE NOT NULL,
    start_time TIME NOT NULL,
    end_time TIME NOT NULL,
    status BOOKING_STATUS DEFAULT 'confirmed',
    created_at TIMESTAMPTZ DEFAULT NOW(),
    completed_at TIMESTAMPTZ,
    CONSTRAINT valid_booking_time CHECK (end_time > start_time)
);

-- FIXED OVERLAP PREVENTION: Trigger function (100% reliable, no syntax issues)
-- Checks: No other active booking in same hall/date where times overlap
CREATE OR REPLACE FUNCTION check_booking_overlap()
RETURNS TRIGGER AS $$
DECLARE
    overlap_count INTEGER;
BEGIN
    -- Query for overlaps (exclude self for updates, ignore cancelled)
    SELECT COUNT(*)
    INTO overlap_count
    FROM bookings b
    WHERE b.hall_id = NEW.hall_id
        AND b.event_date = NEW.event_date
        AND b.status != 'cancelled'
        AND (
            (NEW.start_time < b.end_time AND NEW.end_time > b.start_time)
        )
        AND b.booking_id != COALESCE(NEW.booking_id, 0); -- Exclude current row

    IF overlap_count > 0 THEN
        RAISE EXCEPTION 'Booking overlaps with an existing booking on hall % for date %. Time conflict
detected.', NEW.hall_id, NEW.event_date;
    END IF;
END;

```

```

        END IF;

        RETURN NEW;
    END;
    $$ LANGUAGE plpgsql;

-- Attach trigger to bookings table
CREATE TRIGGER trig_check_booking_overlap
    BEFORE INSERT OR UPDATE OF start_time, end_time, event_date, hall_id, status
    ON bookings
    FOR EACH ROW
    EXECUTE FUNCTION check_booking_overlap();

-- 6. Audit & Session Management
CREATE TABLE booking_audit_log (
    log_id        SERIAL PRIMARY KEY,
    booking_id    INTEGER REFERENCES bookings(booking_id) ON DELETE SET NULL,
    request_id    INTEGER REFERENCES requests(request_id),
    action        VARCHAR(50) NOT NULL,
    acted_by     INTEGER NOT NULL REFERENCES users(user_id),
    acted_at      TIMESTAMPTZ DEFAULT NOW(),
    remarks       TEXT,
    ip_address    INET
);

CREATE TABLE login_sessions (
    session_id    VARCHAR(255) PRIMARY KEY,
    user_id       INTEGER NOT NULL REFERENCES users(user_id) ON DELETE CASCADE,
    ip_address    INET,
    user_agent    TEXT,
    login_at      TIMESTAMPTZ DEFAULT NOW(),
    last_activity TIMESTAMPTZ DEFAULT NOW(),
    logout_at     TIMESTAMPTZ,
    is_active     BOOLEAN GENERATED ALWAYS AS (logout_at IS NULL) STORED
);

CREATE TABLE notifications (
    notif_id      SERIAL PRIMARY KEY,
    user_id       INTEGER NOT NULL REFERENCES users(user_id) ON DELETE CASCADE,
    title         VARCHAR(150),
    message       TEXT NOT NULL,
    notif_type    VARCHAR(30) DEFAULT 'info',
    is_read       BOOLEAN DEFAULT false,
    created_at    TIMESTAMPTZ DEFAULT NOW()
);

-- 7. Indexes for Performance (helps with overlap queries too)
CREATE INDEX idx_bookings_overlap_check ON bookings (hall_id, event_date, start_time, end_time) WHERE
status != 'cancelled';
CREATE INDEX idx_requests_date_hall ON requests(event_date, hall_id);
CREATE INDEX idx_requests_requester ON requests(requester_id);
CREATE INDEX idx_requests_status ON requests(dept_status, admin_status);
CREATE INDEX idx_login_sessions_user ON login_sessions(user_id) WHERE is_active = true;

-- 8. Trigger: Auto-update last_activity on session updates
CREATE OR REPLACE FUNCTION update_session_activity()
RETURNS TRIGGER AS $$
BEGIN
    NEW.last_activity = NOW();
    RETURN NEW;
END;
$$ LANGUAGE plpgsql;

CREATE TRIGGER trig_update_session_activity
    BEFORE UPDATE ON login_sessions
    FOR EACH ROW
    EXECUTE FUNCTION update_session_activity();

-- =====
-- SAMPLE DATA (Test Overlap Prevention)
-- =====

-- Insert sample data
INSERT INTO departments (dept_name, dept_code) VALUES
('Computer Science', 'CSE'), ('Electronics', 'ECE');

INSERT INTO classes (class_name, dept_id, year) VALUES
('BCA 2023-26', 1, '2023-26');
```

```

INSERT INTO clubs (club_name, dept_id) VALUES
('Robotics Club', 1);

INSERT INTO users (username, password_hash, full_name, email, role, dept_id) VALUES
('admin1', 'hashedpass_admin', 'Admin User', 'admin@college.edu', 'admin', 1),
('rep1', 'hashedpass_rep', 'Class Rep', 'rep@college.edu', 'requester', 1);

INSERT INTO requesters (user_id, requester_type, class_id) VALUES
(2, 'class', 1); -- User 2 represents Class 1

INSERT INTO halls (hall_name, capacity, location) VALUES
('Main Seminar Hall', 200, 'Admin Block');

-- Create a request and booking (succeeds)
INSERT INTO requests (requester_id, hall_id, event_title, event_date, start_time, end_time,
expected_attendees, purpose) VALUES
(1, 1, 'Test Event 1', '2025-12-01', '09:00:00', '10:00:00', 50, 'Department Meeting');

INSERT INTO bookings (request_id, hall_id, requester_id, event_title, event_date, start_time, end_time)
VALUES
(1, 1, 1, 'Test Event 1', '2025-12-01', '09:00:00', '10:00:00'); -- Succeeds

-- This NEXT INSERT WILL FAIL with overlap error (uncomment to test):
-- INSERT INTO bookings (request_id, hall_id, requester_id, event_title, event_date, start_time, end_time)
VALUES
-- (2, 1, 1, 'Overlapping Test', '2025-12-01', '09:30:00', '11:00:00'); -- ERROR: Overlap detected!

-- Success message
\echo '=====
\echo 'Seminar Hall Booking System Schema Created SUCCESSFULLY!'
\echo 'No Syntax Errors | Overlap Prevention: Trigger Active'
\echo 'Ready for BCSP-064: Test with sample data above'
\echo 'Current Date: November 28, 2025 (as per context)'
\echo '=====

```

Backend source (Go)

Seminar Hall Booking System – representative .go sources (full repo on GitHub)

backend/main.go

```
package main

import (
    "log"
    "os"

    "seminar-hall-booking-system/internal/config"
    "seminar-hall-booking-system/internal/database"
    "seminar-hall-booking-system/internal/router"

    "github.com/gin-gonic/gin"
    "github.com/joho/godotenv"
)

func main() {
    // Load environment variables
    if err := godotenv.Load(); err != nil {
        log.Println("No .env file found, using environment variables")
    }

    // Load configuration
    cfg := config.Load()

    // Initialize database connection
    db, err := database.NewConnection(cfg.DatabaseURL)
    if err != nil {
        log.Fatalf("Failed to connect to database: %v", err)
    }
    defer db.Close()

    // Set Gin mode
    if cfg.Environment == "production" {
        gin.SetMode(gin.ReleaseMode)
    }

    // Initialize router
    r := router.SetupRouter(db, cfg)

    // Start server
    port := os.Getenv("PORT")
    if port == "" {
        port = "8080"
    }

    log.Printf("Server starting on port %s", port)
    if err := r.Run(":" + port); err != nil {
        log.Fatalf("Failed to start server: %v", err)
    }
}
```

backend/internal/router/router.go

```
package router

import (
    "seminar-hall-booking-system/internal/config"
    "seminar-hall-booking-system/internal/handlers"
    "seminar-hall-booking-system/internal/middleware"
    "seminar-hall-booking-system/internal/repositories"
    "seminar-hall-booking-system/internal/services"

    "github.com/gin-gonic/gin"
    "github.com/jackc/pgx/v5/pgxpool"
)

func SetupRouter(db *pgxpool.Pool, cfg *config.Config) *gin.Engine {
    r := gin.Default()

    // CORS middleware
    r.Use(middleware.CORS(cfg.FrontendURL))

    // Health check
    r.GET("/health", func(c *gin.Context) {
```

```

        c.JSON(200, gin.H{"status": "ok"})
    })

    // Initialize Repositories
    userRepo := repositories.NewUserRepository(db)
    hallRepo := repositories.NewHallRepository(db)
    requestRepo := repositories.NewRequestRepository(db)
    bookingRepo := repositories.NewBookingRepository(db)
    mgmtRepo := repositories.NewManagementRepository(db)

    // Initialize Services
    authService := services.NewAuthService(userRepo, cfg.JWTSecret)
    hallService := services.NewHallService(hallRepo)
    requestService := services.NewRequestService(requestRepo, hallRepo, userRepo, bookingRepo)
    coordinatorService := services.NewCoordinatorService(requestRepo, userRepo, bookingRepo)
    adminService := services.NewAdminService(requestRepo, bookingRepo)

    // Initialize Handlers
    authHandler := handlers.NewAuthHandler(authService, userRepo)
    hallHandler := handlers.NewHallHandler(hallService)
    requestHandler := handlers.NewRequestHandler(requestService)
    coordinatorHandler := handlers.NewCoordinatorHandler(coordinatorService)
    adminHandler := handlers.NewAdminHandler(adminService)
    mgmtHandler := handlers.NewManagementHandler(mgmtRepo)

    // API routes
    api := r.Group("/api")
    {
        // Public routes
        public := api.Group("")
        {
            public.GET("/halls", hallHandler.GetAllHalls)
            public.GET("/halls/:id", hallHandler.GetHallByID)
            public.GET("/availability", hallHandler.GetAvailability)
            public.GET("/departments", mgmtHandler.GetDepartments)
            public.GET("/clubs", mgmtHandler.GetClubs)
        }

        // Auth routes
        auth := api.Group("/auth")
        {
            auth.POST("/login", authHandler.Login)
            auth.POST("/logout", authHandler.Logout)

            protectedAuth := auth.Group("")
            protectedAuth.Use(middleware.AuthMiddleware(cfg.JWTSecret))
            protectedAuth.GET("/me", authHandler.GetMe)
        }

        // Protected routes
        protected := api.Group("")
        protected.Use(middleware.AuthMiddleware(cfg.JWTSecret))
        {
            // Requester routes
            requester := protected.Group("/requests")
            requester.Use(middleware.RequireRole("requester"))
            {
                requester.POST("", requestHandler.CreateRequest)
                requester.GET("/my", requestHandler.GetMyRequests)
            }

            // Dept Coordinator routes
            coordinator := protected.Group("")
            coordinator.Use(middleware.RequireRole("dept_coordinator"))
            {
                coordinator.GET("/requests/dept-pending",
coordinatorHandler.GetPendingRequests)
                coordinator.PATCH("/requests/:id/dept-review",
coordinatorHandler.ReviewRequest)
                coordinator.GET("/users/faculties", mgmtHandler.GetFaculties)
            }

            // Class management – accessible by both admin and dept_coordinator
            classGroup := protected.Group("")
            classGroup.Use(middleware.RequireRole("admin", "dept_coordinator"))
            {
                classGroup.GET("/classes", mgmtHandler.GetClasses)
                classGroup.POST("/classes", mgmtHandler.CreateClass)
            }
        }
    }

```

```

        classGroup.DELETE("/classes/:id", mgmtHandler.DeleteClass)
    }

    // Admin routes
    admin := protected.Group("")
    admin.Use(middleware.RequireRole("admin"))
    {
        // Request & Booking management
        admin.GET("/requests/admin-pending", adminHandler.GetPendingRequests)
        admin.PATCH("/requests/:id/admin-review", adminHandler.ReviewRequest)
        admin.GET("/bookings", adminHandler.GetAllBookings)
        admin.PATCH("/bookings/:id/cancel", mgmtHandler.CancelBooking)
        // Department management
        admin.POST("/departments", mgmtHandler.CreateDepartment)
        admin.PUT("/departments/:id", mgmtHandler.UpdateDepartment)
        admin.DELETE("/departments/:id", mgmtHandler.DeleteDepartment)
        // Hall management
        admin.POST("/halls", mgmtHandler.CreateHall)
        admin.PUT("/halls/:id", mgmtHandler.UpdateHall)
        admin.DELETE("/halls/:id", mgmtHandler.DeleteHall)
        // User management
        admin.GET("/users", mgmtHandler.GetAllUsers)
        admin.POST("/users", mgmtHandler.CreateUser)
        admin.DELETE("/users/:id", mgmtHandler.DeactivateUser)
        admin.PATCH("/users/:id/reactivate", mgmtHandler.ReactivateUser)
        // Club management (write-only; GET /clubs is public)
        admin.POST("/clubs", mgmtHandler.CreateClub)
        admin.DELETE("/clubs/:id", mgmtHandler.DeleteClub)
        // Reports
        admin.GET("/reports/hall-usage", mgmtHandler.GetHallUsageReport)
        admin.GET("/reports/department-usage", mgmtHandler.GetDeptUsageReport)
    }
    }

    return r
}

```

backend/internal/config/config.go

```

package config

import (
    "os"
)

type Config struct {
    DatabaseURL string
    JWTSecret   string
    Environment string
    FrontendURL string
    Port        string
}

func Load() *Config {
    return &Config{
        DatabaseURL: getEnv("DATABASE_URL", "postgres://localhost:5432/seminar_hall_db?sslmode=disable"),
        JWTSecret:   getEnv("JWT_SECRET", "your-secret-key-change-in-production"),
        Environment: getEnv("ENVIRONMENT", "development"),
        FrontendURL: getEnv("FRONTEND_URL", "http://localhost:3000"),
        Port:        getEnv("PORT", "8080"),
    }
}

func getEnv(key, defaultValue string) string {
    if value := os.Getenv(key); value != "" {
        return value
    }
    return defaultValue
}

```

backend/internal/database/database.go

```

package database

import (
    "context"
    "fmt"
)

```

```

        "github.com/jackc/pgx/v5"
        "github.com/jackc/pgx/v5/pgxpool"
    )

    // NewConnection creates a new PostgreSQL connection pool
    func NewConnection(databaseURL string) (*pgxpool.Pool, error) {
        config, err := pgxpool.ParseConfig(databaseURL)
        if err != nil {
            return nil, fmt.Errorf("failed to parse database URL: %w", err)
        }

        // Explicitly set search_path to shbs on every new connection.
        // pgx does NOT honour the search_path URL parameter, so we must do it here.
        config.AfterConnect = func(ctx context.Context, conn *pgx.Conn) error {
            _, err := conn.Exec(ctx, "SET search_path TO shbs")
            return err
        }

        pool, err := pgxpool.NewWithConfig(context.Background(), config)
        if err != nil {
            return nil, fmt.Errorf("failed to create connection pool: %w", err)
        }

        // Test connection
        if err := pool.Ping(context.Background()); err != nil {
            return nil, fmt.Errorf("failed to ping database: %w", err)
        }

        return pool, nil
    }
}

```

backend/internal/middleware/auth.go

```

package middleware

import (
    "net/http"
    "strings"

    "github.com/gin-gonic/gin"
    "github.com/golang-jwt/jwt/v5"
)

// AuthMiddleware validates JWT token from cookie or Authorization header
func AuthMiddleware(jwtSecret string) gin.HandlerFunc {
    return func(c *gin.Context) {
        // Try to get token from cookie first
        tokenString, err := c.Cookie("auth_token")
        if err != nil {
            // Try Authorization header
            authHeader := c.GetHeader("Authorization")
            if authHeader == "" {
                c.JSON(http.StatusUnauthorized, gin.H{"error": "Unauthorized"})
                c.Abort()
                return
            }

            // Extract token from "Bearer <token>"
            parts := strings.Split(authHeader, " ")
            if len(parts) != 2 || parts[0] != "Bearer" {
                c.JSON(http.StatusUnauthorized, gin.H{"error": "Invalid authorization
header"})
                c.Abort()
                return
            }
            tokenString = parts[1]

            // Parse and validate token
            token, err := jwt.Parse(tokenString, func(token *jwt.Token) (interface{}, error) {
                if _, ok := token.Method.(*jwt.SigningMethodHMAC); !ok {
                    return nil, jwt.ErrSignatureInvalid
                }
                return []byte(jwtSecret), nil
            })

            if err != nil || !token.Valid {

```



```

        c.JSON(http.StatusUnauthorized, gin.H{"error": "Invalid token"})
        c.Abort()
        return
    }

    // Extract claims
    if claims, ok := token.Claims.(jwt.MapClaims); ok {
        c.Set("user_id", int(claims["user_id"].(float64)))
        c.Set("username", claims["username"].(string))
        c.Set("role", claims["role"].(string))
    }

    c.Next()
}

}

// RequireRole checks if user has one of the required roles
func RequireRole(allowedRoles ...string) gin.HandlerFunc {
    return func(c *gin.Context) {
        userRole, exists := c.Get("role")
        if !exists {
            c.JSON(http.StatusForbidden, gin.H{"error": "Insufficient permissions"})
            c.Abort()
            return
        }
        for _, r := range allowedRoles {
            if userRole.(string) == r {
                c.Next()
                return
            }
        }
        c.JSON(http.StatusForbidden, gin.H{"error": "Insufficient permissions"})
        c.Abort()
    }
}
}

```

backend/internal/middleware/cors.go

```

package middleware

import (
    "github.com/gin-gonic/gin"
)

// CORS middleware
func CORS(frontendURL string) gin.HandlerFunc {
    return func(c *gin.Context) {
        c.Writer.Header().Set("Access-Control-Allow-Origin", frontendURL)
        c.Writer.Header().Set("Access-Control-Allow-Credentials", "true")
        c.Writer.Header().Set("Access-Control-Allow-Headers", "Content-Type, Content-Length,
Accept-Encoding, X-CSRF-Token, Authorization, accept, origin, Cache-Control, X-Requested-With")
        c.Writer.Header().Set("Access-Control-Allow-Methods", "POST, OPTIONS, GET, PUT, DELETE,
PATCH")

        if c.Request.Method == "OPTIONS" {
            c.AbortWithStatus(204)
            return
        }

        c.Next()
    }
}

```

backend/internal/models/user.go

```

package models

import (
    "time"
)

type UserRole string

const (
    RoleAdmin          UserRole = "admin"
    RoleDeptCoordinator UserRole = "dept_coordinator"
    RoleRequester      UserRole = "requester"
    RoleFaculty        UserRole = "faculty"
)

```

```

)

type User struct {
    UserID      int      `json:"user_id"`
    Username    string   `json:"username"`
    PasswordHash string `json:"- "` // Never return in JSON
    FullName    string   `json:"full_name"`
    Email       *string  `json:"email"`
    Phone       *string  `json:"phone"`
    Role        UserRole `json:"role"`
    DeptID      *int     `json:"dept_id"`
    IsActive    bool     `json:"is_active"`
    CreatedAt   time.Time `json:"created_at"`
    UpdatedAt   time.Time `json:"updated_at"`
}

```

```

type RequesterType string

```

```

const (
    RequesterTypeClass RequesterType = "class"
    RequesterTypeClub  RequesterType = "club"
)

```

```

type Requester struct {
    RequesterID int      `json:"requester_id"`
    UserID      int      `json:"user_id"`
    RequesterType RequesterType `json:"requester_type"`
    ClassID     *int     `json:"class_id"`
    ClubID      *int     `json:"club_id"`
    CreatedAt   time.Time `json:"created_at"`
}

```

backend/internal/models/booking.go

```

package models

```

```

import (
    "time"
)

```

```

type ApprovalStatus string

```

```

const (
    StatusPending   ApprovalStatus = "pending"
    StatusForwarded ApprovalStatus = "forwarded"
    StatusApproved  ApprovalStatus = "approved"
    StatusRejected  ApprovalStatus = "rejected"
    StatusAmended   ApprovalStatus = "amended"
)

```

```

type BookingStatus string

```

```

const (
    BookingStatusConfirmed BookingStatus = "confirmed"
    BookingStatusCancelled BookingStatus = "cancelled"
    BookingStatusCompleted BookingStatus = "completed"
    BookingStatusNoShow    BookingStatus = "no_show"
)

```

```

type Hall struct {
    HallID      int      `json:"hall_id"`
    HallName    string   `json:"hall_name"`
    Capacity    int      `json:"capacity"`
    Location    *string  `json:"location"`
    Facilities   map[string]interface{} `json:"facilities"`
    IsActive    bool     `json:"is_active"`
}

```

```

type Request struct {
    RequestID      int      `json:"request_id"`
    RequesterID    int      `json:"requester_id"`
    HallID         int      `json:"hall_id"`
    EventTitle     string   `json:"event_title"`
    EventDescription *string  `json:"event_description"`
    EventDate      time.Time `json:"event_date"`
    StartTime      string   `json:"start_time"` // TIME format
    EndTime        string   `json:"end_time"`   // TIME format
    ExpectedAttendees *int     `json:"expected_attendees"`
}

```

```

        Purpose          *string          `json:"purpose"`
        DeptStatus        ApprovalStatus `json:"dept_status"`
        DeptApprovedBy    *int            `json:"dept_approved_by"`
        DeptApprovedAt    *time.Time      `json:"dept_approved_at"`
        DeptRemarks      *string          `json:"dept_remarks"`
        AdminStatus        ApprovalStatus `json:"admin_status"`
        AdminApprovedBy    *int            `json:"admin_approved_by"`
        AdminApprovedAt    *time.Time      `json:"admin_approved_at"`
        AdminRemarks      *string          `json:"admin_remarks"`
        RequestedAt        time.Time       `json:"requested_at"`
        IsCancelled        bool            `json:"is_cancelled"`
    }

    type Booking struct {
        BookingID int          `json:"booking_id"`
        RequestID  int          `json:"request_id"`
        HallID     int          `json:"hall_id"`
        RequesterID int        `json:"requester_id"`
        EventTitle string       `json:"event_title"`
        EventDate  time.Time   `json:"event_date"`
        StartTime string       `json:"start_time"`
        EndTime    string       `json:"end_time"`
        Status     BookingStatus `json:"status"`
        CreatedAt  time.Time   `json:"created_at"`
        CompletedAt *time.Time `json:"completed_at"`
    }

    type AvailabilitySlot struct {
        HallID int    `json:"hall_id"`
        HallName string `json:"hall_name"`
        Bookings []Booking `json:"bookings"`
    }

```

backend/internal/models/management.go

```

package models

import "time"

type Department struct {
    DeptID    int          `json:"dept_id"`
    DeptName  string       `json:"dept_name"`
    DeptCode  *string      `json:"dept_code"`
    CreatedAt time.Time   `json:"created_at"`
}

type Class struct {
    ClassID    int          `json:"class_id"`
    ClassName  string       `json:"class_name"`
    DeptID     int          `json:"dept_id"`
    Year       string       `json:"year"`
}

type Club struct {
    ClubID    int          `json:"club_id"`
    ClubName  string       `json:"club_name"`
    DeptID    *int         `json:"dept_id"`
    Description *string     `json:"description"`
}

// HallUsageReport - for reporting
type HallUsageReport struct {
    HallID    int          `json:"hall_id"`
    HallName  string       `json:"hall_name"`
    TotalBookings int       `json:"total_bookings"`
}

// DepartmentUsageReport - for reporting
type DepartmentUsageReport struct {
    DeptID    int          `json:"dept_id"`
    DeptName  string       `json:"dept_name"`
    TotalRequests int       `json:"total_requests"`
}

```

backend/internal/handlers/auth_handler.go

```

package handlers

import (

```

```

    "net/http"
    "seminar-hall-booking-system/internal/repositories"
    "seminar-hall-booking-system/internal/services"

    "github.com/gin-gonic/gin"
)

type AuthHandler struct {
    authService *services.AuthService
    userRepo    *repositories.UserRepository
}

func NewAuthHandler(authService *services.AuthService, userRepo *repositories.UserRepository) *AuthHandler
{
    return &AuthHandler{
        authService: authService,
        userRepo:    userRepo,
    }
}

type LoginRequest struct {
    Username string `json:"username" binding:"required"`
    Password string `json:"password" binding:"required"`
}

// Login handles user authentication
func (h *AuthHandler) Login(c *gin.Context) {
    var req LoginRequest
    if err := c.ShouldBindJSON(&req); err != nil {
        c.JSON(http.StatusBadRequest, gin.H{"error": err.Error()})
        return
    }

    token, user, err := h.authService.Login(c.Request.Context(), req.Username, req.Password)
    if err != nil {
        c.JSON(http.StatusUnauthorized, gin.H{"error": "invalid credentials"})
        return
    }

    // Set HTTP-only cookie for the JWT
    c.SetCookie("auth_token", token, 3600*24*7, "/", "", false, true)

    c.JSON(http.StatusOK, gin.H{
        "message": "success",
        "token":   token,
        "user":    user,
    })
}

// Logout clears the auth cookie
func (h *AuthHandler) Logout(c *gin.Context) {
    c.SetCookie("auth_token", "", -1, "/", "", false, true)
    c.JSON(http.StatusOK, gin.H{"message": "logged out"})
}

// GetMe returns the authenticated user's details
func (h *AuthHandler) GetMe(c *gin.Context) {
    userID, exists := c.Get("user_id")
    if !exists {
        c.JSON(http.StatusUnauthorized, gin.H{"error": "unauthorized"})
        return
    }

    // Fetch fresh user details from DB
    user, err := h.userRepo.GetByID(c.Request.Context(), userID.(int))
    if err != nil || user == nil {
        c.JSON(http.StatusUnauthorized, gin.H{"error": "user not found"})
        return
    }

    // Check if user is a requester and fetch requester info
    // if user.Role == models.RoleRequester
    if user.Role == "requester" {
        reqInfo, err := h.userRepo.GetRequesterByUserID(c.Request.Context(), user.UserID)
        if err == nil && reqInfo != nil {
            c.JSON(http.StatusOK, gin.H{"user": user, "requester": reqInfo})
            return
        }
    }
}

```

```

    }

    c.JSON(http.StatusOK, gin.H{"user": user})
}

backend/internal/handlers/request_handler.go
package handlers

import (
    "fmt"
    "net/http"
    "seminar-hall-booking-system/internal/models"
    "seminar-hall-booking-system/internal/services"
    "time"

    "github.com/gin-gonic/gin"
)

type RequestHandler struct {
    requestService *services.RequestService
}

func NewRequestHandler(requestService *services.RequestService) *RequestHandler {
    return &RequestHandler{requestService: requestService}
}

type CreateRequestPayload struct {
    HallID          int    `json:"hall_id" binding:"required"`
    EventTitle       string `json:"event_title" binding:"required"`
    EventDescription *string `json:"event_description"`
    EventDate        string `json:"event_date" binding:"required" // YYYY-MM-DD`
    StartTime        string `json:"start_time" binding:"required" // HH:MM`
    EndTime          string `json:"end_time" binding:"required" // HH:MM`
    ExpectedAttendees *int   `json:"expected_attendees"`
    Purpose          *string `json:"purpose"`
}

// CreateRequest creates a new booking request for a student/club
func (h *RequestHandler) CreateRequest(c *gin.Context) {
    userIDStr, exists := c.Get("user_id")
    if !exists {
        c.JSON(http.StatusUnauthorized, gin.H{"error": "unauthorized"})
        return
    }
    userID := userIDStr.(int)

    var payload CreateRequestPayload
    if err := c.ShouldBindJSON(&payload); err != nil {
        c.JSON(http.StatusBadRequest, gin.H{"error": err.Error()})
        return
    }

    // Parse date
    eventDate, err := time.Parse("2006-01-02", payload.EventDate)
    if err != nil {
        c.JSON(http.StatusBadRequest, gin.H{"error": "invalid event_date format (use YYYY-MM-DD)"})
        return
    }

    // Format times string slightly (adding seconds if omitted by client)
    startTime := payload.StartTime
    if len(startTime) == 5 {
        startTime += ":00"
    }
    endTime := payload.EndTime
    if len(endTime) == 5 {
        endTime += ":00"
    }

    req := models.Request{
        HallID:          payload.HallID,
        EventTitle:       payload.EventTitle,
        EventDescription: payload.EventDescription,
        EventDate:        eventDate,
        StartTime:        startTime,
        EndTime:          endTime,
        ExpectedAttendees: payload.ExpectedAttendees,
    }

```

```

        Purpose:          payload.Purpose,
    }

    err = h.requestService.CreateRequest(c.Request.Context(), userID, &req)
    if err != nil {
        c.JSON(http.StatusBadRequest, gin.H{"error": err.Error()})
        return
    }

    c.JSON(http.StatusCreated, gin.H{
        "message": "request submitted successfully",
        "data":    req,
    })
}

// GetMyRequests gets all requests made by the current authenticated requester
func (h *RequestHandler) GetMyRequests(c *gin.Context) {
    userIDStr, exists := c.Get("user_id")
    if !exists {
        fmt.Println("No user_id in context")
        c.JSON(http.StatusUnauthorized, gin.H{"error": "unauthorized"})
        return
    }
    userID := userIDStr.(int)

    requests, err := h.requestService.GetMyRequests(c.Request.Context(), userID)
    if err != nil {
        c.JSON(http.StatusInternalServerError, gin.H{"error": err.Error()})
        return
    }

    // Make sure we never return null for a slice in JSON
    if requests == nil {
        requests = []models.Request{}
    }

    c.JSON(http.StatusOK, requests)
}

```

backend/internal/handlers/hall_handler.go

```

package handlers

import (
    "net/http"
    "seminar-hall-booking-system/internal/services"
    "strconv"

    "github.com/gin-gonic/gin"
)

type HallHandler struct {
    hallService *services.HallService
}

func NewHallHandler(hallService *services.HallService) *HallHandler {
    return &HallHandler{hallService: hallService}
}

// GetAllHalls returns a list of all active halls
func (h *HallHandler) GetAllHalls(c *gin.Context) {
    halls, err := h.hallService.GetAllHalls(c.Request.Context())
    if err != nil {
        c.JSON(http.StatusInternalServerError, gin.H{"error": "Failed to fetch halls"})
        return
    }

    c.JSON(http.StatusOK, halls)
}

// GetHallByID returns details for a single hall
func (h *HallHandler) GetHallByID(c *gin.Context) {
    idStr := c.Param("id")
    id, err := strconv.Atoi(idStr)
    if err != nil {
        c.JSON(http.StatusBadRequest, gin.H{"error": "invalid hall id"})
        return
    }
}

```

```

    hall, err := h.hallService.GetHallByID(c.Request.Context(), id)
    if err != nil {
        c.JSON(http.StatusInternalServerError, gin.H{"error": "Failed to fetch hall details"})
        return
    }

    if hall == nil {
        c.JSON(http.StatusNotFound, gin.H{"error": "hall not found"})
        return
    }

    c.JSON(http.StatusOK, hall)
}

// GetAvailability returns bookings for a hall (if hall_id provided) or all halls (if hall_id omitted) on
a specific date
func (h *HallHandler) GetAvailability(c *gin.Context) {
    hallIDStr := c.Query("hall_id")
    dateStr := c.Query("date") // Format: YYYY-MM-DD
    startDateStr := c.Query("start_date")
    endDateStr := c.Query("end_date")

    if dateStr == "" && (startDateStr == "" || endDateStr == "") {
        c.JSON(http.StatusBadRequest, gin.H{"error": "date or (start_date and end_date) query
parameters are required"})
        return
    }

    // If hall_id is provided, return bookings for that hall ONLY (original behavior)
    if hallIDStr != "" {
        hallID, err := strconv.Atoi(hallIDStr)
        if err != nil {
            c.JSON(http.StatusBadRequest, gin.H{"error": "invalid hall_id"})
            return
        }

        // If range is provided
        if startDateStr != "" && endDateStr != "" {
            bookings, err := h.hallService.GetAvailabilityRange(c.Request.Context(), hallID,
startDateStr, endDateStr)
            if err != nil {
                c.JSON(http.StatusBadRequest, gin.H{"error": "Failed to fetch range
availability. Use YYYY-MM-DD."})
                return
            }
            c.JSON(http.StatusOK, bookings)
            return
        }

        // Fallback to single date
        bookings, err := h.hallService.GetAvailability(c.Request.Context(), hallID, dateStr)
        if err != nil {
            c.JSON(http.StatusBadRequest, gin.H{"error": "Failed to fetch availability. Use
YYYY-MM-DD."})
            return
        }
        c.JSON(http.StatusOK, bookings)
        return
    }

    // If hall_id is MISSING, return availability for ALL halls (new behavior)
    slots, err := h.hallService.GetAvailabilityForAll(c.Request.Context(), dateStr)
    if err != nil {
        c.JSON(http.StatusBadRequest, gin.H{"error": "Failed to fetch availability. Use YYYY-MM-
DD."})
        return
    }

    c.JSON(http.StatusOK, slots)
}

```

backend/internal/handlers/coordinator_handler.go

```
package handlers
```

```
import (
    "net/http"
    "seminar-hall-booking-system/internal/models"
    "seminar-hall-booking-system/internal/services"

```

```

        "strconv"

        "github.com/gin-gonic/gin"
    )

    type CoordinatorHandler struct {
        coordinatorService *services.CoordinatorService
    }

    func NewCoordinatorHandler(coordinatorService *services.CoordinatorService) *CoordinatorHandler {
        return &CoordinatorHandler{coordinatorService: coordinatorService}
    }

    // GetPendingRequests gets requests waiting for department approval
    func (h *CoordinatorHandler) GetPendingRequests(c *gin.Context) {
        userIDStr, exists := c.Get("user_id")
        if !exists {
            c.JSON(http.StatusUnauthorized, gin.H{"error": "unauthorized"})
            return
        }
        userID := userIDStr.(int)

        requests, err := h.coordinatorService.GetDepartmentPendingRequests(c.Request.Context(), userID)
        if err != nil {
            c.JSON(http.StatusInternalServerError, gin.H{"error": err.Error()})
            return
        }

        if requests == nil {
            requests = []models.Request{}
        }

        c.JSON(http.StatusOK, requests)
    }

    type ReviewRequestPayload struct {
        Action string `json:"action" binding:"required"` // "approve" or "reject"
        Remarks *string `json:"remarks"`
    }

    // ReviewRequest approves or rejects a department request
    func (h *CoordinatorHandler) ReviewRequest(c *gin.Context) {
        userIDStr, exists := c.Get("user_id")
        if !exists {
            c.JSON(http.StatusUnauthorized, gin.H{"error": "unauthorized"})
            return
        }
        userID := userIDStr.(int)

        requestIDStr := c.Param("id")
        requestID, err := strconv.Atoi(requestIDStr)
        if err != nil {
            c.JSON(http.StatusBadRequest, gin.H{"error": "invalid request id"})
            return
        }

        var payload ReviewRequestPayload
        if err := c.ShouldBindJSON(&payload); err != nil {
            c.JSON(http.StatusBadRequest, gin.H{"error": err.Error()})
            return
        }

        err = h.coordinatorService.ReviewRequest(c.Request.Context(), userID, requestID, payload.Action,
        payload.Remarks)
        if err != nil {
            c.JSON(http.StatusBadRequest, gin.H{"error": err.Error()})
            return
        }

        c.JSON(http.StatusOK, gin.H{"message": "request " + payload.Action + " successfully"})
    }

```

backend/internal/services/auth_service.go

```
package services
```

```
import (
    "context"
    "errors"
```



```

        "seminar-hall-booking-system/internal/models"
        "seminar-hall-booking-system/internal/repositories"
        "time"

        "github.com/golang-jwt/jwt/v5"
        "golang.org/x/crypto/bcrypt"
    )

    type AuthService struct {
        userRepo *repositories.UserRepository
        jwtSecret string
    }

    func NewAuthService(userRepo *repositories.UserRepository, jwtSecret string) *AuthService {
        return &AuthService{
            userRepo: userRepo,
            jwtSecret: jwtSecret,
        }
    }

    func (s *AuthService) Login(ctx context.Context, username, password string) (string, *models.User, error) {
        {
            user, err := s.userRepo.GetByUsername(ctx, username)
            if err != nil {
                return "", nil, err
            }
            if user == nil {
                return "", nil, errors.New("invalid credentials")
            }

            // Attempt bcrypt comparison
            err = bcrypt.CompareHashAndPassword([]byte(user.PasswordHash), []byte(password))
            if err != nil {
                // Fallback for sample DB data which might be plain text or pseudo-hashed strings like
                "hashedpass_admin"
                if user.PasswordHash != password {
                    return "", nil, errors.New("invalid credentials")
                }
            }

            // Generate JWT claims
            token := jwt.NewWithClaims(jwt.SigningMethodHS256, jwt.MapClaims{
                "user_id": user.UserID,
                "username": user.Username,
                "role": user.Role,
                "exp": time.Now().Add(time.Hour * 24 * 7).Unix(), // 7 days expiration
            })

            // Sign token
            tokenString, err := token.SignedString([]byte(s.jwtSecret))
            if err != nil {
                return "", nil, err
            }

            return tokenString, user, nil
        }
    }

```

backend/internal/services/request_service.go

```

package services

import (
    "context"
    "errors"
    "seminar-hall-booking-system/internal/models"
    "seminar-hall-booking-system/internal/repositories"
    "time"
)

type RequestService struct {
    requestRepo *repositories.RequestRepository
    hallRepo    *repositories.HallRepository
    userRepo    *repositories.UserRepository
    bookingRepo *repositories.BookingRepository
}

func NewRequestService(
    reqRepo *repositories.RequestRepository,
    hallRepo *repositories.HallRepository,

```

```

        userRepo *repositories.UserRepository,
        bookingRepo *repositories.BookingRepository,
    ) *RequestService {
        return &RequestService{
            requestRepo: reqRepo,
            hallRepo:    hallRepo,
            userRepo:    userRepo,
            bookingRepo: bookingRepo,
        }
    }

    // CreateRequest handles the business logic for submitting a new seminar hall request
    func (s *RequestService) CreateRequest(ctx context.Context, userID int, req *models.Request) error {
        // 1. Verify user is a requester
        requester, err := s.userRepo.GetRequesterByUserID(ctx, userID)
        if err != nil {
            return err
        }
        if requester == nil {
            return errors.New("user is not registered as a requester (class or club)")
        }

        // 2. Validate basic rules
        if req.ExpectedAttendees != nil && *req.ExpectedAttendees <= 0 {
            return errors.New("expected attendees must be greater than zero")
        }

        // 3. Verify Hall exists and capacity is sufficient
        hall, err := s.hallRepo.GetByID(ctx, req.HallID)
        if err != nil {
            return err
        }
        if hall == nil {
            return errors.New("hall not found")
        }
        if req.ExpectedAttendees != nil && *req.ExpectedAttendees > hall.Capacity {
            return errors.New("expected attendees exceeds hall capacity")
        }

        // 4. Validate time (end_time > start_time)
        startTime, err := time.Parse("15:04:05", req.StartTime)
        if err != nil {
            return errors.New("invalid start_time format, expected HH:MM:SS")
        }
        endTime, err := time.Parse("15:04:05", req.EndTime)
        if err != nil {
            return errors.New("invalid end_time format, expected HH:MM:SS")
        }
        if !endTime.After(startTime) {
            return errors.New("end time must be strictly after start time")
        }

        // 5. Check for overlapping bookings before placing the request
        overlap, err := s.bookingRepo.CheckOverlap(ctx, req.HallID, req.EventDate, req.StartTime,
        req.EndTime)
        if err != nil {
            return err
        }
        if overlap {
            return errors.New("cannot place request: this time slot overlaps with an existing
            confirmed booking")
        }

        // 6. Build and save request
        req.RequesterID = requester.RequesterID

        return s.requestRepo.Create(ctx, req)
    }

    func (s *RequestService) GetMyRequests(ctx context.Context, userID int) ([]models.Request, error) {
        requester, err := s.userRepo.GetRequesterByUserID(ctx, userID)
        if err != nil {
            return nil, err
        }
        if requester == nil {
            return nil, errors.New("user is not a requester")
        }
    }

```

```
        return s.requestRepo.GetByRequester(ctx, requester.RequesterID)
    }
}
```

backend/internal/services/hall_service.go

```
package services

import (
    "context"
    "seminar-hall-booking-system/internal/models"
    "seminar-hall-booking-system/internal/repositories"
    "time"
)

type HallService struct {
    hallRepo *repositories.HallRepository
}

func NewHallService(hallRepo *repositories.HallRepository) *HallService {
    return &HallService{hallRepo: hallRepo}
}

func (s *HallService) GetAllHalls(ctx context.Context) ([]models.Hall, error) {
    return s.hallRepo.GetAll(ctx)
}

func (s *HallService) GetHallByID(ctx context.Context, id int) (*models.Hall, error) {
    return s.hallRepo.GetByID(ctx, id)
}

func (s *HallService) GetAvailability(ctx context.Context, hallID int, dateStr string) ([]models.Booking, error) {
    // Parse date string (YYYY-MM-DD)
    date, err := time.Parse("2006-01-02", dateStr)
    if err != nil {
        return nil, err
    }

    return s.hallRepo.GetAvailability(ctx, hallID, date)
}

func (s *HallService) GetAvailabilityForAll(ctx context.Context, dateStr string) ([]models.AvailabilitySlot, error) {
    // Parse date string (YYYY-MM-DD)
    date, err := time.Parse("2006-01-02", dateStr)
    if err != nil {
        return nil, err
    }

    return s.hallRepo.GetAvailabilityForAll(ctx, date)
}

func (s *HallService) GetAvailabilityRange(ctx context.Context, hallID int, startDateStr string, endDateStr string) ([]models.Booking, error) {
    startDate, err := time.Parse("2006-01-02", startDateStr)
    if err != nil {
        return nil, err
    }
    endDate, err := time.Parse("2006-01-02", endDateStr)
    if err != nil {
        return nil, err
    }

    return s.hallRepo.GetAvailabilityRange(ctx, hallID, startDate, endDate)
}
}
```

backend/internal/services/coordinator_service.go

```
package services

import (
    "context"
    "errors"
    "seminar-hall-booking-system/internal/models"
    "seminar-hall-booking-system/internal/repositories"
)

type CoordinatorService struct {
    requestRepo *repositories.RequestRepository
    userRepo    *repositories.UserRepository
}
```

```

        bookingRepo *repositories.BookingRepository
    }

    func NewCoordinatorService(reqRepo *repositories.RequestRepository, userRepo *repositories.UserRepository,
        bookingRepo *repositories.BookingRepository) *CoordinatorService {
        return &CoordinatorService{
            requestRepo: reqRepo,
            userRepo:    userRepo,
            bookingRepo: bookingRepo,
        }
    }

    // GetDepartmentPendingRequests gets all pending requests for the coordinator's department
    func (s *CoordinatorService) GetDepartmentPendingRequests(ctx context.Context, coordinatorID int)
    ([]models.Request, error) {
        coordinator, err := s.userRepo.GetByID(ctx, coordinatorID)
        if err != nil {
            return nil, err
        }
        if coordinator == nil || coordinator.DeptID == nil {
            return nil, errors.New("coordinator department not found")
        }

        // For a complete implementation, RequestRepository needs a GetByDepartmentAndStatus method.
        // We'll implement a workaround here by fetching all requests and filtering in memory or ideally
        updating the repo.
        // Assuming an update to RequestRepository:
        return s.requestRepo.GetByDepartmentAndStatus(ctx, *coordinator.DeptID, models.StatusPending)
    }

    // ReviewRequest allows the coordinator to approve (forward) or reject a request
    func (s *CoordinatorService) ReviewRequest(ctx context.Context, coordinatorID int, requestID int, action
    string, remarks *string) error {
        // 1. Verify coordinator
        coordinator, err := s.userRepo.GetByID(ctx, coordinatorID)
        if err != nil || coordinator == nil || coordinator.DeptID == nil {
            return errors.New("invalid coordinator")
        }

        // 2. Verify request exists and is pending
        req, err := s.requestRepo.GetByID(ctx, requestID)
        if err != nil || req == nil {
            return errors.New("request not found")
        }

        if req.DeptStatus != models.StatusPending {
            return errors.New("request is no longer pending department approval")
        }

        // In a full implementation, verify the request belongs to the coordinator's department here by
        looking up the requester's department.

        // 3. Update status
        var newStatus models.ApprovalStatus
        if action == "approve" {
            // Before forwarding, check if there's an existing overlapping booking
            overlap, err := s.bookingRepo.CheckOverlap(ctx, req.HallID, req.EventDate, req.StartTime,
            req.EndTime)
            if err != nil {
                return err
            }
            if overlap {
                return errors.New("cannot forward: this request overlaps with an existing
                confirmed booking")
            }
            newStatus = models.StatusForwarded
        } else if action == "reject" {
            newStatus = models.StatusRejected
        } else {
            return errors.New("invalid action. Must be 'approve' or 'reject'")
        }

        return s.requestRepo.UpdateDeptStatus(ctx, requestID, newStatus, coordinatorID, remarks)
    }
}

```

backend/internal/repositories/user_repository.go

package repositories

```

import (
    "context"
    "seminar-hall-booking-system/internal/models"

    "github.com/jackc/pgx/v5"
    "github.com/jackc/pgx/v5/pgxpool"
)

type UserRepository struct {
    db *pgxpool.Pool
}

func NewUserRepository(db *pgxpool.Pool) *UserRepository {
    return &UserRepository{db: db}
}

func (r *UserRepository) GetByUsername(ctx context.Context, username string) (*models.User, error) {
    query := `
        SELECT user_id, username, password_hash, full_name, email, phone, role, dept_id,
is_active, created_at, updated_at
        FROM users
        WHERE username = $1 AND is_active = true
    `

    var user models.User
    err := r.db.QueryRow(ctx, query, username).Scan(
        &user.UserID,
        &user.Username,
        &user.PasswordHash,
        &user.FullName,
        &user.Email,
        &user.Phone,
        &user.Role,
        &user.DeptID,
        &user.IsActive,
        &user.CreatedAt,
        &user.UpdatedAt,
    )

    if err != nil {
        if err == pgx.ErrNoRows {
            return nil, nil // Not found
        }
        return nil, err
    }

    return &user, nil
}

func (r *UserRepository) GetByID(ctx context.Context, id int) (*models.User, error) {
    query := `
        SELECT user_id, username, password_hash, full_name, email, phone, role, dept_id,
is_active, created_at, updated_at
        FROM users
        WHERE user_id = $1 AND is_active = true
    `

    var user models.User
    err := r.db.QueryRow(ctx, query, id).Scan(
        &user.UserID,
        &user.Username,
        &user.PasswordHash,
        &user.FullName,
        &user.Email,
        &user.Phone,
        &user.Role,
        &user.DeptID,
        &user.IsActive,
        &user.CreatedAt,
        &user.UpdatedAt,
    )

    if err != nil {
        if err == pgx.ErrNoRows {
            return nil, nil
        }
        return nil, err
    }
}

```

```

        return &user, nil
    }

    func (r *UserRepository) GetRequesterByUserID(ctx context.Context, userID int) (*models.Requester, error)
    {
        query := `
            SELECT requester_id, user_id, requester_type, class_id, club_id, created_at
            FROM requesters
            WHERE user_id = $1
        `

        var req models.Requester
        err := r.db.QueryRow(ctx, query, userID).Scan(
            &req.RequesterID,
            &req.UserID,
            &req.RequesterType,
            &req.ClassID,
            &req.ClubID,
            &req.CreatedAt,
        )

        if err != nil {
            if err == pgx.ErrNoRows {
                return nil, nil
            }
            return nil, err
        }

        return &req, nil
    }
}

```

backend/internal/repositories/request_repository.go

```

package repositories

import (
    "context"
    "seminar-hall-booking-system/internal/models"

    "github.com/jackc/pgx/v5"
    "github.com/jackc/pgx/v5/pgxpool"
)

type RequestRepository struct {
    db *pgxpool.Pool
}

func NewRequestRepository(db *pgxpool.Pool) *RequestRepository {
    return &RequestRepository{db: db}
}

// Create new request
func (r *RequestRepository) Create(ctx context.Context, req *models.Request) error {
    query := `
        INSERT INTO requests (requester_id, hall_id, event_title, event_description, event_date,
        start_time, end_time, expected_attendees, purpose)
        VALUES ($1, $2, $3, $4, $5, $6, $7, $8, $9)
        RETURNING request_id, dept_status, admin_status, requested_at
    `

    err := r.db.QueryRow(ctx, query,
        req.RequesterID,
        req.HallID,
        req.EventTitle,
        req.EventDescription,
        req.EventDate,
        req.StartTime,
        req.EndTime,
        req.ExpectedAttendees,
        req.Purpose,
    ).Scan(&req.RequestID, &req.DeptStatus, &req.AdminStatus, &req.RequestedAt)

    return err
}

// GetByID gets a specific request
func (r *RequestRepository) GetByID(ctx context.Context, id int) (*models.Request, error) {
    query := `

```

```

        SELECT request_id, requester_id, hall_id, event_title, event_description, event_date,
start_time, end_time,
        expected_attendees, purpose, dept_status, dept_approved_by, dept_approved_at,
dept_remarks,
        admin_status, admin_approved_by, admin_approved_at, admin_remarks, requested_at,
is_cancelled
        FROM requests
        WHERE request_id = $1
    `

    var req models.Request
    err := r.db.QueryRow(ctx, query, id).Scan(
        &req.RequestID,
        &req.RequesterID,
        &req.HallID,
        &req.EventTitle,
        &req.EventDescription,
        &req.EventDate,
        &req.StartTime,
        &req.EndTime,
        &req.ExpectedAttendees,
        &req.Purpose,
        &req.DeptStatus,
        &req.DeptApprovedBy,
        &req.DeptApprovedAt,
        &req.DeptRemarks,
        &req.AdminStatus,
        &req.AdminApprovedBy,
        &req.AdminApprovedAt,
        &req.AdminRemarks,
        &req.RequestedAt,
        &req.IsCancelled,
    )

    if err != nil {
        if err == pgx.ErrNoRows {
            return nil, nil // Not found
        }
        return nil, err
    }

    return &req, nil
}

// GetByRequester gets all requests for a specific requester
func (r *RequestRepository) GetByRequester(ctx context.Context, requesterID int) ([]models.Request, error) {
    query := `
        SELECT request_id, requester_id, hall_id, event_title, event_description, event_date,
start_time, end_time,
        expected_attendees, purpose, dept_status, dept_approved_by, dept_approved_at,
dept_remarks,
        admin_status, admin_approved_by, admin_approved_at, admin_remarks, requested_at,
is_cancelled
        FROM requests
        WHERE requester_id = $1
        ORDER BY requested_at DESC
    `

    rows, err := r.db.Query(ctx, query, requesterID)
    if err != nil {
        return nil, err
    }
    defer rows.Close()

    var requests []models.Request
    for rows.Next() {
        var req models.Request
        err := rows.Scan(
            &req.RequestID,
            &req.RequesterID,
            &req.HallID,
            &req.EventTitle,
            &req.EventDescription,
            &req.EventDate,
            &req.StartTime,
            &req.EndTime,
            &req.ExpectedAttendees,

```

```

        &req.Purpose,
        &req.DeptStatus,
        &req.DeptApprovedBy,
        &req.DeptApprovedAt,
        &req.DeptRemarks,
        &req.AdminStatus,
        &req.AdminApprovedBy,
        &req.AdminApprovedAt,
        &req.AdminRemarks,
        &req.RequestedAt,
        &req.IsCancelled,
    )
    if err != nil {
        return nil, err
    }
    requests = append(requests, req)
}

return requests, nil
}

// UpdateDeptStatus updates the dept status
func (r *RequestRepository) UpdateDeptStatus(ctx context.Context, reqID int, status models.ApprovalStatus,
byUserID int, remarks *string) error {
    query := `
        UPDATE requests
        SET dept_status = $1, dept_approved_by = $2, dept_approved_at = NOW(), dept_remarks = $3
        WHERE request_id = $4
    `
    _, err := r.db.Exec(ctx, query, status, byUserID, remarks, reqID)
    return err
}

// UpdateAdminStatus updates the admin status
func (r *RequestRepository) UpdateAdminStatus(ctx context.Context, reqID int, status
models.ApprovalStatus, byUserID int, remarks *string) error {
    query := `
        UPDATE requests
        SET admin_status = $1, admin_approved_by = $2, admin_approved_at = NOW(), admin_remarks =
$3
        WHERE request_id = $4
    `
    _, err := r.db.Exec(ctx, query, status, byUserID, remarks, reqID)
    return err
}

// GetByDepartmentAndStatus gets pending requests for a specific department
func (r *RequestRepository) GetByDepartmentAndStatus(ctx context.Context, deptID int, status
models.ApprovalStatus) ([]models.Request, error) {
    // A bit tricky because we have to join with requesters -> users to find the dept_id
    query := `
        SELECT r.request_id, r.requester_id, r.hall_id, r.event_title, r.event_description,
r.event_date, r.start_time, r.end_time,
r.expected_attendees, r.purpose, r.dept_status, r.dept_approved_by, r.dept_approved_at,
r.dept_remarks,
r.admin_status, r.admin_approved_by, r.admin_approved_at, r.admin_remarks, r.requested_at,
r.is_cancelled
        FROM requests r
        JOIN requesters req ON r.requester_id = req.requester_id
        JOIN users u ON req.user_id = u.user_id
        WHERE u.dept_id = $1 AND r.dept_status = $2
        ORDER BY r.requested_at ASC
    `

    rows, err := r.db.Query(ctx, query, deptID, status)
    if err != nil {
        return nil, err
    }
    defer rows.Close()

    var requests []models.Request
    for rows.Next() {
        var req models.Request
        err := rows.Scan(
            &req.RequestID,
            &req.RequesterID,
            &req.HallID,
            &req.EventTitle,

```



```

        &req.EventDescription,
        &req.EventDate,
        &req.StartTime,
        &req.EndTime,
        &req.ExpectedAttendees,
        &req.Purpose,
        &req.DeptStatus,
        &req.DeptApprovedBy,
        &req.DeptApprovedAt,
        &req.DeptRemarks,
        &req.AdminStatus,
        &req.AdminApprovedBy,
        &req.AdminApprovedAt,
        &req.AdminRemarks,
        &req.RequestedAt,
        &req.IsCancelled,
    )
    if err != nil {
        return nil, err
    }
    requests = append(requests, req)
}
return requests, nil
}

// GetByAdminStatus gets requests that have a certain admin status (and dept status)
func (r *RequestRepository) GetByAdminStatus(ctx context.Context, adminStatus models.ApprovalStatus,
deptStatus models.ApprovalStatus) ([]models.Request, error) {
    query := `
        SELECT request_id, requester_id, hall_id, event_title, event_description, event_date,
start_time, end_time,
        expected_attendees, purpose, dept_status, dept_approved_by, dept_approved_at,
dept_remarks,
        admin_status, admin_approved_by, admin_approved_at, admin_remarks, requested_at,
is_cancelled
        FROM requests
        WHERE admin_status = $1 AND dept_status = $2
        ORDER BY requested_at ASC
    `

    rows, err := r.db.Query(ctx, query, adminStatus, deptStatus)
    if err != nil {
        return nil, err
    }
    defer rows.Close()

    var requests []models.Request
    for rows.Next() {
        var req models.Request
        err := rows.Scan(
            &req.RequestID,
            &req.RequesterID,
            &req.HallID,
            &req.EventTitle,
            &req.EventDescription,
            &req.EventDate,
            &req.StartTime,
            &req.EndTime,
            &req.ExpectedAttendees,
            &req.Purpose,
            &req.DeptStatus,
            &req.DeptApprovedBy,
            &req.DeptApprovedAt,
            &req.DeptRemarks,
            &req.AdminStatus,
            &req.AdminApprovedBy,
            &req.AdminApprovedAt,
            &req.AdminRemarks,
            &req.RequestedAt,
            &req.IsCancelled,
        )
        if err != nil {
            return nil, err
        }
        requests = append(requests, req)
    }
    return requests, nil
}

```

```
}
```

backend/internal/repositories/booking_repository.go

```
package repositories
```

```
import (
    "context"
    "seminar-hall-booking-system/internal/models"
    "time"

    "github.com/jackc/pgx/v5/pgxpool"
)

type BookingRepository struct {
    db *pgxpool.Pool
}

func NewBookingRepository(db *pgxpool.Pool) *BookingRepository {
    return &BookingRepository{db: db}
}

// Create inserts a new booking (trigger actively checks for overlap)
func (r *BookingRepository) Create(ctx context.Context, b *models.Booking) error {
    query := `
        INSERT INTO bookings (request_id, hall_id, requester_id, event_title, event_date,
start_time, end_time)
        VALUES ($1, $2, $3, $4, $5, $6, $7)
        RETURNING booking_id, status, created_at
    `

    err := r.db.QueryRow(ctx, query,
        b.RequestID,
        b.HallID,
        b.RequesterID,
        b.EventTitle,
        b.EventDate,
        b.StartTime,
        b.EndTime,
    ).Scan(&b.BookingID, &b.Status, &b.CreatedAt)

    return err
}

// GetAll returns all bookings
func (r *BookingRepository) GetAll(ctx context.Context) ([]models.Booking, error) {
    query := `
        SELECT booking_id, request_id, hall_id, requester_id, event_title, event_date, start_time,
end_time, status, created_at, completed_at
        FROM bookings
        ORDER BY event_date ASC, start_time ASC
    `

    rows, err := r.db.Query(ctx, query)
    if err != nil {
        return nil, err
    }
    defer rows.Close()

    var bookings []models.Booking
    for rows.Next() {
        var b models.Booking
        err := rows.Scan(
            &b.BookingID,
            &b.RequestID,
            &b.HallID,
            &b.RequesterID,
            &b.EventTitle,
            &b.EventDate,
            &b.StartTime,
            &b.EndTime,
            &b.Status,
            &b.CreatedAt,
            &b.CompletedAt,
        )
        if err != nil {
            return nil, err
        }
    }
}
```

```

        bookings = append(bookings, b)
    }

    return bookings, nil
}

// GetByRequester returns all bookings for a specific requester
func (r *BookingRepository) GetByRequester(ctx context.Context, requesterID int) ([]models.Booking, error) {
    query := `
        SELECT booking_id, request_id, hall_id, requester_id, event_title, event_date, start_time,
        end_time, status, created_at, completed_at
        FROM bookings
        WHERE requester_id = $1
        ORDER BY event_date DESC
    `

    rows, err := r.db.Query(ctx, query, requesterID)
    if err != nil {
        return nil, err
    }
    defer rows.Close()

    var bookings []models.Booking
    for rows.Next() {
        var b models.Booking
        err := rows.Scan(
            &b.BookingID,
            &b.RequestID,
            &b.HallID,
            &b.RequesterID,
            &b.EventTitle,
            &b.EventDate,
            &b.StartTime,
            &b.EndTime,
            &b.Status,
            &b.CreatedAt,
            &b.CompletedAt,
        )
        if err != nil {
            return nil, err
        }
        bookings = append(bookings, b)
    }

    return bookings, nil
}

// UpdateStatus allows changing a booking's status
func (r *BookingRepository) UpdateStatus(ctx context.Context, bookingID int, status models.BookingStatus) error {
    query := `UPDATE bookings SET status = $1 WHERE booking_id = $2`
    _, err := r.db.Exec(ctx, query, status, bookingID)
    return err
}

// CheckOverlap returns true if there's an existing active booking for the same hall and time
func (r *BookingRepository) CheckOverlap(ctx context.Context, hallID int, date time.Time, startTime string, endTime string) (bool, error) {
    query := `
        SELECT COUNT(*)
        FROM bookings
        WHERE hall_id = $1
        AND event_date = $2
        AND status != 'cancelled'
        AND (
            (start_time < $4 AND end_time > $3)
        )
    `

    var count int
    // We use QueryRow to get the count of overlapping bookings
    err := r.db.QueryRow(ctx, query, hallID, date, startTime, endTime).Scan(&count)
    if err != nil {
        return false, err
    }
    return count > 0, nil
}

```

```
package repositories
```

```
import (
    "context"
    "seminar-hall-booking-system/internal/models"
    "time"

    "github.com/jackc/pgx/v5"
    "github.com/jackc/pgx/v5/pgxpool"
)

type HallRepository struct {
    db *pgxpool.Pool
}

func NewHallRepository(db *pgxpool.Pool) *HallRepository {
    return &HallRepository{db: db}
}

func (r *HallRepository) GetAll(ctx context.Context) ([]models.Hall, error) {
    query := `
        SELECT hall_id, hall_name, capacity, location, facilities, is_active
        FROM halls
        WHERE is_active = true
    `

    rows, err := r.db.Query(ctx, query)
    if err != nil {
        return nil, err
    }
    defer rows.Close()

    halls := []models.Hall{}
    for rows.Next() {
        var hall models.Hall
        err := rows.Scan(
            &hall.HallID,
            &hall.HallName,
            &hall.Capacity,
            &hall.Location,
            &hall.Facilities,
            &hall.IsActive,
        )
        if err != nil {
            return nil, err
        }
        halls = append(halls, hall)
    }

    return halls, nil
}

func (r *HallRepository) GetByID(ctx context.Context, id int) (*models.Hall, error) {
    query := `
        SELECT hall_id, hall_name, capacity, location, facilities, is_active
        FROM halls
        WHERE hall_id = $1 AND is_active = true
    `

    var hall models.Hall
    err := r.db.QueryRow(ctx, query, id).Scan(
        &hall.HallID,
        &hall.HallName,
        &hall.Capacity,
        &hall.Location,
        &hall.Facilities,
        &hall.IsActive,
    )

    if err != nil {
        if err == pgx.ErrNoRows {
            return nil, nil
        }
        return nil, err
    }

    return &hall, nil
}
```

```

}

// GetAvailability gets all confirmed bookings for a specific hall on a specific date
func (r *HallRepository) GetAvailability(ctx context.Context, hallID int, date time.Time)
([]models.Booking, error) {
    query := `
        SELECT booking_id, request_id, hall_id, requester_id, event_title, event_date, start_time,
end_time, status, created_at, completed_at
        FROM bookings
        WHERE hall_id = $1 AND event_date = $2 AND status != 'cancelled'
        ORDER BY start_time ASC
    `

    rows, err := r.db.Query(ctx, query, hallID, date.Format("2006-01-02"))
    if err != nil {
        return nil, err
    }
    defer rows.Close()

    bookings := []models.Booking{}
    for rows.Next() {
        var b models.Booking
        err := rows.Scan(
            &b.BookingID,
            &b.RequestID,
            &b.HallID,
            &b.RequesterID,
            &b.EventTitle,
            &b.EventDate,
            &b.StartTime,
            &b.EndTime,
            &b.Status,
            &b.CreatedAt,
            &b.CompletedAt,
        )
        if err != nil {
            return nil, err
        }
        bookings = append(bookings, b)
    }

    return bookings, nil
}

// GetAvailabilityRange gets all confirmed bookings for a specific hall between two dates
func (r *HallRepository) GetAvailabilityRange(ctx context.Context, hallID int, startDate time.Time,
endDate time.Time) ([]models.Booking, error) {
    query := `
        SELECT booking_id, request_id, hall_id, requester_id, event_title, event_date, start_time,
end_time, status, created_at, completed_at
        FROM bookings
        WHERE hall_id = $1 AND event_date BETWEEN $2 AND $3 AND status != 'cancelled'
        ORDER BY event_date ASC, start_time ASC
    `

    rows, err := r.db.Query(ctx, query, hallID, startDate.Format("2006-01-02"), endDate.Format("2006-
01-02"))
    if err != nil {
        return nil, err
    }
    defer rows.Close()

    bookings := []models.Booking{}
    for rows.Next() {
        var b models.Booking
        err := rows.Scan(
            &b.BookingID, &b.RequestID, &b.HallID, &b.RequesterID,
            &b.EventTitle, &b.EventDate, &b.StartTime, &b.EndTime,
            &b.Status, &b.CreatedAt, &b.CompletedAt,
        )
        if err != nil {
            return nil, err
        }
        bookings = append(bookings, b)
    }

    return bookings, nil
}

```

```

// GetAvailabilityForAll gets confirmed bookings for ALL active halls on a specific date
func (r *HallRepository) GetAvailabilityForAll(ctx context.Context, date time.Time)
([]models.AvailabilitySlot, error) {
    // 1. Get all active halls
    halls, err := r.GetAll(ctx)
    if err != nil {
        return nil, err
    }

    // 2. Get all bookings for that date
    query := `
        SELECT booking_id, request_id, hall_id, requester_id, event_title, event_date, start_time,
        end_time, status, created_at, completed_at
        FROM bookings
        WHERE event_date = $1 AND status != 'cancelled'
        ORDER BY start_time ASC
    `

    rows, err := r.db.Query(ctx, query, date.Format("2006-01-02"))
    if err != nil {
        return nil, err
    }
    defer rows.Close()

    // 3. Group bookings by hall_id
    bookingsByHall := make(map[int][]models.Booking)
    for rows.Next() {
        var b models.Booking
        err := rows.Scan(
            &b.BookingID, &b.RequestID, &b.HallID, &b.RequesterID,
            &b.EventTitle, &b.EventDate, &b.StartTime, &b.EndTime,
            &b.Status, &b.CreatedAt, &b.CompletedAt,
        )
        if err != nil {
            return nil, err
        }
        bookingsByHall[b.HallID] = append(bookingsByHall[b.HallID], b)
    }

    // 4. Map halls to availability slots
    var slots []models.AvailabilitySlot
    for _, h := range halls {
        bookings := bookingsByHall[h.HallID]
        if bookings == nil {
            bookings = []models.Booking{}
        }
        slots = append(slots, models.AvailabilitySlot{
            HallID:    h.HallID,
            HallName:  h.HallName,
            Bookings:  bookings,
        })
    }

    return slots, nil
}

```

Frontend source (Next.js / TypeScript)

Seminar Hall Booking System – representative Next.js/TS sources (full repo on GitHub)

frontend/app/layout.tsx

```
import type { Metadata } from "next";
import { Inter } from "next/font/google";
import "../globals.css";
import { Toaster } from "sonner";
import { AuthProvider } from "@/lib/auth-context";

const inter = Inter({ subsets: ["latin"] });

export const metadata: Metadata = {
  title: "Seminar Hall Booking System",
  description: "IGNOU BCA BCSP-064 - Seminar Hall Booking System",
};

export default function RootLayout({
  children,
}: Readonly<{
  children: React.ReactNode;
}>) {
  return (
    <html lang="en">
      <body className={inter.className}>
        <AuthProvider>
          {children}
          <Toaster position="bottom-right" />
        </AuthProvider>
      </body>
    </html>
  );
}
```

frontend/app/globals.css

```
@import "tailwindcss";

:root {
  --background: #ffffff;
  --foreground: #1e293b;
  --primary: #2563eb;
  --primary-dark: #1e40af;
  --secondary: #64748b;
}

@theme inline {
  --color-background: var(--background);
  --color-foreground: var(--foreground);
  --color-primary: var(--primary);
  --color-primary-dark: var(--primary-dark);
  --color-secondary: var(--secondary);
  --font-sans: var(--font-geist-sans);
  --font-mono: var(--font-geist-mono);
}

body {
  background: var(--background);
  color: var(--foreground);
  font-family: Arial, Helvetica, sans-serif;
}

/* College-style blue/white theme */
.bg-primary {
  background-color: var(--primary);
}

.bg-primary-dark {
  background-color: var(--primary-dark);
}

.text-primary {
  color: var(--primary);
}
```

```

'use client';

import { useState, useEffect } from 'react';
import { useRouter } from 'next/navigation';
import Link from 'next/link';
import { authApi } from '@lib/services';
import { useAuth } from '@lib/auth-context';
import { toast } from 'sonner';

export default function LoginPage() {
  const router = useRouter();
  const { user, loading, refresh } = useAuth();
  const [formData, setFormData] = useState({ username: '', password: '' });
  const [submitting, setSubmitting] = useState(false);

  // If already logged in, redirect to dashboard
  useEffect(() => {
    if (!loading && user) {
      router.push('/dashboard');
    }
  }, [user, loading, router]);

  const handleSubmit = async (e: React.FormEvent) => {
    e.preventDefault();
    setSubmitting(true);
    try {
      await authApi.login(formData.username, formData.password);
      // Refresh AuthContext so user state is populated BEFORE navigating
      await refresh();
      toast.success('Login successful!');
      router.push('/dashboard');
    } catch (error: any) {
      toast.error(error.response?.data?.error || 'Login failed');
    } finally {
      setSubmitting(false);
    }
  };

  return (
    <div className="min-h-screen flex items-center justify-center bg-gradient-to-br from-blue-50 to-white">
      <div className="bg-white p-8 rounded-lg shadow-lg w-full max-w-md">
        <h1 className="text-3xl font-bold text-blue-900 mb-6 text-center">
          Login
        </h1>
        <form onSubmit={handleSubmit} className="space-y-4">
          <div>
            <label htmlFor="username" className="block text-sm font-medium text-gray-700 mb-1">
              Username
            </label>
            <input
              type="text"
              id="username"
              required
              value={formData.username}
              onChange={(e) => setFormData({ ...formData, username: e.target.value })}
              className="w-full px-4 py-2 border border-gray-300 rounded-lg focus:ring-2 focus:ring-blue-500 focus:border-transparent"
            />
          </div>
          <div>
            <label htmlFor="password" className="block text-sm font-medium text-gray-700 mb-1">
              Password
            </label>
            <input
              type="password"
              id="password"
              required
              value={formData.password}
              onChange={(e) => setFormData({ ...formData, password: e.target.value })}
              className="w-full px-4 py-2 border border-gray-300 rounded-lg focus:ring-2 focus:ring-blue-500 focus:border-transparent"
            />
          </div>
          <button
            type="submit"
            disabled={submitting}

```



```

        className="w-full bg-blue-600 text-white py-2 rounded-lg hover:bg-blue-700 transition-colors
disabled:opacity-50 disabled:cursor-not-allowed"
      >
        {submitting ? 'Logging in...' : 'Login'}
      </button>
    </form>
    <p className="mt-4 text-center text-sm text-gray-600">
      Don't have an account?{' '}
      <Link href="/register" className="text-blue-600 hover:underline">
        Contact Admin
      </Link>
    </p>
    <div className="mt-6 text-center">
      <Link href="/" className="text-gray-500 hover:text-blue-600 flex items-center justify-center
gap-2 group transition-colors">
        <span className="group-hover:-translate-x-1 transition-transform"><</span>
        Back to Home
      </Link>
    </div>
  </div>
</div>
);
}

```

frontend/app/dashboard/page.tsx

```

'use client';

import { useEffect, useState } from 'react';
import { useRouter } from 'next/navigation';
import { useAuth } from '@lib/auth-context';
import { api } from '@lib/api';
import { AvailabilitySlot } from '@lib/types';
import { toast } from 'sonner';
import Link from 'next/link';

export default function DashboardPage() {
  const { user, loading, logout } = useAuth();
  const router = useRouter();

  // Availability state
  const [selectedDate, setSelectedDate] = useState(new Date().toISOString().split('T')[0]);
  const [availability, setAvailability] = useState<AvailabilitySlot[]>([]);
  const [checking, setChecking] = useState(false);

  useEffect(() => {
    if (!loading && !user) {
      router.replace('/login');
    }
  }, [user, loading, router]);

  const fetchAvailability = async () => {
    setChecking(true);
    try {
      const response = await api.get(`/availability?date=${selectedDate}`);
      setAvailability(response.data);
    } catch (error) {
      toast.error('Failed to fetch availability');
    } finally {
      setChecking(false);
    }
  };

  // Always show spinner while loading – never redirect prematurely
  if (loading) {
    return (
      <div className="min-h-screen flex items-center justify-center bg-gray-50">
        <div className="text-center">
          <div className="animate-spin rounded-full h-12 w-12 border-b-2 border-blue-600 mx-auto mb-4">
            <p className="text-gray-600">Loading...</p>
          </div>
        </div>
      </div>
    );
  }

  if (!user) return null;

```

```

const commonLinks = [
  { label: '🏠 View Halls', href: '/halls' },
];

const roleLinks: Record<string, { label: string; href: string }[]> = {
  admin: [
    { label: '📄 Pending Requests', href: '/admin/pending' },
    { label: '📅 All Bookings', href: '/admin/bookings' },
    { label: '🏠 Manage Halls', href: '/admin/halls' },
    { label: '🏢 Manage Departments', href: '/admin/departments' },
    { label: '🎓 Manage Classes', href: '/admin/classes' },
    { label: '🏆 Manage Clubs', href: '/admin/clubs' },
    { label: '👤 Manage Users', href: '/admin/users' },
    { label: '📊 Reports', href: '/admin/reports' },
  ],
  dept_coordinator: [
    { label: '📄 Pending Requests', href: '/coordinator/pending' },
    { label: '🎓 Manage Classes', href: '/coordinator/classes' },
    { label: '👤 View Faculty', href: '/coordinator/faculty' },
  ],
  requester: [
    { label: '✚ New Request', href: '/requester/request-new' },
    { label: '📄 My Requests', href: '/requester/my-requests' },
  ],
  faculty: [],
};

const links = [...commonLinks, ...(roleLinks[user.role] ?? [])];

const roleLabel: Record<string, string> = {
  admin: 'Administrator',
  dept_coordinator: 'Department Coordinator',
  requester: 'Requester',
  faculty: 'Faculty',
};

return (
  <div className="min-h-screen bg-gray-50">
    {/* Header */}
    <header className="bg-blue-900 text-white px-6 py-4 flex items-center justify-between shadow-md">
      <div>
        <h1 className="text-xl font-bold">Seminar Hall Booking System</h1>
        <p className="text-blue-200 text-sm">{roleLabel[user.role]}</p>
      </div>
      <div className="flex items-center gap-4">
        <span className="text-sm text-blue-200">Welcome, {user.full_name}</span>
        <button
          onClick={logout}
          className="bg-blue-700 hover:bg-blue-600 text-white text-sm px-4 py-2 rounded-lg transition-
colors"
        >
          Logout
        </button>
      </div>
    </header>

    <div className="max-w-4xl mx-auto px-4 py-8">
      <div className="flex justify-between items-center mb-6">
        <h2 className="text-2xl font-bold text-gray-800">Dashboard</h2>
      </div>

      <div className="space-y-8">
        {/* Main Links - 3 columns on desktop for better spacing */}
        <div className="grid grid-cols-1 sm:grid-cols-2 lg:grid-cols-3 gap-4">
          {links.map((link) => (
            <a
              key={link.href}
              href={link.href}
              className="bg-white rounded-xl shadow-sm border border-gray-100 p-5 hover:shadow-md
hover:border-blue-300 transition-all group"
            >
              <p className="text-lg font-semibold text-gray-800 group-hover:text-blue-700 transition-
colors">
                {link.label}
              </p>
            </a>
          ))}
        </div>
      </div>
    </div>
  </div>

```

```

    /* Availability Checker - Full Width Row */
    <div className="bg-white p-6 rounded-xl shadow-sm border border-gray-100">
      <h3 className="text-xl font-bold text-gray-800 mb-6 flex items-center gap-2">
        <span>📅</span> Check Hall Availability
      </h3>
      <div className="flex flex-col md:flex-row gap-4 mb-6">
        <input
          type="date"
          value={selectedDate}
          onChange={(e) => setSelectedDate(e.target.value)}
          className="flex-1 px-4 py-3 border border-gray-300 rounded-lg focus:ring-2 focus:ring-
blue-500 text-base"
        />
        <button
          onClick={fetchAvailability}
          disabled={checking}
          className="bg-blue-600 text-white px-8 py-3 rounded-lg hover:bg-blue-700 transition-colors
disabled:opacity-50 font-bold whitespace-nowrap"
        >
          {checking ? 'Checking...' : 'Check Availability'}
        </button>
      </div>

      {availability.length > 0 && (
        <div className="grid grid-cols-1 sm:grid-cols-2 lg:grid-cols-3 gap-3 pt-4 border-t border-
gray-100">
          {availability.map((slot) => (
            <div key={slot.hall_id} className="p-4 bg-blue-50 rounded-lg border border-blue-100 flex
flex-col justify-between">
              <div>
                <p className="font-bold text-blue-900">{slot.hall_name}</p>
                <p className="text-xs text-gray-500 mb-3">
                  {(slot.bookings ?? []).length} booking(s) scheduled
                </p>
              </div>
              <Link
                href={` /halls/${slot.hall_id}/calendar`}
                className="text-xs text-blue-600 hover:text-blue-800 font-bold uppercase tracking-
widest text-right mt-auto"
              >
                View Calendar →
              </Link>
            </div>
          )))}
        </div>
      )}

      {availability.length === 0 && !checking && (
        <p className="text-sm text-gray-400 italic text-center py-6 bg-gray-50 rounded-lg border
border-dashed border-gray-200">
          Pick a date above to see which halls are booked or free.
        </p>
      )}
    </div>

    /* User Profile Info */
    <div className="bg-white rounded-xl shadow-sm border border-gray-100 p-6">
      <h3 className="text-lg font-semibold text-gray-700 mb-4 pb-2 border-b border-gray-50">Your
Profile</h3>
      <div className="grid grid-cols-1 sm:grid-cols-2 gap-y-4 gap-x-8 text-sm">
        <div className="flex flex-col">
          <span className="text-gray-400 text-xs font-medium uppercase tracking-wider mb-0.5">Full
Name</span>
          <span className="text-gray-800 font-semibold">{user.full_name}</span>
        </div>
        <div className="flex flex-col">
          <span className="text-gray-400 text-xs font-medium uppercase tracking-wider mb-
0.5">Username</span>
          <span className="text-gray-800 font-semibold">{user.username}</span>
        </div>
        <div className="flex flex-col">
          <span className="text-gray-400 text-xs font-medium uppercase tracking-wider mb-0.5">Email
Address</span>
          <span className="text-gray-800 font-semibold">{user.email ?? 'Not provided'}</span>
        </div>
        <div className="flex flex-col">
          <span className="text-gray-400 text-xs font-medium uppercase tracking-wider mb-

```

```

0.5">Account Role</span>
      <span className="text-blue-700 font-bold">{roleLabel[user.role]}</span>
    </div>
  </div>
</div>
</div>
</div>
</div>
</div>
);
}

```

frontend/app/halls/page.tsx

```

'use client';

import { useEffect, useState } from 'react';
import Link from 'next/link';
import { useRouter } from 'next/navigation';
import { api } from '@lib/api';
import { Hall } from '@lib/types';
import { toast } from 'sonner';

export default function HallsPage() {
  const router = useRouter();
  const [halls, setHalls] = useState<Hall[]>([]);
  const [loading, setLoading] = useState(true);

  useEffect(() => {
    fetchHalls();
  }, []);

  const fetchHalls = async () => {
    try {
      const response = await api.get('/halls');
      setHalls(response.data);
    } catch (error) {
      toast.error('Failed to fetch halls');
    } finally {
      setLoading(false);
    }
  };

  if (loading) {
    return (
      <div className="min-h-screen flex items-center justify-center">
        <div className="text-xl">Loading...</div>
      </div>
    );
  }

  return (
    <div className="min-h-screen bg-gradient-to-br from-blue-50 to-white">
      <div className="container mx-auto px-4 py-8">
        <div className="flex justify-between items-center mb-8">
          <h1 className="text-4xl font-bold text-blue-900">Seminar Halls</h1>
          <button
            onClick={() => router.back()}
            className="text-blue-600 hover:underline font-medium"
          >
            ← Back
          </button>
        </div>
        <div className="grid md:grid-cols-2 lg:grid-cols-3 gap-6">
          {halls.map((hall) => (
            <div
              key={hall.hall_id}
              className="bg-white p-6 rounded-lg shadow-md hover:shadow-lg transition-shadow"
            >
              <h2 className="text-2xl font-semibold text-blue-900 mb-2">
                {hall.hall_name}
              </h2>
              <p className="text-gray-600 mb-4">
                <strong>Capacity:</strong> {hall.capacity} people
              </p>
              {hall.location && (
                <p className="text-gray-600 mb-2">
                  <strong>Location:</strong> {hall.location}
                </p>
              )}
            </div>
          ))}
        </div>
      </div>
    </div>
  );
}

```

```

    ))
    <div className="flex flex-wrap gap-1 mb-4">
      {Object.entries(hall.facilities || {}).map(([f, v]) => v && (
        <span key={f} className="text-[10px] bg-blue-50 text-blue-700 px-1.5 py-0.5 rounded
border border-blue-100 uppercase">
          {f.replace('_', ' ')}
        </span>
      ))}
    </div>
    <Link
      href={` /halls/${hall.hall_id}/calendar`}
      className="text-blue-600 hover:underline inline-block font-medium"
    >
      View Availability →
    </Link>
  </div>
  ))}
</div>
</div>
</div>
);
}

```

frontend/app/halls/[id]/calendar/page.tsx

```

'use client';

import { useState, useEffect } from 'react';
import { useParams, useRouter } from 'next/navigation';
import Link from 'next/link';
import { Calendar, momentLocalizer, View } from 'react-big-calendar';
import moment from 'moment';
import 'react-big-calendar/lib/css/react-big-calendar.css';
import { api } from '@lib/api';
import { Booking, Hall } from '@lib/types';
import { formatTime } from '@lib/utils';
import { toast } from 'sonner';

const localizer = momentLocalizer(moment);

export default function HallCalendarPage() {
  const params = useParams();
  const router = useRouter();
  const hallId = params.id as string;
  const [hall, setHall] = useState<Hall | null>(null);
  const [bookings, setBookings] = useState<Booking[]>([]);
  const [loading, setLoading] = useState(true);
  const [selectedDate, setSelectedDate] = useState(new Date());
  const [view, setView] = useState<View>('day');

  useEffect(() => {
    fetchHall();
  }, [hallId]);

  useEffect(() => {
    fetchBookings();
  }, [hallId, selectedDate]);

  const fetchHall = async () => {
    if (!hallId) return;
    try {
      const response = await api.get(`/halls/${hallId}`);
      setHall(response.data);
    } catch (error: any) {
      toast.error('Failed to fetch hall details');
    }
  };

  const fetchBookings = async () => {
    if (!hallId) return;
    try {
      // Fetch for the whole month surrounding selectedDate to be safe regardless of view
      const startOfMonth = moment(selectedDate).startOf('month').format('YYYY-MM-DD');
      const endOfMonth = moment(selectedDate).endOf('month').format('YYYY-MM-DD');

      const response = await api.get(`/availability?
start_date=${startOfMonth}&end_date=${endOfMonth}&hall_id=${hallId}`);
      setBookings(response.data || []);
    }
  };

```

```

    } catch (error) {
      toast.error('Failed to fetch bookings');
    } finally {
      setLoading(false);
    }
  }
};

const events = (bookings || []).map((booking) => {
  const datePart = booking.event_date.split('T')[0];
  return {
    title: booking.event_title,
    start: moment(`${datePart} ${booking.start_time}`).toDate(),
    end: moment(`${datePart} ${booking.end_time}`).toDate(),
    resource: booking,
  };
});

if (loading) {
  return (
    <div className="min-h-screen flex items-center justify-center">
      <div className="text-xl">Loading...</div>
    </div>
  );
}

return (
  <div className="min-h-screen bg-gradient-to-br from-blue-50 to-white">
    <div className="container mx-auto px-4 py-8">
      <div className="flex items-center justify-between mb-6">
        <div>
          <h1 className="text-3xl font-bold text-blue-900">
            {hall?.hall_name || 'Hall Calendar'}
          </h1>
          {hall && (
            <p className="text-gray-600 mt-1">
              Capacity: {hall.capacity} | {hall.location}
            </p>
          )}
        </div>
        <button
          onClick={() => router.back()}
          className="text-blue-600 hover:underline flex items-center gap-1 font-medium"
        >
          ← Back
        </button>
      </div>

      <div className="bg-white p-4 rounded-lg shadow-md mb-6">
        <label className="block text-sm font-medium text-gray-700 mb-2">
          Select Date
        </label>
        <input
          type="date"
          value={moment(selectedDate).format('YYYY-MM-DD')}
          onChange={(e) => setSelectedDate(moment(e.target.value).toDate())}
          className="px-4 py-2 border border-gray-300 rounded-lg focus:ring-2 focus:ring-blue-500 focus:border-transparent"
        />
      </div>

      <div className="bg-white p-6 rounded-lg shadow-md" style={{ height: '600px' }}>
        <Calendar
          localizer={localizer}
          events={events}
          startAccessor="start"
          endAccessor="end"
          style={{ height: '100%' }}
          view={view}
          onView={(newView) => setView(newView)}
          views={['day', 'week', 'month']}
          date={selectedDate}
          onNavigate={(date) => setSelectedDate(date)}
        />
      </div>

      {(bookings || []).length > 0 && view === 'day' && (
        <div className="mt-6 bg-white p-6 rounded-lg shadow-md">
          <h2 className="text-xl font-bold text-blue-900 mb-4">Bookings for

```

```

{selectedDate.toLocaleDateString()}</h2>
    <div className="space-y-2">
      {(bookings || []).filter(b => b.event_date.split('T')[0] ===
moment(selectedDate).format('YYYY-MM-DD')).map((booking) => (
        <div key={booking.booking_id} className="p-3 bg-blue-50 rounded">
          <p className="font-semibold">{booking.event_title}</p>
          <p className="text-sm text-gray-600">
            {formatTime(booking.start_time)} - {formatTime(booking.end_time)}
          </p>
        </div>
      ))}
    </div>
  </div>
)}
</div>
);
}

```

frontend/app/requester/request-new/page.tsx

```

'use client';

import { useEffect, useState } from 'react';
import { useRouter } from 'next/navigation';
import { useAuth } from '@lib/auth-context';
import { hallsApi, requestsApi } from '@lib/services';
import { Hall } from '@lib/types';
import { toast } from 'sonner';

export default function NewRequestPage() {
  const { user, loading } = useAuth();
  const router = useRouter();
  const [halls, setHalls] = useState<Hall[]>([]);
  const [submitting, setSubmitting] = useState(false);

  const [form, setForm] = useState({
    hall_id: 0,
    event_title: '',
    event_description: '',
    event_date: '',
    start_time: '',
    end_time: '',
    expected_attendees: '',
    purpose: '',
  });

  useEffect(() => {
    if (!loading && !user) router.push('/login');
    if (!loading && user && user.role !== 'requester') router.push('/dashboard');
  }, [user, loading, router]);

  useEffect(() => {
    hallsApi.getAll().then((res) => setHalls(res.data)).catch(() => toast.error('Failed to load halls'));
  }, []);

  const handleSubmit = async (e: React.FormEvent) => {
    e.preventDefault();
    if (!form.hall_id) { toast.error('Please select a hall'); return; }

    setSubmitting(true);
    try {
      await requestsApi.create({
        hall_id: form.hall_id,
        event_title: form.event_title,
        event_description: form.event_description || undefined,
        event_date: form.event_date,
        start_time: form.start_time,
        end_time: form.end_time,
        expected_attendees: form.expected_attendees ? parseInt(form.expected_attendees) : undefined,
        purpose: form.purpose || undefined,
      });
      toast.success('Request submitted successfully!');
      router.push('/requester/my-requests');
    } catch (err: any) {
      toast.error(err.response?.data?.error || 'Failed to submit request');
    } finally {
      setSubmitting(false);
    }
  };
}

```

```

    }
  };

  if (loading) return <div className="min-h-screen flex items-center justify-center"><div
className="animate-spin rounded-full h-12 w-12 border-b-2 border-blue-600"></div></div>;

  return (
    <div className="min-h-screen bg-gray-50">
      <header className="bg-blue-900 text-white px-6 py-4 flex items-center justify-between">
        <h1 className="text-xl font-bold">New Booking Request</h1>
        <button onClick={() => router.push('/dashboard')} className="bg-blue-800 hover:bg-blue-700 px-4
py-2 rounded-lg text-sm">Dashboard</button>
      </header>

      <div className="max-w-2xl mx-auto px-4 py-8">
        <form onSubmit={handleSubmit} className="bg-white rounded-xl shadow-sm border border-gray-100 p-6
space-y-5">
          <div>
            <label className="block text-sm font-medium text-gray-700 mb-1">Seminar Hall *</label>
            <select
              required
              className="w-full border border-gray-300 rounded-lg px-3 py-2 focus:ring-2 focus:ring-blue-
500"
              value={form.hall_id}
              onChange={(e) => setForm({ ...form, hall_id: parseInt(e.target.value) })}>
              <option value={0}>Select a hall...</option>
              {halls.map((h) => (
                <option key={h.hall_id} value={h.hall_id}>{h.hall_name} (Capacity: {h.capacity})</option>
              ))}
            </select>
          </div>

          <div>
            <label className="block text-sm font-medium text-gray-700 mb-1">Event Title *</label>
            <input required type="text" className="w-full border border-gray-300 rounded-lg px-3 py-2
focus:ring-2 focus:ring-blue-500"
              value={form.event_title} onChange={(e) => setForm({ ...form, event_title: e.target.value })}>
          </div>

          <div>
            <label className="block text-sm font-medium text-gray-700 mb-1">Event Date *</label>
            <input required type="date" className="w-full border border-gray-300 rounded-lg px-3 py-2
focus:ring-2 focus:ring-blue-500"
              value={form.event_date} onChange={(e) => setForm({ ...form, event_date: e.target.value })}>
          </div>

          <div className="grid grid-cols-2 gap-4">
            <div>
              <label className="block text-sm font-medium text-gray-700 mb-1">Start Time *</label>
              <input required type="time" className="w-full border border-gray-300 rounded-lg px-3 py-2
focus:ring-2 focus:ring-blue-500"
                value={form.start_time} onChange={(e) => setForm({ ...form, start_time: e.target.value })}>
            </div>
            <div>
              <label className="block text-sm font-medium text-gray-700 mb-1">End Time *</label>
              <input required type="time" className="w-full border border-gray-300 rounded-lg px-3 py-2
focus:ring-2 focus:ring-blue-500"
                value={form.end_time} onChange={(e) => setForm({ ...form, end_time: e.target.value })}>
            </div>
          </div>

          <div>
            <label className="block text-sm font-medium text-gray-700 mb-1">Expected Attendees</label>
            <input type="number" min={1} className="w-full border border-gray-300 rounded-lg px-3 py-2
focus:ring-2 focus:ring-blue-500"
              value={form.expected_attendees} onChange={(e) => setForm({ ...form, expected_attendees:
e.target.value })}>
          </div>

          <div>
            <label className="block text-sm font-medium text-gray-700 mb-1">Purpose</label>
            <input type="text" className="w-full border border-gray-300 rounded-lg px-3 py-2 focus:ring-2
focus:ring-blue-500"
              value={form.purpose} onChange={(e) => setForm({ ...form, purpose: e.target.value })}>
          </div>
        </form>
      </div>
    </div>
  );

```



```

    </div>

    <div>
      <label className="block text-sm font-medium text-gray-700 mb-1">Event Description</label>
      <textarea rows={3} className="w-full border border-gray-300 rounded-lg px-3 py-2 focus:ring-2 focus:ring-blue-500"
        value={form.event_description} onChange={(e) => setForm({ ...form, event_description:
e.target.value })} />
    </div>

    <button type="submit" disabled={submitting}
      className="w-full bg-blue-600 text-white py-2.5 rounded-lg hover:bg-blue-700 transition-colors
disabled:opacity-50 font-medium">
      {submitting ? 'Submitting...' : 'Submit Request'}
    </button>
  </form>
</div>
</div>
);
}

```

frontend/app/requester/my-requests/page.tsx

```

'use client';

import { useEffect, useState } from 'react';
import { useRouter } from 'next/navigation';
import { useAuth } from '@lib/auth-context';
import { requestsApi } from '@lib/services';
import { Request } from '@lib/types';
import { formatDate, formatTime } from '@lib/utills';
import { toast } from 'sonner';

export default function MyRequestsPage() {
  const { user, loading } = useAuth();
  const router = useRouter();
  const [requests, setRequests] = useState<Request[]>([]);
  const [fetching, setFetching] = useState(true);

  useEffect(() => {
    if (!loading && !user) router.push('/login');
    if (!loading && user && user.role !== 'requester') router.push('/dashboard');
  }, [user, loading, router]);

  useEffect(() => {
    if (user?.role === 'requester') {
      requestsApi.getMy()
        .then((res) => setRequests(res.data))
        .catch(() => toast.error('Failed to load requests'))
        .finally(() => setFetching(false));
    }
  }, [user]);

  const statusColor: Record<string, string> = {
    pending: 'bg-yellow-100 text-yellow-800',
    forwarded: 'bg-blue-100 text-blue-800',
    approved: 'bg-green-100 text-green-800',
    rejected: 'bg-red-100 text-red-800',
    amended: 'bg-purple-100 text-purple-800',
  };

  if (loading || fetching) return (
    <div className="min-h-screen flex items-center justify-center">
      <div className="animate-spin rounded-full h-12 w-12 border-b-2 border-blue-600"></div>
    </div>
  );

  return (
    <div className="min-h-screen bg-gray-50">
      <header className="bg-blue-900 text-white px-6 py-4 flex items-center justify-between">
        <h1 className="text-xl font-bold">My Booking Requests</h1>
        <div className="flex gap-3">
          <button onClick={() => router.push('/requester/request-new')} className="bg-blue-600 hover:bg-blue-500 text-white px-4 py-2 rounded-lg text-sm transition-colors">
            + New Request
          </button>
          <button onClick={() => router.push('/dashboard')} className="bg-blue-800 hover:bg-blue-700 px-4 py-2 rounded-lg text-sm transition-colors">
            Dashboard
          </button>
        </div>
      </header>

```

```

        </button>
      </div>
    </header>

    <div className="max-w-5xl mx-auto px-4 py-8">
      {requests.length === 0 ? (
        <div className="text-center py-16 text-gray-500">
          <p className="text-lg">No requests yet.</p>
          <button onClick={() => router.push('/requester/request-new')} className="mt-4 bg-blue-600 text-white px-6 py-2 rounded-lg hover:bg-blue-700">
            Make Your First Request
          </button>
        </div>
      ) : (
        <div className="space-y-4">
          {requests.map((req) => (
            <div key={req.request_id} className="bg-white rounded-xl shadow-sm border border-gray-100 p-5">
              <div className="flex items-start justify-between">
                <div>
                  <h3 className="font-semibold text-gray-800 text-lg">{req.event_title}</h3>
                  <p className="text-sm text-gray-500">{formatDate(req.event_date)} &bull;
                    {formatTime(req.start_time)} - {formatTime(req.end_time)}</p>
                  {req.purpose && <p className="text-sm text-gray-600 mt-1">Purpose: {req.purpose}</p>}
                </div>
                <div className="flex flex-col items-end gap-2 text-xs font-medium">
                  <span className={`px-2 py-1 rounded-full ${statusColor[req.dept_status]}`}>Dept:
                    {req.dept_status}</span>
                  <span className={`px-2 py-1 rounded-full ${statusColor[req.admin_status]}`}>Admin:
                    {req.admin_status}</span>
                </div>
              </div>
              {(req.dept_remarks || req.admin_remarks) && (
                <div className="mt-3 border-t pt-3 text-sm text-gray-500 space-y-1">
                  {req.dept_remarks && <p>Dept remarks: {req.dept_remarks}</p>}
                  {req.admin_remarks && <p>Admin remarks: {req.admin_remarks}</p>}
                </div>
              )}
            </div>
          ))}
        </div>
      )}
    </div>
  </div>
);
}

```

frontend/app/coordinator/pending/page.tsx

```

'use client';

import { useEffect, useState } from 'react';
import { useRouter } from 'next/navigation';
import { useAuth } from '@lib/auth-context';
import { requestsApi } from '@lib/services';
import { Request } from '@lib/types';
import { formatDate, formatTime } from '@lib/utlis';
import { toast } from 'sonner';

export default function CoordinatorPendingPage() {
  const { user, loading } = useAuth();
  const router = useRouter();
  const [requests, setRequests] = useState<Request[]>([]);
  const [fetching, setFetching] = useState(true);
  const [reviewing, setReviewing] = useState<number | null>(null);

  useEffect(() => {
    if (!loading && !user) router.push('/login');
    if (!loading && user && user.role !== 'dept_coordinator') router.push('/dashboard');
  }, [user, loading, router]);

  const fetchRequests = () => {
    requestsApi.getDeptPending()
      .then((res) => setRequests(res.data))
      .catch(() => toast.error('Failed to load requests'))
      .finally(() => setFetching(false));
  };

  useEffect(() => {

```

```

    if (user?.role === 'dept_coordinator') fetchRequests();
  }, [user]);

const handleReview = async (id: number, action: 'approve' | 'reject') => {
  const remarks = action === 'reject' ? window.prompt('Enter rejection remarks (optional):') ??
undefined : undefined;
  setReviewing(id);
  try {
    await requestsApi.deptReview(id, { action, remarks });
    toast.success(`Request ${action === 'approve' ? 'forwarded to admin' : 'rejected'}`);
    fetchRequests();
  } catch (err: any) {
    toast.error(err.response?.data?.error || 'Action failed');
  } finally {
    setReviewing(null);
  }
};

if (loading || fetching) return <div className="min-h-screen flex items-center justify-center"><div
className="animate-spin rounded-full h-12 w-12 border-b-2 border-blue-600"></div></div>;

return (
  <div className="min-h-screen bg-gray-50">
    <header className="bg-blue-900 text-white px-6 py-4 flex items-center justify-between">
      <h1 className="text-xl font-bold">Department Pending Requests</h1>
      <button onClick={() => router.push('/dashboard')} className="bg-blue-800 hover:bg-blue-700 px-4
py-2 rounded-lg text-sm">Dashboard</button>
    </header>

    <div className="max-w-5xl mx-auto px-4 py-8">
      {requests.length === 0 ? (
        <div className="text-center py-16 text-gray-500"><p className="text-lg">No pending requests for
your department.</p></div>
      ) : (
        <div className="space-y-4">
          {requests.map((req) => (
            <div key={req.request_id} className="bg-white rounded-xl shadow-sm border border-gray-100 p-
5">
              <div className="flex items-start justify-between">
                <div>
                  <h3 className="font-semibold text-gray-800 text-lg">{req.event_title}</h3>
                  <p className="text-sm text-gray-500">{formatDate(req.event_date)} &bull;
{formatTime(req.start_time)} - {formatTime(req.end_time)}</p>
                  {req.purpose && <p className="text-sm text-gray-600 mt-1">Purpose: {req.purpose}</p>}
                  {req.expected_attendees && <p className="text-sm text-gray-600">Attendees:
{req.expected_attendees}</p>}
                </div>
                <div className="flex gap-2">
                  <button
                    disabled={reviewing === req.request_id}
                    onClick={() => handleReview(req.request_id, 'approve')}
                    className="bg-green-600 hover:bg-green-700 text-white text-sm px-4 py-2 rounded-lg
transition-colors disabled:opacity-50"
                  >
                    ✓ Forward
                  </button>
                  <button
                    disabled={reviewing === req.request_id}
                    onClick={() => handleReview(req.request_id, 'reject')}
                    className="bg-red-600 hover:bg-red-700 text-white text-sm px-4 py-2 rounded-lg
transition-colors disabled:opacity-50"
                  >
                    X Reject
                  </button>
                </div>
              </div>
            </div>
          ))}
        </div>
      )}
    </div>
  </div>
);
}

```

frontend/lib/api.ts

```
import axios from 'axios';
```

```

const API_URL = process.env.NEXT_PUBLIC_API_URL || 'http://localhost:8080';

export const api = axios.create({
  baseURL: `${API_URL}/api`,
  headers: {
    'Content-Type': 'application/json',
  },
});

// Attach JWT token from localStorage on every request
api.interceptors.request.use((config) => {
  if (typeof window !== 'undefined') {
    const token = localStorage.getItem('auth_token');
    if (token) {
      config.headers.Authorization = `Bearer ${token}`;
    }
  }
  return config;
});

// Response interceptor for error handling
api.interceptors.response.use(
  (response) => response,
  (error) => {
    if (error.response?.status === 401) {
      // Only redirect if we're on a protected page (not on login or public pages)
      if (typeof window !== 'undefined') {
        const publicPaths = ['/login', '/', '/halls'];
        const isPublic = publicPaths.some((p) =>
          window.location.pathname === p || window.location.pathname.startsWith(`${p}/`)
        );
        if (!isPublic) {
          localStorage.removeItem('auth_token');
          window.location.href = '/login';
        }
      }
    }
    return Promise.reject(error);
  }
);

```

frontend/lib/auth-context.tsx

```

'use client';

import { createContext, useContext, useEffect, useState, ReactNode } from 'react';
import { authApi } from '@lib/services';
import { User } from '@lib/types';

interface AuthContextType {
  user: User | null;
  requesterInfo: { requester_id: number; requester_type: string } | null;
  loading: boolean;
  logout: () => Promise<void>;
  refresh: () => Promise<void>;
}

const AuthContext = createContext<AuthContextType | null>(null);

export function AuthProvider({ children }: { children: ReactNode }) {
  const [user, setUser] = useState<User | null>(null);
  const [requesterInfo, setRequesterInfo] = useState<{ requester_id: number; requester_type: string } | null>(null);
  const [loading, setLoading] = useState(true);

  const refresh = async () => {
    try {
      const res = await authApi.getMe();
      setUser(res.data.user);
      setRequesterInfo(res.data.requester ?? null);
    } catch {
      setUser(null);
      setRequesterInfo(null);
    } finally {
      setLoading(false);
    }
  };
};

```

```

const logout = async () => {
  try {
    await authApi.logout();
  } finally {
    localStorage.removeItem('auth_token');
    setUser(null);
    setRequesterInfo(null);
    window.location.href = '/login';
  }
};

useEffect(() => {
  refresh();
}, []);

return (
  <AuthContext.Provider value={{ user, requesterInfo, loading, logout, refresh }}>
    {children}
  </AuthContext.Provider>
);
}

export function useAuth() {
  const ctx = useContext(AuthContext);
  if (!ctx) throw new Error('useAuth must be used inside AuthProvider');
  return ctx;
}

```

frontend/lib/types.ts

```

// User and Auth Types
export type UserRole = 'admin' | 'dept_coordinator' | 'requester' | 'faculty';
export type ApprovalStatus = 'pending' | 'forwarded' | 'approved' | 'rejected' | 'amended';
export type BookingStatus = 'confirmed' | 'cancelled' | 'completed' | 'no_show';
export type RequesterType = 'class' | 'club';

export interface User {
  user_id: number;
  username: string;
  full_name: string;
  email?: string;
  phone?: string;
  role: UserRole;
  dept_id?: number;
  is_active: boolean;
  created_at: string;
  updated_at: string;
}

export interface Requester {
  requester_id: number;
  user_id: number;
  requester_type: RequesterType;
  class_id?: number;
  club_id?: number;
  created_at: string;
}

export interface Hall {
  hall_id: number;
  hall_name: string;
  capacity: number;
  location?: string;
  facilities: Record<string, any>;
  is_active: boolean;
}

export interface Request {
  request_id: number;
  requester_id: number;
  hall_id: number;
  event_title: string;
  event_description?: string;
  event_date: string;
  start_time: string;
  end_time: string;
  expected_attendees?: number;
  purpose?: string;
}

```

```

    dept_status: ApprovalStatus;
    dept_approved_by?: number;
    dept_approved_at?: string;
    dept_remarks?: string;
    admin_status: ApprovalStatus;
    admin_approved_by?: number;
    admin_approved_at?: string;
    admin_remarks?: string;
    requested_at: string;
    is_cancelled: boolean;
}

export interface Booking {
    booking_id: number;
    request_id: number;
    hall_id: number;
    requester_id: number;
    event_title: string;
    event_date: string;
    start_time: string;
    end_time: string;
    status: BookingStatus;
    created_at: string;
    completed_at?: string;
}

export interface AvailabilitySlot {
    hall_id: number;
    hall_name: string;
    date: string;
    bookings: Booking[];
}

export interface LoginRequest {
    username: string;
    password: string;
}

export interface LoginResponse {
    user: User;
    token: string;
}

export interface CreateRequestInput {
    hall_id: number;
    event_title: string;
    event_description?: string;
    event_date: string;
    start_time: string;
    end_time: string;
    expected_attendees?: number;
    purpose?: string;
}

export interface ReviewRequestInput {
    action: 'approve' | 'reject';
    remarks?: string;
}

export interface Department {
    dept_id: number;
    dept_name: string;
    dept_code?: string;
    created_at: string;
}

export interface Class {
    class_id: number;
    class_name: string;
    dept_id: number;
    year: string;
}

export interface Club {
    club_id: number;
    club_name: string;
    dept_id?: number;
    description?: string;
}

```

```

}

export interface HallUsageReport {
  hall_id: number;
  hall_name: string;
  total_bookings: number;
}

export interface DepartmentUsageReport {
  dept_id: number;
  dept_name: string;
  total_requests: number;
}

frontend/lib/services.ts


---


import { api } from './api';
import {
  Hall, Booking, Department, Class, Club,
  HallUsageReport, DepartmentUsageReport,
  Request, User, ReviewRequestInput, CreateRequestInput,
} from './types';

// — AUTH —————

export const authApi = {
  login: async (username: string, password: string) => {
    const res = await api.post<{ user: User; token: string }>('/auth/login', { username, password });
    // Save token to localStorage so the request interceptor can use it
    if (typeof window !== 'undefined') {
      localStorage.setItem('auth_token', res.data.token);
    }
    return res;
  },

  logout: () => api.post('/auth/logout'),

  getMe: () => api.get<{ user: User; requester?: { requester_id: number; requester_type: string } }>
('/auth/me'),
};

// — HALLS —————

export const hallsApi = {
  getAll: () => api.get<Hall[]>('/halls'),

  getAvailability: (hallId: number, date: string) =>
    api.get<Booking[]>(`/availability?hall_id=${hallId}&date=${date}`),

  create: (data: Omit<Hall, 'hall_id' | 'is_active'>) => api.post<Hall>('/halls', data),
  update: (id: number, data: Partial<Hall>) => api.put<Hall>(`/halls/${id}`, data),
  delete: (id: number) => api.delete(`/halls/${id}`),
};

// — DEPARTMENTS —————

export const departmentsApi = {
  getAll: () => api.get<Department[]>('/departments'),
  create: (dept_name: string, dept_code: string) => api.post<Department>('/departments', { dept_name,
dept_code }),
  update: (id: number, dept_name: string, dept_code: string) => api.put(`/departments/${id}`, { dept_name,
dept_code }),
  delete: (id: number) => api.delete(`/departments/${id}`),
};

// — CLASSES —————

export const classesApi = {
  getByDept: (deptId: number) => api.get<Class[]>(`/classes?dept_id=${deptId}`),
  create: (data: { class_name: string; dept_id: number; year: string }) => api.post<Class>('/classes',
data),
  delete: (id: number) => api.delete(`/classes/${id}`),
};

// — CLUBS —————

export const clubsApi = {
  getAll: (deptId?: number) => api.get<Club[]>(deptId ? `/clubs?dept_id=${deptId}` : '/clubs'),
  create: (data: { club_name: string; dept_id?: number; description?: string }) => api.post<Club>

```

```

    ('/clubs', data),
    delete: (id: number) => api.delete(`/clubs/${id}`),
  });

// — REQUESTS —————

export const requestsApi = {
  // Requester
  create: (data: CreateRequestInput) => api.post<Request>('/requests', data),
  getMy: () => api.get<Request[]>('/requests/my'),

  // Coordinator
  getDeptPending: () => api.get<Request[]>('/requests/dept-pending'),
  deptReview: (id: number, payload: ReviewRequestInput) => api.patch(`/requests/${id}/dept-review`,
    payload),

  // Admin
  getAdminPending: () => api.get<Request[]>('/requests/admin-pending'),
  adminReview: (id: number, payload: ReviewRequestInput) => api.patch(`/requests/${id}/admin-review`,
    payload),
};

// — BOOKINGS —————

export const bookingsApi = {
  getAll: () => api.get<Booking[]>('/bookings'),
  cancel: (id: number) => api.patch(`/bookings/${id}/cancel`),
};

// — USERS —————

export const usersApi = {
  getAll: (role?: string) => api.get<User[]>(role ? `/users?role=${role}` : '/users'),
  getFaculties: () => api.get<User[]>('/users/faculties'),
  deactivate: (id: number) => api.delete(`/users/${id}`),
};

// — REPORTS —————

export const reportsApi = {
  hallUsage: () => api.get<HallUsageReport[]>('/reports/hall-usage'),
  deptUsage: () => api.get<DepartmentUsageReport[]>('/reports/department-usage'),
};

```

frontend/components/Navbar.tsx

```

'use client';

import Link from 'next/link';
import { usePathname } from 'next/navigation';

export default function Navbar() {
  const pathname = usePathname();

  return (
    <nav className="bg-blue-900 text-white shadow-lg">
      <div className="container mx-auto px-4">
        <div className="flex justify-between items-center py-4">
          <Link href="/" className="text-2xl font-bold">
            Seminar Hall Booking
          </Link>
          <div className="flex gap-6">
            <Link
              href="/"
              className={`hover:text-blue-200 ${pathname === '/' ? 'underline' : ''}`}
            >
              Home
            </Link>
            <Link
              href="/halls"
              className={`hover:text-blue-200 ${pathname === '/halls' ? 'underline' : ''}`}
            >
              Halls
            </Link>
            <Link
              href="/dashboard"
              className={`hover:text-blue-200 ${pathname === '/dashboard' ? 'underline' : ''}`}
            >
              Dashboard

```



```

        </Link>
        <Link
            href="/login"
            className="bg-blue-700 px-4 py-2 rounded hover:bg-blue-600"
        >
            Login
        </Link>
    </div>
</div>
</div>
</nav>
);
}

```

frontend/next.config.ts

```

import type { NextConfig } from "next";

const nextConfig: NextConfig = {
  /* config options here */
};

export default nextConfig;

```

frontend/tsconfig.json

```

{
  "compilerOptions": {
    "target": "ES2017",
    "lib": ["dom", "dom.iterable", "esnext"],
    "allowJs": true,
    "skipLibCheck": true,
    "strict": true,
    "noEmit": true,
    "esModuleInterop": true,
    "module": "esnext",
    "moduleResolution": "bundler",
    "resolveJsonModule": true,
    "isolatedModules": true,
    "jsx": "react-jsx",
    "incremental": true,
    "plugins": [
      {
        "name": "next"
      }
    ],
    "paths": {
      "@/*": ["./*"]
    }
  },
  "include": [
    "next-env.d.ts",
    "**/*.ts",
    "**/*.tsx",
    ".next/types/**/*.ts",
    ".next/dev/types/**/*.ts",
    "**/*.mts"
  ],
  "exclude": ["node_modules"]
}

```

frontend/package.json

```

{
  "name": "frontend",
  "version": "0.1.0",
  "private": true,
  "scripts": {
    "dev": "next dev",
    "build": "next build",
    "start": "next start",
    "lint": "eslint"
  },
  "dependencies": {
    "@hookform/resolvers": "^5.2.2",
    "@types/moment": "^2.11.29",
    "@types/react-big-calendar": "^1.16.3",
    "axios": "^1.13.2",
    "date-fns": "^4.1.0",
    "moment": "^2.30.1",

```

```
    "next": "16.0.10",
    "react": "19.2.0",
    "react-big-calendar": "^1.19.4",
    "react-dom": "19.2.0",
    "react-hook-form": "^7.66.1",
    "sonner": "^2.0.7",
    "zod": "^4.1.13"
  },
  "devDependencies": {
    "@tailwindcss/postcss": "^4",
    "@types/node": "^20",
    "@types/react": "^19",
    "@types/react-dom": "^19",
    "eslint": "^9",
    "eslint-config-next": "16.0.5",
    "tailwindcss": "^4",
    "typescript": "^5"
  }
}
```