

Database Synchronization

=====

Configured Master-Master Replication for MariaDB

Database: tootyiraq_tooty_db

Configuration Details

=====

Server 1 (161.97.158.145):

Configuration File Path: /etc/my.cnf

```
server-id=1
log-bin=mysql-bin
auto-increment-increment=2
auto-increment-offset=1
binlog-do-db=tootyiraq_tooty_db
```

Server 2 (162.254.32.217):

Configuration File Path: /etc/my.cnf

```
server-id=2
log-bin=mysql-bin
auto-increment-increment=2
auto-increment-offset=2
binlog-do-db=tootyiraq_tooty_db
```

Firewall Configuration

IP 162.254.32.217 is allowed in the firewall rules on Server 1 (161.97.158.145) for replication purposes.

Starting Replication

To start the replication, execute the following command inside MySQL on both servers:

START SLAVE;

File Synchronization

=====

Configured Lsyncd for File Synchronization

Configuration Details

Configuration File: /etc/lsyncd/lsyncd.conf

Lsyncd Service Script: /etc/init.d/lsyncd

Bash Script Integration:

Script Path: /home/apply_permission.sh

Exclusions:

Excluded api.php file in the router directory on both servers from synchronization.

Lsyncd Status

Lsyncd service is currently stopped on both servers.

Starting Lsyncd Service

To start the Lsyncd service, use the following command on both servers:

---systemctl restart lsyncd