

Documentation of file sync and DB sync

DATABASE SYNC

CONFIGURED MASTER MASTER REPLICATION

Replication DATABASE-tootyiraq_tooty_db

We are added the configuration in /etc/my.cnf in both server

161.97.158.145

```
server-id=1
log-bin=mysql-bin
auto-increment-increment=2
auto-increment-offset=1
binlog-do-db=tootyiraq_tooty_db
```

162.254.32.217

```
server-id=2
log-bin=mysql-bin
auto-increment-increment=2
auto-increment-offset=2
binlog-do-db=tootyiraq_tooty_db
```

we allowed server ip 162.254.32.217 in the firewall

currently the replication is stoped

TO START THE REPLICATION USE THIS COMMAND INSIDE THE MYSQL OF BOTH SERVER

```
-----START SLAVE;
```

file sync

CONFIGURED LSYNCD

CONFIGURE THE LSYNCD ON BOTH SERVER

Configuration file path /etc/lsyncd.cnf
apply_permission.sh file path--/home/apply_permission.sh

connected a bash script to apply_permission.sh to the lsyncd configuraton for the correct premission
also exclude the api.php file in the router directory on both server

lsyncd stoped in both server

To start the service --use this command on both server

command---systemctl restart lsyncd
