

Lab 2 b

1. Raising a number n to a power p is the same as multiplying n by itself p times. Write a function called `power()` that takes a double value for n and an int value for p , and returns the result as double value. Use a default argument of 2 for p , so that if this argument is omitted, the number will be squared. Write a `main()` function that gets values from the user to test this function.

2. A point on the two dimensional plane can be represented by two numbers: an X coordinate and a Y coordinate. For example, (4,5) represents a point 4 units to the right of the origin along the X axis and 5 units up the Y axis. The sum of two points can be defined as a new point whose X coordinate is the sum of the X coordinates of the points and whose Y coordinate is the sum of their Y coordinates.
Write a program that uses a structure called `point` to model a point. Define three points, and have the user input values to two of them. Then set the third point equal to the sum of the other two, and display the value of the new point. Interaction with the program might look like this:
Enter coordinates for P1: 3 4
Enter coordinates for P2: 5 7
Coordinates of P1 + P2 are : 8, 11

3. Create the equivalent of a four function calculator. The program should request the user to enter a number, an operator, and another number. It should then carry out the specified arithmetical operation: adding, subtracting, multiplying, or dividing the two numbers. (It should use a switch statement to select the operation). Finally it should display the result.

When it finishes the calculation, the program should ask if the user wants to do another calculation. The response can be Y or N . Some sample interaction with the program might look like this.

Enter first number, operator, second number: 10/ 3
Answer = 3.333333
Do another (Y/ N)? Y
Enter first number, operator, second number 12 + 100
Answer = 112
Do another (Y/ N) ? N