

Day 20:

Task 1: Java IO Basics

Write a program that reads a text file and counts the frequency of each word using `FileReader` and `FileWriter`.

```
package com.assignment.io;
import java.io.BufferedReader;
import java.io.FileReader;
import java.io.IOException;
import java.util.HashMap;
import java.util.Map;
import java.util.Map;
public class Task1 {
    public static void main(String[] args) {
        String inputFile = "C:\\Users\\bunny\\eclipse-workspace\\wipro\\Assignments\\src\\com\\assignment\\io\\input.txt";
        countWordFrequency(inputFile);
    }
    public static void countWordFrequency(String inputFile) {
        try (BufferedReader reader = new BufferedReader(new FileReader(inputFile))) {
            String line;
            Map<String, Integer> wordCounts = new HashMap<>();
            while ((line = reader.readLine()) != null) {
                String[] words = line.split("\\s+");
                for (String word : words) {
                    word = word.toLowerCase();
                    wordCounts.put(word, wordCounts.getOrDefault(word, 0) + 1);
                }
            }
            for (Map.Entry<String, Integer> entry : wordCounts.entrySet()) {
                System.out.println(entry.getKey() + ": " + entry.getValue());
            }
            System.out.println("Word frequencies counted successfully.");
        } catch (IOException e) {
            System.err.println("An error occurred: " + e.getMessage());
        }
    }
}
```

```
Problems @ Javadoc Declaration Coverage Console ×
<terminated> Task1 [Java Application] C:\Program Files\Java\jdk-17\bin\javaw.exe (01-Jun-2024, 4:06:09 pm – 4:06:1
text,: 1
input,: 1
more.: 1
frequency: 1
and: 1
of: 2
should: 1
text: 2
regardless: 1
case.: 1
a: 1
like: 1
sample,: 1
this: 2
words: 1
its: 1
is: 2
it: 1
sample: 2
each: 1
the: 1
input: 1
contains: 1
counted: 1
to: 1
demonstrate: 1
file.: 1
word: 2
file,: 1
Word frequencies counted successfully.
```

Task 2: Serialization and Deserialization

Serialize a custom object to a file and then deserialize it back to recover the object state.

```

package com.assignment.io;
import java.io.*;
class CustomObject implements Serializable {
    private String name;
    private int age;
    public CustomObject(String name, int age) {
        this.name = name;
        this.age = age;
    }
    public String getName() {
        return name;
    }

    public int getAge() {
        return age;
    }
}

public class Task2 {
    public static void main(String[] args) {
        CustomObject obj = new CustomObject("Sreenath", 24);
        serializeObject(obj, "customObject.ser");
        CustomObject deserializedObj = deserializeObject("customObject.ser");
        if (deserializedObj != null) {
            System.out.println("Deserialized Object:");
            System.out.println("Name: " + deserializedObj.getName());
            System.out.println("Age: " + deserializedObj.getAge());
        }
    }

    private static void serializeObject(Object obj, String fileName) {
        try (ObjectOutputStream outputStream = new ObjectOutputStream(new FileOutputStream(fileName))) {
            outputStream.writeObject(obj);
        } catch (IOException e) {
            System.err.println("Error occurred during serialization: " + e.getMessage());
        }
    }

    private static CustomObject deserializeObject(String fileName) {
        try (ObjectInputStream inputStream = new ObjectInputStream(new FileInputStream(fileName))) {
            Object obj = inputStream.readObject();
            if (obj instanceof CustomObject) {
                return (CustomObject) obj;
            } else {
                System.err.println("Invalid object type found in the file.");
                return null;
            }
        } catch (IOException | ClassNotFoundException e) {
            System.err.println("Error occurred during deserialization: " + e.getMessage());
            return null;
        }
    }
}

```



```

<terminated> Task2 [Java Application] C:\Program
Deserialized Object:
Name: Sreenath
Age: 24

```

Task 3: New IO (NIO)

Use NIO Channels and Buffers to read content from a file and write to another file.

```

package com.assignment.io;

import java.io.IOException;
import java.nio.ByteBuffer;
import java.nio.channels.FileChannel;
import java.nio.file.Paths;
import java.nio.file.Path;
import java.nio.file.StandardOpenOption;
import java.nio.charset.StandardCharsets;
public class Task3 {
    public static void main(String[] args) {
        String sourceFile = "C:\\Users\\bunny\\eclipse-workspace\\wipro\\Assignments\\src\\com\\assignment\\io\\input.txt";
        String destinationFile = "C:\\Users\\bunny\\eclipse-workspace\\wipro\\Assignments\\src\\com\\assignment\\io\\output.txt";
        try {
            System.out.println("Reading content from source file:");
            String sourceContent = readFile(sourceFile);
            System.out.println(sourceContent);

            copyFile(sourceFile, destinationFile);
            System.out.println("Content copied successfully from " + sourceFile + " to " + destinationFile);

            System.out.println("Reading content from destination file:");
            String destinationContent = readFile(destinationFile);
            System.out.println(destinationContent);
        } catch (IOException e) {
            System.err.println("An error occurred: " + e.getMessage());
        }
    }

    private static void copyFile(String sourceFile, String destinationFile) throws IOException {
        Path sourcePath = Paths.get(sourceFile);
        Path destinationPath = Paths.get(destinationFile);

        try (FileChannel sourceChannel = FileChannel.open(sourcePath, StandardOpenOption.READ);
             FileChannel destinationChannel = FileChannel.open(destinationPath, StandardOpenOption.CREATE,
                StandardOpenOption.WRITE, StandardOpenOption.TRUNCATE_EXISTING)) {

            ByteBuffer buffer = ByteBuffer.allocate(1024);

            while (sourceChannel.read(buffer) != -1) {
                buffer.flip();
                while (buffer.hasRemaining()) {
                    destinationChannel.write(buffer);
                }
                buffer.clear();
            }
        }
    }

    private static String readFile(String filePath) throws IOException {
        Path path = Paths.get(filePath);
        StringBuilder content = new StringBuilder();

        try (FileChannel fileChannel = FileChannel.open(path, StandardOpenOption.READ)) {
            ByteBuffer buffer = ByteBuffer.allocate(1024);
            while (fileChannel.read(buffer) > 0) {
                buffer.flip();
                content.append(StandardCharsets.UTF_8.decode(buffer).toString());
                buffer.clear();
            }
        }
        return content.toString();
    }
}

```

Output:

```

<terminated> Task3 [Java Application] C:\Program Files\Java\jdk-17\bin\javaw.exe (01-Jun-2024, 4:27:14 pm - 4:27:16 pm) [pid: 17916]
Reading content from source file:
This is a sample input text file.
It contains some sample words like sample, text, file, input, and more.
The purpose of this text is to demonstrate word frequency counting.
Each word should be counted regardless of its case.
Content copied successfully from C:\Users\bunny\eclipse-workspace\wipro\Assignments\src\com\assignment\io\input.txt to C:\User:
Reading content from destination file:
This is a sample input text file.
It contains some sample words like sample, text, file, input, and more.
The purpose of this text is to demonstrate word frequency counting.
Each word should be counted regardless of its case.

```

Task 4: Java Networking

Write a simple HTTP client that connects to a URL, sends a request, and displays the response headers and body.

```
package com.assignment.io;
import java.io.BufferedReader;

public class Task4 {
    public static void main(String[] args) {
        try {
            URL url = new URL("http://www.example.com");

            URLConnection urlcon = url.openConnection();
            BufferedReader br = new BufferedReader(new InputStreamReader(urlcon.getInputStream()));
            String line;
            while ((line = br.readLine()) != null) {
                System.out.println(line);
            }
            br.close();
        } catch (MalformedURLException e) {
            e.printStackTrace();
        } catch (IOException e) {
            e.printStackTrace();
        }
    }
}
```

Output:

```
<!doctype html>
<html>
<head>
    <title>Example Domain</title>

    <meta charset="utf-8" />
    <meta http-equiv="Content-type" content="text/html; charset=utf-8" />
    <meta name="viewport" content="width=device-width, initial-scale=1" />
    <style type="text/css">
    body {
        background-color: #f0f0f2;
        margin: 0;
        padding: 0;
        font-family: -apple-system, system-ui, BlinkMacSystemFont, "Segoe UI", "Open Sans", "Helvetica Neue", Helvetica, Arial, sans-serif;
    }
    div {
        width: 600px;
        margin: 5em auto;
        padding: 2em;
        background-color: #fdfdff;
        border-radius: 0.5em;
        box-shadow: 2px 3px 7px 2px rgba(0,0,0,0.02);
    }
    a:link, a:visited {
        color: #38488f;
        text-decoration: none;
    }
    @media (max-width: 700px) {
        div {
            margin: 0 auto;

```

```

    }
    a:link, a:visited {
        color: #38488f;
        text-decoration: none;
    }
    @media (max-width: 700px) {
        div {
            margin: 0 auto;
            width: auto;
        }
    }
}
</style>
</head>

<body>
<div>
    <h1>Example Domain</h1>
    <p>This domain is for use in illustrative examples in documents. You may use this
    domain in literature without prior coordination or asking for permission.</p>
    <p><a href="https://www.iana.org/domains/example">More information...</a></p>
</div>
</body>
</html>

```

Task 5: Java Networking and Serialization

Develop a basic TCP client and server application where the client sends a serialized object with 2 numbers and operation to be performed on them to the server, and the server computes the result and sends it back to the client. for eg, we could send 2, 2, "+" which would mean 2 + 2

```

package com.assignment.io;

import java.io.*;

public class TCPClient {
    public static void main(String[] args) {
        String serverAddress = "localhost";
        int serverPort = 2024;

        try (Socket socket = new Socket(serverAddress, serverPort)) {
            ObjectOutputStream outputStream = new ObjectOutputStream(socket.getOutputStream());
            ObjectInputStream inputStream = new ObjectInputStream(socket.getInputStream());

            OperationRequest request = new OperationRequest(2, 2, "+");
            outputStream.writeObject(request);
            outputStream.flush();

            double result = inputStream.readDouble();
            System.out.println("Result received from server: " + result);
        } catch (IOException e) {
            System.err.println("Error occurred: " + e.getMessage());
        }
    }
}

```



```

package com.assignment.io;

import java.io.*;
import java.net.ServerSocket;
import java.net.Socket;

public class TCPServer {
    public static void main(String[] args) {
        int port = 2024;
        try (ServerSocket serverSocket = new ServerSocket(port)) {
            System.out.println("Server is running and listening on port " + port);
            while (true) {
                Socket clientSocket = serverSocket.accept();
                System.out.println("Client connected: " + clientSocket.getInetAddress());

                ObjectOutputStream outputStream = new ObjectOutputStream(clientSocket.getOutputStream());
                ObjectInputStream inputStream = new ObjectInputStream(clientSocket.getInputStream());
                try {
                    OperationRequest request = (OperationRequest) inputStream.readObject();
                    System.out.println("Received operation request: " + request);

                    double result = performOperation(request);
                    outputStream.writeDouble(result);
                    outputStream.flush();
                } catch (ClassNotFoundException e) {
                    System.err.println("Error reading object from client: " + e.getMessage());
                }
                clientSocket.close();
            }
        } catch (IOException e) {
            System.err.println("Error occurred: " + e.getMessage());
        }
    }
}

```

```

        }
        clientSocket.close();
    }
    } catch (IOException e) {
        System.err.println("Error occurred: " + e.getMessage());
    }
}

private static double performOperation(OperationRequest request) {
    double result = 0;

    switch (request.getOperation()) {
        case "+":
            result = request.getNumber1() + request.getNumber2();
            break;
        case "-":
            result = request.getNumber1() - request.getNumber2();
            break;
        case "*":
            result = request.getNumber1() * request.getNumber2();
            break;
        case "/":
            result = request.getNumber1() / request.getNumber2();
            break;
    }
    return result;
}
}

```

```

package com.assignment.io;

import java.io.Serializable;
public class OperationRequest implements Serializable {
    private static final long serialVersionUID = 1L;
    private double number1;
    private double number2;
    private String operation;
    public OperationRequest(double number1, double number2, String operation) {
        this.number1 = number1;
        this.number2 = number2;
        this.operation = operation;
    }
    public double getNumber1() {
        return number1;
    }
    public double getNumber2() {
        return number2;
    }
    public String getOperation() {
        return operation;
    }
}

@Override
public String toString() {
    return "OperationRequest{" +
        "number1=" + number1 +
        ", number2=" + number2 +
        ", operation='" + operation + '\'' +
        '}';
}
}

```

Problems @ Javadoc Declaration Coverage Console ×

[CPServer [Java Application] C:\Program Files\Java\jdk-17\bin\javaw.exe (01-Jun-2024, 4:55:52 pm) [pid: 3120]

Server is running and listening on port 2024

Problems @ Javadoc Declaration Coverage Console ×

<terminated> TCPClient [Java Application] C:\Program Files\Java\jdk-17\bin\javaw.exe (01-Jun-2024, 4:55:52 pm) [pid: 3120]

Result received from server: 4.0

SF-1

Task 6: Java 8 Date and Time API

Write a program that calculates the number of days between two dates input by the user.

```
package com.assignment.io;

import java.time.LocalDate;
import java.time.format.DateTimeFormatter;
import java.time.temporal.ChronoUnit;
import java.util.Scanner;

public class Task6 {
    public static void main(String[] args) {
        Scanner scanner = new Scanner(System.in);


        System.out.println("Enter the first date (YYYY-MM-DD):");
        String firstDateString = scanner.nextLine();
        LocalDate firstDate = LocalDate.parse(firstDateString, DateTimeFormatter.ISO_DATE);

        System.out.println("Enter the second date (YYYY-MM-DD):");
        String secondDateString = scanner.nextLine();
        LocalDate secondDate = LocalDate.parse(secondDateString, DateTimeFormatter.ISO_DATE);

        long daysBetween = ChronoUnit.DAYS.between(firstDate, secondDate);

        System.out.println("Number of days between " + firstDate + " and " + secondDate + ": " + daysBetween);
    }
}
```

Output:



```
14      LocalDate firstDate = LocalDate.parse(firstDateString, D
3
SE- Console X
<terminated> Task6 [Java Application] C:\Program Files\Java\jdk-17\bin\javaw.exe (01-Jun-2024, 5:00:13 pm – 5:00:42 pm) [pid: 1245]
Enter the first date (YYYY-MM-DD):
2024-06-01
Enter the second date (YYYY-MM-DD):
2024-05-02
Number of days between 2024-06-01 and 2024-05-02: -30
```

Task 7: Timezone

Create a timezone converter that takes a time in one timezone and converts it to another timezone.

```

package com.assignment.io;

import java.time.ZonedDateTime;
import java.time.ZoneId;
import java.time.format.DateTimeFormatter;
import java.util.Scanner;

public class Task7 {
    public static void main(String[] args) {
        Scanner scanner = new Scanner(System.in);
        System.out.println("Enter the original time (format: yyyy-MM-dd'T'HH:mm:ss): ");
        String originalTime = scanner.nextLine();
        System.out.println("Enter the original timezone (e.g., Asia/Kolkata): ");
        String originalZone = scanner.nextLine();
        System.out.println("Enter the target timezone (e.g., America/New_York): ");
        String targetZone = scanner.nextLine();
        String convertedTime = convertTimeZone(originalTime, originalZone, targetZone);
        System.out.println("Original time: " + originalTime + " in " + originalZone);
        System.out.println("Converted time: " + convertedTime + " in " + targetZone);
    }

    public static String convertTimeZone(String originalTime, String originalZone, String targetZone) {
        DateTimeFormatter formatter = DateTimeFormatter.ofPattern("yyyy-MM-dd'T'HH:mm:ss");
        ZonedDateTime originalDateTime = ZonedDateTime.parse(originalTime, formatter.withZone(ZoneId.of(originalZone)));
        ZonedDateTime targetDateTime = originalDateTime.withZoneSameInstant(ZoneId.of(targetZone));
        String targetTime = formatter.format(targetDateTime);
        return targetTime;
    }
}

```

Output:

```

<terminated> Task7 [Java Application] C:\Program Files\Java\jdk-17\bin\javaw.exe (01-Jun-2024, 5:15:45 pm – 5:16:16 pm) [pid: 1164]
Enter the original time (format: yyyy-MM-dd'T'HH:mm:ss):
2024-06-01T12:00:00
Enter the original timezone (e.g., Asia/Kolkata):
Asia/Kolkata
Enter the target timezone (e.g., America/New_York):
America/New_York
Original time: 2024-06-01T12:00:00 in Asia/Kolkata
Converted time: 2024-06-01T02:30:00 in America/New_York

```