

Air Guitar: Simulate a Virtual Guitar Playing Experience Using Machine Learning and Arduino

Bingan Chen¹ Shiyu Chen¹ Samantha Reksosamudra¹

¹Dept. of Electrical and Computer Engineering
University of Washington

EE 400: TinyML, Final Project Presentation, May 2024

Introduction

[Introduction](#)[Methodology](#)[Machine Learning Platform](#)[Data Collection](#)[Pipeline](#)[Analysis and Results](#)[Model Explanation](#)[Flex Sensors Data](#)[Accelerometer Data](#)[Results](#)[Confusion Matrix](#)[Features Explorer](#)[Learning Curve](#)[Observations & Insights](#)[Conclusion](#)

- We are creating a virtual guitar playing experience using an Arduino and machine learning.
- Dataset: Data is collected by ourselves (without a guitar in hand).
- Team member and their roles:

Name	Role
Shiyu Chen	Data Collection; ML Models; Demo
Samantha Reksosamudra	Data Collection; Validation; Materials
Bingan Chen	Hardware; Algorithms; Slides; Aesthetic

We used *Edge Impulse* to train our machine learning models.



EDGE IMPULSE

Figure: Edge Impulse Logo

Shiyu: collected data using a flex sensors.




Figure: Flex Sensors

Data Collection

Samantha: collected data using
accelerometer.




Figure: Accelerometer (built-in)

Full Setup

Introduction

Methodology

Machine Learning
Platform

Data Collection

Pipeline

Analysis and
Results

Model Explanation

Flex Sensors Data

Accelerometer Data

Results

Confusion Matrix

Features Explorer

Learning Curve

Observations &
Insights

Conclusion





Figure: Full Setup

[Introduction](#)[Methodology](#)[Machine Learning Platform](#)[Data Collection](#)[Pipeline](#)[Analysis and Results](#)[Model Explanation](#)[Flex Sensors Data](#)[Accelerometer Data](#)[Results](#)[Confusion Matrix](#)[Features Explorer](#)[Learning Curve](#)[Observations & Insights](#)[Conclusion](#)

- ① Collect data using flex sensors and accelerometer.
- ② Train the models using Edge Impulse.
- ③ Load the models onto **two separate** Arduinos Nano 33 BLE Sense.
- ④ Communicate between the two Arduinos *Flex* & *Acc* using BLE using **UART (Universal Asynchronous Receiver-Transmitter)**:
 - ① *Acc* predict the strumming.
 - ② *Acc* sends the prediction [idle, strum] to *Flex*.
 - ③ Once *Flex* receives the signal for strumming, it predicts the chord.
 - ④ *Flex* sends the prediction to the computer.
 - ⑤ The computer plays the sound of the chord.
- ⑤ Play the guitar by strumming.


Flex Sensors Data

- The flex sensors data is used to determine the notes being played.
- Input: 4 axes of flex sensors data in voltage.
- Labels: [A, C, C7, D, E, Em, G, relax] by file name.
- Output: 8 classes of guitar chords.
- Data Loading:
Flex sensors → Arduino Analog Read → script monitoring serial → CSV file.
- Architecture: [400 epochs, learning rate 0.001, batch size 32]



Accelerometer Data

- The accelerometer data is used to determine whether we want to play the note.
- Input: 3 axes of accelerometer data in g-force.
- Labels: [idle, strum]
- Output: 2 classes of strumming.
- Data Loading:
`edge-impulse-cli`
- Architecture: [30 epochs, learning rate 0.0005, batch size 32]



Confusion Matrix

We achieved an **testing accuracy** of 91.21% for the flex sensors model and 99.55% for the accelerometer model.

	A	C	C7	D	E	EM	G	RELAX	UNCEP
A	100%	0%	0%	0%	0%	0%	0%	0%	0%
C	0%	82.9%	0%	0%	7.1%	0%	0%	0%	10%
C7	0%	0%	91.2%	0%	0%	0%	0%	0%	8.8%
D	0%	0%	0%	85.7%	0%	0%	0%	0%	14.3%
E	0%	3.4%	0%	0%	79.5%	0%	0%	0%	17.0%
EM	0%	0%	0%	0%	0%	92.7%	6.1%	0%	1.2%
G	0%	0%	0%	0%	0%	0%	99.0%	0%	1.0%
RELAX	0%	0%	0%	0%	0%	0%	0%	100%	0%
F1 SC	1.00	0.89	0.95	0.92	0.86	0.96	0.97	1.00	

	IDLE	STRUM	UNCERTAIN
IDLE	100%	0%	0%
STRUM	0%	97.7%	2.3%
F1 SCORE	1.00	0.99	

Figure: Accelerometer Confusion Matrix

Figure: Flex Sensors Confusion Matrix

According to the confusion matrix, notes E, Em, C, are a little bit harder to predict as they have similar hand gestures.

[Introduction](#)[Methodology](#)[Machine Learning
Platform](#)[Data Collection](#)[Pipeline](#)[Analysis and
Results](#)[Model Explanation](#)[Flex Sensors Data](#)[Accelerometer Data](#)[Results](#)[Confusion Matrix](#)[Features Explorer](#)[Learning Curve](#)[Observations &
Insights](#)[Conclusion](#)

Features Explorer

They are clustered well in the feature space.

- A - correct
- C - correct
- C7 - correct
- D - correct
- E - correct
- Em - correct
- G - correct
- relax - correct
- C - incorrect
- C7 - incorrect
- D - incorrect
- E - incorrect
- Em - incorrect
- G - incorrect




Figure: Flex Sensors Features Explorer

- idle - correct
- strum - correct
- strum - incorrect




Figure: Accelerometer Features Explorer

Learning Curve


[Introduction](#)[Methodology](#)[Machine Learning Platform](#)[Data Collection](#)[Pipeline](#)[Analysis and Results](#)[Model Explanation](#)[Flex Sensors Data](#)[Accelerometer Data](#)[Results](#)[Confusion Matrix](#)[Features Explorer](#)[Learning Curve](#)[Observations & Insights](#)[Conclusion](#)

Figure: Flex Sensors Learning Curve




Figure: Accelerometer Learning Curve

Note: Both models converge well before the max epochs, but full training is shown for better analysis.

Observations & Insights

[Introduction](#)[Methodology](#)[Machine Learning Platform](#)[Data Collection](#)[Pipeline](#)[Analysis and Results](#)[Model Explanation](#)[Flex Sensors Data](#)[Accelerometer Data](#)[Results](#)[Confusion Matrix](#)[Features Explorer](#)[Learning Curve](#)[Observations & Insights](#)[Conclusion](#)

- The flex sensors are hard to work with if we use the fabric glove. Rubber gloves may fit better but lack of reusability and sanitization.
- We tried bluetooth communication first but it was too laggy and hard to implement. UART (wired) is more reliable.
- The uncertain time required for both Arduino to predict and communicate add additional difficulty to synchronize the strumming and chord playing.
- Python script is a good tool to serve as a bridge between the two Arduino and the computer through serial communication: (pyserial) for serial monitoring and playsound for playing the sound.
- Edge Impulse is a powerful tool for training models.

Conclusion

- We successfully created a virtual guitar playing experience using machine learning and Arduino.
- We achieved a testing accuracy of 91.21% for the flex sensors model and 99.55% for the accelerometer model.
- The project has potential applications in music education and entertainment.
- The project also demonstrates the potential of TinyML in creating interactive experiences.
- Future work includes improving the accuracy of the flex sensors model and reducing the latency of the system.
- A 3D-printed mechanical hand may be used to improve the accuracy of the flex sensors model due to its flexibility and reusability.