

ENGINEERING SPECS

Technical Data Sheet

CALOR MEGA BATCH SYSTEM PARAMETERS

SPECIFICATION CATEGORY	ENGINEERING DETAILS
CONSTRUCTION	Double-walled heavy gauge Stainless Steel (SS304 outer/inner, optional SS316 internal chamber for high-acid produce). Reinforced structural framing.
THERMAL INSULATION	75mm high-density rockwool / mineral wool insulation, minimizing heat dissipation and casing temperature.
CONTROL SYSTEM	Microprocessor-based PID Digital Controller with dual displays for PV (Process Value) and SV (Set Value). Dynamic Pt100 RTD sensor.
CAPACITY RANGE	Standard industrial configurations of 50 kg, 100 kg, 200 kg, 500 kg, and custom 1000+ kg continuous batch processing setups.
DRYING TRAYS	Removable SS304 mesh tray racks. Wire mesh spacing customized for tiny seeds, herbs, or large fruit chunks.
HEATING METHOD	Finned stainless steel armored electric heating elements, with support for steam heating coils or hot water heat exchangers.
AIRFLOW SYSTEM	Direct-drive, dynamically balanced axial flow fans with high-temperature resistance and adjustable speed control for tailored laminar airflow.
TEMPERATURE RANGE	Ambient to 90°C, adjustable with ±1°C accuracy. Built-in thermal safety override cut-off.
HUMIDITY CONTROL	Active electronic humidity transmitter. Automated electric actuator dampers for exhaust air evacuation.
INSTALLATION & SERVICE	Factory-assembled skid-mounted design for rapid commissioning. Simple three-phase electrical input connection.