

SkyLab : An extensible workflow web application for HPC on the cloud

Vincent Paul L. Carpio
Institute of Computer Science College
of Arts and Sciences University of
the Philippines Los Banos
vplcarpio@up.edu.ph

Joseph Anthony C. Hermocilla
Institute of Computer Science College
of Arts and Sciences University of
the Philippines Los Banos
jchermocilla@up.edu.ph

Katrina Joy M. Abriol-Santos
Institute of Computer Science College
of Arts and Sciences University of
the Philippines Los Banos
kat@up.edu.ph

ABSTRACT

Most scientific applications require high performance computing (HPC) which utilizes parallel processing to run tasks quickly and efficiently. MPI clusters are often used to cater this type of tasks but the hardware required can be costly. Peak-Two Cloud (P2C) can host HPC applications in a cloud environment which is relatively cheaper and more convenient due to on-demand provisioning. One of the key features of P2C is vCluster, a tool that can deploy MPI clusters usable through the command line. In this paper, we present the design and implementation, as well as user-evaluation results of SkyLab, a workflow web application on top of vCluster to simplify the process of running MPI applications for users not accustomed to the command line. SkyLab currently supports applications used in bioinformatics, molecular dynamics, molecular docking, and quantum chemistry. The extensible design of SkyLab enables additional tools to be incorporated easily as modules.

CCS CONCEPTS

•**Computer systems organization** → **Embedded systems; Redundancy; Robotics**; •**Networks** → **Network reliability**;

KEYWORDS

cloud computing, high performance computing, web interface

ACM Reference format:

Vincent Paul L. Carpio, Joseph Anthony C. Hermocilla, and Katrina Joy M. Abriol-Santos. 2017. SkyLab : An extensible workflow web application for HPC on the cloud. In *Proceedings of Philippine Computing Science Congress, Cebu City, Philippines, March 2017 (PCSC2017)*, 5 pages. DOI: 10.1145/nnnnnnnn.nnnnnnn

1 INTRODUCTION

Cloud computing has marked significant developments and possibilities in the industry. It focuses on offering services for the different needs of the modern society.

There are three categories of cloud computing services namely, Software as a Service (SaaS), Platform as a Service (PaaS) and Infrastructure as a Service (IaaS). Organizations provide SaaS depending

on the demand. Google Apps is one example of SaaS that can be used to manage email and create documents, etc. PaaS offers developers a platform where they can build and deploy applications. IaaS provides storage, servers and clusters. These tools are primarily created to serve computational needs [1]. A cloud computing platform dynamically allocates, configures, reconfigures and deallocates servers as requested or on demand. This approach ensures the elasticity of cloud computing [4].

Most scientific applications require high performance computing (HPC) which needs CPU intensive computations and large data storage. To be able to host such applications, several computers interconnected in a network such as clusters are needed. This makes scientific computing very costly in terms of hardware infrastructure investment. With the advancement in cloud computing, these scientific applications can be deployed in the cloud without worrying about hardware costs and maintenance [1]. However, studies have shown that network transmission delay is the major drawback in deploying HPC applications in the cloud[4].

Peak-Two Cloud (P2C) is a private cloud based on OpenStack designed for research in deploying HPC applications in the cloud[8]. One of the features introduced by P2C is vCluster. vCluster is a tool that enables a user to deploy a working (Message Passing Interface) cluster on demand and to terminate it after use. P2C has been used by researchers in various fields including bioinformatics, quantum chemistry, and molecular dynamics. These researchers belong to different research groups who have no investment in HPC infrastructure due to limited funding but requires heavy computing resources for their research. vCluster, however, is a command line application which make it difficult for non-technical users (scientists and researchers) to use. A more user-friendly interface is needed in order to enable scientists to focus more on their science rather than on the command line.

Presented in this paper is SkyLab, a workflow web application on top of vCluster that addresses the concern above. Specifically, SkyLab will

- (1) allow users to select tools and execute them via web interface;
- (2) enable developers to easily extend it to support additional tools; and
- (3) support display of results using third party tools.

2 RELATED WORK

Ganglia is a system designed to monitor high performance computing systems. It uses a hierarchical model in managing the system of clusters. It uses optimized data structures and communication algorithms to achieve scalability with high concurrency. It is claimed

Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for components of this work owned by others than ACM must be honored. Abstracting with credit is permitted. To copy otherwise, or republish, to post on servers or to redistribute to lists, requires prior specific permission and/or a fee. Request permissions from permissions@acm.org.

PCSC2017, Cebu City, Philippines

© 2017 ACM. 978-x-xxxx-xxxx-x/YY/MM...\$15.00

DOI: 10.1145/nnnnnnnn.nnnnnnn

to be used by over 500 clusters around the world. This implies that the system is tested and trusted to be used for real-world applications[15].

One of the main inspirations for developing SkyLab is the Yabi system. It provides a web interface with support for workflow environments with focus on introducing HPC applications to non-technical audience. Users can create and reuse workflows, and manage large amounts of data while system administrators can configure tools via the web interface as well. It is currently in use by multiple institutions, and is maintained as an open-source project[10].

Another related project is Web Interface for mpiBLAST (Wimpi-BLAST). It supports mpiBLAST, a parallel implementation of Basic Local Alignment Search Tool (BLAST). BLAST is a software used for sequence homology similarity search in large databases of gene sequences. mpiBLAST can utilize HPC clusters to achieve faster computing speeds but it requires knowledge in using MPI commands to benefit from its advantages. WimpiBLAST addresses this problem by providing the user a web interface to simplify the steps to use mpiBLAST[18].

3 DESIGN AND IMPLEMENTATION

3.1 System Architecture

SkyLab functions as a web front-end for vCluster which is built on top of Peak-Two Cloud.




Figure 1: System Architecture of SkyLab

3.2 MPI clusters

The system spawns a thread (MPIThread) for each active cluster which handles the connection to the assigned cluster via Secure Shell (SSH). Creation and deletion of clusters is done by using vCluster commands while tool activation is done by using p2c-tools. The thread also manages task queuing and execution.

A cluster is either classified as public or private. If it is set to public, every user in the system can use it. On the other hand, for private clusters, the cluster will only be visible to the owner. The owner has the option to share the cluster to other users via the share key generated for the said cluster.

3.3 Tool sets

The system searches for Python packages inside the assigned modules folder and install it on server start. The tool sets will then be available for use with the system. The package must have a Python module named *install.py* which contains function calls for integrating the package with the system. The package must also contain the corresponding views and executable classes for each sub-tool.

3.4 Tasks

The system creates a task object for each task input by the user. A signal will then be sent and it is then received by the corresponding MPIThread which queues the task for execution. When a task is executed, it calls the assigned executable class with the given parameters. On connection error, the task waits exponentially before retrying. If the server crashes while running task execution, the task is just restarted.

Default task execution flow via executable class:

- (1) Needed remote and local directories for execution are cleared or created.
- (2) Input files are uploaded to cluster.
- (3) List of commands given are executed.
- (4) Output files are sent back to the server.
- (5) Remote task folder is deleted.
- (6) Output files are served by the server.

3.5 Technologies

- Programming Language: Python
- Web Framework: Django
- DBMS: MariaDB
- Cloud Infrastructure: Peak-Two Cloud

4 RESULTS AND DISCUSSION

4.1 Supported Tools

AutoDock

It is a software used to simulate protein-ligand docking[16].

AutoDock Vina

It is a software similar to AutoDock 4 but on the average, it provides faster and more accurate computations[19].

DOCK

It is used to predict the small molecule-target interactions[14].

Quantum ESPRESSO

It is an integrated software suite of tools for ab-initio molecular dynamics (MD) simulations and electronic structure calculations[6].

GAMESS

It is used for ab initio molecular quantum chemistry. [17]




Figure 2: Use Case Diagram of SkyLab

Ray

It uses parallel genome assemblies for parallel DNA sequencing [3].

- The user can monitor visible public and private MPI clusters.

4.2 System Features

The system's interface offers different functionalities that simplifies MPI cluster and task management.

- The user is authenticated by logging in with his @up.edu.ph Google account.
- The user can create an MPI cluster with optional tool activations.

Create MPI Cluster

Figure 3: MPI creation form

MPI Clusters

Cluster name	Nodes	IP address	Tasks queued	Status	Visibility	Date created
testcluster1	2	10.0.3.243	1	Connecting	Private	10/25/16 12:44 AM

Showing 1 to 1 of 1 entries

Previous 1 Next

Create MPI cluster Add private cluster

Figure 4: MPI cluster table

- The user can make a private cluster visible by entering a valid share key.

Figure 5: Add private cluster form

- The user can view details about a MPI cluster. If the user is the cluster's owner he has the option to delete the cluster.

testcluster1

Cluster name	Nodes	IP address	Tasks queued	Status	Share key	Visibility	Date created
testcluster1	2	10.0.3.243	1	Connecting	SCOIO	Public OFF	10/25/2016 12:44 a.m.

✖ Delete this cluster

Toolsets

Toolset	Description	Status
AutoDock 4	AutoDock is a suite of automated docking tools. It is designed to predict how small molecules, such as substrates or drug candidates, bind to a receptor of known 3D structure.	Activated
Dock 6	The new features of DOCK 6 include: additional scoring options during minimization; DOCK 3.5 scoring-including Delphi electrostatics, ligand conformational entropy corrections, ligand desolvation, rec...	Activated
GAMESS	The General Atomic and Molecular Electronic Structure System (GAMESS) is a general ab initio quantum chemistry package. Briefly, GAMESS can compute SCF wavefunctions ranging from RHF, ROHF, UHF, GVB, ...	Activated
Ray	Ray is a parallel software that computes de novo genome assemblies with next-generation sequencing data.	Activated
AutoDock Vina	AutoDock Vina is an open-source program for doing molecular docking. It was designed and implemented by Dr. Oleg Trott in the Molecular Graphics Lab at The Scripps Research Institute.	Activated
Quantum ESPRESSO	Quantum Espresso is an integrated suite of Open-Source computer codes for electronic-structure calculations and materials modeling at the nanoscale. It is based on density-functional theory, plane wave...	Activated
Impi	Image processing tool that runs in parallel via MPI	Activated

Figure 6: MPI detail view

- The user can select from a list which tool does he want to use.

Toolsets

AutoDock 4	AutoDock is a suite of automated docking tools. It is designed to predict how small molecules, such as substrates or drug candidates, bind to a receptor of known 3D structure.
AutoDock Vina	AutoDock Vina is an open-source program for doing molecular docking. It was designed and implemented by Dr. Oleg Trott in the Molecular Graphics Lab at The Scripps Research Institute.
Dock 6	The new features of DOCK 6 include: additional scoring options during minimization; DOCK 3.5 scoring-including Delphi electrostatics, ligand conformational entropy corrections, ligand desolvation, etc...
GAMESS	The General Atomic and Molecular Electronic Structure System (GAMESS) is a general ab initio quantum chemistry package. Briefly, GAMESS can compute SCF wavefunctions ranging from RHF, ROHF, UHF, GVB, ...
Impi	Image processing tool that runs in parallel via MPI
Quantum ESPRESSO	Quantum Espresso is an integrated suite of Open-Source computer codes for electronic-structure calculations and materials modeling at the nanoscale. It is based on density-functional theory, plane wave...
Ray	Ray is a parallel software that computes de novo genome assemblies with next-generation sequencing data.

Figure 7: Tool set list view

- The user can submit a task by filling up a tool's task creation form.

GAMESS

MPI Cluster*

Getting an empty list? Try creating an MPI Cluster first.

Input file(s)*

Browse... No files selected.

Submit task

Figure 8: GAMESS task creation form

- The user can monitor created tasks.

Tasks

Task number	Tool	MPI Cluster	Task status	Date created	Last updated
38	Impi (Impi)	testcluster1	Success	11/01/2016 2:56 a.m.	11/01/2016 4:01 a.m.
37	Impi (Impi)	testcluster1	Success	10/31/2016 3:04 p.m.	10/31/2016 3:13 p.m.
34	GAMESS (GAMESS)	testcluster1	Success	10/29/2016 6:27 p.m.	10/29/2016 7:12 p.m.
33	GAMESS (GAMESS)	testcluster1	Success	10/29/2016 6:08 p.m.	10/29/2016 6:20 p.m.
32	GAMESS (GAMESS)	testcluster1	Success	10/29/2016 6:04 p.m.	10/29/2016 6:08 p.m.
31	GAMESS (GAMESS)	testcluster1	Success	10/28/2016 2:24 a.m.	10/28/2016 2:24 a.m.
30	GAMESS (GAMESS)	testcluster1	Success	10/25/2016 11:45 p.m.	10/28/2016 1:46 a.m.
29	GAMESS (GAMESS)	testcluster1	Success	10/25/2016 6:30 a.m.	10/25/2016 6:34 a.m.

Figure 9: Task table view

- The user can view results of tasks. JSmol renders the compatible output files[7].

Task 29

GAMESS @ testcluster1 Success

Input Files:

glyc_mol.mlp.rpt

Output Files:

H2O.log

glyc_mol.mlp.log

task_29-scratch_files.zip




Figure 10: Task detail view

4.3 User Acceptance




Figure 11: Results of QUIS for SkyLab

The system has been evaluated by 56 respondents by answering a survey based on Questionnaire for User Interface Satisfaction (QUIS) [5]. Respondents are students who are unfamiliar with both HPC tools and the concept of MPI systems. Respondents are asked to test features of SkyLab by following a set of instructions and using input files provided. On the average, the users rated their overall experience with SkyLab to 6.9/10. The users listed the simplicity of the user interface to be the most positive aspect of the system while the slow speed of task processing is said to be the most negative. Majority of the tools supported by SkyLab have inherently long processing time which is not known to the respondents. The system does not focus on optimizing the said tools

to achieve better performance but rather it focuses on simplifying the user's task submission process.

5 CONCLUSION AND FUTURE WORK

The system created allows users to manage MPI clusters and submit tasks without the need for technical expertise in scripting. This makes the advantages of HPC available to non-technical users. This is achieved by parsing form inputs to generate commands for task execution. Task files can be download from the server and output files are displayed with the help of JSmol[7]. The system is also configured to install tool sets found in the modules folder making it possible to accommodate additional tools. Based on the user acceptance test conducted, the users found the system to be acceptable in terms of the criteria provided, in general.

The system achieved its main objectives but its features can still be improved and additional features can be introduced. Improved input parameter checking and error handling will make the system more robust. There are still use cases of tools that are yet to be supported. Input file generation can make the process more interactive and more customizable. Workflow design support will enable users to run complex tasks. Support for custom MPI programs will make it easier for developers to utilize the system as a test environment. Task scheduling and resource management algorithms can be used to efficiently handle resource-intensive or time consuming tasks. For example, a cluster can borrow resources from idle clusters. These recommendations will provide the users a better experience in using the system for academic and research purposes.

ACKNOWLEDGMENT

REFERENCES

- [1] Sanjay P. Ahuja and Sindhu Mani. 2012. The State of High Performance Computing in the Cloud. *Journal of Emerging Trends in Computing and Information Sciences* 3, 2 (Feb. 2012), 263–266. <http://www.chinacloud.cn/upload/2012-03/12031713036456.pdf>
- [2] Shajulin Benedict. 2013. Performance issues and performance analysis tools for HPC cloud applications: a survey. *Computing* 95, 2 (2013), 89 – 108. <http://search.ebscohost.com/login.aspx?direct=true&db=a9h&AN=85211339&site=ehost-live>
- [3] Sbastien Boisvert, Frdric Raymond, ftlnie Godzaridis, Franois Laviolette, and Jacques Corbeil. 2012. Ray Meta: scalable de novo metagenome assembly and profiling. *Genome Biology* 13, 12 (2012), R122. DOI: <http://dx.doi.org/10.1186/gb-2012-13-12-r122>
- [4] Ivona Brandic, Ioan Raicu, Satish Narayana Srirama, Oleg Batrashev, Pelle Jakovits, and Eero Vainikko. 2011. Scalability of parallel scientific applications on the cloud. *Scientific Programming* 19, 2/3 (2011), 91 – 105. <http://search.ebscohost.com/login.aspx?direct=true&db=a9h&AN=66692024&site=ehost-live>
- [5] J. P. Chin, V. A. Diehl, and K. L. Norman. 1988. Development of an instrument measuring user satisfaction of the human-computer interface. In *Proceedings of SIGCHI '88 ACM/SIGCHI*. New York, 213–218.
- [6] Paolo Giannozzi, Stefano Baroni, Nicola Bonini, Matteo Calandra, Roberto Car, Carlo Cavazzoni, Davide Ceresoli, Guido L Chiarotti, Matteo Cococcioni, Ismaila Dabo, Andrea Dal Corso, Stefano de Gironcoli, Stefano Fabris, Guido Fratesi, Ralph Gebauer, Uwe Gerstmann, Christos Gougoussis, Anton Kokalj, Michele Lazzeri, Layla Martin-Samos, Nicola Marzari, Francesco Mauri, Riccardo Mazzarello, Stefano Paolini, Alfredo Pasquarello, Lorenzo Paulatto, Carlo Sbraccia, Sandro Scandolo, Gabriele Sclauzero, Ari P Seitsonen, Alexander Smogunov, Paolo Umari, and Renata M Wentzcovitch. 2009. QUANTUM ESPRESSO: a modular and open-source software project for quantum simulations of materials. *Journal of Physics: Condensed Matter* 21, 39 (2009), 395502 (19pp). <http://www.quantum-espresso.org>
- [7] Robert M. Hanson, Jaime Prilusky, Zhou Renjian, Takanori Nakane, and Joel L. Sussman. 2013. JSmol and the Next-Generation Web-Based Representation of 3D Molecular Structure as Applied to Proteopedia. *Israel Journal of Chemistry* 53, 3-4 (2013), 207–216. DOI: <http://dx.doi.org/10.1002/ijch.201300024>
- [8] Joseph Anthony C. Hermocilla. 2014. P2C: Towards Scientific Computing on Private Clouds. In *Proceedings of the National Conference on Information Technology Education (NCITE 2014)*. 162–167.
- [9] Zach Hill and Marty Humphrey. 2009. A Quantitative Analysis of High Performance Computing with Amazon EC2 Infrastructure: The Death of the Local Cluster?. In *Proceedings of the 10th IEEE/ ACM International Conference on Grid Computing (Grid 2009)*. <http://www.cs.virginia.edu/~humphrey/papers/QuantitativeAnalysisEC2.pdf>
- [10] Adam A. Hunter, Andrew B. Macgregor, Tamas O. Szabo, Crispin A. Wellington, and Matthew I. Bellgard. 2012. Yabi: An online research environment for grid, high performance and cloud computing. *Source Code for Biology and Medicine* 7, 1 (2012), 1 – 10. <http://search.ebscohost.com/login.aspx?direct=true&db=a9h&AN=74110216&site=ehost-live>
- [11] Alexandru Iosup, Simon Ostermann, Nezhir Yigitbasi, Radu Prodan, Thomas Fahrigner, and Dick Epema. 2010. Performance Analysis of Cloud Computing Services for Many-Tasks Scientific Computing. (Nov 2010). <http://www.st.eui.tudelft.nl/~iosup/cloud-perf10tpds.in-print.pdf>
- [12] Keith Jackson, Krishna Muriki, Shane Canon, Shreyas Cholia, John Shalf, Harvey Wasserman, and Nicholas Wright. 2010. Performance Analysis of High Performance Computing Applications on the Amazon Web Services Cloud. (2010). <https://www.nersc.gov/assets/NERSC-Staff-Publications/2010/CloudComp.pdf>
- [13] Gideon Juve, Ewa Deelman, Karan Vahi, Gaurang Mehta, Bruce Berriman, Benjamin P. Berman, and Phil Maechling. 2009. Scientific workflow applications on Amazon EC2. In *2009 5th IEEE International Conference on E-Science Workshops*. IEEE, 59–66. http://ieeexplore.ieee.org/xpls/abs_all.jsp?arnumber=5408002
- [14] P. T. Lang, S. R. Brozell, S. Mukherjee, E. T. Pettersen, E. C. Meng, V. Thomas, R. C. Rizzo, D. A. Case, T. L. James, and I. D. Kuntz. 2009. DOCK 6: Combining Techniques to Model RNA-Small Molecule Complexes. *RNA* 15 (2009), 1219–1230.
- [15] Matthew L. Massie, Brent N. Chun, and David E. Culler. 2004. The ganglia distributed monitoring system: design, implementation, and experience. *Parallel Comput.* 30, 7 (2004), 817 – 840. <http://search.ebscohost.com/login.aspx?direct=true&db=a9h&AN=13956548&site=ehost-live>
- [16] G. M. Morris, R. Huey, W. Lindstrom, M. F. Sanner, R. K. Belew, D. S. Goodsell, and A. J. Olson. 2009. Autodock4 and AutoDockTools4: automated docking with selective receptor flexibility. *J. Computational Chemistry* 2009 (2009), 2785–91.
- [17] Michael W. Schmidt, Kim K. Baldrige, Jerry A. Boatz, Steven T. Elbert, Mark S. Gordon, Jan H. Jensen, Shiro Koseki, Nikita Matsunaga, Kiet A. Nguyen, Shujun Su, Theresa L. Windus, Michel Dupuis, and John A. Montgomery. 1993. General atomic and molecular electronic structure system. *Journal of Computational Chemistry* 14, 11 (1993), 1347–1363. DOI: <http://dx.doi.org/10.1002/jcc.540141112>
- [18] Parichit Sharma and Shrikant S. Mantri. 2014. WImpiBLAST: Web Interface for mpiBLAST to Help Biologists Perform Large-Scale Annotation Using High Performance Computing. *PLoS ONE* 9, 6 (2014), 1 – 13. <http://search.ebscohost.com/login.aspx?direct=true&db=a9h&AN=96861207&site=ehost-live>
- [19] Oleg Trott and Arthur J. Olson. 2010. AutoDock Vina: Improving the speed and accuracy of docking with a new scoring function, efficient optimization, and multithreading. *Journal of Computational Chemistry* 31, 2 (2010), 455–461. DOI: <http://dx.doi.org/10.1002/jcc.21334>
- [20] Edward Walker. 2008. Benchmarking Amazon EC2 for High-Performance Scientific Computing. (Oct 2008). <https://www.usenix.org/legacy/publications/login/2008-10/openpdfs/walker.pdf>