

VLAN	Name	Status	Ports
1	default	active	Fa0/10, Fa0/11, Fa0/12, Fa0/13 Fa0/14, Fa0/15, Fa0/16, Fa0/17 Fa0/18, Fa0/19, Fa0/20, Fa0/21 Fa0/22, Fa0/23, Fa0/24, Gig0/2
10	SALES	active	Fa0/1, Fa0/2, Fa0/3, Fa0/4
20	FINANCE	active	Fa0/5, Fa0/6, Fa0/7, Fa0/8 Fa0/9
1002	fddi-default	active	
1003	token-ring-default	active	
1004	fddinet-default	active	
1005	trnet-default	active	
SWITCH_0#			
SWITCH_0#SHOW INTERFACES TRUNK			
Port	Mode	Encapsulation	Status Native vlan
Gig0/1	on	802.1q	trunking 1001
Port	Vlans allowed on trunk		
Gig0/1	10,20		
Port	Vlans allowed and active in management domain		
Gig0/1	10,20		
Port	Vlans in spanning tree forwarding state and not pruned		
Gig0/1	10,20		
SWITCH_0#			

SWITCH_1#SHOW VLAN BRIEF

VLAN Name	Status	Ports
1 default	active	Fa0/7, Fa0/8, Fa0/9, Fa0/10 Fa0/11, Fa0/12, Fa0/13, Fa0/14 Fa0/15, Fa0/16, Fa0/17, Fa0/18 Fa0/19, Fa0/20, Fa0/21, Fa0/22 Fa0/23, Fa0/24
10 SALES	active	Fa0/4, Fa0/5, Fa0/6
20 VLAN0020	active	
30 MARKETING	active	Fa0/1, Fa0/2, Fa0/3
1002 fddi-default	active	
1003 token-ring-default	active	
1004 fddinet-default	active	
1005 trnet-default	active	

SWITCH_1#

SWITCH_1#SHOW INTERFACES TRUNK

Port	Mode	Encapsulation	Status	Native vlan
Gig0/1	on	802.1q	trunking	1001
Gig0/2	on	802.1q	trunking	1001

Port Vlans allowed on trunk

Gig0/1	10,20
Gig0/2	2-1005

Port Vlans allowed and active in management domain

Gig0/1	10,20
Gig0/2	10,20,30

Port Vlans in spanning tree forwarding state and not pruned

Gig0/1	10,20
Gig0/2	10,20,30

SWITCH_1#

Router#SHOW IP ROUTE

Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP
D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
E1 - OSPF external type 1, E2 - OSPF external type 2, E - EGP
i - IS-IS, L1 - IS-IS level-1, L2 - IS-IS level-2, ia - IS-IS inter area
* - candidate default, U - per-user static route, o - ODR
P - periodic downloaded static route

Gateway of last resort is not set

192.168.0.0/24 is variably subnetted, 6 subnets, 3 masks

C	192.168.0.0/28 is directly connected, GigabitEthernet0/0.10
L	192.168.0.14/32 is directly connected, GigabitEthernet0/0.10
C	192.168.0.16/29 is directly connected, GigabitEthernet0/0.20
L	192.168.0.22/32 is directly connected, GigabitEthernet0/0.20
C	192.168.0.24/29 is directly connected, GigabitEthernet0/0.30
L	192.168.0.30/32 is directly connected, GigabitEthernet0/0.30

Router#

Ping from PC0 SALES VLAN to PC10 from MARKETING VLAN.

```
Cisco Packet Tracer PC Command Line 1.0
C:\>ipconfig

FastEthernet0 Connection:(default port)

    Connection-specific DNS Suffix...:
    Link-local IPv6 Address.....: FE80::240:BFF:FEE7:D0E
    IPv6 Address.....: ::
    IPv4 Address.....: 192.168.0.1
    Subnet Mask.....: 255.255.255.240
    Default Gateway.....: ::
                        192.168.0.14

Bluetooth Connection:

    Connection-specific DNS Suffix...:
    Link-local IPv6 Address.....: ::
    IPv6 Address.....: ::
    IPv4 Address.....: 0.0.0.0
    Subnet Mask.....: 0.0.0.0
    Default Gateway.....: ::
                        0.0.0.0

C:\>ping 192.168.0.25

Pinging 192.168.0.25 with 32 bytes of data:

Request timed out.
Reply from 192.168.0.25: bytes=32 time=10ms TTL=127
Reply from 192.168.0.25: bytes=32 time=10ms TTL=127
Reply from 192.168.0.25: bytes=32 time=10ms TTL=127

Ping statistics for 192.168.0.25:
    Packets: Sent = 4, Received = 3, Lost = 1 (25% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 10ms, Maximum = 10ms, Average = 10ms

C:\>|
```