


[Home](#)[Compiler](#)[Automata](#)[AWS](#)[IoT](#)[Computer Fundamentals](#)[Control System](#)[Java](#)[HTML](#)[CSS](#)

Simplification of CFG

As we have seen, various languages can efficiently be represented by a context-free grammar. All the grammar are not always optimized that means the grammar may consist of some extra symbols(non-terminal). Having extra symbols, unnecessary increase the length of grammar. Simplification of grammar means reduction of grammar by removing useless symbols. The properties of reduced grammar are given below:

1. Each variable (i.e. non-terminal) and each terminal of G appears in the derivation of some word in L .
2. There should not be any production as $X \rightarrow Y$ where X and Y are non-terminal.
3. If ϵ is not in the language L then there need not to be the production $X \rightarrow \epsilon$.

Let us study the reduction process in detail./p>



Removal of Useless Symbols

A symbol can be useless if it does not appear on the right-hand side of the production rule and does not take part in the derivation of any string. That symbol is known as a useless symbol. Similarly, a variable can be useless if it does not take part in the derivation of any string. That variable is known as a useless variable.

For Example:

```
T → aaB | abA | aaT
A → aA
B → ab | b
C → ad
```

In the above example, the variable 'C' will never occur in the derivation of any string, so the production $C \rightarrow ad$ is useless. So we will eliminate it, and the other productions are written in such a way that variable C can never reach from the starting variable 'T'.

Production $A \rightarrow aA$ is also useless because there is no way to terminate it. If it never terminates, then it can never produce a string. Hence this production can never take part in any derivation.

To remove this useless production $A \rightarrow aA$, we will first find all the variables which will never lead to a terminal string such as variable 'A'. Then we will remove all the productions in which the variable 'B' occurs.

Elimination of ϵ Production

The productions of type $S \rightarrow \epsilon$ are called ϵ productions. These type of productions can only be removed from those grammars that do not generate ϵ .

Step 1: First find out all nullable non-terminal variable which derives ϵ .

Step 2: For each production $A \rightarrow a$, construct all production $A \rightarrow x$, where x is obtained from a by removing one or more non-terminal from step 1.

Step 3: Now combine the result of step 2 with the original production and remove ϵ productions.

Example:

Remove the production from the following CFG by preserving the meaning of it.

```
S → XYX  
X → 0X |  $\epsilon$   
Y → 1Y |  $\epsilon$ 
```

Solution:

Now, while removing ϵ production, we are deleting the rule $X \rightarrow \epsilon$ and $Y \rightarrow \epsilon$. To preserve the meaning of CFG we are actually placing ϵ at the right-hand side whenever X and Y have appeared.

Let us take

```
S → XYX
```

If the first X at right-hand side is ϵ . Then

$$S \rightarrow YX$$

Similarly if the last X in R.H.S. = ϵ . Then

$$S \rightarrow XY$$

If $Y = \epsilon$ then

$$S \rightarrow XX$$

If Y and X are ϵ then,

$$S \rightarrow X$$

If both X are replaced by ϵ

$$S \rightarrow Y$$

Now,

$$S \rightarrow XY \mid YX \mid XX \mid X \mid Y$$

Now let us consider

$$X \rightarrow 0X$$

If we place ϵ at right-hand side for X then,

$$X \rightarrow 0$$

$$X \rightarrow 0X \mid 0$$

Similarly $Y \rightarrow 1Y \mid 1$

Collectively we can rewrite the CFG with removed ϵ production as

```
S → XY | YX | XX | X | Y  
X → 0X | 0  
Y → 1Y | 1
```

Removing Unit Productions

The unit productions are the productions in which one non-terminal gives another non-terminal. Use the following steps to remove unit production:

Step 1: To remove $X \rightarrow Y$, add production $X \rightarrow a$ to the grammar rule whenever $Y \rightarrow a$ occurs in the grammar.

Step 2: Now delete $X \rightarrow Y$ from the grammar.

Step 3: Repeat step 1 and step 2 until all unit productions are removed.

For example:

```
S → 0A | 1B | C  
A → 0S | 00  
B → 1 | A  
C → 01
```

Solution:

$S \rightarrow C$ is a unit production. But while removing $S \rightarrow C$ we have to consider what C gives. So, we can add a rule to S .

```
S → 0A | 1B | 01
```

Similarly, $B \rightarrow A$ is also a unit production so we can modify it as

```
B → 1 | 0S | 00
```

Thus finally we can write CFG without unit production as

```
S → 0A | 1B | 01
```

A → 0S | 00
B → 1 | 0S | 00
C → 01

← Prev

Next →

 Youtube For Videos Join Our Youtube Channel: [Join Now](#)

Feedback

- Send your Feedback to feedback@javatpoint.com




Help Others, Please Share








Learn Latest Tutorials

 [Splunk tutorial](#)













 [SPSS tutorial](#)

 Splunk	 SPSS	 Swagger tutorial Swagger	 T-SQL tutorial Transact-SQL	 Tumblr tutorial Tumblr
 React tutorial ReactJS	 Regex tutorial Regex	 Reinforcement learning tutorial Reinforcement Learning	 R Programming tutorial R Programming	 RxJS tutorial RxJS
 React Native tutorial React Native	 Python Design Patterns Python Design Patterns	 Python Pillow tutorial Python Pillow	 Python Turtle tutorial Python Turtle	 Keras tutorial Keras


Preparation


 Aptitude Aptitude	 Logical Reasoning Reasoning	 Verbal Ability Verbal Ability	 Interview Questions Interview Questions	 Company Interview Questions Company Questions
--	--	--	--	--


Trending Technologies


 Artificial Intelligence Tutorial Artificial Intelligence	 AWS Tutorial AWS	 Selenium tutorial Selenium	 Cloud Computing tutorial Cloud Computing	 Hadoop tutorial Hadoop
 ReactJS Tutorial ReactJS	 Data Science Tutorial Data Science	 Angular 7 Tutorial Angular 7	 Blockchain Tutorial Blockchain	 Git Tutorial Git
 Machine Learning Tutorial Machine Learning	 DevOps Tutorial DevOps			


B.Tech / MCA

 DBMS tutorial
DBMS


 Data Structures
tutorial
Data Structures


 DAA tutorial
DAA

 Operating
System tutorial
Operating System


 Computer
Network tutorial
Computer Network


 Compiler
Design tutorial
Compiler Design


 Computer
Organization and
Architecture
Computer
Organization

 Discrete
Mathematics
Tutorial
Discrete
Mathematics

 Ethical Hacking
Tutorial
Ethical Hacking


 Computer
Graphics Tutorial
Computer Graphics


 Software
Engineering
Tutorial
Software
Engineering


 html tutorial
Web Technology


 Cyber Security
tutorial
Cyber Security


 Automata
Tutorial
Automata


 C Language
tutorial
C Programming


 C++ tutorial
C++

 Java tutorial
Java

 .Net
Framework
tutorial
.Net

 Python tutorial
Python

 List of
Programs
Programs

 Control
Systems tutorial
Control System

 Data Mining
Tutorial
Data Mining

 Data
Warehouse
Tutorial
Data Warehouse

