

Join algorithms in Database

Difficulty Level: Easy • Last Updated: 24 Dec, 2021

Read Discuss

There are two algorithms to compute natural join and conditional join of two relations in database: Nested loop join, and Block nested loop join.

To understand these algorithms we will assume there are two relations, relation R and relation S. Relation R has T_R tuples and occupies B_R blocks. Relation S has T_S tuples and occupies B_S blocks. We will also assume relation R is the outer relation and S is the inner relation.

Nested Loop Join

In the nested loop join algorithm, for each tuple in outer relation, we have to compare it with all the tuples in the inner relation then only the next tuple of outer relation is considered. All pairs of tuples which satisfy the condition are added in the result of the join.

This algorithm is called nested join because it consists of nested for loops.


We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our Cookie Policy & Privacy Policy

Login

Register


Let's see some cases to understand the performance of this algorithm,

Case-1: Assume only two blocks of main memory are available to store blocks from R and S relation.



So, the total block transfers needed = $T_R * B_S + B_R$

Case-2: Assume one relation fits entirely in the main memory and there is at least space for one extra block.



In this case, the blocks of relation S (that is, the inner relation) are only transferred once and kept in the main memory and the blocks of relation R are transferred sequentially. So, all the blocks of both the relation are transferred only once.

So, the total block transfers needed = $B_R + B_S$

The relation with a lesser number of blocks should be the outer relation to minimizing the total number of blocks access required in the main memory to complete the join. That is, $min(B_R, B_S)+1$ is the minimum number of blocks in the main memory required to join two relations so that no block is transferred more than once.

In nested loop join, more access cost is required to join relations if the main memory space allocated for join is very limited.

Block Nested Loop Join:

In block nested loop ining for a block of outer relation, all the tuples in that block are

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our <u>Cookie Policy & Privacy Policy</u>


```
for each tuple t_R in T_R do

for each tuple t_S in T_S do

compare (t_R, t_S) if they satisfies the condition add them in the result of the join end end end end
```

Let's look at some similar cases as nested loop join,


Case-1: Assume only two blocks of main memory are available to store blocks from R and S relation.



For each block of relation R, we have to transfer all blocks of relation S and each block of relation R should be transferred only once.

So, the total block transfers needed = $B_R + B_R * B_S$

Case-2: Assume one relation fits entirely in the main memory and there is at least space for one extra block.



In this case, total block transfers needed are similar to nested loop join.

Block nested loop join algorithm reduces the access cost compared to nested loop join if the main memory space allocated for join is limited.

Related GATE questions:

- Gate IT 2005 | Question 84
- <u>Gate IT 2005 | Question 85</u>

Related Articles

- 1. SQL | Join (Cartesian Join & Self Join)
- 2. Inner Join vs Outer Join
- 3. Difference between Inner Join and Outer Join in SQL
- 4. Difference between Natural join and Inner Join in SQL
- 5. Difference between Natural join and Cross join in SQL
- 6. Full join and Inner join in MS SQL Server
- 7. Left join and Right join in MS SQL Server

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our <u>Cookie Policy</u> & <u>Privacy Policy</u>

10. Difference between Hash Join and Sort Merge Join

Like 1

Previous

Article Contributed By:



Vote for difficulty

Current difficulty: Easy

Easy Normal Medium Hard Expert

Improved By: devanidarshak01

Article Tags: DBMS, GATE CS

Practice Tags: DBMS

Improve Article Report Issue

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our <u>Cookie Policy</u> & <u>Privacy Policy</u>

Sector-136, Noida, Uttar Pradesn - 201305

feedback@geeksforgeeks.org

Company	Learn
About Us	DSA
Careers	Algorithms
In Media	Data Structures
Contact Us	SDE Cheat Sheet
Privacy Policy	Machine learning
Copyright Policy	CS Subjects
Advertise with us	Video Tutorials
	Courses

News	Languages
Top News	Python
Technology	Java
Work & Career	CPP
Business	Golang
Finance	C#
Lifestyle	SQL
Knowledge	Kotlin

Web Development

Web Tutorials	Write an Article
Django Tutorial	Improve an Article
HTML	Pick Topics to Write
JavaScript	Write Interview Experience
Bootstrap	Internships

Contribute

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our Cookie Policy & Privacy Policy



We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our <u>Cookie Policy</u> & <u>Privacy Policy</u>