

MongoDB Commands with Typical Ubuntu

`mongosh` Output

Start Mongo Shell

```
mongosh
```

Output

```
Current Mongosh Log ID: 6644fcbf6c3e3f6f6d0f1abc
Connecting to:          mongodb://127.0.0.1:27017/?
directConnection=true&serverSelectionTimeoutMS=2000&appName=mongosh+2.2.6
Using MongoDB:          6.0.14
Using Mongosh:           2.2.6

For mongosh info see: https://www.mongodb.com/docs/mongosh-shell/

-----
  The server generated these startup warnings when booting
  2026-05-15T10:20:11.111+00:00: Access control is not enabled for the
  database.
  -----

test>
```

1. Create / Switch Database

```
use mydb
```

Output

```
switched to db mydb
```

2. Create Collection

```
db.createCollection("users")
```

Output

```
{ ok: 1 }
```

3. Insert One Document

```
db.users.insertOne({
  name: "Alice",
  age: 25,
  city: "Bangalore"
})
```

Output

```
{
  acknowledged: true,
  insertedId: ObjectId('6644fd1c6c3e3f6f6d0f1abd')
}
```

4. Insert Multiple Documents

```
db.users.insertMany([
  { name: "Bob", age: 30 },
  { name: "Charlie", age: 28 }
])
```

Output

```
{
  acknowledged: true,
  insertedIds: {
    '0': ObjectId('6644fd506c3e3f6f6d0f1abe'),
    '1': ObjectId('6644fd506c3e3f6f6d0f1abf')
  }
}
```

5. Find All Documents

```
db.users.find()
```

Output

```
[
  {
    _id: ObjectId('6644fd1c6c3e3f6f6d0f1abd'),
    name: 'Alice',
    age: 25,
    city: 'Bangalore'
  },
  {
    _id: ObjectId('6644fd506c3e3f6f6d0f1abe'),
    name: 'Bob',
    age: 30
  },
  {
    _id: ObjectId('6644fd506c3e3f6f6d0f1abf'),
    name: 'Charlie',
    age: 28
  }
]
```

6. Pretty Format

```
db.users.find().pretty()
```

Output

```
{
  _id: ObjectId('6644fd1c6c3e3f6f6d0f1abd'),
  name: 'Alice',
  age: 25,
  city: 'Bangalore'
}
{
  _id: ObjectId('6644fd506c3e3f6f6d0f1abe'),
  name: 'Bob',
  age: 30
}
{
  _id: ObjectId('6644fd506c3e3f6f6d0f1abf'),
```

```
    name: 'Charlie',  
    age: 28  
  }
```

7. Find Specific Document

```
db.users.find({ name: "Alice" })
```

Output

```
[  
  {  
    _id: ObjectId('6644fd1c6c3e3f6f6d0f1abd'),  
    name: 'Alice',  
    age: 25,  
    city: 'Bangalore'  
  }  
]
```

8. Update One Document

```
db.users.updateOne(  
  { name: "Alice" },  
  { $set: { age: 26 } }  
)
```

Output

```
{  
  acknowledged: true,  
  insertedId: null,  
  matchedCount: 1,  
  modifiedCount: 1,  
  upsertedCount: 0  
}
```

9. Update Multiple Documents

```
db.users.updateMany(  
  {},  
  { $set: { active: true } }  
)
```

Output

```
{  
  acknowledged: true,  
  insertedId: null,  
  matchedCount: 3,  
  modifiedCount: 3,  
  upsertedCount: 0  
}
```

10. Verify Updated Documents

```
db.users.find().pretty()
```

Output

```
{  
  _id: ObjectId('6644fd1c6c3e3f6f6d0f1abd'),  
  name: 'Alice',  
  age: 26,  
  city: 'Bangalore',  
  active: true  
}  
{  
  _id: ObjectId('6644fd506c3e3f6f6d0f1abe'),  
  name: 'Bob',  
  age: 30,  
  active: true  
}  
{  
  _id: ObjectId('6644fd506c3e3f6f6d0f1abf'),  
  name: 'Charlie',  
  age: 28,  
  active: true  
}
```

11. Delete One Document

```
db.users.deleteOne({ name: "Bob" })
```

Output

```
{ acknowledged: true, deletedCount: 1 }
```

12. Delete Multiple Documents

```
db.users.deleteMany({ age: { $lt: 29 } })
```

Output

```
{ acknowledged: true, deletedCount: 2 }
```

13. Show Databases

```
show dbs
```

Output

```
admin    40.00 KiB
config  72.00 KiB
local    72.00 KiB
mydb     40.00 KiB
```

14. Show Collections

```
show collections
```

Output

```
users
```

15. Drop Collection

```
db.users.drop()
```

Output

```
true
```

16. Drop Database

```
db.dropDatabase()
```

Output

```
{ ok: 1, dropped: 'mydb' }
```