

stored procedure

it is a precompiled version of set
of statements

queries

use mydatabase;

select * from student;

delimiter //

create procedure procedure1()
begin

select * from student;

select * from sports;

```
end;
```

```
//
```

```
delimiter ;
```

```
call procedure1();
```

stored procedure with parameter
[also known as stored procedure
INPUT parameter]

```
query
```

```
-----
```

```
use mydatabase;
```

```
select * from student;
```

```
delimiter //
```

```
create procedure procedure2( rno
int)
begin

select * from student where rollno =
rno;

end;

//
delimiter ;

call procedure2(3);

storing table value into temporary
variable
-----
-----

use mydatabase;
```

```
select * from student;
```

```
select mark into @smark from student  
where rollno = 3;  
select @smark;
```

```
select mark into @smark from student  
where rollno = 3;  
select @smark as 'result';
```

```
select mark into @smark from student  
where rollno = 3;  
select concat(' result is ', @smark  
) as 'result';
```

stored procedure with 'OUT'
parameter

out parameters taking out the

values from the procedure block

query

drop procedure procedure3;

delimiter //

create procedure procedure3(rno int,
out smark int)

begin

select mark into smark from student
where rollno = rno;

end;

//

delimiter ;

```
call procedure3(3, @smark);  
select concat(' result is ', @smark)  
as 'result';
```