SEWAGE MONITORING SYSTEM

A PROJECT REPORT

Submitted by

SRIATCHAYA N

THARANEESWARAN S

in partial fulfillment of the requirement

for the award of the degree

of

BACHELOR OF ENGINEERING

In

ELECTRONICS AND COMMUNICATION ENGINEERING

K.S. RANGASAMY COLLEGE OF TECHNOLOGY

(Autonomous)

TIRUCHENGODE – 637 215

APRIL 2026

K.S. RANGASAMY COLLEGE OF T ECHNOLOGY
TIRUCHENGODE - 637 215

BONAFIDE CERTIFICATE

Certified that this project report titled **"SEWAGE MONITORING SYSTEM"** is the bonafide work of **SRIATCHAYA N (73772213203)** and**THARANEESWARAN S (73772213209)** who carried out the project under my supervision. Certified further, that to the best of my knowledge the work reported herein does not form part of any other project report or dissertation on the basis of which a degree or award was conferred on an earlier occasion on this or any other candidate.

SIGNATURE

Mr.R.Mohanraj , B.E, M.Tech, (Ph.D)

SUPERVISOR

Assistant Professor

Department of Electronics and Communication Engineering

SIGNATURE

Dr.C.Rajasekaran, M.E., Ph.D

HEAD OF THE DEPARTMENT

Department of Electronics and Communication Engineering

Submitted for the viva-voce examination held on ……

Internal Examiner **External Examiner**

DECLARATION

We jointly declare that the project report on **"SEWAGE MONITORING SYSTEM"** is the result of original work done by us and best of our knowledge, similar work has not been submitted to **"ANNA UNIVERSITY, CHENNAI"** for the requirement of Degree of Bachelor of Engineering in Electronics and Communication Engineering. This project report is submitted on the partial fulfilment of the requirement of the award of Degree of Bachelor of Engineering in Electronics and Communication Engineering.

Signature

SRIATCHAYA N

THARANEESWARAN S

Place: Tiruchengode

Date:

ACKNOWLEDGEMENT

We wish to express our sincere gratitude to our Honorable Chairman **Thiru. R. SRINIVASAN, B.B.M.,** for providing immense facilities at our institution.

We would like to express our sincere gratitude to our Vice Chairman, **Thiru. K. S. SACHIN, MBA (UK).,** for providing a supportive environment for the completion of our project work.

We are truly grateful to express our gratitude to our beloved Principal **Dr. R. GOPALAKRISHNAN, M.E., Ph.D.,** for the encouragement given towards the progress and completion of our project.

We proudly render our immense gratitude to the Head of the Department **Dr. C. RAJASEKARAN, M.E., Ph.D.,** for his effective leadership, encouragement and guidance in the project.

We are highly indebted to provide our heartfelt thanks to our supervisor **Mr. R. MOHANRAJ,B.E., M.TECH., (Ph.D)**for his valuable ideas, encouragement and supportive guidance throughout the project.

We wish to extend our sincere thanks to all faculty members of **Department of Electronics and Communication Engineering,** for their valuable suggestions, kind co-operation and constant encouragement for successful completion of this project.

We wish to acknowledge the help received from various Departments, individuals, and the AICTE IDEA Lab facilities in the successful completion of this project.

ABSTRACT

Sewage maintenance workers often work in underground environments where harmful gases and poor ventilation can create dangerous conditions. During the decomposition of waste, toxic gases such as methane (CH_4), hydrogen sulfide (H_2S), ammonia (NH_3), and carbon monoxide (CO) are released, which can cause serious health issues like breathing problems, unconsciousness, and even death. Traditional monitoring methods mostly depend on manual checking or portable gas detectors, which do not provide continuous monitoring or immediate alerts, making them less effective in ensuring worker safety.This project proposes an IoT-based sewage monitoring system that continuously monitors environmental conditions in real time. The system uses gas sensors along with temperature and humidity sensors to detect changes in the environment. A microcontroller processes the sensor data and compares it with predefined safety levels. If any parameter exceeds the safe limit, the system immediately triggers an alert using a buzzer and also sends a warning message through wireless communication modules such as Wi-Fi or LoRa. The system is designed to be low-cost, portable, and easy to use, making it suitable for real-time deployment in sewage environments. In addition to safety monitoring, the proposed system also supports real-time data visualization and remote supervision, allowing authorities to track environmental conditions without physically entering hazardous areas. The continuous data collection helps in maintaining records that can be used for analysis and decision-making. This improves not only worker safety but also operational efficiency in sewage management. By reducing the need for manual inspection and enabling faster emergency response, the system contributes to safer and smarter urban infrastructure.

Keywords: *Internet of Things (IoT), Sewage Monitoring, Gas Detection, Wireless Communication, Worker Safety, Environmental Monitoring*

This Sewage Monitoring System aligns with using IoT technology to improve infrastructure safety. It enables real-time monitoring of hazardous gases, ensuring better protection for sewage worker. The system promotes innovation by providing a smart, reliable, and efficient solution for modern sewage management.

TABLE OF CONTENTS

CHAPTER	TITLE	PAGE NO.
	ABSTRACT	v
	LIST OF FIGURES	viii
	LIST OF ABBREVIATIONS	ix
1	**INTRODUCTION**	**1**
	1.1 PROBLEM STATEMENT	2
	1.2 LAGS IN EXISTING SYSTEM	3
2	**LITERATURE REVIEW**	**5**
	2.1 FINDINGS FROM RELATED PAPERS	6
	2.2 CONCLUSIONS FROM THE LITERATURE REVIEW	9
3	**PROPOSED SYSTEM AND METHODOLOGY**	**11**
	3.1 MATERIALS	11
	3.1.1 EMBEDDED SYSTEM AND PROGRAMMING ENVIRONMENT	12
	3.1.2 SENSORS AND COMMUNICATION MODULES	13
	3.2 BLOCK DIAGRAM	16
	3.3 SYSTEM COMMUNICATION APPROACH	17
	3.4 USER INTERFACE AND EXPERIENCE DESIGN	17
	3.5 DATA PROGRESSING AND THRESHOLD ANALYSIS	18
	3.6 ALERT GENERATION AND COMMUNICATION	19
4	**EXPERIMENTAL SETUP AND PROCEDURE**	**20**
	4.1 EXPERIMENTAL SETUP	20
	4.2 EXPERIMENTAL PROCEDURE	21
	4.3 DATA ACQUISTION AND SOURCES	22
	4.4 SENSOR DATA PROCESSING AND CALIBRATION	24
	4.5 THRESHOLD ANALYSIS AND DECISION MECHANISM	25
	4.6 REAL-TIME MONITORING AND ALERT SYSTEM	26
	4.7 SECURITY APPROACH	26

5 RESULTS AND DISCUSSION 28

5.1 SYSTEM HARDWARE PERFORMANCE 28
5.2 COMMUNICATION AND DATA TRANSMISSION RESULTS 29
5.3 SENSOR PERFORMANCE AND DATA ANALYSIS 30
5.4 OUTPUT RESULTS AND SYSTEM EFFECTIVESS 31
5.5 DISCUSSION 32

6 CONCLUSION 35
7 REFERENCE 37
LIST OF PUBLICATIONS 39
APPENDIX 1 41

LIST OF FIGURES

FIGURE NO.	TITLE	PAGE NO.
3.1	ESP8266	14
3.2	System Dashboard	15
3.3	Block diagram	16
5.1	Software Flowchart	30
5.2	System Output	32

LIST OF ABBREVIATIONS

GSM – Global System for Mobile Communication

Wi-Fi – Wireless Fidelity

LoRa – Long Range Communication

WSN – Wireless Sensor Network

PCB – Printed Circuit Board

ADC – Analog to Digital Converter

GPS – Global Positioning System

CHAPTER 1

INTRODUCTION

Sewage management plays a vital role in maintaining public health, environmental safety, and urban sanitation. It involves the collection, treatment, and disposal of wastewater generated from residential, industrial, and commercial sources. Workers engaged in sewage maintenance are responsible for inspecting, cleaning, and repairing underground drainage systems such as pipelines, septic tanks, and manholes. However, these environments are highly dangerous due to the presence of toxic gases, limited ventilation, high humidity, and confined working conditions. During the natural decomposition of organic waste materials, harmful gases such as methane (CH_4), hydrogen sulfide (H_2S), ammonia (NH_3), and carbon monoxide (CO) are produced. These gases can accumulate in enclosed spaces and reach dangerous levels without warning.

Exposure to such toxic gases can cause severe health issues including breathing difficulties, eye irritation, dizziness, nausea, unconsciousness, and even death. Hydrogen sulfide, for instance, is extremely dangerous even at low concentrations and can quickly lead to fatal consequences. Methane is highly flammable and poses an explosion risk, while carbon monoxide is a colorless and odorless gas that can silently affect workers without immediate detection. In many cases, accidents occur due to the lack of proper monitoring systems and delayed detection of hazardous conditions. Despite advancements in safety regulations, many sewage maintenance operations still rely on traditional practices that are insufficient for ensuring worker safety.

With the rapid growth of urban populations and expansion of sewage infrastructure, the need for advanced monitoring solutions has become increasingly important. The Internet of Things (IoT) has emerged as a powerful technology that enables real-time monitoring, data collection, and remote communication. By integrating sensors, microcontrollers, and wireless communication systems, IoT-based solutions can continuously monitor environmental conditions and provide immediate alerts when unsafe situations arise. This project aims to develop an IoT-based sewage monitoring system that enhances worker safety by detecting hazardous gases and environmental parameters in real time and providing timely warnings to prevent accidents.

1.1 PROBLEM STATEMENT

Sewage management has become a critical concern in modern urban environments, as it directly impacts public health, environmental safety, and infrastructure sustainability. The increasing population and rapid urbanization have led to the expansion of sewage systems, making their maintenance more complex and hazardous. During the decomposition of waste materials, toxic gases such as methane, hydrogen sulfide, ammonia, and carbon monoxide are released. These gases accumulate in confined underground spaces, creating dangerous conditions for sewage maintenance workers. Ensuring safe working conditions and timely monitoring of these environments is essential to prevent accidents and protect human lives.

However, existing methods for monitoring sewage environments face several limitations. Traditional approaches mainly rely on manual inspection and portable gas detection devices. These methods are time-consuming, require human intervention, and do not provide continuous monitoring. Workers are often exposed to hazardous environments while performing inspections, increasing the risk of health issues and accidents. Moreover, portable devices provide only temporary readings and fail to detect sudden changes in gas concentrations, making them unreliable for real-time safety assurance.

In addition, many existing systems focus only on basic gas detection without providing a comprehensive analysis of environmental conditions. Important parameters such as temperature, humidity, and variations in gas levels over time are often not considered. This limits the ability to fully understand the severity of hazardous conditions inside sewage systems. Without detailed monitoring and analysis, it becomes difficult to predict dangerous situations and take preventive actions.

Another major limitation is the lack of real-time monitoring and remote accessibility. Most traditional systems do not support continuous data transmission or remote supervision, making it difficult for authorities to monitor conditions inside sewage systems from a safe location. In emergency situations, delays in detecting hazardous conditions and communicating warnings can lead to serious consequences, including injuries and fatalities. There is a clear need for systems that provide instant alerts and allow authorities to respond quickly.

Furthermore, existing solutions often lack user-friendly interfaces and integrated platforms for data visualization. Many monitoring systems are complex and require technical expertise to operate, which reduces their practical usability.

To address these challenges, there is a need for an automated and intelligent system that can continuously monitor sewage environments, detect hazardous gas levels, and provide real-time alerts. The system should be capable of analysing environmental conditions accurately and transmitting data to remote locations for effective supervision. Additionally, it should offer an easy-to-use interface that allows users to monitor conditions and respond to emergencies without requiring specialized technical knowledge.

Therefore, this project aims to develop an IoT-based sewage monitoring system integrated with real-time sensing, wireless communication, and alert mechanisms. The proposed system ensures continuous monitoring of toxic gases and environmental parameters, providing timely warnings and remote accessibility. This approach enhances worker safety, reduces dependency on manual inspection, and supports the development of safer and more efficient sewage management systems.

Another major problem is the lack of remote monitoring and communication systems. Supervisory authorities are often unaware of real-time conditions inside sewage systems, making it difficult to take preventive actions. Delayed response during emergencies further increases the risk to workers. Therefore, there is a critical need for an automated, reliable, and real-time monitoring system that can continuously track environmental conditions, detect hazardous gases, and provide immediate alerts to both workers and authorities.

1.2 LAGS IN EXISTING METHODS

Despite the availability of various techniques for monitoring sewage environments, existing methods still face several limitations that affect their efficiency, accuracy, and practical usability. These gaps highlight the need for more advanced and reliable solutions to ensure the safety of sewage maintenance workers and improve environmental monitoring.

One of the major limitations of traditional methods is their heavy dependence on manual efforts. Sewage monitoring is often carried out through physical inspection and the use of portable gas detectors, which require workers to enter hazardous underground environments. These approaches are time-consuming, labor-intensive, and expose workers to dangerous conditions. As a result, ensuring continuous safety becomes difficult, especially in confined spaces where gas levels can change rapidly.

Another significant drawback is the lack of continuous and automated monitoring. Most existing systems provide only momentary readings rather than real-time tracking of environmental conditions. Without automation, it becomes challenging to detect sudden increases in toxic gas levels, leading to delayed response and increased risk of accidents.

Existing methods also often focus only on basic gas detection without providing a comprehensive analysis of environmental conditions. While detecting gases such as methane or carbon monoxide is important, other critical parameters like temperature, humidity, and variations in gas concentration over time are not adequately monitored. This limits the ability to fully understand the severity and dynamics of hazardous conditions within sewage systems.

Another major limitation is the lack of real-time communication and remote monitoring capabilities. Many traditional systems do not support wireless data transmission, making it difficult for supervisory authorities to access real-time information. This results in delayed decision-making during emergencies, increasing the risk to workers. The absence of centralized monitoring systems further limits effective supervision and control.

In addition, the accuracy and reliability of some basic monitoring devices are limited. Sensor calibration issues, environmental interference, and lack of multi-gas detection capabilities can lead to incorrect readings or failure to detect hazardous conditions. This reduces the overall dependability of the monitoring system and may result in unsafe situations going unnoticed.Furthermore, most existing solutions lack user-friendly interfaces and integrated platforms for data visualization. Many systems are designed for technical users and require specialized knowledge to operate. There is limited availability of systems that allow users to easily monitor environmental conditions and receive alerts in a simple and understandable format.

Another gap is the lack of integrated and scalable system design. Many existing solutions do not combine sensing, data processing, communication, and alert mechanisms into a single unified system. This limits their ability to provide a complete and efficient monitoring solution. Additionally, scalability for large sewage networks and adaptability to different environments are not fully addressed.

To overcome these limitations, there is a need for an advanced IoT-based sewage monitoring system that integrates real-time sensing, automated data processing, wireless communication, and user-friendly interfaces. Such a system should be capable of continuously monitoring environmental conditions, detecting hazardous gases, and providing instant alerts. It should also support remote monitoring and data visualization, enable effective decision-making and improve overall safety in sewage management.

CHAPTER 2
LITERATURE REVIEW

The literature on sewage monitoring systems reflects a gradual evolution from traditional gas detection methods to advanced Internet of Things (IoT)-based intelligent monitoring solutions. Earlier approaches primarily relied on standalone gas sensors and manual inspection techniques, which provided only local readings and required human intervention. These methods were simple to implement but lacked continuous monitoring capability and real-time alert mechanisms. Additionally, they were highly dependent on human presence, making them unsafe and inefficient for hazardous underground environments. With the introduction of embedded systems and microcontrollers, basic automation was achieved, enabling improved gas detection accuracy; however, these systems still lacked remote accessibility and scalability.

With the advancement of wireless communication and IoT technologies, more sophisticated sewage monitoring systems have been developed. These systems integrate multiple sensors with communication modules such as Wi-Fi, GSM, and LoRa to enable real-time data transmission and remote monitoring. Recent studies have shown that IoT-based systems significantly enhance monitoring efficiency by providing continuous environmental tracking and instant alert generation when gas levels exceed safe limits. Furthermore, the integration of cloud platforms and data visualization tools has improved usability, allowing authorities to monitor conditions remotely and make timely decisions. Multi-sensor integration has also enhanced the capability to detect various hazardous gases along with environmental parameters such as temperature and humidity, providing a more comprehensive analysis of sewage conditions.

More recent research focuses on advanced technologies such as machine learning, data analytics, and intelligent monitoring systems to further improve performance and reliability. Predictive analysis techniques are being explored to identify potential hazardous conditions before they occur, enabling proactive safety measures. Wearable sensor-based systems have also been introduced to monitor both environmental conditions and worker exposure levels in real time. Additionally, improvements in communication technologies such as LoRaWAN have enhanced long-range connectivity and reliability in underground environments. Despite these advancements, challenges such as sensor accuracy, power consumption, communication reliability, and system scalability still exist. Overall, the literature highlights continuous progress toward automation, real-time monitoring, and intelligent decision-making, while emphasizing the need for more robust, energy-efficient, and scalable sewage monitoring solutions.

2.1 FINDINGS FROM RELATED PAPERS

G. Kalpana et al. (2024) proposed an IoT-based toxic gas detection system for sewage safety. The study focused on monitoring hazardous gases in sewage environments using sensor networks. The results showed improved safety measures and real-time alert mechanisms, helping to prevent accidents and ensure worker protection.

L. M. Pires et al. (2024) developed a LoRa-based IoT system for environmental monitoring. The work emphasized long-range communication with low power consumption. The system demonstrated efficient data transmission and reliable monitoring over large areas, making it suitable for smart environmental applications.

C. Cacciuttolo et al. (2024) introduced IoT sensor networks with LoRa connectivity for safe and sustainable work environments. The study highlighted real-time monitoring of environmental conditions. The results showed enhanced workplace safety and improved data reliability through scalable IoT solutions.

S. Mythili et al. (2024) proposed an IoT-ML framework for monitoring wastewater contaminants. The approach combined machine learning with IoT sensors to improve detection accuracy. The system achieved better prediction and classification of contaminants, ensuring efficient wastewater management.

A. Pagano et al. (2024) developed a smart water IoT framework for monitoring water distribution systems. The study focused on real-time tracking of water quality and flow. The results demonstrated improved resource management and early detection of faults in distribution networks.

Z. Zhou et al. (2024) proposed an IoT-empowered digital twin framework for continuous gas emission monitoring. The system integrated real-time data with virtual models for accurate analysis. The results showed improved monitoring efficiency and predictive capabilities in emission control systems.

T. Olivares, and F. M. Delicado (2024) designed a low-cost IoT ecosystem for environmental contamination detection. The study emphasized affordability and scalability. The system achieved reliable detection with reduced implementation cost, making it accessible for widespread use.

K. Sruthi and P. Ravi (2024) developed an IoT-enabled wearable sensor network for sewage worker safety monitoring. The study focused on real-time health and environmental tracking. The results improved worker safety by providing early warnings of hazardous conditions.

A. Pendharkar and J. Chillapalli, K. (2023) proposed an IoT-based sewage monitoring system for smart city applications. The system enabled continuous monitoring of sewage conditions. The results showed improved efficiency in waste management and urban sanitation systems.

P. Patel and V. Rao (2023) developed a smart sewer environment monitoring system using IoT sensors. The study focused on detecting harmful gases and environmental changes. The results demonstrated enhanced monitoring accuracy and timely alerts.

S. N. Jeffery and S. H. Newaz (2023) proposed a LoRa-based IoT-enabled wearable sensor network for sewage environment monitoring. The system ensured long-range communication and real-time updates. The results improved safety and monitoring efficiency in hazardous environments.

B. T. Nguyen and A. V. Nguyen (2022) developed an IoT application for gas leakage monitoring systems. The study focused on early detection of gas leaks. The results showed increased safety through timely alerts and continuous monitoring.

M. Aarthi and A. Bhuvaneshwaran (2022) proposed an IoT-based drainage and waste monitoring system for smart cities. The system enabled efficient waste tracking and management. The results demonstrated improved urban sanitation and reduced environmental impact.

M. Shanthi et al(2021) developed a system for detection, monitoring, and control of toxic gas using IoT. The study focused on real-time gas detection and alert systems. The results showed improved safety and effective control mechanisms.

S. Sindhu and D. M. Saravanan (2021) presented a comprehensive study on toxic gas detection using IoT sensors. The work reviewed various sensing technologies and methodologies. The results highlighted improved detection techniques and system efficiency.

S. U. Suganthi and R. Kumar (2021) proposed a coal mine safety monitoring system using LoRa wireless communication. The system focused on monitoring hazardous conditions in mines. The results showed reliable long-distance communication and improved safety.

J. B. Sanger and L. Sitanayah, (2021) developed a sensor-based garbage gas detection system. The study focused on detecting harmful gases from waste. The results demonstrated effective monitoring and improved environmental safety.

R. Nirmala, and R. Navamathavan (2021) reviewed recent advancements in liquefied petroleum gas sensors. The study analyzed different sensor technologies and performance metrics. The results highlighted improvements in sensitivity and detection accuracy.

R. Walambe, and K. Kotecha (2021) proposed gas detection using multimodal AI sensor fusion. The system combined multiple sensor inputs with AI techniques. The results showed enhanced detection accuracy and reliability.

D. Nurul Saiyidah et al. (2021) developed a LoRaWAN-based smart sewerage monitoring system. The study sed on efficient communication and monitoring. The results demonstrated improved system performance and scalability.

2.2 CONCLUSIONS FROM THE LITERATURE REVIEW

The literature review highlights that IoT-based technologies have significantly improved the efficiency and reliability of sewage monitoring systems. Traditional methods such as manual inspection and standalone gas detection devices often fail to provide continuous monitoring and real-time alerts. These approaches are highly dependent on human intervention and are not suitable for hazardous underground environments. In contrast, IoT-based systems enable real-time data collection, continuous monitoring, and instant alert generation, thereby enhancing worker safety and reducing the risk of accidents. Overall, IoT provides a robust and scalable solution for modern sewage monitoring applications.

With the integration of sensor networks and microcontroller-based systems, there has been a major improvement in environmental monitoring and gas detection. Advanced gas sensors are capable of detecting multiple hazardous gases such as methane, hydrogen sulfide, ammonia, and carbon monoxide with improved accuracy. The use of embedded systems allows efficient data processing and threshold-based decision-making. Furthermore, the integration of wireless communication technologies such as Wi-Fi, GSM, and LoRa enables remote monitoring and real-time data transmission, making these systems highly effective for large-scale sewage networks.

The review also highlights the importance of multi-sensor integration and communication technologies in improving system performance. By combining gas sensors with temperature and humidity sensors, modern systems provide a more comprehensive analysis of environmental conditions. Additionally, long-range communication technologies such as LoRa and LoRaWAN have enhanced connectivity in underground environments where traditional communication methods are limited.

Recent research also emphasizes the role of wearable sensor networks and intelligent monitoring systems in improving individual worker safety and providing immediate alerts.

Furthermore, advancements in data analytics and intelligent systems have contributed to the development of predictive and automated monitoring solutions. Techniques such as machine learning and sensor fusion improve detection accuracy and reduce false alarms. Cloud-based platforms and IoT frameworks enable real-time data visualization and remote accessibility, supporting better decision-making and efficient system management. These developments enhance the overall usability and effectiveness of sewage monitoring systems.

Additionally, maintaining accuracy under varying environmental conditions and ensuring long-term durability of sensors are important concerns. However, the overall findings confirm that IoT-based sewage monitoring systems provide a reliable, efficient, and scalable solution for real-time environmental monitoring. These insights strongly support the development of intelligent, automated systems to improve worker safety and modernize sewage management infrastructure.

CHAPTER 3

PROPOSED SYSTEM AND METHODOLOGY

The proposed methodology presents a structured and systematic approach for monitoring hazardous conditions in sewage environments using IoT-based sensing and communication technologies. The overall framework is designed to continuously detect toxic gases, analyze environmental conditions, and provide real-time alerts to ensure worker safety. The methodology integrates sensor data acquisition, signal processing, threshold-based analysis, wireless communication, and alert generation into a unified system.

The process begins with the deployment of various sensors in sewage environments to collect real-time data. Gas sensors are used to detect hazardous gases such as methane (CH_4), hydrogen sulfide (H_2S), ammonia (NH_3), and carbon monoxide (CO). In addition, temperature and humidity sensors are included to monitor environmental conditions. These sensors act as the primary input sources for the system and continuously capture data from the surroundings.

Once the data is collected, it is processed by a microcontroller unit, such as Arduino or ESP8266. The microcontroller receives analog or digital signals from the sensors and converts them into meaningful data. Basic preprocessing steps such as filtering noise, calibration, and normalization are performed to ensure accuracy and reliability of the readings. This stage ensures that variations due to environmental interference do not affect the monitoring process.

After preprocessing, the system performs threshold-based analysis to evaluate the safety level of the environment. Predefined safe limits are set for each gas and environmental parameter. The microcontroller continuously compares the sensed values with these threshold levels. If any parameter exceeds the safe limit, the system identifies it as a hazardous condition. This step is crucial for real-time decision-making and ensures immediate detection of dangerous situations.

Following analysis, the system initiates alert generation and communication mechanisms. When unsafe conditions are detected, a buzzer is activated to provide an immediate warning to nearby workers. Simultaneously, wireless communication modules such as Wi-Fi or LoRa are used to transmit the data to remote monitoring systems. Notifications can be sent to supervisors or authorities, enabling quick response and preventive action without requiring physical presence in hazardous areas.

The next stage involves real-time data monitoring and visualization. The collected data is transmitted to a web-based or cloud-based platform where it can be displayed in the form of dashboards, graphs, and live readings. This allows authorities to monitor environmental conditions remotely and analyze trends over time. The system provides continuous updates, making it easier to track changes and identify potential risks in advance.

An important component of the proposed methodology is continuous monitoring and system integration. The system operates in a loop, continuously sensing, processing, analyzing, and transmitting data. This ensures uninterrupted monitoring of sewage environments. The integration of sensing, processing, communication, and alert mechanisms into a single system improves efficiency, reliability, and usability.

Finally, the system provides a user-friendly interface for interaction and control. Users can access real-time data, receive alerts, and monitor system status through a simple interface without requiring technical expertise. The overall system is designed to be low-cost, portable, and scalable, making it suitable for real-world deployment in sewage systems.

Overall, the proposed methodology offers a comprehensive and efficient solution for sewage monitoring. By combining IoT-based sensing, real-time processing, wireless communication, and intelligent alert mechanisms, the system ensures improved worker safety, reduces manual intervention, and supports the development of smart and secure sewage management systems.

3.1 MATERIALS

3.1.1 EMBEDDED SYSTEM AND PROGRAMMING ENVIRONMENT

In this project, an embedded system-based approach is used as the core platform for implementing the sewage monitoring system. Microcontrollers such as Arduino or ESP8266 are selected due to their simplicity, flexibility, and strong capability to interface with multiple sensors and communication modules. These platforms are widely used in IoT applications as they support real-time data acquisition, processing, and control with minimal power consumption.

It supports embedded C/C++ programming and includes a wide range of libraries for sensor integration, communication protocols, and device control. This makes it suitable for developing real-time monitoring systems without requiring complex setup or high-end hardware.

In this project, the Arduino IDE is used to program the microcontroller for reading sensor values, processing data, and controlling output devices. The system continuously collects environmental data from sensors and performs basic preprocessing such as calibration and noise filtering to ensure accuracy. The microcontroller then compares the sensor values with predefined threshold limits to determine whether the environment is safe or hazardous.

When unsafe conditions are detected, the programmed logic activates alert mechanisms such as a buzzer and also triggers communication modules to send notifications. The programming environment allows easy modification of system parameters, making the system flexible and adaptable to different environmental conditions. Overall, the embedded system and programming environment provide a reliable and efficient platform for implementing the proposed sewage monitoring system.

3.1.2 SENSORS AND COMMUNICATION MODULES

The proposed IoT-based sewage monitoring system is developed using a combination of hardware components, sensors, and embedded system methodologies to ensure real-time monitoring of hazardous environmental conditions. The materials used in this system include a microcontroller unit, gas sensors, temperature and humidity sensors, wireless communication modules, display units, and alert devices. The microcontroller, such as Arduino Nano (ATmega328P) or ESP32, acts as the central processing unit responsible for collecting, processing, and transmitting sensor data. Gas sensors from the MQ-series (such as MQ-6 or MQ-135) are utilized to detect hazardous gases like methane (CH_4), ammonia (NH_3), carbon monoxide (CO), and hydrogen sulfide (H_2S). Temperature and humidity sensors such as DHT11 or DHT22 are used to monitor environmental conditions that influence gas behavior in sewage systems.



Figure 3.1 ESP8266

In addition to gas sensors, temperature and humidity sensors are used to monitor environmental conditions. ESP8266 is shown in the Figure 3.1 These parameters are important as they influence gas behavior and overall safety inside sewage systems. By integrating multiple sensors, the system provides a comprehensive analysis of the environment rather than focusing on a single parameter.

The communication module is another essential component of the system. Technologies such as Wi-Fi (ESP8266) or LoRa are used to transmit the collected data to remote monitoring systems. These modules enable real-time data transfer, allowing authorities to monitor conditions from a safe location. LoRa communication is especially useful in underground environments due to its long-range capability and low power consumption.

The system also includes output devices such as buzzers for alert generation. When gas levels exceed safe limits, the buzzer provides an immediate warning to nearby workers. Simultaneously, the communication module sends notifications to remote users, ensuring quick response during emergency situations.

Moreover, the integration of communication modules enhances system connectivity and data accessibility. Real-time data can be stored, monitored, and analyzed using IoT platforms, enabling better decision-making. This connectivity also allows for future enhancements such as cloud storage, predictive analysis, and integration with smart city infrastructure.

Overall, the integration of sensors and communication modules ensures accurate data collection, reliable transmission, and effective alert generation. This combination enhances the safety, efficiency, and practicality of the sewage monitoring system, making it suitable for real-world applications.




Figure 3.2 System Dashboard

The methodology involves a systematic process beginning with sensor initialization and calibration to ensure accurate data acquisition. The System Dashboard is shown in the Figure 3.2 Once initialized, sensors continuously collect environmental data at predefined intervals. The microcontroller reads the sensor outputs and converts analog signals into digital values using an internal analog-to-digital converter. The processed data is then compared against predefined safety threshold values to determine the presence of hazardous conditions. If the sensor readings exceed the threshold limits, the system triggers an alert mechanism, activating the buzzer and sending notifications through the communication module.

After data processing, the system compares the sensor readings with predefined safety threshold values to evaluate environmental conditions. If any parameter exceeds the safe limits, the system identifies it as a hazardous situation. In such cases, an alert mechanism is triggered, which activates a buzzer to warn nearby workers. Simultaneously, the communication module sends notifications to remote users or authorities, enabling immediate action and improving overall safety in sewage environments.

The collected data is also transmitted wirelessly to a monitoring system where it can be stored, visualized, and analyzed. This enables remote supervision and timely decision-making by authorities. The overall methodology ensures continuous monitoring, real-time alert generation, and improved safety for sewage maintenance workers. The integration of low-cost hardware components with efficient communication technologies makes the system scalable, reliable, and suitable for practical deployment in sewage environments.

3.2 BLOCK DIAGRAM




Figure 3.3 Block Diagram

The block diagram of the proposed IoT-based sewage monitoring system illustrates the flow of data from sensing to alert generation through different functional units working together to ensure worker safety. The Block Diagram is shown in the Figure 3.3. The sensing unit consists of gas sensors such as MQ-4, MQ-7, MQ-136, and MQ-135 to detect hazardous gases like methane, carbon monoxide, hydrogen sulfide, and ammonia, along with a temperature and humidity sensor (DHT11/DHT22) to monitor environmental conditions. These sensors continuously collect data and send it to the processing unit, which is a microcontroller such as Arduino Nano or ESP32.

The microcontroller converts analog signals into digital values and compares them with predefined safety thresholds to determine whether the environment is safe or hazardous. The processed data is then transmitted through the communication unit using technologies such as Wi-Fi, GSM, or LoRa to a remote monitoring system or cloud platform, where the data is displayed, stored, and analyzed for real-time supervision.

Overall, the system performs continuous monitoring, real-time data transmission, and instant alert generation, thereby significantly improving safety and enabling quick response in hazardous sewage environments.

3.3 SYSTEM COMMUNICATION APPROACH

The system communication approach of the proposed IoT-based sewage monitoring system is designed to ensure reliable, real-time transmission of environmental data from underground sewage locations to remote monitoring platforms.

The communication process begins at the sensing unit, where gas sensors and environmental sensors collect data and forward it to the microcontroller for processing. Once the data is processed and evaluated against predefined safety thresholds, it is transmitted through a wireless.

LoRa technology is particularly effective for underground sewage environments due to its long-range capability, low power consumption, and ability to penetrate obstacles, making it ideal for continuous monitoring in harsh conditions. The transmitted data is received by a cloud-based or local monitoring system where it is stored, visualized, and analyzed in real time. This enables authorities to remotely monitor environmental conditions and respond quickly to hazardous situations. Additionally, the communication system supports bidirectional data flow, allowing remote commands or configuration updates to be sent back to the microcontroller if required.

The system is designed to minimize latency and ensure reliable data transmission even in challenging underground environments by selecting appropriate communication protocols and error-handling mechanisms. Overall, the communication approach ensures seamless connectivity, real-time monitoring, and immediate alert delivery, thereby enhancing the effectiveness and reliability of the sewage safety monitoring system.

3.4 User Interface and Experience Design

The user interface (UI) and user experience (UX) design of the proposed IoT-based sewage monitoring system are developed to ensure simplicity, clarity, and ease of use for both field workers and supervisory authorities.

The interface is designed to display real-time environmental parameters such as gas concentration levels, temperature, and humidity in an intuitive and easily understandable format. A local display unit, such as a 16×2 LCD, provides immediate on-site information, enabling workers to quickly assess safety conditions without requiring additional devices.

In addition, a remote user interface is implemented through a web or mobile-based application, allowing authorities to monitor sewage conditions from any location. The interface includes graphical representations such as charts and status indicators to visualize data trends and highlight abnormal conditions. Color-coded alerts (green for safe, yellow for caution, and red for danger) are used to improve readability and quick decision-making.

The system also incorporates notification features such as SMS or app-based alerts to inform users instantly when hazardous conditions are detected. The user experience is further enhanced by ensuring minimal interaction complexity, fast response time, and clear navigation across different sections of the interface. Accessibility and responsiveness are considered to ensure compatibility across various devices, including smartphones and computers. Overall, the UI/UX design focuses on providing real-time visibility, quick interpretation of data, and efficient response to emergencies, thereby improving usability and ensuring effective monitoring of sewage environments.

3.5 DATA PROCESSING AND THRESHOLD ANALYSIS

After acquiring data from the sensors, the system performs data processing to ensure that the readings are accurate and reliable. The microcontroller receives analog signals from the sensors and converts them into digital values using an internal analog-to-digital converter (ADC). This conversion allows the system to interpret the sensor outputs effectively. Basic preprocessing techniques such as noise filtering and signal stabilization are applied to eliminate fluctuations and improve the consistency of the readings.

Once the data is processed, the system performs threshold-based analysis to evaluate environmental safety. Predefined threshold values are set for each parameter, including gas concentration levels, temperature, and humidity, based on standard safety limits. The microcontroller continuously compares the real-time sensor readings with these threshold values to determine whether the environment is within a safe operating range or not.If the sensor values remain within the acceptable limits, the system continues normal monitoring without interruption.

However, when any parameter exceeds the predefined threshold, it indicates the presence of a hazardous condition such as toxic gas accumulation or abnormal environmental changes.

3.6 ALERT GENERATION AND COMMUNICATION

When a hazardous condition is detected, the system immediately activates alert mechanisms to ensure the safety of workers. A buzzer is triggered to provide an audible warning signal, alerting individuals present in the sewage environment about the danger. This immediate alert helps workers take precautionary measures and move away from the hazardous area.

In addition to local alerts, the system uses communication modules such as Wi-Fi or LoRa to transmit data and warning notifications to remote users or authorities. The information is sent in real time, allowing supervisors to monitor the situation from a safe location. This remote communication capability ensures quick response during emergencies and enhances the overall efficiency and reliability of the sewage monitoring system.

CHAPTER 4

EXPERIMENTAL SETUP AND PROCEDURE

4.1 EXPERIMENTAL SETUP

The experimental setup of the proposed system is designed to evaluate the performance and effectiveness of the IoT-based sewage monitoring system in detecting hazardous environmental conditions. It includes the selection of hardware components, sensor configuration, microcontroller programming, and communication modules required for real-time monitoring and alert generation.

For this project, various sensors such as gas sensors, temperature sensors, and humidity sensors are used to collect environmental data. These sensors are carefully selected and interfaced with the microcontroller to detect toxic gases like methane, hydrogen sulfide, ammonia, and carbon monoxide. The sensors are placed in a controlled test environment to simulate sewage conditions and evaluate the system's ability to detect changes accurately.

The implementation is carried out using a microcontroller platform such as Arduino or ESP8266, programmed through the Arduino IDE. This platform allows efficient handling of sensor inputs, data processing, and control of output devices. The system is powered using a stable power supply, and all components are connected through a properly designed circuit to ensure reliable operation during testing.

Before executing the system, calibration and testing of sensors are performed to ensure accurate readings. Each sensor is tested individually to verify its response to different environmental conditions. Proper calibration helps in minimizing errors and ensures that the collected data reflects actual conditions. This step is essential for improving the reliability and performance of the system.

The core of the experimental setup involves real-time data acquisition and processing. The microcontroller continuously reads sensor values and converts them into digital form for analysis. Threshold values are predefined for each parameter, and the system compares real-time readings with these limits to detect hazardous conditions. When the values exceed safe levels, the system identifies it as a potential risk.

The alert mechanism is also tested as part of the experimental setup. A buzzer is used to provide immediate local alerts when unsafe conditions are detected. In addition, communication modules such as Wi-Fi or LoRa are integrated to transmit data to remote monitoring systems. The system is tested for its ability to send real-time notifications and ensure proper communication between devices.

Furthermore, the system's performance is evaluated under different environmental conditions to analyse its responsiveness and reliability. Multiple test scenarios are created by varying gas concentrations and environmental parameters. The system's accuracy in detecting hazardous conditions and its response time is carefully observed and recorded.

Overall, the experimental setup provides a complete environment for testing the proposed sewage monitoring system, from data acquisition and processing to alert generation and communication. It ensures that the system operates efficiently, responds quickly to hazardous conditions, and delivers reliable performance for real-world sewage monitoring applications.

4.2 EXPERIMENTAL PROCEDURE

The experimental procedure of the proposed system follows a systematic sequence of steps to implement and evaluate the IoT-based sewage monitoring system for detecting hazardous environmental conditions. Each step is carefully designed to ensure accurate data acquisition, reliable processing, and effective alert generation.

The process begins with the selection and assembly of hardware components required for the system. Sensors such as gas sensors, temperature sensors, and humidity sensors are interfaced with the microcontroller. These components are connected using appropriate circuit connections to form a complete monitoring setup. The sensors act as the primary input sources, continuously capturing environmental data from the surroundings.

Once the hardware setup is completed, the next step involves programming the microcontroller using the Arduino IDE. The program is designed to read sensor values, process the data, and control output devices such as buzzers and communication modules. The code includes predefined threshold values for each parameter to identify safe and unsafe conditions. After writing the program, it is compiled and uploaded to the microcontroller for execution.

After programming, sensor calibration and testing are performed to ensure accurate readings. Each sensor is tested under different conditions to verify its response and sensitivity. Calibration is carried out to adjust the sensor outputs according to standard reference values. This step is essential to improve the accuracy and reliability of the system during real-time operation.

Following calibration, the system begins real-time data acquisition and processing. The sensors continuously monitor environmental conditions and send data to the microcontroller. The microcontroller converts analog signals into digital values and compares them with predefined threshold limits. This continuous monitoring ensures that any sudden change in environmental conditions is detected immediately.

When the sensor readings exceed the threshold values, the system identifies the presence of hazardous conditions. At this stage, the alert mechanism is activated. A buzzer is triggered to provide an immediate warning to nearby workers. This ensures that workers are alerted in real time and can take necessary precautions to avoid exposure to toxic gases.

Simultaneously, the communication module transmits the data and alert notifications to remote monitoring systems. Technologies such as Wi-Fi or LoRa are used to send real-time updates to authorities or supervisors. This allows remote monitoring of sewage conditions and enables quick decision-making during emergency situations.

Finally, the system performance is evaluated under different test conditions by varying gas concentrations and environmental parameters. The response time, accuracy, and reliability of the system are observed and recorded. The entire procedure ensures a smooth flow from hardware setup to real-time monitoring and alert generation, making the system efficient, reliable, and suitable for practical sewage monitoring applications.

4.3 DATA ACQUISITION AND SOURCES

The success of the proposed sewage monitoring system largely depends on the accuracy, reliability, and consistency of the data collected from the environment. In this project, real-time environmental data is acquired using multiple sensors integrated into the system. The aim is to ensure that the collected data accurately represents the conditions inside sewage environments, including variations in gas concentration, temperature, and humidity.

The primary sources of data in this system are gas sensors and environmental sensors. Gas sensors are used to detect hazardous gases such as methane (CH_4), hydrogen sulfide (H_2S), ammonia (NH_3), and carbon monoxide (CO), which are commonly present in sewage systems. Temperature and humidity sensors are also included to monitor environmental conditions, as these factors influence gas behavior and overall safety. These sensors continuously capture real-time data from the surroundings.

To evaluate the system performance, data is collected under different environmental conditions. Various test scenarios are created by exposing the sensors to different gas concentrations and environmental variations. This helps in analyzing how the system responds to normal as well as hazardous conditions. The collected data represents both safe and unsafe conditions, allowing the system to effectively differentiate between them.

During data acquisition, proper attention is given to sensor placement and calibration. Sensors are positioned in such a way that they can effectively detect gas accumulation in the environment. Calibration is performed using standard reference conditions to ensure accurate readings and reduce measurement errors. This step is essential for maintaining the reliability and consistency of the system.

Once the data is collected, it is organized and processed by the microcontroller. The sensor readings are continuously monitored and compared with predefined threshold values. The data is also displayed through serial monitoring or transmitted to remote platforms for further analysis. This structured handling of data ensures that the system operates efficiently in real-time conditions.

In addition to real-time monitoring, the system allows data to be observed over a period of time to identify patterns and variations in environmental conditions. This helps in understanding how gas levels change under different situations and improves the effectiveness of the monitoring system. The communication modules further enable the transmission of this data to remote users, making it accessible for supervision and analysis.

The collected data is not divided into training or testing sets as in software-based systems, but instead evaluated based on system response, accuracy, and reliability under different conditions. The performance of the system is measured by its ability to detect hazardous conditions correctly and generate timely alerts.

Overall, the data acquisition and source selection process ensures that the system operates using accurate, real-time, and reliable environmental data. This plays a crucial role in achieving effective gas detection, timely alert generation, and improved safety in sewage monitoring applications.

4.4 SENSOR DATA PROCESSING AND CALIBRATION

The system implementation involves the integration of both hardware and software components to achieve an efficient real-time sewage monitoring system. The design focuses on ensuring safety, reliability, and continuous monitoring in hazardous environments. Each component is carefully selected and interconnected to perform specific functions, contributing to the overall system performance.

Sensor data processing and calibration are important steps in the proposed sewage monitoring system, as they enhance the accuracy and reliability of the collected environmental data. These steps focus on converting raw sensor outputs into meaningful information and ensuring that the data is properly conditioned for analysis and decision-making.

After data acquisition, the system receives raw signals from gas sensors and environmental sensors. These signals may contain noise and fluctuations due to environmental variations such as temperature and humidity. To address this, preprocessing techniques such as noise filtering, signal smoothing, and calibration are applied. Calibration is performed using standard reference values to ensure that the sensor readings accurately represent real-world conditions.

The process of data processing involves converting analog sensor outputs into digital values using the microcontroller's analog-to-digital converter (ADC). This conversion enables the system to interpret the sensor readings effectively. The processed data is then adjusted based on calibration factors to correct any deviations and improve measurement accuracy.

In addition to basic processing, the system derives meaningful insights from the sensor data. For example, gas concentration levels are analyzed to determine the intensity of toxic gases present in the environment. Similarly, temperature and humidity readings are evaluated to understand environmental conditions that may influence gas behavior. These processed values act as key parameters for further analysis.

Furthermore, the system may combine multiple sensor readings to improve accuracy and reliability. For instance, high gas concentration along with increased temperature may indicate a higher risk level. Such combined analysis enhances the system's ability to detect hazardous conditions more effectively.

Overall, sensor data processing and calibration ensure that the system operates with high accuracy and consistency. These steps play a crucial role in improving system performance and enabling reliable real-time monitoring of sewage environments.

4.5 THRESHOLD ANALYSIS AND DECISION MECHANISM

Threshold analysis and decision-making form the core logic of the proposed sewage monitoring system. This stage is responsible for evaluating environmental conditions and determining whether the situation is safe or hazardous based on predefined limits.

After processing the sensor data, the system compares the readings with predefined threshold values. These threshold limits are set based on permissible exposure levels for different gases such as methane, hydrogen sulfide, ammonia, and carbon monoxide. Temperature and humidity thresholds are also defined to monitor environmental safety effectively.

The decision mechanism continuously evaluates the sensor readings in real time. If all parameters remain within safe limits, the system continues normal monitoring. However, if any parameter exceeds its threshold value, the system identifies the condition as hazardous. This immediate detection is essential for preventing accidents and ensuring worker safety.

In addition to individual parameter analysis, the system may consider combined conditions to improve decision accuracy. For example, simultaneous increase in multiple gas concentrations may indicate a more critical situation compared to a single parameter exceeding the limit. This enhances the reliability of the decision-making process.

The threshold analysis ensures quick and efficient identification of dangerous situations without the need for complex computations. It provides a simple yet effective approach for real-time monitoring and response in sewage environments.

Overall, the decision mechanism plays a vital role in the system by enabling timely detection of hazardous conditions and triggering appropriate actions to ensure safety.

4.6 REAL-TIME MONITORING AND ALERT SYSTEM

The real-time monitoring and alert system are a key component of the proposed sewage monitoring system, responsible for providing immediate warnings and ensuring effective communication during hazardous situations. This stage ensures that both local users and remote authorities are informed about environmental conditions without delay.

Once a hazardous condition is detected through threshold analysis, the system activates the alert mechanism. A buzzer is used to generate an audible warning signal, alerting workers present in the sewage environment. This immediate alert helps workers take quick action and avoid exposure to toxic gases.

In addition to local alerts, the system incorporates communication modules such as Wi-Fi or LoRa for remote monitoring. These modules transmit sensor data and alert notifications to remote users or authorities in real time. This allows supervisors to monitor the situation from a safe location and take necessary preventive measures.

The system also supports continuous real-time monitoring, where environmental data is updated at regular intervals. This enables users to track changes in gas concentration and environmental conditions over time. The availability of real-time data improves situational awareness and helps in making informed decisions.

Furthermore, the integration of communication technologies ensures reliable data transmission even in challenging environments such as underground sewage systems. Long-range communication methods like LoRa enhance connectivity and make the system suitable for large-scale deployment.

Overall, the real-time monitoring and alert system significantly improves safety and efficiency by providing instant alerts and enabling remote supervision. It ensures that hazardous conditions are detected and addressed promptly, making the system highly effective for sewage monitoring applications.

4.7 SECURITY APPROACH

The security approach of the proposed IoT-based sewage monitoring system is designed to ensure the protection of data, devices, and communication channels from unauthorized access and potential cyber threats.

Since the system involves real-time transmission of environmental data through wireless networks, it is essential to implement strong security mechanisms at multiple levels. At the device level, secure authentication methods are used to ensure that only authorized sensors and microcontrollers can connect to the network. Unique device IDs and password-based access control are implemented to prevent unauthorized access. At the communication level, data encryption techniques such as Secure Sockets Layer (SSL) or Transport Layer Security (TLS) are used to protect data during transmission between the microcontroller and the remote monitoring system. This prevents data interception and tampering by malicious users.

In addition, the system incorporates secure communication protocols such as MQTT with authentication and encryption to ensure reliable and protected data exchange. Network-level security measures such as firewalls and intrusion detection systems can be integrated to monitor suspicious activities and prevent attacks. The cloud or remote monitoring platform is secured using user authentication mechanisms such as username-password login or two-factor authentication (2FA), ensuring that only authorized personnel can access sensitive data. Regular firmware updates and software patches are recommended to address vulnerabilities and enhance system security over time. Data integrity is maintained by validating sensor data before processing and storage, reducing the risk of false or manipulated readings.

Furthermore, physical security measures such as protective enclosures for hardware components are implemented to prevent tampering in harsh sewage environments. The system is designed with a layered security approach, combining device security, communication security, and application-level protection. Overall, the proposed security approach ensures confidentiality, integrity, and availability of the system, making it reliable and safe for real-world deployment in sewage monitoring applications.

CHAPTER 5
RESULTS AND DISCUSSION

5.1 SYSTEM HARDWARE PERFORMANCE

The developed system is centered around the Arduino Nano microcontroller, which acts as the brain of the entire setup. It is responsible for collecting data from various sensors, processing it, and controlling communication modules. The performance of the Arduino Nano was observed to be stable and efficient during continuous operation in both controlled and real-time environments.

The ATmega328P microcontroller integrated within the Arduino Nano plays a crucial role in executing instructions and handling sensor data. It efficiently manages multiple inputs from gas sensors, temperature sensors, and humidity sensors without any significant delay. The processing capability of the microcontroller ensures smooth operation of the system.

The board includes essential supporting components such as a crystal oscillator, voltage regulator, and communication interfaces. These components contribute to maintaining stable voltage levels and proper timing operations. This ensures that the system performs reliably even in fluctuating environmental conditions.

The digital and analog input/output pins of the Arduino Nano were effectively utilized for interfacing with sensors and modules. The availability of 14 digital pins and 6 analog pins allows flexibility in connecting multiple devices simultaneously. This makes the system scalable for future enhancements.

The Pulse Width Modulation (PWM) pins were used for controlling alert mechanisms such as buzzers and vibration modules. These features help in generating real-time alerts to workers when hazardous conditions are detected. The response from these modules was quick and consistent.

The power supply arrangement of the Arduino Nano ensures uninterrupted operation. The system can be powered through USB or an external battery, making it suitable for portable applications. This flexibility is important for deployment in sewage environments where continuous power supply may not be available.

Overall, the hardware performance of the system was found to be reliable, efficient, and suitable for real-time monitoring applications. The Arduino Nano proved to be an effective choice for implementing a compact and low-cost monitoring solution.

5.2 COMMUNICATION AND DATA TRANSMISSION RESULTS

The communication system of the project integrates GSM and Wi-Fi modules to ensure effective data transmission and alert generation. The GSM module is primarily used to send notifications to users when hazardous conditions are detected. The performance of the GSM module was tested under various conditions.

The GSM module successfully transmitted alert messages to registered mobile numbers whenever sensor values exceeded predefined thresholds. The message delivery time was observed to be minimal, ensuring timely alerts to workers and supervisors. This plays a critical role in emergency situations.

In addition to GSM, the system also uses the ESP8266 Wi-Fi module for internet-based communication. This module enables data transfer between the microcontroller and the web application. The ESP8266 performed efficiently with stable connectivity during testing.

The Wi-Fi module operates at a frequency of 80MHz to 160MHz and supports real-time data transmission. It ensures that sensor readings are continuously updated on the web interface without significant delay. This allows remote monitoring of environmental conditions.

The integration of both GSM and Wi-Fi communication enhances the reliability of the system. Even if one communication method fails, the other can still provide necessary data transmission. This redundancy improves system robustness.

Overall, the communication system demonstrated high efficiency, reliability, and responsiveness. It ensures that critical information is transmitted without delay, thereby enhancing worker safety.

5.3 SENSOR PERFORMANCE AND DATA ANALYSIS

The system utilizes multiple sensors to monitor environmental conditions such as toxic gases, temperature, and humidity. The performance of these sensors was analyzed based on accuracy, response time, and reliability.

Gas sensors used in the system were able to detect harmful gases such as carbon monoxide, methane, and hydrogen sulphide. The sensors responded quickly to changes in gas concentration, enabling early detection of hazardous conditions.

Temperature and humidity sensors also showed consistent performance during testing. They provided accurate readings when compared with standard measurement devices. This ensures reliable monitoring of environmental parameters.




Figure 5.1 Software Flowchart

The collected sensor data was continuously transmitted to the control unit and recorded for analysis. Real-time data logging helped in understanding environmental variations during sewage operations. The Software Flowchart is shown in Figure 5.1. This data is useful for identifying risk patterns.

The response time of the sensors was observed to be minimal, allowing quick detection and alert generation. This is important in preventing accidents caused by sudden changes in environmental conditions.

Data analysis was performed by comparing sensor readings with predefined safety thresholds. Whenever the values exceeded safe limits, alerts were triggered. This confirms the effectiveness of the system in hazard detection.

Overall, the sensor performance was found to be accurate, responsive, and reliable. The data analysis results validate the system's capability to provide real-time environmental monitoring.

5.4 OUTPUT RESULTS AND SYSTEM EFFECTIVENESS

In this project, a complete real-time sewage monitoring prototype has been physically developed and tested. The output setup clearly shows that the system is not limited to sensing alone, but extends to real-time processing, display, alert generation, and automatic response. The entire system is built around a custom PCB integrated with an Arduino Nano, which acts as the central controller for all operations.

From the hardware arrangement, multiple environmental sensors have been successfully interfaced with the microcontroller. These include gas sensors (for detecting harmful gases like methane, carbon monoxide, etc.) and a temperature-humidity sensor module. These sensors continuously collect real-time environmental data from the surroundings. The output setup confirms that sensor readings are actively fed into the controller and processed without delay.

A key achievement in this setup is the real-time visualization of data using the 16x2 LCD display mounted on the board. The LCD is directly interfaced with the Arduino Nano and displays live values such as gas levels, temperature, and humidity. This ensures that the system provides immediate on-site feedback, which is critical in sewage environments where quick decisions are required.

The project also successfully implements an alert mechanism using a buzzer. When the sensed gas concentration exceeds the predefined safety threshold, the buzzer is automatically activated. This provides an instant warning to the worker. The presence of the buzzer in the output setup confirms that real-time hazard detection and alerting have been effectively achieved.

Another major functionality implemented in this setup is automatic actuation. A relay module is used to control an exhaust fan, which is clearly visible in the output image. When toxic gas levels rise beyond safe limits, the relay is triggered, and the fan is turned ON automatically to improve ventilation.This shows that the system is capable of taking corrective action without human intervention, which is a critical requirement in hazardous environments.

The system also includes a communication module, which enables external alert transmission. This ensures that alerts are not only limited to the local environment but can also be sent to remote users or control rooms. This feature enhances overall safety by ensuring that help can be initiated even if the worker is unable to respond.

Finally, the overall setup demonstrates a well-integrated and modular design, where sensing, processing, display, alert, and control units work together seamlessly. The successful implementation of all these components in a single working prototype proves that the system is practical, reliable, and suitable for real-time deployment in sewage monitoring applications.




Figure 5.2 System output

5.5 DISCUSSION

The results obtained from the proposed sewage monitoring system clearly indicate that the integration of sensor technology, microcontrollers, and wireless communication can significantly enhance worker safety in hazardous environments. The system was able to continuously monitor critical environmental parameters such as toxic gas concentration, temperature, and humidity, providing real-time insights into working conditions.

This demonstrates the effectiveness of combining embedded systems with IoT-based communication for safety-critical applications.The performance of the Arduino Nano microcontroller played a vital role in ensuring smooth system operation. Its ability to process multiple sensor inputs simultaneously without delay confirms its suitability for real-time monitoring applications. The stability of the hardware, even during prolonged usage, indicates that the system can be reliably deployed in continuous monitoring scenarios such as sewage environments.

The communication modules, including GSM and Wi-Fi (ESP8266), showed strong performance in transmitting data and alerts. The GSM module ensured that emergency notifications were delivered promptly to users, while the Wi-Fi module enabled real-time data visualization through the web interface. This dual communication approach increases system reliability and ensures that critical information reaches users without failure.

Sensor performance was another important aspect analyzed in this project. The gas sensors demonstrated high sensitivity to hazardous gases, allowing early detection of dangerous conditions. Similarly, temperature and humidity sensors provided stable and accurate readings. The quick response time of these sensors ensures that the system can react immediately to sudden environmental changes, thereby reducing potential risks.

The alert mechanism proved to be highly effective in warning both workers and supervisors about unsafe conditions. During testing, the system successfully triggered alerts when predefined thresholds were exceeded. This immediate response capability is crucial in preventing accidents and ensuring timely evacuation or corrective measures in hazardous environments.

Despite the positive results, certain challenges were observed during implementation. Signal strength variations in underground environments slightly affected communication in some cases. Additionally, the dependency on battery power highlights the need for efficient energy management. The output is shown in the Figure 5.2 These challenges indicate areas where further improvements can be made to enhance system performance.

Overall, the discussion highlights that the proposed system is a reliable, efficient, and practical solution for real-time sewage monitoring.

The combination of accurate sensing, effective communication, and timely alerts makes it a valuable tool for improving worker safety. With further enhancements such as advanced analytics and improved power management, the system can be extended for large-scale industrial applications.

CHAPTER 6

CONCLUSION

The proposed sewage monitoring system presents an effective and innovative solution for enhancing worker safety in hazardous sewage environments. By integrating advanced sensing technologies with real-time communication systems, the project successfully addresses the critical challenges associated with traditional monitoring methods. The system ensures continuous monitoring of environmental parameters such as toxic gases, temperature, and humidity, thereby reducing the risk of accidents and health hazards faced by sewage workers.

One of the key strengths of the system lies in its ability to provide real-time data transmission using wireless communication technologies. The implementation of LoRa-based communication, along with GSM and Wi-Fi modules, enables long-range, low-power, and reliable data transfer even in underground and remote locations. This ensures that critical information reaches the control room and concerned personnel without delay, enabling quick decision-making and emergency response.

The wearable design of the monitoring device enhances the practicality and usability of the system. Its compact and lightweight nature allows workers to carry it comfortably during their operations without any hindrance. This ensures that safety monitoring becomes an integral part of their work routine rather than an additional burden. The portability of the device makes it highly suitable for dynamic and confined sewage environments.

Another significant contribution of the proposed system is its decentralized and scalable architecture. By utilizing a wireless sensor network, the system eliminates the need for complex wired infrastructure and reduces installation and maintenance costs. The decentralized approach also minimizes the risk of a single point of failure, thereby improving system reliability and robustness in large-scale deployments.

The alert mechanism integrated into the system plays a crucial role in ensuring worker safety. The system is capable of detecting unsafe conditions and generating immediate alerts through messages and alarms. This real-time warning system enables workers to take preventive actions and helps supervisors respond promptly to emergencies, thereby significantly reducing the chances of severe incidents.

Despite its advantages, the system also highlights certain areas for future improvement, such as enhancing sensor accuracy, optimizing power consumption, and improving communication reliability in extreme underground conditions. Incorporating advanced technologies like cloud computing, IoT analytics, and machine learning can further improve the system's performance by enabling predictive analysis and intelligent decision-making.

In conclusion, the proposed system demonstrates a reliable, cost-effective, and efficient approach to real-time sewage monitoring. It not only improves worker safety but also provides a scalable solution for modern industrial applications. With further enhancements and real-world implementation, the system has the potential to significantly contribute to safer and smarter sewage management practices.

REFERENCES

[1] G. Kalpana, A. Dharnesh, S. Reshikanth, and P. Prasad 2024, “IoT-based toxic gas detection system for sewage safety,” *Journal of Electrical Engineering and Automation*, vol. 6, no. 3, pp. 199–209.

[2] L. M. Pires, J. C. Ferreira, and M. S. Rodrigues 2024, “LoRa-based IoT system for environmental monitoring,” *Future Internet*, vol. 16, no. 6, pp. 127–138.

[3] C. Cacciuttolo et al. 2024, “IoT sensor networks with LoRa connectivity for safe and sustainable work environments,” *Sensors*, vol. 24, no. 3, pp. 1–18.

[4] S. Mythili, K. L. Neela, and T. Mahesh Selvi 2024, “IoT-ML framework for monitoring wastewater contaminants,” *Desalination and Water Treatment*, vol. 285, pp. 1–12.

[5] A. Pagano et al. 2024, “Smart water IoT framework for monitoring water distribution systems,” *IEEE Internet of Things Journal*, vol. 11, no. 4, pp. 5623–5632.

[6] Z. Zhou et al. 2024, “IoT-empowered digital twin framework for continuous gas emission monitoring,” *IEEE Access*, vol. 12, pp. 115623–115635.

[7] J. Aira, T. Olivares, and F. M. Delicado 2024, “Low-cost IoT ecosystem for environmental contamination detection,” *Sensors*, vol. 24, no. 2, pp. 1–14.

[8] K. Sruthi and P. Ravi 2024, “IoT-enabled wearable sensor network for sewage worker safety monitoring,” *International Journal of Advanced Networking and Applications*, vol. 15, no. 1, pp. 6100–6107.

[9] A. Pendharkar, J. Chillapalli, K. Dhakate, and S. Gogoi 2023, “IoT-based sewage monitoring system for smart city applications,” *IEEE Conference on Computer Communication and Informatics (ICCCI)*, pp. 1–5.

[10] P. Patel and V. Rao 2023, “Smart sewer environment monitoring using IoT sensors,” *International Journal of Intelligent Systems*, vol. 18, no. 4, pp. 215–222.

[11] S. N. Jeffery, S. H. Newaz, and S. Nafi 2023, “LoRa-based IoT-enabled wearable sensor network for sewage environment monitoring,” *IEEE International Conference on Smart Sensors*, pp. 55–60.

[12] B. T. Nguyen and A. V. Nguyen 2022, “IoT application for gas leakage monitoring systems,” *International Journal of Engineering Science and Technology*, vol. 13, no. 2, pp. 45–52.

[13] M. Aarthi and A. Bhuvaneshwaran 2022, “IoT-based drainage and waste monitoring system for smart cities,” *Journal of Environmental Informatics*, vol. 38, no. 3, pp. 150–160.

[14] M. Shanthi 2021, “Detection, monitoring and control of toxic gas using IoT,” *Information Technology in Industry*, vol. 9, no. 1, pp. 112–118.

[15] S. Sindhu, D. M. Saravanan, and S. Srividhya 2021, “Toxic gas detection using IoT sensors: A comprehensive study,” *Sensors International*, vol. 2, pp. 1–10.

[16] S. U. Suganthi and R. Kumar 2021, “Coal mine safety monitoring system using LoRa wireless communication,” *Materials Today: Proceedings*, vol. 46, pp. 8670–8676.

[17] J. B. Sanger, L. Sitanayah, and I. Ahmad 2021, “Sensor-based garbage gas detection system,” *IEEE International Conference on Smart Computing*, pp. 215–220.

[18] K. Aishwarya, R. Nirmala, and R. Navamathavan 2021, “Recent advancements in liquefied petroleum gas sensors: A review,” *Sensors International*, vol. 2, pp. 100103.

[19] P. Narkhede, R. Walambe, and K. Kotecha 2021, “Gas detection using multimodal AI sensor fusion,” *IEEE Access*, vol. 9, pp. 97845–97855.

[20] D. Nurul Saiyidah et al. 2021, “LoRaWAN-based smart sewerage monitoring system,” *International Conference on IoT Systems Engineering*, pp. 101–106.

LIST OF PUBLICATIONS

1. Tharaneeswaran S, Sri Atchaya N, Mr.R. Mohan Raj, M.E., “Sewage Monitoring System”, 2nd International Conference on Smart Technology and Artificial Intelligence (STAI 2026) held at ACM Fremont Chapter, USA during April04-05, 2026.



2nd International Conference on Smart Technology and Artificial Intelligence (STAI 2026)

Organized by

ACM Fremont Chapter, USA

CERTIFICATE OF PRESENTATION

This is to certify that **Tharaneeswaran S** has presented the paper titled **Sewage Monitoring System** authored by **Mohan Raj R, Sri Atchaya N, Tharaneeswaran S** in the 2nd International Conference on Smart Technology and Artificial Intelligence (STAI 2026) held at ACM Fremont Chapter, USA during April 04-05, 2026.

STAI 2026/PC/683_2

Rakesh Keshava
Chair, ACM Fremont Chapter, USA
(General Chair)

Mukesh Saraswat
Jaypee Institute of Information Technology, India
(General Chair)

Springer

https://stai2026.estindiafoundation.org/

APPENDIX 1

PYTHON SIMULATION

```
import csv
import os
import random
import time
from datetime import datetime

# ============================================================
# SEWAGE MONITORING SYSTEM
# Python Simulation Prototype
# ============================================================

# Project folders
DATA_FOLDER = "data"
CSV_FILE = os.path.join(DATA_FOLDER, "sensor_data.csv")

# Number of readings
NUMBER_OF_READINGS = 20

# Time between readings
READING_INTERVAL = 1

# Safety thresholds
TEMPERATURE_LIMIT = 50.0
HUMIDITY_LIMIT = 90.0

CH4_LIMIT = 100.0
CO_LIMIT = 50.0
H2S_LIMIT = 10.0
NH3_LIMIT = 35.0

# ============================================================
# CREATE DATA FOLDER
# ============================================================

def create_data_folder():
    if not os.path.exists(DATA_FOLDER):
        os.makedirs(DATA_FOLDER)

# ============================================================
# SENSOR SIMULATION
# ============================================================

def read_temperature():
    return round(random.uniform(25.0, 55.0), 2)

def read_humidity():
    return round(random.uniform(40.0, 100.0), 2)

def read_ch4():
    return round(random.uniform(5.0, 150.0), 2)
```

```
def read_co():
    return round(random.uniform(2.0, 80.0), 2)

def read_h2s():
    return round(random.uniform(0.5, 20.0), 2)

def read_nh3():
    return round(random.uniform(5.0, 60.0), 2)

# ============================================================
# READ ALL SENSORS
# ============================================================

def read_all_sensors():

    sensor_data = {
        "temperature": read_temperature(),
        "humidity": read_humidity(),
        "ch4": read_ch4(),
        "co": read_co(),
        "h2s": read_h2s(),
        "nh3": read_nh3()
    }

    return sensor_data

# ============================================================
# CHECK SENSOR SAFETY
# ============================================================

def check_safety(sensor_data):

    alerts = []

    temperature = sensor_data["temperature"]
    humidity = sensor_data["humidity"]
    ch4 = sensor_data["ch4"]
    co = sensor_data["co"]
    h2s = sensor_data["h2s"]
    nh3 = sensor_data["nh3"]

    # Temperature
    if temperature > TEMPERATURE_LIMIT:
        alerts.append(
            f"High temperature: {temperature} °C"
        )

    # Humidity
    if humidity > HUMIDITY_LIMIT:
        alerts.append(
            f"High humidity: {humidity} %"
        )

    # Methane
    if ch4 > CH4_LIMIT:
```

```
        alerts.append(
            f"High methane (CH4): {ch4} ppm"
        )

    # Carbon monoxide
    if co > CO_LIMIT:
        alerts.append(
            f"High carbon monoxide (CO): {co} ppm"
        )

    # Hydrogen sulfide
    if h2s > H2S_LIMIT:
        alerts.append(
            f"High hydrogen sulfide (H2S): {h2s} ppm"
        )

    # Ammonia
    if nh3 > NH3_LIMIT:
        alerts.append(
            f"High ammonia (NH3): {nh3} ppm"
        )

    # Determine system status
    if len(alerts) == 0:
        status = "SAFE"

    elif len(alerts) == 1:
        status = "WARNING"

    else:
        status = "DANGER"

    return status, alerts

# ============================================================
# CONTROL EXHAUST FAN AND BUZZER
# ============================================================

def control_devices(status):

    if status == "SAFE":

        fan = "OFF"
        buzzer = "OFF"

    elif status == "WARNING":

        fan = "ON"
        buzzer = "OFF"

    else:

        fan = "ON"
        buzzer = "ON"

    return fan, buzzer
```

```
# ============================================================
# DISPLAY SENSOR VALUES
# ============================================================

def display_sensor_data(sensor_data):

    print()
    print("=" * 60)
    print("            SEWAGE MONITORING SYSTEM")
    print("=" * 60)

    print(
        f"Temperature : {sensor_data['temperature']} °C"
    )

    print(
        f"Humidity    : {sensor_data['humidity']} %"
    )

    print(
        f"CH4         : {sensor_data['ch4']} ppm"
    )

    print(
        f"CO          : {sensor_data['co']} ppm"
    )

    print(
        f"H2S         : {sensor_data['h2s']} ppm"
    )

    print(
        f"NH3         : {sensor_data['nh3']} ppm"
    )

    print("-" * 60)

# ============================================================
# DISPLAY SYSTEM STATUS
# ============================================================

def display_status(status, fan, buzzer):

    print(f"System Status : {status}")
    print(f"Exhaust Fan   : {fan}")
    print(f"Buzzer        : {buzzer}")

    print("=" * 60)

# ============================================================
# DISPLAY ALERTS
# ============================================================

def display_alerts(status, alerts):
```

```
    if status == "SAFE":

        print("No abnormal condition detected.")

    else:

        print()
        print("!" * 60)

        if status == "WARNING":
            print("WARNING: ABNORMAL CONDITION DETECTED")

        else:
            print("DANGER: CRITICAL CONDITION DETECTED")

        print("!" * 60)

        for alert in alerts:
            print("ALERT:", alert)

        print("!" * 60)

# ============================================================
# SAVE SENSOR DATA
# ============================================================

def save_reading(sensor_data, status, fan, buzzer, alerts):

    file_exists = os.path.exists(CSV_FILE)

    with open(
        CSV_FILE,
        mode="a",
        newline="",
        encoding="utf-8"
    ) as file:

        writer = csv.writer(file)

        # Create column headings for a new file
        if not file_exists:

            writer.writerow([
                "Timestamp",
                "Temperature_C",
                "Humidity_Percent",
                "CH4_ppm",
                "CO_ppm",
                "H2S_ppm",
                "NH3_ppm",
                "System_Status",
                "Exhaust_Fan",
                "Buzzer",
                "Alerts"
            ])
```

```
        writer.writerow([
            datetime.now().strftime(
                "%Y-%m-%d %H:%M:%S"
            ),
            sensor_data["temperature"],
            sensor_data["humidity"],
            sensor_data["ch4"],
            sensor_data["co"],
            sensor_data["h2s"],
            sensor_data["nh3"],
            status,
            fan,
            buzzer,
            " | ".join(alerts)
            if alerts
            else "None"
        ])

# ============================================================
# DISPLAY FINAL SUMMARY
# ============================================================

def show_summary(
    total_readings,
    safe_count,
    warning_count,
    danger_count
):

    print()
    print("=" * 60)
    print("            MONITORING SUMMARY")
    print("=" * 60)

    print(f"Total Readings : {total_readings}")
    print(f"SAFE           : {safe_count}")
    print(f"WARNING        : {warning_count}")
    print(f"DANGER         : {danger_count}")

    print("-" * 60)

    print(
        f"Sensor data saved to: {CSV_FILE}"
    )

    print("=" * 60)

# ============================================================
# MAIN PROGRAM
# ============================================================

def main():

    print("=" * 60)
    print("      SMART SEWAGE MONITORING SYSTEM")
    print("            PYTHON PROTOTYPE")
```

```
print("=" * 60)

print()
print("Initializing monitoring system...")

# Create data folder
create_data_folder()

print("Data folder ready.")

# Counters
safe_count = 0
warning_count = 0
danger_count = 0

print("Sensors initialized.")
print("Monitoring started.")

try:

    # Take multiple sensor readings
    for reading_number in range(
        1,
        NUMBER_OF_READINGS + 1
    ):

        print()
        print(
            f"Reading {reading_number}"
            f" / {NUMBER_OF_READINGS}"
        )

        # Read sensors
        sensor_data = read_all_sensors()

        # Display sensor values
        display_sensor_data(sensor_data)

        # Check safety
        status, alerts = check_safety(
            sensor_data
        )

        # Control devices
        fan, buzzer = control_devices(
            status
        )

        # Display status
        display_status(
            status,
            fan,
            buzzer
        )

        # Display alerts
```

```
            display_alerts(
                status,
                alerts
            )

            # Save data
            save_reading(
                sensor_data,
                status,
                fan,
                buzzer,
                alerts
            )

            # Update counters
            if status == "SAFE":

                safe_count += 1

            elif status == "WARNING":

                warning_count += 1

            else:

                danger_count += 1

            # Wait before next reading
            if reading_number < NUMBER_OF_READINGS:

                time.sleep(
                    READING_INTERVAL
                )

    except KeyboardInterrupt:

        print()
        print("Monitoring stopped by user.")

    finally:

        total_readings = (
            safe_count
            + warning_count
            + danger_count
        )

        show_summary(
            total_readings,
            safe_count,
            warning_count,
            danger_count
        )

        print()
        print("Program completed.")
```

```
# ============================================================
# START PROGRAM
# ============================================================

if __name__ == "__main__":
    main()
```