

SRI BHARATHI TECH

Filter Media Offerings

SRI BHARATHI GROUP

- Established by an eminent visionary with more than 40 years of industrial deep-rooted experience and expertise keeping the outlook on the fast-flourishing technical advance which gallops incredibly beyond leaps and bounds
- Scrupulously developed high quality filter pads, filter papers, filter bags and industrial filtering equipment
- Affiliated with technical leaders and other organizations in the filtering industry
- Mission is to manufacture of products with pristine purity
- Committed to the sublime aspect of maintaining precise standards of the products
- Continued endeavor in the avenue of Research & Development
- Our lofty ethical principles are commensurate with our promises

VALUES WE BRING IN

- Highly customizable specification in terms of crucial aspects like fiber length, viscosity, moisture etc
- We provide great value add not only in terms of quality but also professional after sales services
- Use On-Demand approach to tailor the product based on your need to suite your requirements on:
  - Shape
  - Size / Dimension
  - Technical Specification
- Filter Pads are manufactured using
  - Wood Pulp
  - Cellulose Pulp
  - Hybrid/Mixture Pulp
- Adhering to high quality standards
- Competitive pricing
- Offer 24x7 support
- Protected from the dollar exchange rate fluctuation
- Certified for usage in food and pharmaceutical industries
- Offers end-to-end support which includes water proof packaging, transportation, etc



FOOD GRADE SAFETY MEASURES

- 100% secure and protected from any external adulteration/contamination
- We do not use any solvent / chemical and adhere to the strict norms of Food & Pharmaceutical Industries
- Fully automated and lesser human intervention for the high quality and safety of pads
- ISO 9001-2000 Certified manufacturing unit
- Dun & Bradstreet Certified

PRODUCTS

- Filter papers & pads
- High Temperature Filter Pads
- Activated carbon filter pads
- Filter cartridges
  - Spun bonded filter cartridge
  - Wound filter cartridge
  - Stainless steel filter cartridge
  - Polypropylene pleated filter cartridge
- Filter bags for liquid
- Filter housing
  - Polypropylene filter cartridge housings
  - Stainless Steel filter cartridge housings
  - Stainless steel filter bags housings
- Dust collection filter cartridges



DOMAIN AREAS

Intermediate Filtration	Final Filtration	Sterile Filtration
• Filter Pads • Filter Papers • Membrane Filter Cartridges	• Filter Pads • Filter Papers • Membrane Cartridges • Modular Filter System	• Capsule Filters • Mini Filter Cartridges • PES Membrane Cartridges

FILTER PAD & PAPERS



We manufacture a wide range of filter papers & pads on a very highly sophisticated production plant. The entire process of manufacturing is untouched by hand from the pulping stage to the finished product.

This is a high precision completely automatic plant which ensures a uniformly produced filter media for excellent purity and frees from external contaminants qualities vital for sensitive industries like drugs, pharmaceuticals, foods, beverages, chemicals, cosmetics etc.

Our raw material is continuously monitored for quality control. Constant laboratory tests are conducted to check filtration efficiency, pad porosity, absorbency, filtration speed and bursting factor. The fibers of our filter paper & pads are also subjected to a special porous chemically inert wet-strength impregnation process to impart very high mechanical strength while filtering aqueous. We also manufacture handmade filter papers & pads as per customers' requirement.



Grade	Thickness (in mm)	G.S.M	Porosity (in sec)	B.F. (in kg/cm2)	Bulk (in gm/cc)	Application
PPN-01	0.4	100	8	4	0.004	Coarse filtration
PPN-15	0.7	150	5	4	0.004	
SW-15	1.2	900	120	10	0.011	Fine filtration
MMCR-1	1	500	5	4	0.002	Clarifying filtration
MMCR-15	1.5	650	7	7	0.025	
MMCR-2	2	800	8	10	0.033	
MMCR-25	2.5	1100	8	10	0.022	
MMCR-3	3	1300	10	10	0.023	
MMC-05	0.5	250	4 to 5	3	0.002	Clarifying & polishing
MMC-1	1	500	6 to 7	5	0.002	
MMC-15	1.5	700	10	5	0.016	
MMC-02	2	850	8	7	0.024	

MMC-25	2.5	1050	14	10	0.023	
W-15	1.5	750	20	7	0.0021	Fine filtration for pharma & liqueur industries
MMCW-02	2.0	950	25	10	0.0021	
MMCW-25	2.5	1250	25	10	0.0021	
BK-02	2	800	12	8	(custom)	Decolorization and deodorization

The raw material used in manufacturing of the Filter Pads is 100% natural pulp and is unbleached. It is manufactured and continuously monitored under the rules of food and it is food gradable.

ACTIVATED CARBON FILTER PADS

Carbon has been used for many years in loose form to remove color and odor from liquids. In certain applications the loose carbon can be replaced with a carbon impregnated filter pad. When using loose carbon, it is necessary to remove the carbon with some means of filtration. If that includes a plate and frame filter press, then the press can be dressed with activated carbon filter pads, eliminating the need for dumping loose carbon into a mixing tank, and then scraping the carbon off of a filter paper or cloth.



We offer its series in two grades namely BK2 & BK25. Each grade can be manufactured with different degrees of carbon composition, allowing it to help optimize your filtration.

HIGH TEMPERATURE FILTER PAD FOR EDIBLE OIL



Manage your oil for healthier and profitable frying.

Good oil management practices begin with an understanding of what common conditions break down cooking oil and how to counter them. Frequent filtering is the best way to preserve oil quality and our High Temperature Filter Pads for the cooking oil helps you in achieving the best oil management strategy.

- Filter pad which can withstand up to 200°C temperature
- Premium grade Carbon and Non-Carbon variants are available

- Recycles the cooking oil for reuse thus helps in reducing the cost
- Helps remove the trans fats from the cooking oil
- Widely used in the deep filtration scenarios like:
    - High temperature cooking oil filtration for the food industries / star hotels
    - High temperature liquid/chemical which requires fine / deep filtration for the removal of residues / foreign particles
- Food grade raw materials are used which makes it a perfect product to filter edible cooking oil
- Available in standard as well custom sizes

SPUN BONDED FILTER CARTRIDGE



Spun bonded filter cartridges are made of 100% polypropylene fibers. The fibers have been carefully spun together to form a true gradient density from outer to inner surface. Filter cartridges available with core & without core version.

The superior structure remains integral even under severe operating conditions and has no media migration. Polypropylene fibers are blown continuously on the central molded core, without the need for binders, resins or lubricants.

Operation Unfiltered fluid passes through a depth filter matrix, enabling the progressive retention of finer particles, providing high efficiency, high dirt retention & filter life. Fluid flows from outside to inside through filter media. Particulates are held securely in the filter matrix and clean fluid flows to the downstream side of the cartridge.

Salient features

- Free of Surfactants, Binders and Adhesives
- Excellent flow with low pressure drop
- High dirt holding capacity
- High strength & pressure resistance
- 100 % Polypropylene for wide chemical compatibility
- Nominal & absolute filtration rating
- One piece construction up to 1016 mm & more

Technical specification

Sizes	10”/ 20”/ 30”/ 40” (Length)
Micron Rating	0.5 / 1 / 5 / 10 / 25 / 50 / 75 / 100

Outer Diameter	64 mm (2.5”) / 114 mm (4.5”) / 6” / 8”
Inner Diameter	25 mm / 28 mm / 48 mm

Configuration

- Double Open Type (DOE Type)
- Code 7 (226 O Ring Design)

Construction

- Spun bonded filter cartridges are made of 100% polypropylene

Applications

Food & beverages	Pharmaceuticals	Fine chemicals
Magnetic coating	Petrochemicals	Petroleum & Gas
Water treatment	Metal finishing	Cosmetics

WOUND FILTER CARTRIDGE



Wound cartridges are designed to meet the most demanding filtration duties. They offer an economic, compact, easily installed and maintained filtration system for removal of particulate removal from liquid. Wound cartridges are manufactured from a variety of carefully selected raw materials. These are processed into fibers of specific grades using the latest technology. After carding & spinning into roving they are wound into cartridges with carefully controlled micron rating. From raw material to finished products we are in control of the quality and filtration characteristics. They are appreciated due to high dirt holding capacity and to the rugged construction which allow facing different applications in liquid and gas filtration. Operation Unfiltered fluid passes through a depth filter matrix, enabling the progressive retention of finer particles, providing high efficiency, high dirt retention & filter life. Fluid flows from outside to inside through filter media.

Salient features

- Standard and customized sizes to fit most housings
- Filtration rating from 1 to 100 Micron
- High strength & pressure resistance
- Manufactured in continuous length
- Full range of sizes from 10” to 60” Length
- Excellent flow with low pressure drop
- High dirt holding capacity

- Compatible with a wide range of fluids
- NSF & FDA approved

Technical specification

Sizes	10”/ 20”/ 30”/ 40” / 60” (Length)
Micron Rating	0.5 to 100
Outer Diameter	58 mm to 200 mm
Inner Diameter	25 mm

Configuration

- Double Open Type (DOE Type)
- Code 7 (226 O Ring Design)

Construction

- Polypropylene with polypropylene core
- Cotton with stainless steel core

Applications

- Polypropylene wound filter cartridge

Organic acids	Oils
Concentrated alkalis	Water
Organic solvents	Electroplating solution

- Cotton wound filter cartridge

Vegetable oils	Dilute acids
Organic solvents	Portable liquids
Alkalis	Petroleum and Gas

POLYPROPYLENE PLEATED CARTRIDGE



Polypropylene filter cartridges are precisely manufactured for use in critical filtration applications within food, pharmaceuticals, bio-tech, dairy, beverages, brewing, semiconductor, water treatment & other demanding process industries.

Polypropylene pleated cartridges use the very latest gradient density micro fiber media technology to provide a combination of excellent micro ratings, high flow rates and high contaminant

holding capacities. A special combination of polypropylene media with variation in the fiber diameter has created a gradient density matrix, ranging from open on the outside to finer on the inside, thereby providing a filter within filter, which considerably increases contamination holding capacity & throughput.

All components used in the manufacture are biologically safe, chemically inert and meet FDA and other international quality requirements. Polypropylene offers an extremely broad chemical compatibility making it suitable for many applications.

Salient features

- All polypropylene construction
- Absolute & nominal efficiency
- 0.1 to 40 Micron ratings
- Gradient density micron fiber media
- High surface area of more than 0.5 m2
- Robust outer cage
- Biologically safe
- Non fiber migration
- Thermally welded construction
- FDA approved filters

Technical specification

Sizes	10”/ 20”/ 30”/ 40” (Length)
Micron Rating	0.1 / 0.2 / 0.45 / 1 to 50
Outer Diameter	69 mm
Inner Diameter	28 mm

Configuration

- Double Open Type (DOE Type)
- Code 7 F (226 O Ring Design)
- Code 7 S (226 O Ring Design/flat)
- Code 3 F (222 O Ring Design)
- Code 3 S (222 O Ring Design/flat)

Applications

- Fine chemicals and pharmaceuticals

D.I. water	R.O. prefiltration
Oral drugs	Biological fluids
Ophthalmic liquids	Petroleum and Gas

- Photographic film & paper

Antihalation coatings	Developer chemicals
Emulsions	Gelatin

- Beverages

Wine	Beer
Fruit juices	Alcohols

STAINLESS STEEL CARTRIDGE



Stainless steel cartridges are designed to overcome the temperature and chemical compatibility limitations of fabric or synthetic fiber media. This will offer very high temperature resistance & can withstand high differential pressure. Stainless steel cartridges are offered in SS 304, SS 316, & SS 316 l material. These elements can be plain cylindrical or pleated configuration to increase filtration area.

Normally all stainless steel pleated & cylindrical filters are supported with coarser filter media to ensure any direct damages to main filtering media under process upsets.

A bubble point test can be done to certify that no opening larger than the specified pore size exists in product joints or seams. No media migration due to stainless steel material. These elements can be back washed & reused.

Type of filters

- Stainless steel wire mesh type
- Stainless steel sintered metal type
- Stainless steel random fiber / sintered metal fiber type

Type of filter design

- Plain cylindrical design
- Pleated configuration design

Salient features

- Stable pore shapes

- High permeability
- Low pressure drop
- High dirt-holding capacity (longer lifetime)
- High temperature resistance
- High differential pressure withstand capacity
- Strong corrosion resistant
- Back flushing
- Excellent mechanical strength
- No media migration
- Size customization

Construction of sintered material

- The composite fiber material is then sintered together with a wire mesh under vacuum conditions and rolled to mats of a specific thickness.
- Stainless Cartridge can be wrought into tubes, cartridges or discs, plain, pleated or according to customer requests.

Technical specification

Sizes	10”/ 20”/ 30”/ 40” (Length) Customized sizes are available as well.
Micron Rating	0.5 / 1 / 3 / 5 / 10 / 20 / 25 / 50 & more
Outer Diameter	64 mm
Inner Diameter	28 mm

Configuration

- Double Open Type (DOE Type)
- Code 7 F (226 O Ring Design)
- Code 7 S (226 O Ring Design/flat)
- Code 3 F (222 O Ring Design)
- Code 3 S (222 O Ring Design/flat)
- 1” NPT / BSP Connection

Applications

Catalyst recovery in petrochemical & chemical industries	Polymer filtration	Cross flow filtration
Petroleum and Gas filtration	Analytical devices	Medical devices
Oil filtration	Hot gas filtration	Aerosol application
Fuel & hydraulic oil filtration	Gas–liquid separation	R.O. prefiltration

PLEATED DUST COLLECTION CARTRIDGE

Pleated dust collection cartridges are made of 100 % polyester media with different coatings on it , as per requirement of applications. Manufacturer of dust collectors originally designed to build the dust collection cartridges in equipment, whereas pleated bags can be used for existing dust collectors in place of conventional dust collection bags, without modifications.



This polyester media is made of high tenacity filament yarn without using any binding agent. Thus hard finished material is very stable against hot gas attack & structurally durable.

This unique & hard finished material provides features of good pleat ability, high durability, and unique structure of very fine filament yarn which offer high performance in filtration. Thermally tight bonded media provide washability, excellent palatability, stable structure, fine dust release and good resistance of particle penetration into the media.

This filter media is pleated in different pleated depths and height to accommodate desired filtration area. The construction pleated spun bonded filter media placed in a cylindrical configuration with support of metal core & encapsulated with metal end caps to form pleated dust collection cartridges. The end caps are configured to mount as a clean side or dirt side fitment. In case of metal caps these bags are supported with soft sponge rubber sealing to ensure positive sealing of filter while fitment.

Salient features

- High filtration area up to 20 m^2
- Universal fixing arrangements
- Open pleat spacing
- Low consumption of compressed air (for cleaning)
- High efficiency due to surface filtration
- Very high air to cloth ratio
- Very high filtration efficiency
- Filtration Area: 0.96 m^2 to 20.0 m^2

Filter media

- Spun Bonded Polyester Media

Coating

- PTFE coating for oil & moisture removal
- Aluminum coating for anti-static application
- Stainless steel coating for anti-static application
- Fire retardant coating
- PTFE lamination for very sticky dust

Sizes

- Diameter of element: 150 mm / 225 mm / 325 mm (O.D)
- Length of element: 300 mm to 1400 mm (customizable)

Configuration

- Flange type model
- Three lug type model
- Standard type model

Applications

Pharmaceuticals	Steel & power
Powder coating	Cement & chemicals
Metals & minerals	Paints & pigments