

Package ‘scPipeline’

February 25, 2025

Title Seurat and Related R Packages for End-to-End Single Cell Analysis

Version 0.1.0.0

Author Viswanadham Sridhara [aut, cre] (<<https://orcid.org/0000-0003-0688-6140>>)

Maintainer Viswanadham Sridhara <Sridhara.0mics@gmail.com>

Description Reports markers list, differentially expressed genes, associated pathways, cell-type annotations, does batch correction and other related single cell analyses all wrapped within Seurat.

Imports Seurat, batchelor, dplyr, ReactomeGSA, celldex, SingleR, SummarizedExperiment, biomaRt, magrittr, rlang

License MIT + file LICENSE

Encoding UTF-8

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.2

VignetteBuilder knitr

Suggests knitr, rmarkdown

Contents

AnnotateCellsWithSingleR	2
ConvertGeneIdentifiers	2
ReactomeData	3
SeuratLowDim	3
SeuratMarkers	4
SeuratPreprocess	4
TransferAnnotations	5
Index	6

AnnotateCellsWithSingleR

Annotate cells in a Seurat object using SingleR with Celldex

Description

This function annotates the cells in a Seurat object using the SingleR package with reference data obtained from the Celldex package.

Usage

```
AnnotateCellsWithSingleR(seurat_object, reference_data = NULL, assay = "RNA")
```

Arguments

`seurat_object` A Seurat object to be annotated.

`reference_data` A reference dataset to use for annotation (e.g., `HumanPrimaryCellAtlasData` from `Celldex`). If `NULL`, `HumanPrimaryCellAtlasData` is used by default.

`assay` The assay in the Seurat object to use for annotation. Default is "RNA".

Value

The Seurat object with cell annotations added to the metadata.

ConvertGeneIdentifiers

Convert Gene Identifiers in a Seurat Object

Description

This function takes a Seurat object with gene identifiers as row names (e.g., RefSeq, Ensembl, Entrez) and converts those identifiers to gene symbols (or Ensembl Gene IDs) using the `biomaRt` package. The function can handle various types of gene identifiers and returns a Seurat object with updated row names.

Usage

```
ConvertGeneIdentifiers(
  seurat_object,
  id_type = "refseq",
  to_id_type = "symbol"
)
```

Arguments

`seurat_object` A Seurat object. The row names of the Seurat object's data or assay slot should represent gene identifiers (e.g., RefSeq, Ensembl, or Entrez IDs).

`id_type` A string specifying the type of the input gene identifiers. Options are: "refseq", "ensembl", "entrez". Default is "refseq".

`to_id_type` A string specifying the type of output gene identifiers. Options are: "symbol", "ensembl". Default is "symbol".

Value

A Seurat object with updated gene names (row names) based on the specified conversion.

ReactomeData

Reactome Data Analysis for Seurat Object

Description

This function performs pathway analysis using ReactomeGSA on a Seurat object with cluster information.

Usage

```
ReactomeData(lowdim_seurat_object)
```

Arguments

lowdim_seurat_object

Seurat object that has clusters information

Value

A list containing: - GSVA result (gsva_result) - Pathway expression data (pathway_expression)
- Max difference between pathway expression values (max_difference)

SeuratLowDim

Create a Low dimensional Seurat object from scaled seurat object

Description

This function converts the transformed data to low-dimensional data for downstream analysis.

Usage

```
SeuratLowDim(scaled_seurat_object, ...)
```

Arguments

scaled_seurat_object

A scaled Seurat object.

...

Additional arguments to be passed for downstream analyses.

Value

A Seurat object.

SeuratMarkers

A thresholded markers list for better calculation of DE genes

Description

This function calculates differentially expressed genes using `Seurat::FindAllMarkers`.

Usage

```
SeuratMarkers(lowdim_seurat_object)
```

Arguments

`lowdim_seurat_object`
Seurat object with cluster information

Value

A list containing two marker lists: - Full markers list - Thresholded markers list with `min.pct = 0.1`

SeuratPreprocess

Preprocess count data and create a Seurat object

Description

This function preprocesses count data, optionally applying batch correction using `batchelor::fastMNN`, and creates a Seurat object.

Usage

```
SeuratPreprocess(
  counts_data,
  meta.data = NULL,
  batch_column = NULL,
  use_fastMNN = FALSE,
  ...
)
```

Arguments

`counts_data` A matrix or data frame of count data.
`meta.data` A data frame containing metadata to include in the Seurat object. Default is `NULL`.
`batch_column` A vector or factor specifying batch assignments for each cell. Default is `NULL`.
`use_fastMNN` Logical. Whether to apply batch correction using `fastMNN`. Default is `FALSE`.
`...` Additional arguments to be passed to `Seurat::CreateSeuratObject`.

Value

A Seurat object.

TransferAnnotations	<i>Transfer annotations to Seurat clusters</i>
---------------------	--

Description

This function assigns cluster-level annotations in a Seurat object based on the majority annotation of cells within each cluster.

Usage

```
TransferAnnotations(seurat_object, annotation_col, cluster_col, output_col)
```

Arguments

seurat_object	Seurat object containing cluster and annotation information.
annotation_col	The name of the metadata column with annotations (character string).
cluster_col	The name of the metadata column with cluster information (character string).
output_col	The name of the output column to store cluster annotations (character string).

Value

The Seurat object with an additional column in its metadata, specified by output_col.

Index

AnnotateCellsWithSingleR, [2](#)

ConvertGeneIdentifiers, [2](#)

ReactomeData, [3](#)

SeuratLowDim, [3](#)

SeuratMarkers, [4](#)

SeuratPreprocess, [4](#)

TransferAnnotations, [5](#)