

I want to learn how AMR - Adaptative Mesh Refinement works and what are the state of the art in the use of this method.

How AMR Works and Current Frontiers

Adaptive mesh refinement **works by solving on a coarse mesh, estimating where error or important physics concentrate, then locally refining or coarsening the grid during the simulation** (Zhu et al., 2024; Amor-Martín & García-Castillo, 2021). Its state of the art is moving beyond classic gradient-based refinement toward **anisotropic, high-order, GPU/exascale, and machine-learning-guided** AMR, but robust error indicators, geometry handling, and scalable unsteady multiphysics remain active challenges (Vivarelli et al., 2025).

Core Workflow

AMR allocates fine resolution only near features such as interfaces, shocks, vortices, boundaries, or geometric details, while keeping the rest of the domain coarse (Papoutsakis et al., 2018; Schmidmayer et al., 2019). This usually cuts memory and CPU cost relative to a uniformly fine mesh without giving up comparable accuracy in the important regions (Zhang et al., 2020; Zhu et al., 2024; Vivarelli et al., 2025).

The canonical loop is **solve → estimate → mark → refine/coarsen**, repeated as the solution evolves (Zhu et al., 2024; Amor-Martín & García-Castillo, 2021). In practice, codes tag cells using user-defined error estimates or heuristics such as first or second derivatives, curvature, or application-specific indicators, then rebuild the mesh locally (Zhang et al., 2020; Vedam & Engblom, 2025).




FIGURE 1 Typical adaptive mesh refinement update cycle

Main Design Choices

Approach	What Refines	Typical Strength	Example Evidence
Patch-based	Nested grid patches	Efficient hierarchy management	(Schmidmayer et al., 2019)
Cell-based	Individual cells	Flexible local adaptation	(Schmidmayer et al., 2019)
Block-based	Groups of cells	Good balance for HPC	(Schmidmayer et al., 2019; Zhang et al., 2020)

Approach	What Refines	Typical Strength	Example Evidence
h / p / hp	Cell size, order, or both	Match discontinuities and smooth regions	(Papoutsakis et al., 2018)
Anisotropic	Direction-specific refinement	Efficient for layers and stretched features	(Freret et al., 2022; Cervený et al., 2019)

FIGURE 2 Major AMR families and refinement modes

Non-conforming refinement is common because local refinement creates hanging nodes or level transitions that must be constrained or interpolated correctly (Cervený et al., 2019; Antepara et al., 2020). Data structures are therefore central: recent methods use octrees, quadrees, binary trees, dual cell/face trees, linked lists, or fully threaded trees to support fast splitting, merging, connectivity updates, and repartitioning (Papoutsakis et al., 2018; Schmidmayer et al., 2019).

State of the Art

Current AMR research is expanding in **four directions** (Vivarelli et al., 2025):

- **High-performance frameworks** now target laptops through exascale systems, as in AMReX, with dynamic regridding and load balancing for multiphysics PDE and particle-mesh codes (Zhang et al., 2020).
- **High-order and hp adaptivity** combines local mesh refinement with polynomial-order enrichment, especially useful where vortices or shear layers need more accuracy than pure h-refinement provides (Papoutsakis et al., 2018; Vivarelli et al., 2025).
- **Anisotropic and unstructured AMR** is advancing for 3D compressible, tetrahedral, prismatic, and hybrid meshes, improving efficiency for boundary layers, wakes, and complex geometries (Freret et al., 2022; Cervený et al., 2019; Amor-Martín & García-Castillo, 2021).
- **AI-guided refinement** is an emerging frontier, using PINNs, GNNs, GCNs, Gaussian mixture models, and reinforcement learning to replace heuristic tagging or costly adjoints in some settings (Zhu et al., 2024; Vivarelli et al., 2025).

Applications already span shock hydrodynamics, multiphase flow, fluid–structure interaction, immersed boundaries, plasma PIC, transonic flow, and Lagrangian hydrodynamics (Berger & Colella, 1989; Schmidmayer et al., 2019; Arshad et al., 2025). Reported gains are often large but problem-dependent: examples in this set include about **4× faster** level-set multiphase simulations, **40%+ fewer cells** in immersed-boundary flow, **50%+ fewer cells** with PINN-guided unstructured refinement, **up to 70% lower cost** with dominant-balance AMR, and **order-of-magnitude less grid** for one transonic strategy (Ngo & Choi, 2017; Saravanan et al., 2021; Zhu et al., 2024; Kumar & Nair, 2024; Vedam & Engblom, 2025).

Practical Caveats

The hardest unresolved issue is still the **refinement indicator**: gradients are cheap and widely used, but they can over-refine broad regions and do not guarantee lower global or goal-specific error (Zhu et al., 2024; Vivarelli et al., 2025). Adjoint-based methods tend to improve target quantities more efficiently, but they are more complex and expensive to deploy (Vivarelli et al., 2025).

Other persistent bottlenecks are mesh quality preservation, flux conservation across non-conforming interfaces, moving geometry support, particle consistency, and parallel load balancing on heterogeneous hardware (Arshad et al., 2025; Antepara et al., 2020; Dubey et al., 2021). So AMR is already mature and widely effective, but the **state of the art** is best described as a shift from hand-tuned local refinement toward automated, anisotropic, high-order, and hardware-aware adaptation rather than a single settled method.

These search results were found and analyzed using Consensus, an AI-powered search engine for research. Try it at <https://consensus.app>. © 2026 Consensus NLP, Inc. Personal, non-commercial use only; redistribution requires copyright holders' consent.

References

- Amor-Martín, A., & García-Castillo, L. (2021). Adaptive Semi-Structured Mesh Refinement Techniques for the Finite Element Method. *Applied Sciences*, 11, 3683. <https://doi.org/10.3390/app11083683>
- Antepara, O., Balcázar, N., & Oliva, A. (2020). Tetrahedral adaptive mesh refinement for two-phase flows using conservative level-set method. *International Journal for Numerical Methods in Fluids*, 93, 481 - 503. <https://doi.org/10.1002/fld.4893>
- Arshad, T., Chen, Y., & Tóth, G. (2025). Adaptive mesh refinement in semi-implicit particle-in-cell method. *Comput. Phys. Commun.*, 316, 109806. <https://doi.org/10.1016/j.cpc.2025.109806>
- Berger, M., & Colella, P. (1989). Local adaptive mesh refinement for shock hydrodynamics. *Journal of Computational Physics*, 82, 64-84. [https://doi.org/10.1016/0021-9991\(89\)90035-1](https://doi.org/10.1016/0021-9991(89)90035-1)
- Cervený, J., Dobrev, V., & Kolev, T. (2019). Non-Conforming Mesh Refinement for High-Order Finite Elements. *SIAM J. Sci. Comput.*, 41, C367-C392. <https://doi.org/10.1137/18m1193992>
- Dubey, A., Berzins, M., Burstedde, C., Norman, M., Unat, D., Wahib, M., Hinsén, K., & Dubey, A. (2021). Structured Adaptive Mesh Refinement Adaptations to Retain Performance Portability With Increasing Heterogeneity. *Computing in Science & Engineering*, 23, 62-66. <https://doi.org/10.1109/mcse.2021.3099603>
- Freret, L., Williamschen, M., & Groth, C. (2022). Enhanced anisotropic block-based adaptive mesh refinement for three-dimensional inviscid and viscous compressible flows. *J. Comput. Phys.*, 458, 111092. <https://doi.org/10.1016/j.jcp.2022.111092>
- Kumar, G., & Nair, A. G. (2024). Dominant balance-based adaptive mesh refinement for incompressible fluid flows. *J. Comput. Phys.*, 547, 114522. <https://doi.org/10.1016/j.jcp.2025.114522>
- Ngo, L. C., & Choi, H. (2017). A multi-level adaptive mesh refinement method for level set simulations of multiphase flow on unstructured meshes. *International Journal for Numerical Methods in Engineering*, 110, 947 - 971. <https://doi.org/10.1002/nme.5442>
- Papoutsakis, A., Sazhin, S., Begg, S., Danaila, I., & Luddens, F. (2018). An efficient Adaptive Mesh Refinement (AMR) algorithm for the Discontinuous Galerkin method: Applications for the computation of compressible two-phase flows. *J. Comput. Phys.*, 363, 399-427. <https://doi.org/10.1016/j.jcp.2018.02.048>
- Saravanan, V., Choung, H., & Lee, S. (2021). Cell-based hybrid adaptive mesh refinement algorithm for immersed boundary method. *International Journal for Numerical Methods in Fluids*, 94, 272 - 294. <https://doi.org/10.1002/fld.5054>
- Schmidmayer, K., Petitpas, F., & Daniel, E. (2019). Adaptive Mesh Refinement algorithm based on dual trees for cells and faces for multiphase compressible flows. *J. Comput. Phys.*, 388, 252-278. <https://doi.org/10.1016/j.jcp.2019.03.011>

- Vedam, A. J., & Engblom, W. A. (2025). Exploring a Novel Adaptive Mesh Refinement Strategy for Transonic Flows. *International Journal for Numerical Methods in Engineering*, 126. <https://doi.org/10.1002/nme.70226>
- Vivarelli, G., Qin, N., & Shahpar, S. (2025). A Review of Mesh Adaptation Technology Applied to Computational Fluid Dynamics. *Fluids*. <https://doi.org/10.3390/fluids10050129>
- Zhang, W., Myers, A., Gott, K., Almgren, A., & Bell, J. (2020). AMReX: Block-structured adaptive mesh refinement for multiphysics applications. *The International Journal of High Performance Computing Applications*, 35, 508 - 526. <https://doi.org/10.1177/10943420211022811>
- Zhu, Y., Zhao, S., Zhou, Y., Liang, H., & Bian, X. (2024). An unstructured adaptive mesh refinement for steady flows based on physics-informed neural networks. *J. Comput. Phys.*, 540, 114283. <https://doi.org/10.1016/j.jcp.2025.114283>