

ECS - ELASTIC CONTAINER SERVICE TASKS

=====

1. Setup a highly available ecs cluster with load balancer and dynamic port mapping.

NOTE:

Your cluster should maintain atleast 6 tasks at any point of time and should be highly available across multiple AZ's.

Use the below image from deployment:

sabair0509/hiring-app:works

Highly Available ECS Cluster with ALB & Dynamic Port Mapping

Objective

Deploy ECS (EC2 launch type) with:

- Application Load Balancer
- Dynamic Port Mapping
- Minimum 6 running tasks
- Multi-AZ high availability
- Image: sabair0509/hiring-app:works

Step 1: Create IAM Roles

ECS Instance Role

- IAM → Create Role → AWS Service → EC2
- Attach: AmazonEC2ContainerServiceforEC2Role
- Name: ecsInstanceRole

ECS Task Execution Role

- IAM → Create Role → AWS Service → ECS Task
- Attach: AmazonECSTaskExecutionRolePolicy
- Name: ecs-task-execution

Step 2: Create ECS Cluster (EC2)

- ECS → Create Cluster → EC2 Instances
- Cluster name: hiring-app-cluster
- Instance type: t3.large

- Min: 2 instances
- Max: 6
- Instance role: ecsInstanceRole

Ensure instances launch in multiple AZs.

Step 3: Create Task Definition

- ECS → Task Definitions → Create
- Family: hiring-app-task-definition
- Launch type: EC2
- Network mode: bridge
- CPU: 0.5 vCPU
- Memory: 1GB

Container

- Name: hiring-app
- Image: sabair0509/hiring-app:works
- Container port: 8080
- Host port: 0 (Dynamic port mapping)

Step 4: Create Target Group

- EC2 → Target Groups → Create
- Type: Instances
- Protocol: HTTP
- Port: 80
- Health check path: /
- Success codes: 200-499

Step 5: Create Application Load Balancer

- EC2 → Load Balancers → Create ALB
- Name: hiring-alb
- Scheme: Internet-facing
- Select 2 subnets (Multi-AZ)
- Listener: HTTP 80
- Forward to target group

Step 6: Create ECS Service

- Cluster → Create Service

- Task definition: Latest
- Service name: hiring-app-service
- Launch type: EC2
- Desired tasks: 6
- Deployment type: Rolling update

Load Balancing

- Use existing ALB
- Select target group
- Container: hiring-app
- Port: 8080

Step 7: Enable Auto Scaling

- Minimum tasks: 6
- Maximum tasks: 12
- Policy: Target Tracking
- Metric: ECSServiceAverageCPUUtilization
- Target: 70%

Result

- 6 tasks always running
- Tasks distributed across multiple AZs
- ALB distributes traffic
- Dynamic port mapping enabled
- Highly available architecture achieved

Cluster

Amazon Elastic Container Service

←

Favorites and recents

Express Mode

Clusters

Namespaces

Task definitions

Daemon task definitions

Account settings

AWS Resource Explorer

AWS Batch

Amazon ECR

Repositories

Online learning workshop

Documentation

Discover products

Subscriptions

Tell us what you think

Create cluster

Create cluster

info

An Amazon ECS cluster groups together tasks, and services, and allows for shared capacity and common configurations. All of your tasks, services, and capacity must belong to a cluster.

Cluster configuration

Cluster name

hiring-app-cluster

Cluster name must be 1 to 255 characters. Valid characters are a-z, A-Z, 0-9, hyphens (-), and underscores (_).

Service Connect defaults - optional

Infrastructure - advanced

info

Configure the manner of obtaining compute resources that will be used to host your application.

Select a method of obtaining compute capacity

Your cluster is automatically configured for AWS Fargate (serverless), but you may choose to add Amazon EC2 instances (servers).

☐ Fargate only

Serverless - you don't think about creating or managing servers. Great for most common workloads.

☐ Fargate and Managed Instances

Managed instances - Amazon ECS will manage patching and scaling on your behalf while giving you configurability about the types of instances. Great for more advanced workloads.

☒ Fargate and Self-managed instances

Self-managed instances - you must ensure the instances are patched and scaled properly, and you have full control over the instances.

Auto Scaling group (ASG)

info

Create a new Auto Scaling group - advanced

Use an existing Auto Scaling group

Provisioning model

Select a provisioning model for your instances

☒ On-demand

With on-demand instances, you pay for compute capacity by the hour, with no long-term commitments or upfront payments.

☐ Spot

Amazon EC2 Spot instances let you take advantage of unused EC2 capacity in the AWS cloud. [Learn more](#)

Amazon Elastic Container Service

Amazon Elastic Container Service

Favorites and recents

Express Mode

Clusters

Namespaces

Task definitions

Daemon task definitions

Account settings

AWS Resource Explorer

AWS Batch

Amazon ECR

Repositories

Online learning workshop

Documentation

Discover products

Subscriptions

Tell us what you think

Create cluster

Container Instance Amazon Machine Image (AMI)

Choose the Amazon ECS-optimized AMI for your instance.

Amazon Linux 2023

EC2 Instance type

Choose based on the workloads you plan to run on this cluster.

c7i-flex.large

x86_64

2 vCPU 4 GiB Memory

EC2 Instance role

An instance role is used by Amazon EC2 instances to make AWS API requests. If you don't already have an instance IAM role created, we can create one for you.

ecsinstanceRole

arn:aws:iam::299582146630:instance-profile/ecsinstanceRole

Create new instance profile

Desired capacity

Specify the number of instances to launch in your cluster.

Minimum

2

Maximum

6

SSH Key pair

If you do not specify a key pair, you can't connect to the instances via SSH unless you choose an AMI that is configured to allow users another way to log in.

devops.key

Create a new key pair

Root EBS volume size

You can increase the size of the root EBS volume to allow for greater image and container storage.

30

A min of 30 GiB and a max of 16,384 GiB is allowed.

Network settings

The default VPC, subnets, and security groups are selected by default.

Network settings

The default VPC, subnets, and security groups are selected by default.

VPC

Select a VPC to use for your Amazon ECS resources.

vpc-00148488443198382

default

Create a new VPC

Subnets

Select the subnets where your instances are launched and your tasks run. We recommend that you use three subnets for production.

Choose subnets

Clear current selection

subnet-09d53b9b035621be1

public-subnet

us-east-1a 172.31.4.0/22

subnet-05e7719471ca947ce

my-subnet-01

us-east-1c 172.31.0.0/22

Security group

Choose an existing security group or create a security group.

Use an existing security group

Create a new security group

Security group name

Choose an existing security group.

Choose security groups

sg-04833ef46f464b763

default

Auto-assign public IP

Choose whether to auto-assign a public IP to the Amazon EC2 instances

Turn on

Amazon Elastic Container Service

Amazon Elastic Container Service

Favorites and recents

Express Mode

Clusters

Namespaces

Task definitions

Daemon task definitions

Account settings

AWS Resource Explorer

AWS Batch

Amazon ECR

Repositories

Online learning workshop

Documentation

Discover products

Subscriptions

Cluster hiring-app-cluster has been created successfully.

View cluster

Clusters (1)

Search clusters

By default, we only load up to 1,000 clusters at a time.

Cluster	Services	Tasks	Container instances	CloudWatch monitoring	Capacity provider strategy
hiring-app-cluster	0	No tasks running	0 EC2	Default	No default found

EC2 > Instances

Instances (2/2) info

Connect Instance state Actions Launch instances

Instance state: running

Name	Instance ID	Instance state	Instance type	Status check	Availability Zone	Public IPv4 DNS	Public IPv4 ...	Elastic IP	IPv6 IPs
ECS Instance - ...	i-07051e0777181b14d	Running	c7i-flex.large	3/3 checks passed	us-east-1c	-	-	-	-
ECS Instance - ...	i-096cb47c79ac92f80	Running	c7i-flex.large	3/3 checks passed	us-east-1a	-	-	-	-

IAM > Roles

Roles (14) info

Delete Create role

Search

Role name	Trusted entities	Last activity
AWSServiceRoleForAmazonMQ	AWS Service: mq (Service-Linked Role)	26 days ago
AWSServiceRoleForAPIGateway	AWS Service: ops.apigateway (Service-Linked Role)	-
AWSServiceRoleForAutoScaling	AWS Service: autoscaling (Service-Linked Role)	6 minutes ago
AWSServiceRoleForECS	AWS Service: ecs (Service-Linked Role)	-
AWSServiceRoleForElasticLoadBalancing	AWS Service: elasticloadbalancing (Service-Linked Role)	25 days ago
AWSServiceRoleForRDS	AWS Service: rds (Service-Linked Role)	58 minutes ago
AWSServiceRoleForResourceExplorer	AWS Service: resource-explorer-2 (Service-Linked Role)	11 minutes ago

IAM > Roles > Create role

Step 2: Add permissions

Trusted entity type

- ☒ **AWS service**
Allow AWS services like EC2, Lambda, or others to perform actions in this account.
- ☐ **AWS account**
Allow entities in other AWS accounts belonging to you or a 3rd party to perform actions in this account.
- ☐ **Web identity**
Allows users federated by the specified external web identity provider to assume this role to perform actions in this account.
- ☐ **SAML 2.0 federation**
Allow users federated with SAML 2.0 from a corporate directory to perform actions in this account.
- ☐ **Custom trust policy**
Create a custom trust policy to enable others to perform actions in this account.

Use case

Allow an AWS service like EC2, Lambda, or others to perform actions in this account.

Service or use case

Elastic Container Service

Choose a use case for the specified service.

Use case

- ☐ **Elastic Container Service**
Allows ECS to create and manage AWS resources on your behalf.
- ☐ **Elastic Container Service Autoscale**
Allows Auto Scaling to access and update ECS services.
- ☒ **Elastic Container Service Task**
Allows ECS tasks to call AWS services on your behalf.
- ☐ **EC2 Role for Elastic Container Service**
Allows EC2 instances in an ECS cluster to access ECS.

Step 1

Step 2

Step 3

Select trusted entity

Add permissions

Name, review, and create

Use existing policy

Create inline policy

Permissions policies (2/1215)

Choose one or more policies to attach to your new role.

amazonecs

Filter by Type

All types

1 match

Policy name

Type

Description

AmazonECSTaskExecutionRolePolicy

AWS managed

Provides access to other AWS service reso...

Set permissions boundary - optional

Cancel

Previous

Next

Step 1

Step 2

Step 3

Select trusted entity

Add permissions

Name, review, and create

Role details

Role name

ecs-task-execution

Description

Allows ECS tasks to call AWS services on your behalf.

Step 1: Select trusted entities

Edit

Amazon Elastic Container Service

Task definitions

Task definitions (0)

Filter task definitions

Filter status

Active

Deploy

Create new revision

Create new task definition

Task definition

Status of last revision

No task definitions

Create new task definition

Amazon Elastic Container Service

Create new task definition

Task definition configuration

Task definition family

hiring-app-task-definition

▼ Infrastructure requirements

Launch type

AWS Fargate

Managed Instances

Amazon EC2 instances

OS, Architecture, Network mode

Operating system/Architecture

Linux/X86_64

Network mode

bridge

Task size

CPU

0.5 vCPU

Memory

1 GB

Amazon Elastic Container Service

Favorites and recents

Express Mode

Clusters

Namespaces

Task definitions

Daemon task definitions

Account settings

AWS Resource Explorer

AWS Batch

Amazon ECR

Repositories

Online learning workshop

Documentation

Discover products

Subscriptions

Tell us what you think

Create new task definition

Task role

ecs-task-execution

Create new role

Task execution role

Create default role

Create new role

Task placement - optional

Fault injection - optional

Container - 1

Essential container

Remove

Container details

Specify a name, container image, and whether the container should be marked as essential. Each task definition must have at least one essential container.

Name

hiring-app

Up to 255 letters (uppercase and lowercase), numbers, hyphens, and underscores are allowed.

Essential container

Yes

Image URI

sabair0509/hiring-app:works

Browse ECR Images

Up to 255 letters (uppercase and lowercase), numbers, hyphens, underscores, colons, periods, forward slashes, and number signs are allowed.

Private registry

Private registry authentication

Store credentials in Secrets Manager, and then use the credentials to reference images in private registries.

Port mappings

Add port mappings to allow the container to access ports on the host to send or receive traffic. For port name, a default will be assigned if left blank.

Host port

0

Container port

8080

Protocol

TCP

Port name

container-port-protocol

App protocol

HTTP

Remove

Amazon Elastic Container Service

Favorites and recents

Express Mode

Clusters

Namespaces

Task definitions

Daemon task definitions

Account settings

AWS Resource Explorer

AWS Batch

Amazon ECR

Repositories

Online learning workshop

Documentation

Discover products

Subscriptions

Tell us what you think

Task definition successfully created

hiring-app-task-definition:1 has been successfully created. You can use this task definition to deploy a service or run a task.

View task definition

hiring-app-task-definition:1

Last updated September 1, 2026, 17:29 (UTC+5:30)

Deploy

Actions

Create new revision

Overview

ARN

aws:ecs:us-east-1:299582146630:task-definition:hiring-app-task-definition:1

Status

ACTIVE

Time created

September 1, 2026, 17:29 (UTC+5:30)

App environment

EC2

Task role

ecs-task-execution

Task execution role

ecsTaskExecutionRole

Operating system/Architecture

Linux/X86_64

Network mode

bridge

Fault injection

Turned off

Containers

JSON

Task placement

Volumes (0)

Requires attributes

Tags

Task size

Task CPU

512 units (0.5 vCPU)

Task CPU maximum allocation for containers

CPU (unit)

0 50 100 150 200 250 300 350 400 450 500

hiring-app Shared task CPU

Task memory

1,024 MiB (1 GiB)

Task memory maximum allocation for container memory reservation

Memory (MiB)

0 100 200 300 400 500 600 700 800 900 1000

hiring-app Shared task memory

EC2 > Target groups > Create target group

Create target group

Step 2 - recommended

Register targets

Step 3

Review and create

Create target group

A target group can be made up of one or more targets. Your load balancer routes requests to the targets in a target group and performs health checks on the targets.

Settings - immutable

Choose a target type and the load balancer and listener will route traffic to your target. These settings can't be modified after target group creation.

Target type

Indicate what resource type you want to target. Only the selected resource type can be registered to this target group.

☒ **Instances**
Supports load balancing to instances in a VPC. Integrate with Auto Scaling Groups or ECS services for automatic management.
Suitable for: ALB NLB GWL

☐ **IP addresses**
Supports load balancing to VPC and on-premises resources. Facilitates routing to IP addresses and network interfaces on the same instance. Supports IPv6 targets.
Suitable for: ALB NLB GWL

☐ **Lambda function**
Supports load balancing to a single Lambda function. ALB required as traffic source.
Suitable for: ALB

☐ **Application Load Balancer**
Allows use of static IP addresses and PrivateLink with an Application Load Balancer. NLB required as traffic source.
Suitable for: NLB

Target group name

Name must be unique per Region per AWS account.

hiring-app-tg-8080

Accepts: a-z, A-Z, 0-9, and hyphen (-). Can't begin or end with hyphen. 1-32 total characters; Count: 18/32

Protocol

Protocol for communication between the load balancer and targets.

HTTP

Port

Port number where targets receive traffic. Can be overridden for individual targets during registration.

8080

1-65535

IP address type

Only targets with the indicated IP address type can be registered to this target group.

☒ **IPv4**
Each instance has a default network interface (eth0) that is assigned the primary private IPv4 address. The instance's primary private IPv4 address is

EC2 > Target groups > Create target group

Create target group

Step 2 - recommended

Register targets

Step 3

Review and create

Create target group

A target group can be made up of one or more targets. Your load balancer routes requests to the targets in a target group and performs health checks on the targets.

Settings - immutable

Choose a target type and the load balancer and listener will route traffic to your target. These settings can't be modified after target group creation.

Target type

Indicate what resource type you want to target. Only the selected resource type can be registered to this target group.

☒ **Instances**
Supports load balancing to instances in a VPC. Integrate with Auto Scaling Groups or ECS services for automatic management.
Suitable for: ALB NLB GWL

☐ **IP addresses**
Supports load balancing to VPC and on-premises resources. Facilitates routing to IP addresses and network interfaces on the same instance. Supports IPv6 targets.
Suitable for: ALB NLB GWL

☐ **Lambda function**
Supports load balancing to a single Lambda function. ALB required as traffic source.
Suitable for: ALB

☐ **Application Load Balancer**
Allows use of static IP addresses and PrivateLink with an Application Load Balancer. NLB required as traffic source.
Suitable for: NLB

Target group name

Name must be unique per Region per AWS account.

hiring-app-tg-8080

Accepts: a-z, A-Z, 0-9, and hyphen (-). Can't begin or end with hyphen. 1-32 total characters; Count: 18/32

Protocol

Protocol for communication between the load balancer and targets.

HTTP

Port

Port number where targets receive traffic. Can be overridden for individual targets during registration.

8080

1-65535

IP address type

Only targets with the indicated IP address type can be registered to this target group.

☒ **IPv4**
Each instance has a default network interface (eth0) that is assigned the primary private IPv4 address. The instance's primary private IPv4 address is

VPC

Select the VPC with the instances that you want to include in the target group. Only VPCs that support the IP address type selected above are available in this list.

vpc-00148488443198382 (default) [Create VPC](#)

172.31.0.0/16

Protocol version

☒ **HTTP1**
Send requests to targets using HTTP/1.1. Supported when the request protocol is HTTP/1.1 or HTTP/2.

☐ **HTTP2**
Send requests to targets using HTTP/2. Supported when the request protocol is HTTP/2 or gRPC, but gRPC-specific features are not available.

☐ **gRPC**
Send requests to targets using gRPC. Supported when the request protocol is gRPC.

Health checks

The associated load balancer periodically sends requests, per the settings below, to the registered targets to test their status.

Health check protocol

HTTP

Health check path

Use the default path of "/" to perform health checks on the root, or specify a custom path if preferred.

/

Up to 1024 characters allowed.

Advanced health check settings

Target optimizer - optional [info](#)

Enforce a maximum number of concurrent requests on a target. This is particularly useful for compute-intensive workloads like complex data processing or inference.

[Target optimizer](#)

EC2 > Target groups > hiring-app-tg-8080 > Register targets

Filter instances

☐

Instance ID

☐

i-096cb47c79ac92f80

☐

i-07051e077181b14d

ECS Instance - hiring-app-cluster

Running

default

us-east-1a

172.31.6.105

subnet-09d53b9b035621be1

September 1, 2026, 17:01 (UTC+05:30)

ECS Instance - hiring-app-cluster

Running

default

us-east-1c

172.31.3.195

subnet-05e7719471ca947ce

September 1, 2026, 17:01 (UTC+05:30)

0 selected

Ports for the selected instances

Ports for routing traffic to the selected instances.

80

1-65535 (separate multiple ports with commas)

Include as pending below

2 selections are now pending below. Include more or register targets when ready.

Review targets

Targets (2)

Filter targets

Show only pending

[Remove all pending](#)

Instance ID

Name

Port

State

Security groups

Zone

Private IPv4 address

Subnet ID

Launch time

[i-096cb47c79ac92f80](#)

ECS Instance - hiring-app-cluster

8080

Running

default

us-east-1a

172.31.6.105

subnet-09d53b9b035621be1

September 1, 2026, 17:01 (UTC+05:30)

[i-07051e077181b14d](#)

ECS Instance - hiring-app-cluster

8080

Running

default

us-east-1c

172.31.3.195

subnet-05e7719471ca947ce

September 1, 2026, 17:01 (UTC+05:30)

2 pending

[Cancel](#) [Register pending targets](#)

Search

[Alt + S]

IAM

VPC

EC2

S3

Route 53

Certificate Manager

United States (N. Virginia)

Srihari (299582146630)

EC2

Target groups

Create target group

Advanced health check settings

Restore defaults

Health check port

The port the load balancer uses when performing health checks on targets. By default, the health check port is the same as the target group's traffic port. However, you can specify a different port as an override.

Traffic port

Override

Healthy threshold

The number of consecutive health check successes required before considering an unhealthy target healthy.

5

2-10

Unhealthy threshold

The number of consecutive health check failures required before considering a target unhealthy.

2

2-10

Timeout

The amount of time, in seconds, during which no response means a failed health check.

5

seconds

2-120

Interval

The approximate amount of time between health checks of an individual target.

30

seconds

5-300

Success codes

The HTTP codes to use when checking for a successful response from a target. You can specify multiple values (for example, "200,202") or a range of values (for example, "200-299").

200-495

Searchload balancers

Ask Amazon Q

IAM

VPC

EC2

S3

Route 53

Certificate Manager

United States (N. Virginia)

Srihari (299582146630)

EC2

Load balancers

Create Application Load Balancer

Create Application Load Balancer

The Application Load Balancer distributes incoming HTTP and HTTPS traffic across multiple targets such as Amazon EC2 instances, microservices, and containers, based on request attributes. When the load balancer receives a connection request, it evaluates the listener rules in priority order to determine which rule to apply, and if applicable, it selects a target from the target group for the rule action.

How Application Load Balancers work

Basic configuration

Load balancer name

Name must be unique within your AWS account and can't be changed after the load balancer is created.

hiring-app-alb

A maximum of 32 alphanumeric characters including hyphens are allowed, but the name must not begin or end with a hyphen.

Scheme

Info

Scheme can't be changed after the load balancer is created.

Internet-facing

Internal

Load balancer IP address type

Info

Select the front-end IP address type to assign to the load balancer. The VPC and subnets mapped to this load balancer must include the selected IP address types. Public IPv4 addresses have an additional cost.

IPv4

Dualstack

Dualstack without public IPv4

Searchload balancers

Ask Amazon Q

IAM

VPC

EC2

S3

Route 53

Certificate Manager

United States (N. Virginia)

Srihari (299582146630)

EC2

Load balancers

Create Application Load Balancer

Network mapping

Info

The load balancer routes traffic to targets in the selected subnets, and in accordance with your IP address settings.

VPC

Info

The load balancer will exist and scale within the selected VPC. The selected VPC is also where the load balancer targets must be hosted unless routing to Lambda or on-premises targets, or if using VPC peering. To confirm the VPC for your targets, view [target groups](#).

vpc-00148488443198382

(default)

Create VPC

IP pools

Info

You can optionally choose to configure an IPAM pool as the preferred source for your load balancers IP addresses. Create or view [Pools](#) in the [Amazon VPC IP Address Manager console](#).

Use IPAM pool for public IPv4 addresses

Availability Zones and subnets

Info

Select at least two Availability Zones and a subnet for each zone. A load balancer node will be placed in each selected zone and will automatically scale in response to traffic. The load balancer routes traffic to targets in the selected Availability Zones only.

us-east-1a (use1-az1)

Subnet

Only CIDR blocks corresponding to the load balancer IP address type are used. At least 8 available IP addresses are required for your load balancer to scale efficiently. Selected subnets must have Network ACL inbound and outbound ALLOW rules, and internet gateway (IGW) routes configured to allow traffic.

subnet-09d53b9b035621be1 (public-subnet)

172.31.0.0/22

Network ACL ALLOW rules: Inbound (1) Outbound (1) | Route table: IGW (1)

us-east-1c (use1-az4)

Subnet

Only CIDR blocks corresponding to the load balancer IP address type are used. At least 8 available IP addresses are required for your load balancer to scale efficiently. Selected subnets must have Network ACL inbound and outbound ALLOW rules, and internet gateway (IGW) routes configured to allow traffic.

subnet-05e7719471ca947ce (my-subnet-01)

172.31.0.0/22

Network ACL ALLOW rules: Inbound (1) Outbound (1) | Route table: IGW (1)

load balancers

Ask Amazon

IAM

VPC

EC2

S3

Route 53

Certificate Manager

United States (N. Virginia)

Srihari

EC2

Load balancers

Create Application Load Balancer

Security groups

Info

A security group is a set of firewall rules that control the traffic to your load balancer. Listed security groups are in the same VPC as you selected above. Selected security groups must include at least 1 inbound rule and 1 outbound rule to allow traffic to your load balancer.

Security groups

Select up to 5 security groups

default (sg-04833ef46f464b763)

Inbound rule (10)

Outbound rule (1)

Create security group

Listeners and routing

Info

A listener is a process that checks for connection requests using the port and protocol you configure. The rules that you define for a listener determine how the load balancer routes requests to its registered targets.

▼ Listener HTTP:80

Remove

Protocol

HTTP

Port

80

1-65535

Default action

Info

The default action is used if no other rules apply. Choose the default action for traffic on this listener.

Routing action

Forward to target groups

Redirect to URL

Return fixed response

Forward to target group

Info

Choose a target group and specify routing weight or create target group.

Target group

hiring-app-tg-8080

Target type: Instance, IPv4 | Target stickiness: Off

HTTP

Weight

1

0-999

Percent

100%

Search

[Alt+S]

IAM

VPC

EC2

S3

Route 53

Certificate Manager

United States (N. Virginia)

Srihari

Amazon Elastic Container Service

Clusters

hiring-app-cluster

Create service

Amazon Elastic Container Service

←

Favorites and recents

Express Mode

Clusters

Namespaces

Task definitions

Daemon task definitions

Account settings

AWS Resource Explorer

AWS Batch

Amazon ECR

Repositories

Online learning workshop

Documentation

Discover products

Subscriptions

Tell us what you think

Service details

Task definition family

Select an existing task definition family. To create a new task definition, go to Task definitions.

hiring-app-task-definition

Task definition revision

Latest

Select the task definition revision from the 100 most recent entries, or enter a revision. Leave the field blank to use the latest revision.

1

Service name

Assign a service name that is unique for this cluster.

hiring-app-task-definition-service-bb06a89e

Up to 255 letters (uppercase and lowercase), numbers, underscores, and hyphens are allowed. Service names must be unique within a cluster.

Environment

Amazon EC2

Existing cluster

hiring-app-cluster

▼ Compute configuration - advanced

Compute options

Info

To ensure task distribution across your compute types, use appropriate compute options.

Capacity provider strategy

Launch type

Launch tasks directly without the use of a capacity provider strategy.

Launch type

Info

Select either managed capacity (Fargate), or custom capacity (EC2 or user-managed, External instances). External instances are registered to your cluster using the ECS Anywhere capability.

EC2

Search

[Alt+S]

IAM

VPC

EC2

S3

Route 53

Certificate Manager

United States (N. Virginia)

Srihari

Amazon Elastic Container Service

Clusters

hiring-app-cluster

Create service

Amazon Elastic Container Service

←

Favorites and recents

Express Mode

Clusters

Namespaces

Task definitions

Daemon task definitions

Account settings

AWS Resource Explorer

AWS Batch

Amazon ECR

Repositories

Online learning workshop

Documentation

Discover products

Deployment configuration

Info

Scheduling strategy

Info

Replica

Place and maintain a desired number of tasks across your cluster.

Daemon

Place and maintain one copy of your task on each container instance.

Desired tasks

Specify the number of tasks to launch.

6

Availability Zone rebalancing

Info

Turn on Availability Zone rebalancing

Amazon ECS automatically detects Availability Zone imbalances in task distributions across an ECS service, and evenly redistributes ECS service tasks across Availability Zones.

Health check grace period

Info

0

seconds

► Deployment options

► Deployment failure detection

Info

hiring-app-cluster

Cluster overview

Cluster ARN: [arn:aws:ecs:us-east-1:299582146630:cluster/hiring-app-cluster](#)

Status: Active

CloudWatch monitoring: Default

Action logs: Turned off

Services: 1 active | 0 draining

Tasks: 6 running | 0 pending

Registered container instances: 2

Services (1) Info

Service name	ARN	Status	Scheduling strategy	Launch type	Task definition	Deployments and tasks	Last deployment
hiring-app-task-definition-service- du...	arn:aws:ecs:us-east-1:299582146630:task-definition/hiring-app-task-definition-service-du...	Active	Any scheduling strategy	EC2	hiring-ap...	6/6 Tasks running	Completed

hiring-app-alb

Successfully created listener.

Introducing new Capacity Utilization metric for ALB

hiring-app-alb

Details

Load balancer type: Application

Status: Active

VPC: [vpc-0014848843198382](#)

Load balancer IP address type: IPv4

Scheme: Internet-facing

Hosted zone: Z355XDOTRQ7X7K

Availability Zones: [subnet-09d53b9b035621be1](#) us-east-1a (use1-az1), [subnet-05e7719471ca947ce](#) us-east-1c

Date created: September 2, 2026, 12:12 (UTC+05:30)

Load balancer ARN: [arn:aws:elasticloadbalancing:us-east-1:299582146630:loadbalancer/app/hiring-app-alb/69bb84a531e674ce](#)

Listeners and rules (2) Info

Listeners and rules

Network mapping

Resource map

Security

Monitoring

Integrations

Attributes

Capacity

Tags

Welcome to Techie Horizon