

Privy API Integration Guide

Version - 2.6
Date - 1st Oct 2026

Table of Contents

Table of Contents 2
API: Create Aggregated-Notice 4
Overview 4
Request Body 5
Response Body 10
Headers 11
Sample Input message 11
Sample output message 13
Sample Error message 14
Expected Responses 14
API: Attach Metadata - Aggregated 20
Overview 20
Request Body 20
Response Body 20
Headers 22
Sample Input message 22
Sample output message 23
Sample Error message 25
Metadata Key and Value Validations 26
Expected Responses 27
API: Create Flex ANC 33
Overview 33
Request Body 33
1.1 Top level 33
1.2 notice_workflow_settings 33
1.3 for_grant 34
1.4 business_processes[] 34
1.5 search 34
1.6 for_update 35
Response Body 36
Headers 37
Sample Input message 38
Sample output message 38
Sample Error message 39
Expected Responses 40
API: Submit Flex ANC 41
Overview 41
Request Body 41
1.1 Envelope 41

1.2 Every element 41
1.3 Grant elements 41
1.4 Update elements 42
1.5 Which purposes to send 42
Response Body 43
Headers 43
Sample Input message 44
Sample output message 45
Sample Error message 45
Expected Responses 45
API: Generate DPAR Link 47
Summary 47
Requirement background for Operation 47
Request Parameters 47
Response Parameters 48
Headers 48
Sample Input message 49
Sample output message 49
API: Consent Validation 50
Summary 50
Requirement background for Operation 50
Request Parameters 50
Response Parameters 50
Headers 51
Sample Input message 51
Sample output message 52
API: Bulk Consent Revocation 53
Overview 53
Request Body 53
Response Body 56
Headers 56
Sample Input message 57
Sample output message 57
Sample Error message 58
Privy error codes 58
Things to know 60
Webhook: Aggregated Notice Submitted 61
Overview 61
Webhook Response 61
Sample Webhook message 63
Webhook: Consent Artifact Created Or Updated 65

Summary 65
Webhook Body Parameters 65
Sample Webhook Response 67
Webhook: Consent Expired 69
Summary 69
Webhook Body Parameters 69
Sample Webhook Response 70
Privy error codes 71
Whitelisting 72
User Access in Client Environment 72
Application Integration in Client Environment 72

API: Create Aggregated-Notice

Overview

This API allows a Data Fiduciary to initiate and create an Aggregated Notice for a Data Principal. An Aggregated Notice represents a grant or update request for consent across multiple business processes, based on different identifiers of the same Data Principal. Once created, the API responds with the generated notice workflow ID and the associated access links for user interaction.

Env	URL	METHOD
PROD		POST
UAT	https://privy.idfy.com/api/v2/notice_workflow/create	POST

Request Body

Field Name	Data Type	Length	Optional/ Mandatory	Description	Example Values
group_reference_id	String	-	Mandatory	Unique identifier generated by the Data Fiduciary for this workflow. Used for tracking, audits, or future lookups. Reusing a previously used value returns 422 GROUP_REFERENCE_ID_ALREADY_TAKEN (no idempotency).	"12062026230190"
for_grant	Object	-	Optional	Grant defaults applied across the whole journey. Each business process can override any key via its own for_grant.	-
for_grant.data_principal_id	String	-	Mandatory, wherever a grant can happen	The create identity - a per-journey pseudonym, not a durable customer id. Can be set here or within a business process's own for_grant; after merging, it must be present for every business process that grants.	"005a6d85-61b7-4495-bb78-44a033ef0e1f"
for_grant.reference_id	String	-	Mandatory, wherever a grant can happen	Goes together with data_principal_id; same rules apply. Used for tracking, audits, or future lookups.	"personal-loan-application-no-1234"
for_grant.consent_settings.expires_in_hours	Integer	min: 1, no maximum (taken as-is, not clamped)	Optional (default: whatever set in business process)	How long the granted consent stays valid, in hours. Distinct from notice_workflow_settings.expires_in_hours, which is the link's validity, not the consent's.	25920

for_grant.metadata	Object (map)	up to 20 keys; key format [a-zA-Z0-9_-]+	Optional (default: none)	Attached when the business process grants. Ordinary keys (e.g. product_type) are stored on the notice record; identifier keys (e.g. crn) are also written to the search registry so future journeys can find this customer - always include the identifier on upsert entries. If the same key appears in both search.by and metadata, both values must match, else 422 VALIDATION_ERROR.	
for_grant.metadata[].key	String	key format [a-zA-Z0-9_-]+	Mandatory	The metadata key name.	"crn"
for_grant.metadata[].value	String	-	Mandatory	The value associated with the key.	"CRN77421"
notice_workflow_settings	Object	-	Mandatory	Link, language, and how the notice looks	-
notice_workflow_settings.default_language	String	ISO code (e.g. en, hi)	Mandatory	Language the notice displays by default. Every business process in the bundle must support it, else 422 LANGUAGE_NOT_SUPPORTED.	"en"
notice_workflow_settings.expires_in_minutes	Integer	min: 30, max: 259200	Mandatory	How long the notice link stays valid.	60
notice_workflow_settings.redirection_url	String	min: 2	Optional (default: popup)	URL the Data Principal is redirected to after submitting the notice.	"https://google.com"
notice_workflow_settings.sms_comms	Boolean	true, false	Optional (default: false)	Send the notice link to the principal over SMS. If true, at least one entry's for_grant.metadata (top level or any BP) must	true

				carry a valid phone_number - that number is used; it doesn't have to be on every BP. Two different numbers across BPs, an invalid number, or none anywhere give 422.	
notice_workflow_settings.email_comms	Boolean	true, false	Optional (default: false)	Send the notice link to the principal over email. If true, at least one entry's for_grant.metadata (top level or any BP) must carry a valid email - that email is used; it doesn't have to be on every BP. Two different emails across BPs, an invalid email, or none anywhere gives 422.	true
notice_workflow_settings.view_mode	String	-	Optional (default: processing_purpose)	What one row on the notice represents: a consent purpose or a processing purpose.	consent_purpose/processing_purpose/user_attributes/processing_done
notice_workflow_settings.purpose_default_selection	String	-	Optional (default: only_mandatory_selected)	Which checkboxes should be checked by default once notice opens: only the mandatory purposes, or all of them.	all_selected / only_mandatory_selected
notice_workflow_settings.show_consent_duration	Boolean	-	Mandatory	Whether to show consent durations on the notice.	false
notice_workflow_settings.merge_rule	String	-	Optional	This key lets you decide how you want to show the content of the notice Default - no_merge	no_merge, dedupe_common_only, merge_all
notice_workflow_settings.notice_theme	String	-	Optional	This key lets you decide the display structure of the notice	privy_default, grouped_cp_plain, pp_card, pp_flat

				Default - privy_default	
business_processes	Array of Objects	1 to 20 entries	Mandatory	The business processes in this bundle. Order in the array is the display order. The same business process code cannot appear twice (422 DUPLICATE_BUSINESS_PROCESS_IN_PAYLOAD).	-
business_processes[].business_process_code	String	-	Mandatory	Which business process this entry represents. An unknown code returns 422 BUSINESS_PROCESS_NOT_FOUND.	"tmA4nSCSdS"
business_processes[].business_process_version	Integer	min: 0	Optional (default: latest published)	Version of the business process. Fixed at create time - won't change if a newer version is later published.	1
business_processes[].for_grant	Object	-	Optional	Grant details for this entry, overriding the workflow-level for_grant key by key (metadata merges per metadata key rather than replacing the whole list). Same shape as the workflow-level for_grant.	
business_processes[].search	Object	-	Optional (no search = plain grant)	How to look up the customer and what to do with the result - the only thing the server decides for you. Omit this and the business process simply grants.	{"by": [{"key": "crn", "value": "CRN77421"}], "if_available": "update", "if_not_available": "grant"}
business_processes[].search.by	Object	at least one identifying key below; multiple keys must all	Mandatory within search	Who to look for. An empty by, or any key not in the allowed list, is 422 VALIDATION_ERROR. If more than one customer matches, the whole create	[{"key": "crn", "value": "CRN77421"}]

		match (AND)		fails with 422 MULTIPLE_ENTRIES_FOUND - the server never picks one.	
business_processes[].search.by[].key	String	allowed values: crn, data_principal_id, reference_id, phone, email	Mandatory (within each by entry)	Which identifier type this entry represents. data_principal_id and reference_id must be supplied together as a pair (both entries present) or not at all.	"crn"
business_processes[].search.by[].value	String	format depends on key	Mandatory (within each by entry)	The identifier value corresponding to key.	"CRN77421"
business_processes[].search.if_available	String	update / error	Optional (default: update)	What to do when the customer is found. update shows their existing consents to update; error fails with 422 DATA_PRINCIPAL_ALREADY_AVAILABLE.	"update"
business_processes[].search.if_not_available	String	grant / error	Optional (default: grant)	What to do when the customer is not found. grant issues a fresh grant; error fails with 422 DATA_PRINCIPAL_NOT_AVAILABLE. Both policies set to error are rejected.	"grant"
business_processes[].for_update	Object	-	Optional	Configuration for the update case.	-
business_processes[].for_update.show_consent_states	Array of Strings	any subset of deferred, granted, revoked	Optional (default: ["deferred", "revoked"])	Which of the customer's existing consents the update notice shows. Rows the principal doesn't touch stay unchanged - silence never means reject or revoke.	["deferred", "revoked"]

Response Body

Field Name	Data Type	Length	Description	Example Values

data	Object	-	Object containing the details of the created notice workflow.	-
data.notice_workflow_id	String (UUID)	-	Unique identifier for the notice workflow (the overall bundle). Use it for attach-metadata, status checks, and webhooks.	"9f4e1a2b-6c33-4d78-b0e1-7a2c9d4f5b60"
data.status	String	-	Current state of the notice workflow lifecycle. Always pending at create; moves pending → submitted → completed, or cancelled.	"pending"
data.sms_comms	Boolean	-	Whether SMS delivery of the notice link was requested (echoed).	false
data.email_comms	Boolean	-	Whether email delivery of the notice link was requested (echoed).	false
data.business_processes	Array of Objects	-	One entry per business process submitted, in the order they were sent.	-
data.business_processes[].data_principal_id	String	-	The identity this notice was created (grant) or updated (update) under. On update it's the past journey's identity - usually different from what you sent, and can differ between entries.	"9b2e6a41-77c3-4f10-a2d4-c81b5e9f3a02"
data.business_processes[].reference_id	String	-	Goes together with data_principal_id above; same rules.	"PRIV-CC-883201"
data.business_processes[].business_process_code	String	-	BP code as resolved and stamped, echoed.	"CC_PRODUCT_TNC"
data.business_processes[].business_process_version	Integer	-	BP version as resolved and stamped, echoed.	1
data.business_processes[].searched_by	Array of Strings	-	On update only: which identifier(s) matched. Absent on grant. Metadata was attached exactly when notice_type is grant - there is no separate flag.	["crn"]
data.link_details	Object	-	What you give the principal (page / iframe) and its expiry.	-
data.link_details.link	String	-	Publicly accessible link the Data Principal uses to view the notice. Valid for notice_workflow_settings.expires_in_hours.	"https://privy.idfy.com/principal/notice_workflow/9f4e1a2b-6c33-4d78-b0e1-7a2c9d4f5b60?access_token=<jwt>"
data.link_details.embed_link	String	-	Secure URL that can be embedded directly into partner or client applications so the Data Principal can view and interact with the notice within the host environment.	"https://privy.idfy.com/principal/notice_workflow/9f4e1a2b-6c33-4d78-b0e1-7a2c9d4f5

				b60/embed?access_token=<jwt>"
data.link_details.expires_at	String (timestamp)	-	Expiry timestamp of the link itself, aligned to notice_workflow_settings.expires_in_hours.	"2026-07-18T12:00:00Z"

Headers

Field	Length	M/O	Description
account-id		M	Account ID provided by Privy
api-key		M	Authentication Key provided by Privy
Content-Type		M	application/json
x-privy-user-type		M	String value; Should be always “data-fiduciary”

Sample Input message


```
{
  "group_reference_id": "CC-OM-GR-11160",
  "for_grant": {
    "data_principal_id": "9b2e6a41-77c3-4f10-a2d4-c81b5e9f3a02",
    "reference_id": "PRIV-CC-883201",
    "consent_settings": {
      "expires_in_hours": 8760
    },
    "metadata": [
      {
        "key": "channel",
        "value": "mobile_app"
      },
      {
        "key": "phone_number",
        "value": "+919812345678"
      },
      {
        "key": "email",
        "value": "asha@example.com"
      }
    ]
  },
  "notice_workflow_settings": {
    "default_language": "en",
    "expires_in_minutes": 30,
    "redirection_url": "https://privy.idfy.com/consent/done",
    "sms_comms": true,
    "email_comms": true,
    "view_mode": "processing_purpose",
```

```
    "purpose_default_selection": "only_mandatory_selected",
    "show_consent_duration": false,
    "merge_rule": "dedupe_common_only",
    "notice_theme": "grouped_cp_plain",
  },
  "business_processes": [
    {
      "business_process_code": "CC_PRODUCT_TNC",
      "business_process_version": 1,
      "for_grant": {
        "metadata": [
          {
            "key": "product_type",
            "value": "credit_card"
          },
          {
            "key": "crn",
            "value": "CRN77421"
          }
        ]
      }
    },
    {
      "business_process_code": "Omnibus_MARKETING",
      "business_process_version": 1,
      "search": {
        "by": [
          {
            "key": "crn",
            "value": "CRN77421"
          }
        ],
        "if_available": "update",
        "if_not_available": "grant"
      },
      "for_update": {
        "show_consent_states": [
          "deferred",
          "revoked"
        ]
      },
      "for_grant": {
        "metadata": [
          {
            "key": "crn",
            "value": "CRN77421"
          }
        ]
      }
    }
  ]
}
```

Sample output message


```
{
  "data": {
    "notice_workflow_id": "9f4e1a2b-6c33-4d78-b0e1-7a2c9d4f5b60",
    "status": "pending",
    "sms_comms": true,
    "email_comms": true,
    "business_processes": [
      {
        "notice_id": "7dbeee44-0cea-46f8-915a-94e376b6fdfa",
        "notice_type": "grant",
        "data_principal_id": "9b2e6a41-77c3-4f10-a2d4-c81b5e9f3a02",
        "reference_id": "PRIV-CC-883201",
        "business_process_code": "CC_PRODUCT_TNC",
        "business_process_version": 1
      },
      {
        "notice_id": "2bbeee44-0cea-46f8-915a-94e376b6fjk9",
        "notice_type": "update",
        "data_principal_id": "7a11e0aa-1c2b-4e33-9a01-88b2c1d0f4e5",
        "reference_id": "PRIV-ONB-2021-77002",
        "business_process_code": "CC_MARKETING",
        "business_process_version": 1,
        "searched_by": [
          "crn"
        ]
      }
    ],
    "link_details": {
      "link":
"https://privy.idfy.com/principal/notice_workflow/9f4e1a2b-6c33-4d78-b0e1-7a2c9d4f5b60?access_token=<jwt>",
      "embed_link":
"https://privy.idfy.com/principal/notice_workflow/9f4e1a2b-6c33-4d78-b0e1-7a2c9d4f5b60/embed?access_token=<jwt>",
      "expires_at": "2026-07-18T12:00:00Z"
    }
  }
}
```


Sample Error message


```
{
 "error": {
  "details": {
   "code": "VALIDATION_ERROR",
   "message": "request validation failed",
   "errors": {
    "business_processes": {
     "0": {
      "search": {
       "by": [
        "\"pan\" is not a searchable identifier (data_principal_id+reference_id, crn, phone, email)"
       ]
      }
     }
    },
    "notice_workflow_settings": {
```

```
      "view_mode": [
        "must be one of: consent_purpose, processing_purpose"
      ]
    }
  }
 }
}
```

Expected Responses

Status Code	Scenarios		Response Body
201		Created	{ "data": { "notice_workflow_id": "9f4e1a2b-6c33-4d78-b0e1-7a2c9d4f5b60", "status": "pending", "sms_comms": true, "email_comms": true, "business_processes": [{ "notice_id": "7dbeee44-0cea-46f8-915a-94e376b6fdfa", "notice_type": "grant", "data_principal_id": "9b2e6a41-77c3-4f10-a2d4-c81b5e9f3a02", "reference_id": "PRIV-CC-883201", "business_process_code": "CC_PRODUCT_TNC", "business_process_version": 1 }, { "notice_id": "2bbeee44-0cea-46f8-915a-94e376b6fjk9", "notice_type": "update", "data_principal_id": "7a11e0aa-1c2b-4e33-9a01-88b2c1d0f4e5", "reference_id": "PRIV-ONB-2021-77002", "business_process_code": "CC_MARKETING", "business_process_version": 1, "searched_by": ["crn"] }], "link_details": { "link": "https://privy.idfy.com/principal/notice_workflow/9f4e1a2b-6c33-4d78-b0e1-7a2c9d4f5b60?access_token=<jwt>", "embed_link": "https://privy.idfy.com/principal/notice_workflow/9f4e1a2b-6c33-4d78-b0e1-7a2c9d4f5b60/embed?a

			ccess_token=<jwt>", "expires_at": "2026-07-18T12:00:00Z" } } }

422	Incorrect value passed in search by and incorrect value passed in view mode	VALIDATION_ERROR	{
			"error": {
			"details": {
			"code": "VALIDATION_ERROR",
			"message": "request validation failed",
			"errors": {
			"business_processes": {
			"0": {
			"search": {
			"by": ["\"pan\" is not a searchable identifier (data_principal_id+reference_id, crn, phone_number, email)"]
			}
			}
			},
			"notice_workflow_settings": {
			"view_mode": ["must be one of: consent_purpose, processing_purpose"]
			}
			}
			}
			}
			}

422	Group reference id not passed in request and incorrect value in expires in hours	VALIDATION_ERROR	{
			"error": {
			"details": {
			"group_reference_id": ["is required"],
			"notice_workflow_settings": ["expires_in_hours: must be between 1 and 4320 hours"]
			}
			}
			}

422	This group_reference_id was used by an earlier	GROUP_REFERENCE_ID_ALREADY_TAKEN	{
			"error": {
			"details": {
			"code": "GROUP_REFERENCE_ID_ALREADY_TAKEN",

	successful create for this data fiduciary.		"message": "group_reference_id has already been taken" } } }

422	Non supported language passed in any one of the business process	LANGUAGE_NOT_SUPPORTED	{
			"error": {
			"details": {
			"code": "LANGUAGE_NOT_SUPPORTED",
			"message": "CC_MKTG: language \"mr\" is not supported by this business process",
			"business_process_code": "CC_MKTG",
			"index": 0
			}
			}
			}

422	Non existing business process passed in request body	BUSINESS_PROCESS_NOT_FOUND	{
			"error": {
			"details": {
			"code": "BUSINESS_PROCESS_NOT_FOUND",
			"message": "uPXhd6m82f: business process not found",
			"business_process_code": "uPXhd6m82f",
			"index": 1
			}
			}
			}

422	If the search found no existing consent and the value set for if_not_available key is "error", you will receive this error	DATA_PRINCIPAL_NOT_AVAILABLE	{
			"error": {
			"details": {
			"code": "DATA_PRINCIPAL_NOT_AVAILABLE",
			"message": "CC_MKTG: no data principal is available for this search and if_not_available is \"error\"",
			"business_process_code": "CC_MKTG",
			"index": 0,
			"searched_by": ["crn"]
			}
			}
			}

422	If the search found an existing consent and the value set for if_available key is "error", you will receive this error	DATA_PRINCIPAL_ALREADY_AVAILABLE	{
			"error": {
			"details": {
			"code": "DATA_PRINCIPAL_ALREADY_AVAILABLE",
			"message": "CC_TNC: a data principal is already available for this search and if_available is \"error\"",
			"business_process_code": "CC_TNC",
			"index": 1,
			"searched_by": ["crn"]
			}
			}
			}

422	You pinned a business_process_version, but the principal's existing consents sit on a different version. Privy does not silently move a consent between versions.	CONSENT_ALREADY_EXISTS	{
			"error": {
			"details": {
			"code": "CONSENT_ALREADY_EXISTS",
			"message": "vFTiYt0dZ7: consents already exist on a different business process version",
			"business_process_code": "vFTiYt0dZ7",
			"index": 0
			}
			}
			}

422	The same business_process_code appears more than once in business_processes[]	DUPLICATE_BUSINESS_PROCESS_IN_PAYLOAD	{
			"error": {
			"details": {
			"code": "DUPLICATE_BUSINESS_PROCESS_IN_PAYLOAD",
			"message": "the same business_process_code appears more than once in the bundle: CC_MKTG"
			}
			}
			}

401	No api key	Unauthorized	{"message":"No API key found in request"}

403	Incorrect api key or account id	Forbidden	{"message":"Invalid authentication credentials"}

403	Incorrect value in user-type	Forbidden	{
			"error": "Invalid user-type provided must be in [data-fiduciary,data-processor,user]"
			}

400	x-privy-user-type header missing	Bad Request	{
			"error": "Missing required headers: Either x-privy-user-type or x-cgp-user-type"
			}

429	Too many requests within the set limit for Data Fiduciaryl. (In Data Fiduciaryl scenario this is not applicable)	Too Many Requests	{ "errors": "Rate Limit Reached" }

500	Tested on IDfy staging environment. No mechanism to test on Data Fiduciaryl Environment	Internal Server Error	{
			"error": {
			"details": {
			"code": "INTERNAL_SERVER_ERROR",
			"message": "notice workflow creation failed; nothing was saved"
			}
			}
			}

500	Tested on IDfy staging environment. No mechanism to test on Data Fiduciaryl Environment	Internal Server Error	{
			"error": {
			"details": {
			"code": "MULTIPLE_CONSENT_ENTRIES_FOUND",
			"message": "Request cannot be processed as multiple entries are already available",
			"business_process_code": "vFTiYt0dZ7",
			"index": 0

			} } }

503	Tested on the IDfy staging environment. No mechanism to test on Data Fiduciaryl Environment	Service Unavailable	{
			"error": {
			"details": {
			"code": "SERVICE_TEMPORARILY_UNAVAILABLE",
			"message": "DPR verification is temporarily unavailable. Please retry."
			}
			}
			}

Privy™ by IDfy

API: Attach Metadata - Aggregated

Overview

Attach Metadata API enables a Data Fiduciary to attach a metadata for a particular Aggregated Notice. The bank can choose to attach as many as 20 metadata.

Env	URL	METHOD
PROD		POST
UAT	https://privy.idfy.com/api/v1/notice_workflows/{:notice_workflow_id}/metadata	POST

the `:notice_workflow_id` mentioned here is the request identifier as provided from the Create Aggregate Notice Response

Request Body

Field Name	Data Type	Length	Optional/ Mandatory	Description	Example Values
metadata	Array		Mandatory	A list (array) of key–value pairs used to store additional, customizable information about the Grant Notice. Each item is an object with key and value fields. Attach external references, user context, tracking info, etc.	
key	String	min: 1, max: 255	Mandatory	The name or identifier of the metadata entry. Acts as the label for external mapping or internal tracking.	crn
value	String	min: 1, max: 255	Mandatory	The corresponding value for the given metadata key. Stores the actual data or reference.	customer_12345609

Response Body

Field Name	Data Type	Length	Description	Values

data	Object		The main container object for the response payload, containing details about the updated or referenced notice.	
notice_workflow_id	String		Identifier for aggregated notice	4ddcf44d-3f31-4b6e-bb8c-5d4f00f09c76
status	String		Overall Status of the attachment: “succeeded”, "partially_succeeded", “failed”	succeeded
succeeded	Array of Object		List of notices where metadata was attached successfully	
succeeded[0].data_principal_id	String		A unique identifier for the Data Principal (the individual whose personal data is associated with the notice). Confirms which user's notice was acted on or updated.	dpi-abc
succeeded[0].type	String		Type of the notice	grant
succeeded[0].notice_id	String		Unique identifier for the notice.	e094693b-bbf5-4046-a53e-62022ee351f4
succeeded[0].reference_id	String		A custom identifier supplied by the Data Fiduciary during notice creation. Helps the fiduciary link the notice back to their internal system (like an application number or case ID).	personal-loan-application-no-1234
succeeded[0].metadata	Array		Additional key-value data used to give context or track related business identifiers.	
succeeded[0].metadata[0].key	String	min: 1, max: 255	The metadata key name.	crn
succeeded[0].metadata[0].value	String	min: 1, max: 255	The associated value.	customer_12345609
failed	Array of Object		List of notices where attach metadata failed	
failed[0].data_principal_id	String		A unique identifier for the Data Principal (the individual whose personal data is associated with the notice). Confirms which user's notice was acted on or updated.	dpi-abc
failed[0].type	String		Type of the notice	grant
failed[0].notice_id	String		Unique identifier for the notice.	e094693b-bbf5-4046-a53e-62022ee351f4
failed[0].reference_id	String		A custom identifier supplied by the Data Fiduciary during notice	personal-loan-application-no-1234

			creation. Helps the fiduciary link the notice back to their internal system (like an application number or case ID).	
failed[0].error	Object		Object containing error details	
failed[0].error.code	String		Code of the error : Like: METADATA_LIMIT_EXCEEDED, METADATA_VALUE_CONFLICT	METADATA_LIMIT_EXCEEDED
failed[0].error.message	String		Message of the error	Metadata count exceeds 20!
failed[0].error.details	Object		Details of the error	
failed[0].error.details.metadata	Array		List of keys which failed to attach due to conflict	
failed[0].error.details.metadata[0].key	String		Name of the key which failed to attach due to conflict.	“crn”

Headers

Field	Length	M/O	Description
account-id		M	Account ID provided by Privy
api-key		M	Authentication Key provided by Privy
Content-Type		M	application/json
x-privy-user-type		M	String value; Should be always “data-fiduciary”

Sample Input message

```
{
  "metadata": [
    {
      "key": "crn",
      "value": "customer_12345609"
    }
  ]
}
```

Sample output message

- Sample Success Output message - Status code 200


```
{
   "data": {
      "notice_workflow_id": "4ddcf44d-3f31-4b6e-bb8c-5d4f00f09c76",
      "status": "succeeded",
      "succeeded": [
         {
            "notice_id": "c149a1fc-0bcb-40d2-8a1a-907b1981d6d8",
            "type": "grant",
            "reference_id": "ref-123",
            "data_principal_id": "dp-456",
            "metadata": [
               {
                  "key": "crn",
                  "value": "CRN1234567"
               },
               {
                  "key": "product_context_id",
                  "value": "j385hdnf9"
               }
            ]
         }
      ],
      "failed": []
   }
}
```


- Sample Partial Success Output message - Status code 207


```
{
   "data": {
      "notice_workflow_id": "4ddcf44d-3f31-4b6e-bb8c-5d4f00f09c76",
      "status": "partially_succeeded",
      "succeeded": [
         {
            "notice_id": "c149a1fc-0bcb-40d2-8a1a-907b1981d6d8",
            "type": "grant",
            "reference_id": "ref-123",
            "data_principal_id": "dp-456",
            "metadata": [
               {
                  "key": "crn",
                  "value": "CRN1234567"
               }
            ]
         }
      ],
      "failed": [
         {
            "notice_id": "9777db4f-bbf5-4046-a53e-62022ee351f4",
            "type": "grant",
            "reference_id": "ref-123",
            "data_principal_id": "dp-456",
            "error": {
```

```
            "code": "METADATA_VALUE_CONFLICT",
            "message": "One or more keys are already set with a different value on this notice",
            "details": {
              "metadata": [
                {
                  "key": "crn"
                },
                {
                  "key": "product_context_id"
                }
              ]
            }
          }
        },
        {
          "notice_id": "e094693b-bbf5-4046-a53e-62022ee351f4",
          "type": "grant",
          "reference_id": "ref-124",
          "data_principal_id": "dp-457",
          "error": {
            "code": "METADATA_LIMIT_EXCEEDED",
            "message": "Metadata count exceeds 20!"
          }
        }
      ]
    }
}
```


- Sample Error message - Status code 422


```
{
  "error": {
    "details": {
      "notice_workflow_id": "4ddcf44d-3f31-4b6e-bb8c-5d4f00f09c76",
      "status": "failed",
      "succeeded": [],
      "failed": [
        {
          "notice_id": "c0ada45f-cf9e-4c61-abd2-29ab2f77f3af",
          "type": "grant",
          "reference_id": "ref-124",
          "data_principal_id": "dp-456",
          "error": {
            "code": "METADATA_VALUE_CONFLICT",
            "message": "One or more keys are already set with a different value on this notice",
            "details": {
              "metadata": [
                {
                  "key": "crn"
                },
                {
                  "key": "product_context_id"
                }
              ]
            }
          }
        },
        {
```

```
            "notice_id": "c149a1fc-0bcb-40d2-8a1a-907b1981d6d8",
            "type": "grant",
            "reference_id": "ref-123",
            "data_principal_id": "dp-456",
            "error": {
               "code": "METADATA_LIMIT_EXCEEDED",
               "message": "Metadata count exceeds 20!"
            }
         }
      ]
   }
 }
}
```

In case of 422, the same object is present inside the “error.details” object.
Every entry in failed carries an error block. Most codes use {code, message}; the changeset case uses {code, errors} with a
nested field-level errors map (no message).

Code	Error format	Meaning
METADATA_VALUE_CONFLICT	{code, message, details}	One or more keys in the request already exist on this notice. details lists the metadata keys which have value conflicts.
METADATA_LIMIT_EXCEEDED	{code, message}	More than 20 keys sent in metadata
VALIDATION_ERROR	{code, errors}	Validation failure
NOTICE_NOT_FOUND	{code, message}	Notice Not found
INTERNAL_ERROR	{code, message}	Internal Server Error

Sample Error message

```
{
 "error": {
  "details": {
   "key": "Invalid input"
  }
 }
}
```

Metadata Key and Value Validations

- key - Key allows 255 characters with following validations:
    - Letters (A–Z, a–z)
    - Numbers (0–9)
    - Underscore _
    - Spaces (including tabs/line breaks)
- Predefined keys that are supported
    - crn
    - email
    - phone_number
    - product_context_id
    - onboarding_partner
    - policy_number
    - application_reference_id
- value (except for predefined keys) - Allows 255 characters with following validations
    - Letters (A–Z, a–z)
    - Numbers (0–9)
    - Hyphen -
    - Underscore _
    - Hash #
    - Space
    - Punctuation: period `.`, comma `,`, colon `:`, semicolon `;`, exclamation `!`, question mark `?`, parentheses `( )`, single quote `'`, double quote `"`
- value (predefined keys) - Allows 255 characters with the following validations:
    - crn
        - Letters (A–Z, a–z)
        - Numbers (0–9)
        - Hyphen -
        - Underscore _
        - Hash #
    - phone_number - Allows 10-15 digits
        - Plus sign (leading only) +
        - Numbers (0–9)
        - Space
        - Parentheses ( )
        - Hyphen -
        - Period .
    - email - Allows 255 characters with following validations
        - Letters (A–Z, a–z)
        - Numbers (0–9)

        - Period .
        - At symbol @ (exactly one)
        - Must end in a dot followed by 2+ letters (e.g. .com, .in)
    - product_context_id, onboarding_partner, policy_number, application_reference_id
        - Letters (A–Z, a–z)
        - Numbers (0–9)
        - Hyphen -
        - Underscore _
        - Hash #

Expected Responses

Status Code	Scenarios		Response Body
200		Created	{ "data": { "notice_workflow_id": "4ddcf44d-3f31-4b6e-bb8c-5d4f00f09c76", "status": "succeeded", "succeeded": [{ "notice_id": "c149a1fc-0bcb-40d2-8a1a-907b1981d6d8", "type": "grant", "reference_id": "ref-123", "data_principal_id": "dp-456", "metadata": [{ "key": "crn", "value": "CRN1234567" }, { "key": "product_context_id", "value": "j385hdnf9" }] }], "failed": [] } }
207		Partially Successful	{

			"data": {
			"notice_workflow_id": "4ddcf44d-3f31-4b6e-bb8c-5d4f00f09c76",
			"status": "partially_succeeded",
			"succeeded": [
			{
			"notice_id": "c149a1fc-0bcb-40d2-8a1a-907b1981d6d8",
			"type": "grant",
			"reference_id": "ref-123",
			"data_principal_id": "dp-456",
			"metadata": [
			{
			"key": "crn",
			"value": "CRN1234567"
			}
			]
			}
			],
			"failed": [
			{
			"notice_id": "9777db4f-bbf5-4046-a53e-62022ee351f4",
			"type": "grant",
			"reference_id": "ref-123",
			"data_principal_id": "dp-456",
			"error": {
			"code": "METADATA_VALUE_CONFLICT",
			"message": "One or more keys are already set with a different value on this notice",
			"details": {
			"metadata": [
			{
			"key": "crn"
			},
			{
			"key": "product_context_id"
			}
			]
			}
			}
			},
			{
			"notice_id": "e094693b-bbf5-4046-a53e-62022ee351f4",

Privy™

			"type": "grant",
			"reference_id": "ref-124",
			"data_principal_id": "dp-457",
			"error": {
			"code": "METADATA_LIMIT_EXCEEDED",
			"message": "Metadata count exceeds 20!"
			}
			}
			]
			}
			}

400	Anything except UUID	Bad Request	{
			"error": {
			"details": {
			"code": "INVALID_PUBLIC_ID",
			"message": "Invalid workflow public_id"
			}
			}
			}

404	You pass an incorrect UUID in the url whose notices does not exits	Not Found	{
			"error": {
			"details": {
			"code": "WORKFLOW_NOT_FOUND",
			"message": "Notice Workflow not found"
			}
			}
			}

422		Unprocessable Entity	{
			"error": {
			"details": {
			"notice_workflow_id": "4ddcf44d-3f31-4b6e-bb8c-5d4f00f09c76",
			"status": "failed",
			"succeeded": [],
			"failed": [
			{
			"notice_id": "c0ada45f-cf9e-4c61-abd2-29ab2f77f3af",
			"type": "grant",
			"reference_id": "ref-124",
			"data_principal_id": "dp-456",
			"error": {
			"code": "METADATA_VALUE_CONFLICT",

			"message": "One or more keys are already set with a different value on this notice",
			"details": {
			"metadata": [
			{
			"key": "crn"
			},
			{
			"key": "product_context_id"
			}
			]
			}
			}
			},
			{
			"notice_id": "c149a1fc-0bcb-40d2-8a1a-907b1981d6d8",
			"type": "grant",
			"reference_id": "ref-123",
			"data_principal_id": "dp-456",
			"error": {
			"code": "METADATA_LIMIT_EXCEEDED",
			"message": "Metadata count exceeds 20!"
			}
			}
			]
			}
			}
			}

422	If you pass an empty array	Unprocessable Entity	{
			"error": {
			"details": {
			"code": "VALIDATION_ERROR",
			"message": "metadata is required and must be a non-empty array"
			}
			}
			}

422	More than 20 metadata objects passed in request	Unprocessable Entity	{
			"error": {
			"details": {
			"code": "METADATA_TOO_LARGE",
			"message": "metadata must contain at most 20 entries"
			}

			} }

422	If you pass any other string except key or value, you will get this error	Unprocessable Entity	{
			"error": {
			"details": {
			"code": "VALIDATION_ERROR",
			"message": "Each metadata entry must include 'key' and 'value' as strings"
			}
			}
			}

422	Pass same key name in the request	Unprocessable Entity	{
			"error": {
			"details": {
			"code": "DUPLICATE_KEY_IN_PAYLOAD",
			"message": "Same key appears more than once in the metadata array"
			}
			}
			}

422	One or more values are not a string	Unprocessable Entity	{
			"error": {
			"details": {
			"code": "VALIDATION_ERROR",
			"message": "One or more metadata values are invalid"
			}
			}
			}

401	No api key	Unauthorized	{"message":"No API key found in request"}
403	Incorrect api key or account id	Forbidden	{"message":"Invalid authentication credentials"}

403	Incorrect value in x-privy-user-type	Forbidden	{
			"error": "Invalid user-type provided must be in [data-fiduciary,data-processor,user]"
			}

400	x-privy-user-type header missing	Bad Request	{
			"error": "Missing required headers: Either x-privy-user-type or x-cgp-user-type"
			}

429	Too many requests within the set limit for	Too Many Requests	{ "errors": "Rate Limit Reached" }

	Data Fiduciaryl. (In Data Fiduciaryl scenario this is not applicable)		

500	Any unhandled exception in the request pipeline.	Internal Server Error	{
			"error": {
			"details": {
			"code": "INTERNAL_ERROR",
			"message": "Internal server error"
			}
			}
			}

Privy™
by IDfy

API: Create Flex ANC

Overview

The Flex ANC Create API lets you initiate a notice workflow containing one or more notices, each held in a pending state until it is submitted. For every business process in the request, the response returns the applicable business taxonomy, resolved as an update when a consent record already exists for the data principal, or as a grant when none exists yet.

Env	URL	Method
PROD		POST
UAT	https://privy.idfy.com/api/v1/flex_notices/notice_workflow/create	POST

Request Body

1.1 Top level

Field Name	Data Type	Length	Optional/Mandatory	Description	Example Values
group_reference_id	String	3 to 255	Mandatory	^[a-zA-Z0-9/()._-]+$. At most one pending workflow per data fiduciary may hold it. Retrying while pending replays that workflow; a cancelled one releases it; a submitted or completed one holds it permanently.	ONB-2026-08-31-000117
notice_workflow_settings	Object	—	Mandatory	See section 1.2 below.	—
for_grant	Object	—	Optional	Workflow-level grant defaults, inherited by every entry.	—
business_processes	Array	1 to 20 entries	Mandatory	See section 1.4 below.	—

1.2 notice_workflow_settings

Field Name	Data Type	Length	Optional/Mandatory	Description	Example Values
default_language	String	—	Mandatory	A supported locale. Every business process in the bundle must support it, or the request is rejected.	en
expires_in_hours	Integer	1 to 4320	Mandatory	How long the workflow stays submittable.	24

1.3 for_grant

Accepted at the top level, per entry, or both. A per-entry for_grant overrides the workflow-level one key by key, and metadata merges per metadata key: workflow-level keys survive unless the entry repeats them, and entry-only keys are added.

Field Name	Data Type	Length	Optional/Mandatory	Description	Example Values
data_principal_id	String	3 to 255	Mandatory (after merge, on any entry that can grant)	^[a-zA-Z0-9/(). _-]+$. No spaces.	dp_8f31c0a4e7
reference_id	String	3 to 255	Mandatory (same condition)	Same rules as data_principal_id.	ref_20260831_44190
consent_settings.expires_in_hours	Integer	24 to 867240, or -1	Optional	-1 means "until the purpose is met" and normalises to 0 internally. 0 sent directly is rejected: -1 is the only way to ask for it. Omitted means the business process rule's own duration.	8760
metadata	Array of {key, value}	—	Optional	Keys are charset-validated. Repeating a key within one list is rejected.	[{"key": "phone_number", "value": "+910000000000"}]

1.4 business_processes[]

Field Name	Data Type	Length	Optional/Mandatory	Description	Example Values
business_process_code	String	1 to 10	Mandatory	Must exist and be published under your data fiduciary. Tenant-scoped and case-sensitive.	Kx7mQ2Ab9T
business_process_version	Integer	min: 1	Optional	Omitted means latest published, which also lets an existing consent on any version be updated where it sits.	1
search	Object	—	Optional	See section 1.5 below. Omit it and the entry is always a grant. Cannot be omitted on an entry that also sends for_update.	—
for_grant	Object	—	Optional	As above (1.3). Rejected on an entry that can never grant.	—
for_update	Object	—	Optional	See section 1.6 below. Requires a search on the same entry.	—

1.5 search

Field Name	Data Type	Length	Optional/Mandatory	Description	Example Values
by	Array of {key, value}	1 to 5 entries	Mandatory	AND-composed. key is one of crn, data_principal_id, reference_id, phone_number, email — anything else is rejected. Note phone is not searchable; only phone_number is. data_principal_id and reference_id must be sent together. Each key may appear at most once.	{"key": "crn", "value": "CRN00012345"}
if_available	String	—	Optional	update (default) or error.	update
if_not_available	String	—	Optional	grant (default) or error.	grant

1.6 for_update

Field Name	Data Type	Length	Optional/Mandatory	Description	Example Values
show_consent_states	Array of string	—	Optional	Any subset of deferred, granted, revoked, mandatory. Default ["deferred", "revoked"].	["deferred", "revoked", "granted"]
consent_settings.expires_in_hours	Integer	24 to 867240, or -1	Optional	Same rules as for_grant.consent_settings.	8760

Value	Returns	Actionable at submit
deferred	Purposes with no consent record, including mandatory rules never granted	Yes
revoked	Purposes whose consent was withdrawn	Yes
granted	Currently granted, non-mandatory purposes	No, display only
mandatory	Currently granted purposes on mandatory or non-revocable rules	No, display only

Purposes outside the requested set are omitted from the response entirely, not returned and marked. This applies to update entries only: a grant entry has no consent state to filter on, so it returns every processing purpose the business process defines, regardless of what show_consent_states says.

Response Body

HTTP status: 201 Created

Top level

Field Name	Data Type	Length	Description	Example Values
notice_workflow_id	UUID	—	The handle for submit.	3fa2dedf-b1d5-4548-ae65-67306b35812a
group_reference_id	String	—	Echoed back for correlation. ANC create v2 does not return it.	ONB-2026-08-31-000117
status	String	—	pending.	pending
expires_at	Timestamp	—	When the workflow stops being submittable.	2026-09-01T09:14:22Z
locale	String	—	The language the content was actually rendered in. Distinct from the request's default_language, which is what you asked for. On a single-business-process call the two always agree, which is why the flex endpoints need only one name.	en
available_locales	Array of {locale, label}	—	The intersection across every business process in the bundle.	{"locale": "en", "label": "English"}
business_processes	Array	—	One per entry, in request order.	—

business_processes[] envelope

Field Name	Data Type	Length	Description	Example Values
notice_id	UUID	—	Identifies this notice at submit.	9b1d4c22-77aa-4d31-b0d2-1c55e9f0aa31
notice_type	String	—	grant or update, resolved by the server.	update
business_process_code	String	—	—	Kx7mQ2Ab9T
business_process_version	Integer	—	The version actually resolved.	1
data_principal_id	String	—	—	dp_8f31c0a4e7
reference_id	String	—	—	ref_20260831_44190
searched_by	Array of string	—	Update entries only. The search.by keys that matched. Because by is AND-composed, a match means every key matched, so this always equals the key set you sent. It is an echo, kept for parity with ANC create v2.	["crn"]

Field Name	Data Type	Length	Description	Example Values
consent_update_in_progress	Boolean	—	Update entries only. A consent update for this business process is already running.	false
content	Object	—	See below.	—

content

Field	Grant	Update
business_process {code, version, name, description}	Yes	Yes
eulas[] {name, link}	Yes	Yes
consent_purposes[].{code, label, description}	Yes	Yes
consent_purposes[].expires_in_hours	Yes	Yes
processing_purposes[].{id, code, label, description}	Yes	Yes
processing_purposes[].is_mandatory	Yes	Yes
processing_purposes[].user_attributes[] {code, label}	Yes	Yes
processing_purposes[].current_consent_status	No	granted, deferred or revoked
processing_purposes[].expires_at	No	Yes, null when there is no consent
processing_purposes[].last_updated_at	No	Yes
processing_purposes[].is_revokable	No	Yes
processing_purposes[].cooldown_duration_minutes	No	Yes, forced to 0 when status is deferred

Headers

Field	Length	M/O	Description
account-id		M	Account ID provided by Privy
api-key		M	Authentication Key provided by Privy
Content-Type		M	application/json
x-privy-user-type		M	String value; Should be always “data-fiduciary”

Sample Input message

```
{
 "group_reference_id": "ONB-2026-08-31-000117",
 "notice_workflow_settings": {
  "default_language": "en",
  "expires_in_hours": 24
 },
 "for_grant": {
  "data_principal_id": "dp_8f31c0a4e7",
  "reference_id": "ref_20260831_44190",
  "consent_settings": { "expires_in_hours": 8760 },
  "metadata": [
   { "key": "phone_number", "value": "+910000000000" },
   { "key": "customer_segment", "value": "retail" }
  ]
 },
 "business_processes": [
  {
   "business_process_code": "Kx7mQ2Ab9T",
   "business_process_version": 1,
   "search": {
    "by": [ { "key": "crn", "value": "CRN00012345" } ],
    "if_available": "update",
    "if_not_available": "grant"
   },
   "for_update": {
    "show_consent_states": ["deferred", "revoked", "granted"],
    "consent_settings": { "expires_in_hours": 8760 }
   },
   "for_grant": {
    "metadata": [ { "key": "channel", "value": "mobile" } ]
   }
  },
  {
   "business_process_code": "Rn4pW8Ld3V",
   "search": {
    "by": [
     { "key": "data_principal_id", "value": "dp_8f31c0a4e7" },
     { "key": "reference_id", "value": "ref_20260831_44190" }
    ]
   }
  }
 ]
}
```

Sample output message

```
{
 "data": {
  "notice_workflow_id": "3fa2dedf-b1d5-4548-ae65-67306b35812a",
  "group_reference_id": "ONB-2026-08-31-000117",
  "status": "pending",
  "expires_at": "2026-09-01T09:14:22Z",
  "locale": "en",
  "available_locales": [
   { "locale": "en", "label": "English" },
   { "locale": "hi", "label": "Hindi" }
  ],
  "business_processes": [
   {
    "notice_id": "9b1d4c22-77aa-4d31-b0d2-1c55e9f0aa31",
```

```
      "notice_type": "update",
      "business_process_code": "Kx7mQ2Ab9T",
      "business_process_version": 1,
      "data_principal_id": "dp_8f31c0a4e7",
      "reference_id": "ref_20260831_44190",
      "searched_by": ["crn"],
      "consent_update_in_progress": false,
      "content": {
        "business_process": { "code": "Kx7mQ2Ab9T", "version": 1, "name": "Cards", "description": "..." },
        "eulas": [],
        "consent_purposes": [
          {
            "code": "cp_marketing",
            "label": "Marketing",
            "expires_in_hours": 8760,
            "processing_purposes": [
              { "id": "gAAAAAB7k9Rd...", "code": "pp_mk_cross_sell",
                "current_consent_status": "revoked", "is_mandatory": false,
                "is_revokable": true, "cooldown_duration_minutes": 4320 },
              { "id": "gAAAAABq3wZx...", "code": "pp_mk_newsletter",
                "current_consent_status": "deferred", "is_mandatory": false,
                "is_revokable": true, "cooldown_duration_minutes": 0 }
            ]
          }
        ]
      }
    },
    {
      "notice_id": "32886f4f-5153-4e1c-981f-6f03e86bb727",
      "notice_type": "grant",
      "business_process_code": "Rn4pW8Ld3V",
      "business_process_version": 1,
      "data_principal_id": "dp_8f31c0a4e7",
      "reference_id": "ref_20260831_44190",
      "content": {
        "business_process": { "code": "Rn4pW8Ld3V", "version": 1, "name": "Account opening" },
        "eulas": [ { "name": "Notice PDF", "link": "https://example.test/notice.pdf" } ],
        "consent_purposes": [
          {
            "code": "cp_legitimate_use",
            "label": "Legitimate purposes",
            "expires_in_hours": 24,
            "processing_purposes": [
              { "id": "gAAAAAB2c1p...", "code": "pp_md_audit_monitoring", "is_mandatory": true },
              { "id": "gAAAAAB5t8Qm...", "code": "pp_op_service_comms", "is_mandatory": false }
            ]
          }
        ]
      }
    }
  ]
 }
}
```

Sample Error message

```
{
 "error": {
   "details": {
     "code": "BUSINESS_PROCESS_NOT_FOUND",
     "message": "uPXhd6m82f: business process not found",
     "business_process_code": "uPXhd6m82f",
```

```
    "index": 1
  }
 }
}
```

Expected Responses

Code	Error Code	Arrives when
201	Created	The workflow was created (or an existing pending workflow was returned for a retried group_reference_id).
422	VALIDATION_ERROR	A required field is missing or the wrong type, business_processes is not an array of objects, a metadata entry is not a key/value pair, an enum value is outside its set, a length or charset rule fails, or any of the cross-field rules above is broken. Every problem is reported in one response.
422	GROUP_REFERENCE_ID_ALREADY_TAKEN	The reference has been used before by this fiduciary and the earlier workflow is no longer pending. Look the workflow up rather than recreating it.
422	DUPLICATE_BUSINESS_PROCESS_IN_PAYLOAD	The same business process code appears more than once in the bundle.
422	BUSINESS_PROCESS_NOT_FOUND	Three situations, told apart by message: the code does not exist under this fiduciary, it exists but is not published, or the pinned version does not exist.
422	LANGUAGE_NOT_SUPPORTED	At least one business process in the bundle does not support default_language. Send a language every one supports, or split the bundle.
422	DATA_PRINCIPAL_NOT_AVAILABLE	The search found nothing andi if_not_available: is set to error
422	DATA_PRINCIPAL_ALREADY_AVAILABLE	The search found the principal and if_available: is set to error
422	CONSENT_ALREADY_EXISTS	A business_process_version was pinned, but the principal's existing consents for that business process sit on a different version. Omit the version to update them where they are.
500	INTERNAL_SERVER_ERROR	Validation and resolution passed but the workflow could not be persisted. Nothing was saved. Retry once, then raise it.
503	SERVICE_TEMPORARILY_UNAVAILABLE	A dependency was unreachable after the bounded retry.

API: Submit Flex ANC

Overview

The Flex ANC Submit API lets you close out a notice workflow opened by create. It records the data principal's decision for every notice in that workflow, granting or updating consent as applicable, and returns the resulting status for each one.

Env	URL	Method
PROD		POST
UAT	https://privy.idfy.com/api/v1/flex_notices/notice_workflow/submit	POST

Request Body

1.1 Envelope

Field Name	Data Type	Length	Optional/Mandatory	Description	Example Values
notice_workflow_id	UUID	—	Mandatory	The id returned by create. Must belong to the calling fiduciary and still be pending.	3fa2dedf-b1d5-4548-ae65-67306b35812a
notices	Array	1 to 20	Mandatory	Every entry from the create response must appear exactly once.	—

1.2 Every element

Field Name	Data Type	Length	Optional/Mandatory	Description	Example Values
notice_id	UUID	—	Mandatory	From the create response.	32886f4f-5153-4e1c-981f-6f03e86bb727
type	String	—	Mandatory	grant or update. Must equal the type the server resolved at creation.	grant

1.3 Grant elements

Field Name	Data Type	Length	Optional/Mandatory	Description	Example Values
action	String	—	Mandatory	accepted or rejected.	accepted

Field Name	Data Type	Length	Optional/Mandatory	Description	Example Values
submitted_consents	Array	min: 1	Mandatory	One entry per processing purpose the create response returned for this notice.	—

submitted_consents[] sub-fields (grant):

Field Name	Data Type	Length	Optional/Mandatory	Description	Example Values
processing_purpose_id	String	—	Mandatory	The opaque id from the create response, echoed unchanged.	gAAAAAB2c1p...
is_selected	Boolean	—	Mandatory	Whether the principal agreed to this purpose.	true

1.4 Update elements

An update element has no action field. An update has no notice-level verdict; each purpose carries its own transition.

Field Name	Data Type	Length	Optional/Mandatory	Description	Example Values
submitted_consents	Array	min: 1	Mandatory	One entry per processing purpose the create response returned for this notice.	—

submitted_consents[] sub-fields (update):

Field Name	Data Type	Length	Optional/Mandatory	Description	Example Values
processing_purpose_id	String	—	Mandatory	The opaque id from the create response, echoed unchanged.	gAAAAAB7k9Rd...
current_consent_status	String	—	Mandatory	Echo the value the create response gave for this purpose. Checked against the status inside the id, so a mismatch is rejected.	revoked
desired_consent_status	String	—	Mandatory	Must be granted. Sending revoked is rejected: this API cannot withdraw consent.	granted

1.5 Which purposes to send

Send every purpose, the create response returned for that notice, selected or not.

Purpose as returned at create	Send	Result
current_consent_status: "deferred"	desired: "granted"	New consent written.
current_consent_status: "revoked"	desired: "granted"	Consent re-granted.
current_consent_status: "granted", is_mandatory: true	current: "granted", desired: "granted"	No change, no write. Must still be sent.

Purpose as returned at create	Send	Result
current_consent_status: "granted", is_mandatory: false	current: "granted", desired: "granted"	No change, no write.
Any	desired: "revoked"	Rejected.

A purpose returned with current_consent_status: "granted" is informational. It cannot be changed on this API, because withdrawal is not supported here.

Response Body

HTTP status: 200 OK

Field Name	Data Type	Length	Description	Example Values
notice_workflow_id	UUID	—	Echoed.	3fa2dedf-b1d5-4548-ae65-67306b35812a
status	String	—	submitted.	submitted
updated_at	Timestamp	—	Server time of the commit.	2026-09-01T09:41:02Z
notices[]	Array	—	One per submitted notice.	—
notices[].notice_id	UUID	—	—	32886f4f-5153-4e1c-981f-6f03e86bb727
notices[].type	String	—	grant or update.	grant
notices[].consent_status	String	—	accepted, rejected or no_op.	accepted

Read the returned status, not the action you sent. They can differ, and the cases where they differ are the ones that matter:

You sent	Result	Why
grant, action: "accepted", nothing selected	rejected	An acceptance with no consents is a refusal.
update, nothing actionable	no_op	Every purpose was already granted; nothing was written.

A no_op is a success. It means the request was valid and there was nothing to do. An update notice completes asynchronously: consent_status: "accepted" means the task was accepted, not that the consent records are written yet. A grant notice completes synchronously.

Headers

Field	Length	M/O	Description
account-id		M	Account ID provided by Privy
api-key		M	Authentication Key provided by Privy

Content-Type		M	application/json
x-privy-user-type		M	String value; Should be always “data-fiduciary”

Sample Input message

```
{
 "notice_workflow_id": "3fa2dedf-b1d5-4548-ae65-67306b35812a",
 "notices": [
  {
   "notice_id": "32886f4f-5153-4e1c-981f-6f03e86bb727",
   "type": "grant",
   "action": "accepted",
   "submitted_consents": [
    { "processing_purpose_id": "gAAAAAB2c1p...", "is_selected": true },
    { "processing_purpose_id": "gAAAAAB5t8Qm...", "is_selected": false }
   ]
  },
  {
   "notice_id": "9b1d4c22-77aa-4d31-b0d2-1c55e9f0aa31",
   "type": "update",
   "submitted_consents": [
    { "processing_purpose_id": "gAAAAAB7k9Rd...",
      "current_consent_status": "revoked", "desired_consent_status": "granted" },
    { "processing_purpose_id": "gAAAAABq3wZx...",
      "current_consent_status": "granted", "desired_consent_status": "granted" }
   ]
  }
 ]
}
```

OR — a refusal:

```
{
 "notice_workflow_id": "3fa2dedf-b1d5-4548-ae65-67306b35812a",
 "notices": [
  {
   "notice_id": "32886f4f-5153-4e1c-981f-6f03e86bb727",
   "type": "grant",
   "action": "rejected",
   "submitted_consents": [
    { "processing_purpose_id": "gAAAAAB2c1p...", "is_selected": false },
    { "processing_purpose_id": "gAAAAAB5t8Qm...", "is_selected": false }
   ]
  },
  {
   "notice_id": "9b1d4c22-77aa-4d31-b0d2-1c55e9f0aa31",
   "type": "update",
   "submitted_consents": [
    { "processing_purpose_id": "gAAAAAB7k9Rd...",
      "current_consent_status": "revoked", "desired_consent_status": "revoked" },
    { "processing_purpose_id": "gAAAAABq3wZx...",
      "current_consent_status": "deferred", "desired_consent_status": "deferred" }
   ]
  }
 ]
}
```

A grant notice is refused with action: "rejected". Selections are not read on that path, so send submitted_consents for shape or omit the flags; either way the record stores are rejected and no consents are written. A mandatory purpose does not block a refusal: the mandatory check runs only on an acceptance. An update notice has no action; a refusal is every purpose sent with desired_consent_status equal to its current_consent_status, which produces consent_status: "no_op". Nothing is written and the request succeeds. A refusal is a recorded outcome, not an error: it returns 200 with consent_status of rejected and no_op respectively.

Sample output message


```
{
 "data": {
  "notice_workflow_id": "3fa2dedf-b1d5-4548-ae65-67306b35812a",
  "status": "submitted",
  "updated_at": "2026-09-01T09:41:02Z",
  "notices": [
   { "notice_id": "32886f4f-5153-4e1c-981f-6f03e86bb727", "type": "grant",
     "consent_status": "accepted" },
   { "notice_id": "9b1d4c22-77aa-4d31-b0d2-1c55e9f0aa31", "type": "update",
     "consent_status": "accepted" }
  ]
 }
}
```


Sample Error message


```
{
 "error": {
  "details": {
   "code": "INCOMPLETE_PAYLOAD",
   "message": "..."
  }
 }
}
```


Expected Responses

Code	Error Code	Arrives when
200	OK	The submission was processed and every notice's consent_status is set (accepted, rejected or no_op).
400	INVALID_PUBLIC_ID (ANC submit)	notice_workflow_id is not a well-formed id.
404	WORKFLOW_NOT_FOUND (ANC submit)	No workflow with that id exists for the calling fiduciary. Also the answer when the id belongs to someone else.
404	INVALID_DATA_PRINCIPAL (ANC submit)	The workflow's data principal not found
409	WORKFLOW_ALREADY_SUBMITTED (ANC submit)	The workflow has already been submitted. A retry after a successful submit lands here.

Code	Error Code	Arrives when
409	WORKFLOW_ALREADY_COMPLETED (ANC submit)	The workflow has already completed.
410	WORKFLOW_LINK_EXPIRED (ANC submit)	Past the workflow's expires_at. The name says "link" for historical reasons; the condition is the workflow TTL.
410	WORKFLOW_DEACTIVATED (ANC submit)	The workflow was deactivated.
422	VALIDATION_ERROR (ANC v2 and ANC submit)	A required field is missing or the wrong type, or an enum value is outside its set. Also returned when desired_consent_status is revoked, which is not an accepted value on this API.
422	INCOMPLETE_PAYLOAD (ANC submit)	At least one notice from the create response is missing from notices.
422	INVALID_NOTICE (ANC submit)	A notice_id does not belong to this workflow, or its type does not match what the server resolved at create.
422	DUPLICATE_NOTICE_ID_IN_PAYLOAD (ANC submit)	The same notice_id appears more than once.
422	INVALID_SUBMISSION (ANC submit)	A notice failed for a reason specific to its contents. Several situations, told apart by message: a mandatory purpose was sent unselected, a purpose id could not be resolved, or the echoed current_consent_status disagrees with the one inside the id.
422	INVALID_STATUS_TRANSITION (flex update)	The value is legal but the transition is not, for example an already-granted purpose marked as a change. Also covers a purpose whose rule is not revocable.
423	LOCK_CONFLICT (ANC submit)	A consent operation is already running for this principal on one of the business processes in the bundle. Retry after it finishes.
500	INTERNAL_ERROR (ANC submit)	An unexpected failure. Whether anything was written is reported in the message.
503	SERVICE_TEMPORARILY_UNAVAILABLE (ANC submit and ANC v2)	A dependency was unreachable after the bounded retry.

API: Generate DPAR Link

Summary

Description
This API endpoint generates a DPAR portal link, enabling Data Fiduciaries and Processors to retrieve and display the DPAR portal link for a specific Data Principal. This functionality facilitates the integration of the DPAR flow within their applications, allowing Data Principals to access and review their consent history.

Requirement background for Operation

URL	METHOD
https://privy.idfy.com/api/v1/dpar/generate_link	POST

Request Parameters

Field Name	Data Type	Length	Optional/Mandatory	Description	Example Values
data_principal_id	String	min: 3, max: 255	**Mandatory**	Unique identifier of the Data Principal for whom the DPAR portal link is being requested. Specifies the individual whose consent records and history should be made accessible via the portal link.	005a6d85-61b7-4495-bb78-44a033ef0e1f
reference_id	String	min: 3, max: 255	Optional	A unique identifier generated by the Data Fiduciary to reference this specific Grant Notice. Used for tracking, audits, or future lookups.	personal-loan-application-no-1234
expires_in_hours	Integer		Optional	Defines the validity duration (in hours) for which the DPAR portal link remains active. Controls how long the generated portal link should remain accessible to the Data Principal. After expiration, the link becomes invalid for security reasons.	8 Default Value - 0.5 hours
metadata	Object	max: 1	Optional		

metadata.crn OR metadata.phone OR metadata.email	String	min: 1, max: 255	Mandatory	Any one of the customer identifiers - Email, CRN or phone	123456

Response Parameters

Field Name	Data Type	Length	Description	Example Values
data	Object		A container object holding the metadata and access details for the generated DPAR link.	
data.data_fiduciary_id	String	min: 3, max: 255	The unique identifier of the Data Fiduciary that initiated the DPAR portal link generation. Indicates which organisation is responsible for the data usage and requested the portal lin	6a6c58d9a14c
data.data_prinicpal_id	String	min: 3, max: 255	Unique identifier of the Data Principal for whom the DPAR portal link is being requested. Specifies the individual whose consent records and history should be made accessible via the portal link.	005a6d85-61b7-4495-bb78-44a033ef0e1f
data.expires_at	String		The exact expiration timestamp (in UTC) of the DPAR portal link. Indicates when the link will no longer be valid or accessible	2025-06-03T14:07:14.475358Z
data.link	String		The secure DPAR portal URL generated for the Data Principal. This is the actual link that can be sent or embedded to allow the Data Principal to view their consent history.	https://privy.idfy.com/principal/dpar/eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9
data.reference_id	String	min: 3, max: 255	A unique identifier generated by the Data Fiduciary to reference this specific Grant Notice. Used for tracking, audits, or future lookups.	personal-loan-application-no-1234

Headers

Field	Length	M/O	Description
account-id		M	Account ID provided by Privy
api-key		M	Authentication Key provided by Privy
Content-Type		M	application/json
x-privy-user-type		M	String value; Should be always “data-fiduciary”

Sample Input message

```
{
  "data_principal_id": "53e8c9d4-0675-4da6-a3bd-551abd129457",
  "reference_id": "test-2",
  "expires_in_hours": 24
}
OR

{
    "metadata": {
        "crn": "123456"
    },
    "expires_in_hours": 1
}
```

Sample output message

```
{
  "data": {
    "expires_at": "2024-11-25T04:44:13.626054Z",
    "link":
"https://privy.idfy.com/principal/dpar/eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9.eyJkYXRhX2ZpZ
HVjaWFyeV9pZCI6IjZhNmM1OGQ5YTE0YyIsImRhdGFfcHJpbmNpcGFsX2lkIjoiNTNlOGM5ZDQtMDY3NS00ZGE2LW
EzYmQtNTUxYWJkMTI5NDU3IiwiZXhwIjoxNzQwMTIwMjAwLCJvdV9pZCI6IjZhNmM1OGQ5YTE0YyIsImF1ZCI6Ikp
va2VuIiwiZXhwIjoxNzQwMTI1NjAwLCJpYXQiOjE3NDAxMTg0MDAsImlzcyI6Ikpva2VuIiwianRpIjoiMzBqMjh0
cDliZjIycGI5MGRrMDAycGwxIiwibmJmIjoxNzQwMTE4NDAwfQ.f1Yyz-sc1j3Va8tykC5OSMFacvnpeWGaL3dCcH
KYpfk",
    "data_principal_id": "53e8c9d4-0675-4da6-a3bd-551abd129457",
    "reference_id": "test-2",
    "data_fiduciary_id": "d8055f254352"
  }
}
```

API: Consent Validation

Summary

Description
This API endpoint allows a Data Fiduciary to for validating consents against a given Data Principal ID (DPID)/Reference ID and Processing Purpose Code.

Requirement background for Operation

URL	METHOD
https://privy.idfy.com/api/v1/consents/validate/instant	POST

Request Parameters

Field Name	Data Type	Length	Optional/Mandatory	Description	Example Values
id	String		Mandatory	Data Principal ID or Reference ID for which the consents need to be validated	53e8c9d4-0675-4da6-a3bd-551abd129457
type	String	min: 1, max: 255	Mandatory	The type of Identifier passed in id	data_principal_id / reference_id
processing_purpose_code	String	min: 1, max: 255	Mandatory	The processing purpose code against which the consents need to be validated	customer_12345609
business_process_code	String		Optional	Code representing the associated business process.	0TMehhqWAU

Response Parameters

Field Name	Data Type	Length	Description	Values
data	Object		The main container object for the response payload, containing details about the consent.	
id	String		Data Principal ID or Reference ID for which the consents need to be validated	dpi-abc
type	String		The type of Identifier passed in id	completed
results	String		Object containing information about the consent for the processing purpose	e094693b-bbf5-4046-a53e-62022ee351f4

			code passed in request	
processing_purpose_code	String		The processing purpose code against which the consents need to be validated	personal-loan-application-no-1234
consent_id	String		Unique ID of the consent object.	0f708400-57bb-4d2f-89a6-8b1e25d409a4
is_consent_active	Boolean		Key to identify if the consent is still active or not	true / false
status	String		The status of the consent	accepted / revoked
business_process_code	String		Code representing the associated business process.	0TMehhqWAU
business_process_version	Integer		Version of the business process	1
consent_purpose_code	String		Code representing the consent purpose.	K62PTgmkJc
consent_purpose_version	Integer		Version of the consent purpose configuration.	1
recorded_at	String		The date and time at which the consent was recorded in the system	2024-10-01T12:00:00Z
user_attributes	Array		List of user attributes associated with the processing purpose code	[phone_number]

Headers

Field	Length	M/O	Description
account-id		M	Account ID provided by Privy
api-key		M	Authentication Key provided by Privy
Content-Type		M	application/json
x-privy-user-type		M	String value; Should be always “data-fiduciary”

Sample Input message

```
{
  "id": "53e8c9d4-0675-4da6-a3bd-551abd129457",
  "type": "data_principal_id",
  "processing_purpose_codes": ["autopay_setup"],
  "business_process_code": "0TMehhqWAU"
}
```

Sample output message


```
{
  "data": {
    "id": "7426d3d1-30f1-4fa9-89d4-01529ba82b31",
    "type": "data_principal_id",
    "results": [
        {
            "processing_purpose_code": "autopay_setup",
            "consent_id": "0f708400-57bb-4d2f-89a6-8b1e25d409a4",
            "is_consent_active": true,
            "status": "accepted",
            "business_process_code": "0TMehhqWAU",
            "business_process_version": 1,
            "consent_purpose_code": "K62PTgmkJc",
            "consent_purpose_version": 1,
            "recorded_at": "2024-10-01T12:00:00Z",
           "user_attributes":[
              "phone_number"
           ]
        }
    ]
  }
}
```


Privy™ by IDfy

API: Bulk Consent Revocation

Overview

This API allows a Data Fiduciary to revoke many Data Principals' consent in one call, in scenarios where the consent needs to be withdrawn before its actual expiry for a whole group of customers at once - a closed account, an abandoned journey, or a discontinued product. One request submits either a CSV file or a JSON list of entries; Privy validates the whole submission and accepts it as a single job. Accepted jobs are processed in Privy's end-of-day run: each listed customer's active consents under the named business process are revoked, sealed into the signed consent artifact, and written to the audit trail as "withdrawn by data fiduciary - purpose met". Nothing is revoked at submit time.

Env	URL	METHOD
PROD		POST
UAT	https://privy.idfy.com/api/api/v2/consents/revoke/bulk	POST

Request Body

One request is either a CSV upload **or** a JSON body, never both. Privy tells them apart by **Content-Type**. Everything downstream is identical; the response's **source_format** says which one was used.

Fields common to both options

Field Name	Data Type	Length	Optional/ Mandatory	Description	Example Values
reason	String		Mandatory	Why the purpose ended; one value for the whole submission. Allowed values: ACCOUNT_CLOSURE, JOURNEY_DROPOFF, PRODUCT_DISCONTINUED, OTHER	ACCOUNT_CLOSURE
reason_note	String	1-255	Mandatory (if reason = OTHER)	Free text explaining the reason when reason is OTHER	Card programme sunset

Option A – CSV upload (Content-Type: multipart/form-data)

Field Name	**Data Type**	**Length**	**Optional/Mandatory**	**Description**	**Example Values**
file	File (CSV)	≤10 MiB, ≤100,000 rows	Mandatory (only when Content-Type: multipart/form-data)	The CSV file part. RFC 4180: UTF-8, comma-separated, header row first, exactly the six columns below in order	closures.csv
data_principal_id	String (column)	3–255	Mandatory (with reference_id, or omit both)	Identifies the customer with reference_id. Both or neither; when present the other identifier columns are ignored	9b2e6a41-77c3-4f10-a2d4-c81b5e9f3a02
reference_id	String (column)	3–255	Mandatory (with data_principal_id, or omit both)	The Data Fiduciary's own reference for the customer	ACC-883201
crn	String (column)	1–255	Optional	Any one or more of crn / email / phone_number when the identifier pair above is not given. Several on one row must all match (AND)	CRN77421
email	String (column)	RFC 5322, ≤254	Optional	–	a@example.com
phone_number	String (column)	10-21 It can include: An optional leading + A country code of 1–4 digits An area code of 1–4 digits, optionally in parentheses The rest of the number is in up to two groups, separated by a space, hyphen (-), or dot (.)	Optional	–	+91-9000012345
business_process_code	String (column)	≤10	Mandatory	A published business process	HOME_LOAN

				of yours, whose consents to revoke	

Option B – JSON body (Content-Type: application/json)

Field Name	Data Type	Length	Optional/Mandatory	Description	Example Values
data	Array of Objects	≤1,000 entries	Mandatory (only when Content-Type: application/json)	The list of revoke entries	
data[].data_principal_id	String	3–255	Mandatory (with reference_id, or omit both)	Identifies the customer with reference_id. Both or neither; when present the other identifier fields are ignored	9b2e6a41-77c3-4f10-a2d4-c81b5e9f3a02
data[].reference_id	String	3–255	Mandatory (with data_principal_id, or omit both)	The Data Fiduciary's own reference for the customer	ACC-883201
data[].crn	String	1–255	Optional	Any one or more of crn / email / phone_number when the identifier pair above is not given. Several on one entry must all match (AND)	CRN77421
data[].email	String	RFC 5322, ≤254	Optional	–	a@example.com
data[].phone_number	String	10-21 It can include: An optional leading + A country code of 1–4 digits An area code of 1–4 digits, optionally in parentheses The rest of the number is in up to two groups, separated by a space, hyphen (-), or dot (.)	Optional	–	+91-9000012345
data[].business_p	String	≤10	Mandatory	A published	HOME_LOAN

rocess_code				business process of yours, whose consents to revoke	

Rules: every row/entry needs business_process_code and at least one identifier group (the data_principal_id/reference_id pair, or any of crn/email/phone_number). CSV quoting is allowed but never needed – no accepted value contains a comma. At most 100,000 rows per file, 1,000 entries per JSON body. The same customer may appear on several rows for different business processes; the same customer twice for the same business process is accepted and the second row is a no-op. D**uplicates.** Privy hashes the submitted content (the CSV bytes, or the JSON data array serialised) and compares it with every job of yours still pending or processing. A match returns that job's job_id and creates nothing, so a retry after a timeout is safe. Once a job has finished, the same content submitted again is a new job.

Response Body

Response code **202**. The input is validated and stored; a job exists and is queued for the end-of-day run. Nothing is revoked yet.

Field Name	Data Type	Length	Description	Example Values
data	Object			
data.job_id	uuid		Privy's id for the job; quote it to support	5c2c8f1e-3b7a-4c1d-9e2f-0a1b2c3d4e5f
data.rows_total	Integer		Rows counted (CSV header excluded)	25000
data.source_format	String	csv · json	Which option was used	csv

Headers

Field	Length	M/O	Description
account-id		M	Account ID provided by Privy
api-key		M	Authentication Key provided by Privy
Content-Type		M	multipart/form-data for the CSV option, application/json for the JSON option
x-privy-user-type		M	String value; Should be always "data-fiduciary"

Sample Input message

```
curl -X POST 'https://<host>/api/v2/consents/purpose-met/bulk'
  -H 'api-key: <api-key>'
  -H 'account-id: <ou-id>/<account-id>'
  -H 'x-privy-user-type: data-fiduciary'
  -F 'reason=ACCOUNT_CLOSURE'
  -F 'file=@closures.csv;type=text/csv'

  OR

curl -X POST 'https://<host>/api/v2/consents/purpose-met/bulk'
  -H 'api-key: <api-key>'
  -H 'account-id: <ou-id>/<account-id>'
  -H 'x-privy-user-type: data-fiduciary'
  -H 'Content-Type: application/json'
  -d '{
    "reason": "ACCOUNT_CLOSURE",
    "data": [
      { "data_principal_id": "9b2e6a41-77c3-4f10-a2d4-c81b5e9f3a02", "reference_id": "ACC-883201", "business_process_code":
"HOME_LOAN" },
      { "crn": "CRN77421", "business_process_code": "HOME_LOAN" },
      { "crn": "CRN77421", "email": "a@example.com", "business_process_code": "CREDCARD" }
    ]
  }'
```

Sample output message

```
{
  "data": {
    "job_id": "5c2c8f1e-3b7a-4c1d-9e2f-0a1b2c3d4e5f",
    "rows_total": 25000,
    "source_format": "csv"
  }
}
```

Sample Error message


```
{
  "error": {
    "details": {
      "code": "VALIDATION_ERROR",
      "message": "Request validation failed",
      "fields": {
        "reason": ["must be one of: ACCOUNT_CLOSURE, JOURNEY_DROPOFF, PRODUCT_DISCONTINUED, OTHER"]
      }
    }
  }
}
```


Privy error codes

S.No	Error Code	Error description	Response body
1	401 UNAUTHORIZED	api-key, account-id or x-privy-user-type missing or invalid	{ "error": { "details": { "code": "UNAUTHORIZED", "message": "..." } } }
2	403 FORBIDDEN	The caller may not act for that data fiduciary; or x-privy-resource-data-fiduciary-id sent by a data-fiduciary / missing for a data-processor	{ "error": { "details": { "code": "FORBIDDEN", "message": "..." } } }
3	429 TOO_MANY_REQUESTS	Too many submissions from your account in a short window; wait, then resend the same request	{ "error": { "details": { "code": "TOO_MANY_REQUESTS", "message": "Too much work is already queued for this account — retry later", "reason": "pending_rows_exceeded", "pending_rows": 199500, "incoming_rows": 1176, "max_pending_rows": 200000 } } } OR { "error": { "details": { "code": "TOO_MANY_REQUESTS", "message": "Too much work is already queued for this account — retry later", "reason": "pending_jobs_exceeded", "pending_jobs": 20, "max_pending_jobs": 20 } } }
4	413 PAYLOAD_TOO_LARGE	Body over 10 MiB; split the input into several files	{ "error": { "details": { "code": "PAYLOAD_TOO_LARGE", "message": "..." } } }
5	415 UNSUPPORTED_MEDIA	Multipart without a file part, or JSON without a	{ "error": { "details": { "code": "UNSUPPORTED_MEDIA_TYPE", "message": "..." } } }

	_TYPE	data array; pick one option and send its required part	
6	422 VALIDATIO N_ERROR	Common fields wrong, or more than 1,000 entries in data; all problems collected in one response	{ "error": { "details": { "code": "VALIDATION_ERROR", "message": "Request validation failed", "fields": { "field": ["messages"] } } } }
7	422 INVALID_FIL E	The CSV as a whole cannot be accepted (CSV option only): invalid_content_ty pe · file_empty · invalid_encoding · invalid_header (+ expected, received) · no_data_rows · too_many_rows (+ total_rows, max_rows: 100000)	{ "error": { "details": { "code": "INVALID_FILE", "message": "CSV header does not match the template", "reason": "invalid_header", "expected": [...], "received": [...] } } }
8	422 INVALID_RO WS	One or more rows / entries wrong – every one is checked	{ "error": { "details": { "code": "INVALID_ROWS", "message": "3 of 25000 rows are invalid", "total_rows": 25000, "total_invalid": 3, "errors": [{ "row": 17, "column": "business_process_code", "code": "unknown_business_process" }, { "row": 4021, "column": "reference_id", "code": "reference_id_required" }], "errors_truncated": false } } }
9	503 STORAGE_ UNAVAILAB LE	Input could not be stored; retry after a short wait, safe to retry	{ "error": { "details": { "code": "STORAGE_UNAVAILABLE", "message": "..." } } }

Row codes in INVALID_ROWS.errors[].code (row is the 1-based data row – CSV header excluded, JSON entries numbered from 1):

Row code	**Meaning**
business_process_code_required	Field empty
unknown_business_process	Not a published business process of yours
identifier_required	No identifier on the row
data_principal_id_required	reference_id given without data_principal_id

reference_id_required	data_principal_id given without reference_id
invalid_data_principal_id / invalid_reference_id	3–255 chars of A-Z a-z 0-9 / ( ) . _ -
invalid_crn	1–255 chars of A-Z a-z 0-9 - _ #
invalid_email	Not an RFC 5322 address, or over 254 chars
invalid_phone_number	10-21 It can include: An optional leading + A country code of 1–4 digits An area code of 1–4 digits, optionally in parentheses The rest of the number is in up to two groups, separated by a space, hyphen (-), or dot (.)
column_count_mismatch	The row has more or fewer commas than the header (CSV only)
malformed_quoting	An unclosed or stray quote (CSV only)
field_too_long	A value over 255 bytes

Things to know

- **End-of-day processing.** Accepted jobs are run in Privy's end-of-day batch, not at submit time.
- **Not reversible.** Revoked consents are not restored by any API; the customer can consent again only through a new notice.
- **Mandatory consents are revoked too.** This flow acts on your behalf and bypasses the customer-facing protections.
- **Processing time.** All jobs on the platform share one processing rate. A 100,000-row job alone takes on the order of an hour; concurrent jobs take proportionally longer.
- **Audit.** Every revoked consent shows in the customer's consent timeline as withdrawn by the data fiduciary, purpose met, and in your consent APIs as performed_by: data_fiduciary.
- **Duplicates & retries.** A retry of the exact same content while a matching job is pending or processing returns the existing job_id and creates nothing.

Webhook: Aggregated Notice Submitted

Overview

This webhook is triggered when a data principal (user) accepts an aggregated notice issued by a data fiduciary (organization). The webhook payload includes key information that helps track the accepted consent and related business details.

Webhook Response

Field Name	Data Type	Length	Optional/ Mandatory	Description	Example Values
notice_workflow_id	String	36	Mandatory	Unique ID of the aggregated grant notice that was presented and submitted.	d4ee0cc2-1056-4925-9e20-61654f3fe024
group_reference_id	String	min: 3, max: 255	Mandatory	Custom reference string provided by the Data Fiduciary to track this notice across systems. Mandatory to be unique	personal-loan-account-123467
inserted_at	String	28	Mandatory	Timestamp indicating when the aggregated notice record was inserted.	2024-05-23T11:05:24.532236Z
updated_at	String	28	Mandatory	Timestamp indicating when the aggregated notice record was last updated (usually when the Data Principal submitted their response)	2024-05-23T11:05:32.123825Z
mandatory_consents_granted	String	Min: 29, max: 35	Mandatory	This key tells you whether all/some/none mandatory consents were accepted by the customer Possible Values: all_mandatory_consents_accepted / partial_mandatory_consents_accepted / all_mandatory_consents_rejected / no_mandatory_consents_present	all_mandatory_consents_accepted / partial_mandatory_consents_accepted / all_mandatory_consents_rejected / no_mandatory_consents_present
status	String	9	Mandatory	Indicates the status of the grant notice flow.	submitted

				Possible Values: submitted	
historic	Boolean	Min: 4, max: 5	Optional	Possible values: true / false	true / false
notices	Array of Object	min: 1	Mandatory	List of two notices created with mandatory BP and optional BP	
notices[0].data_fiduciary_id	String	12	Mandatory	Identifier of the Data Fiduciary that issued the grant notice	f30c280c794e
notices[0].data_principal_id	String	min: 3, max: 255	Mandatory	Unique identifier for the Data Principal (the individual) who submitted the notice.	cbd4610a-687c-4f30-acd7-fb32b82db0ff
notices[0].notice_id	String	36	Mandatory	Unique ID of the grant notice that was presented and submitted.	d4ee0cc2-1056-4925-9e20-61654f3fe024
notices[0].reference_id	String	min: 3, max: 255	Mandatory	Custom reference string provided by the Data Fiduciary to track this notice across systems.	personal-loan-account-123467
notices[0].business_process_name	String	min: 3, max: 255	Mandatory	Code for the associated business process (e.g., opening an account, applying for a loan).	tmA4nSCSdS
notices[0].business_process_code	String	max: 10	Mandatory	Human-readable name of the business process.	Personal Loan Account
notices[0].business_process_version	Integer		Mandatory	Version number of the business process.	1
notices[0].consent_status	String	8	Mandatory	Outcome of the consent action taken by the Data Principal. Possible values: accepted / rejected	accepted
notices[0].selected_language	String	min: 2, max: 8	Mandatory	Language selected by the Data Principal while interacting with the notice. Possible values: as, bn, br, doi, en, gom, gu, hi, kn, ks, mai, ml, mni-Mtei, mr, ne, or, pa, sa, sd, st, ta, te, ur	en
notices[0].resource_type	String	min: 12, max: 13	Mandatory	Type of resource involved in the webhook Possible values: grant_notice /	grant_notice / update_notice

				update_notice	
notices[0].submitted_consents	Array of object	0	Mandatory	List of consent items submitted along with the notice. This may be empty if no granular consent objects were present or needed. Possible values: []	[]
notices[0].status	String	9	Mandatory	Status of the notice Possible values: submitted	
notices[0].updated_at	String	28	Mandatory	Timestamp indicating when the notice record was last updated (usually when the Data Principal submitted their response)	
notices[0].inserted_at	String	28	Mandatory	Timestamp indicating when the notice record was inserted.	

Sample Webhook message


```
{
  "notice_workflow_id": "bc36b36e-d52e-44ba-a90e-975fac8fb10b",
  "group_reference_id": "ANC-TEST-00",
  "inserted_at": "2026-05-05T10:35:05.145679Z",
  "historic": false,
  "notices": [
   {
    "business_process_code": "hIdHGPrrkT",
    "business_process_name": "Bank Account Opening",
    "business_process_version": 1,
    "consent_status": "accepted",
    "data_fiduciary_id": "b431ab8cf2a1",
    "data_principal_id": "dpr0",
    "inserted_at": "2026-05-05T10:35:05.155897Z",
    "notice_id": "c149a1fc-0bcb-40d2-8a1a-907b1981d6d8",
    "reference_id": "ref0",
    "resource_type": "grant_notice",
    "selected_language": "en",
    "status": "submitted",
    "submitted_consents": [],
    "updated_at": "2026-05-05T10:36:21.891445Z"
   },
   {
    "business_process_code": "hQKc6rCxUP",
    "business_process_name": "Home Loan",
    "business_process_version": 4,
    "consent_status": "accepted",
    "data_fiduciary_id": "b431ab8cf2a1",
    "data_principal_id": "dpr0",
    "inserted_at": "2026-05-05T10:36:21.871784Z",
```

```
    "notice_id": "c0ada45f-cf9e-4c61-abd2-29ab2f77f3af",
    "reference_id": "ref1",
    "resource_type": "update_notice",
    "selected_language": "en",
    "status": "submitted",
    "submitted_consents": [],,
    "updated_at": "2026-05-05T10:36:21.884362Z"
   }
  ],
  "mandatory_consents_granted": "all_mandatory_consents_accepted",
  "status": "submitted",
  "updated_at": "2026-05-05T10:36:21.878652Z"
}
```


Privy™ by IDfy

Webhook: Consent Artifact Created Or Updated

Summary

Description
This webhook is triggered whenever a consent artifact is updated—whether through initial grant, revoke, or reconsent actions—and contains a digitally signed, hash-verified record of the user's consent decisions. It includes metadata such as the notice and business process details, timestamps, and a secure URL to access the signed artifact. Each submitted consent entry reflects the specific data attributes and purposes for which the user has acted (e.g., accepted), ensuring auditability, data integrity, and regulatory compliance.

Webhook Body Parameters

Field Name	Data Type	Length	Optional/Mandatory	Description	Example Values
reference_id	String	min: 3, max: 255		Custom identifier provided by the Data Fiduciary to track this specific consent flow.	personal-loan-account-123467
data_fiduciary_id	String	min: 3, max: 255		Identifier for the Data Fiduciary issuing or updating the consent.	idfy-ops
data_principal_id	String	min: 3, max: 255		Unique identifier for the Data Principal who performed the action (grant, revoke, reconsent).	a23d5f90-9bfb-43cf-824f-38b4d9a6b9ae
notice_id	String	min: 3, max: 255		Identifier of the related grant notice.	97099ee9-ebe3-4645-a840-5dadc8366314
business_process_code	String			Code representing the associated business process.	a0hV7X6uWh
business_process_version	String			Version of the business process.	1
business_unit_code	String			Internal code for the business unit initiating the consent request.	xHnWWS4SAn
business_unit_name	String			Human-readable name of the business unit.	Banking
business_unit_version	String			Version of the business unit configuration.	1
artifact_hash	String			Base64-encoded SHA256 hash of the final consent artifact content, used to verify data integrity.	gwfppajwia4xscnmpvwebigaiad362mjyq0mixbpcf0=
artifact_signature	String			Cryptographic signature of the consent artifact, used for authenticity verification.	(Long base64 signature)
artifact_url	String			Signed URL to access the complete consent artifact JSON. Usually hosted in secure object storage.	(Signed GCS URL)

status	String			Indicates the nature of the webhook event.	consent_artifacts_updated
notice_completed_at	String			Timestamp when the original grant notice interaction was completed by the Data Principal.	2025-03-05T11:04:37.161853Z
signature_generation_timestamp	String			Timestamp when the digital signature for this artifact was created.	2025-03-05T11:04:37.351404Z
selected_language	String			Language selected by the Data Principal during the notice interaction.	en
policy_name	String				Loans
policy_version	String				1
policy_code	String				AiVwMBBWad
metadata	Array of Objects	max: 20	Mandatory	A list (array) of key–value pairs used to store additional, customizable information about the Grant Notice. Each item is an object with key and value fields. Attach external references, user context, tracking info, etc.	
metadata[0].key	String	min: 1, max: 255	Mandatory	The metadata key name. In case of AFL, it will be customer id	crn
metadata[0].value	String	min: 1, max: 255	Mandatory	Value of customer id	customer_12345609
submitted_consents	Object			Each object represents a single consent item captured in the artifact.	
submitted_consents.action	String			The action performed on the consent.	accepted
submitted_consents.consent_id	String			Unique ID of the consent object.	cbead2b2-b0ae-444e-90a2-5097ff9f5031
submitted_consents.consent_purpose_code	String			Code representing the consent purpose.	lrMrk2omik
submitted_consents.consent_purpose_version	Integer			Version of the consent purpose configuration.	1
submitted_consents.processing_purpose_code	String			Code representing the purpose for which the data will be processed.	ntdrcEzOrr
submitted_consents.user_attributes	String			Array of the type of user data the consent applies to.	[“Delivery Address”]
submitted_consents.data_integrity	Object				
submitted_consents.data_integrity.hash	String			Integrity hash for this specific consent record to detect tampering.	lraxwkeclmvfqb2rwt7dqhtdzxgvr85qzxbuxu3db2i=

submitted_consents.minor_data_principal_id	Integer			ID of a minor if the consent was given on behalf of one. null if not applicable.	null
submitted_consents.performed_at	String			Timestamp when the consent action was performed.	2025-03-05T11:04:37.140135Z
submitted_consents.performed_by	String			Who performed the action	self

Sample Webhook Response


```
{
  "artifact_hash": "6s1ac18lgay5+8zztmsgmawy0bfr3dqagqhrvkpgm2k=",
  "artifact_signature":
"Zfa3DCnGFRlFICXnkypS4w7rAwpN2NP+Kczb81SerRiQLLjK8F2HRpY4d8CpWHCu8+ZlisgUn6JLPhmztBzLMi44
wrnL2AQnITqGLWuqs2CQAykZF8tvEGmfyL9detePBRDHJjwsRkSo4EqvrkE/senYsUo93ctrYrnOid3Wm3RTKHQzf
Mh2mj1tm3QeFbGU5VWEv0YEEU53D4xLSOXnR1FiBw8jiguZthvrRCPJscJOivMWXfsJgxm+0yw4VtY+hqyR2MlAaC
bmtISEmRKRiK/d9srfKh8SDEmc47rfzyggLvohit6P1MAY3Hu8MbbrP7TPcdBz/GlcN4Rm3UZyEw==",
  "artifact_url":
"https://storage.googleapis.com/tucana-consent-shield/cgp/consents/a5bda99bd74f-0TMehhqWA
U-1-e59a5e6cef42d7e42d4875e9b967fdf52e53c721eb46a2493fcd5bcb58416d10-5876c32d3f338b13315f
909cc7e8def08c4a9368682f1b265e07c35024159fe9.json?X-Goog-Algorithm=GOOG4-RSA-SHA256&X-Goo
g-Credential=consent-governance%40idfy-data-lake-prod.iam.gserviceaccount.com%2F20250722%
2Fauto%2Fstorage%2Fgoog4_request&X-Goog-Date=20250722T125923Z&X-Goog-Expires=259200&X-Goo
g-SignedHeaders=host&response-content-disposition=attachment%3B%20filename%3Dcgp%2Fconsen
ts%2Fa5bda99bd74f-0TMehhqWAU-1-e59a5e6cef42d7e42d4875e9b967fdf52e53c721eb46a2493fcd5bcb58
416d10-5876c32d3f338b13315f909cc7e8def08c4a9368682f1b265e07c35024159fe9.json&response-con
tent-type=application%2Fjson&X-Goog-Signature=13efd33511aafe16c7df236862ef90c55adbedb96fe
9a44b779a6576a0803d3bc5e48d0955e57fa01e3e77807b7959816891d5ba542933f4807fee06490b29600fab
d8cbe698be715f2ddbac87a731c924f3a663545e7eba73c1ad2f033cfc1f335d94379e6b3eab5dc8c65f59660
ea1643ee9f6b9d64c95f861750a0ae8ea389de3d213262ccaed157a21670f5657b250b67a7e309c75fa92fd5e
56525a0d2a5746d3c4ed2ac582197e05e3ac4495c3ec07566b7303635677660c55ad478131c6cfaba0c00239e
3ac80f217e2065b478f8d648c07ea6b6b64d0776141b619c96127d533b120cb16c08e92114a4e91a5a391a2ef
1e20548b65ca5193c3267384",
  "business_process_code": "0TMehhqWAU",
  "business_process_name": "Personal Loan",
  "business_process_version": "1",
  "business_unit_code": "AiVwMBBWad",
  "business_unit_name": "Loans",
  "business_unit_version": "1",
  "data_fiduciary_id": "d8055f254352",
  "data_principal_id": "67cc4ede-d933-47c0-90f8-7a500354ea43",
  "metadata":[
     {
       "key": "crn",
       "value": "customer_123456"
     },
     {
       "key": "email",
       "value": "test@email.com"
     }
   ],
```

```
  "notice_completed_at": "2025-07-22T12:59:23.163626Z",
  "notice_id": "e0044d04-83b1-4891-b97a-20b56487dcb7",
  "policy_code": "AiVwMBBWad",
  "policy_name": "Loans",
  "policy_version": "1",
  "reference_id": "7a500354ea43",
  "selected_language": "en",
  "signature_generation_timestamp": "2025-07-22T12:59:23.255808Z",
  "status": "consent_artifacts_updated",
  "submitted_consents": [
    {
      "action": "accepted",
      "consent_id": "507c4340-76a6-46f1-80a7-3c2fd28fdcf1",
      "consent_purpose_code": "K62PTgmkJc",
      "consent_purpose_name": "E-Mandate",
      "consent_purpose_version": 1,
      "data_integrity": {
        "hash": "hq7nc45fjnhnljitdlwa7f4ys6y0rwe+vpxapcdtyi4="
      },
      "data_principal_id": "67cc4ede-d933-47c0-90f8-7a500354ea43",
      "language": "en",
      "minor_data_principal_id": null,
      "performed_at": "2025-07-22T12:59:23.129306Z",
      "performed_by": "self",
      "processing_purpose_code": "autopay_setup",
      "processing_purpose_name": "Autopay Setup",
      "reference_id": "7a500354ea43",
      "user_attributes": ["Bank Account and IFSC Code"]
    },
    {
      "action": "accepted",
      "consent_id": "42b20ac0-1647-4dea-a8be-842820440d91",
      "consent_purpose_code": "K62PTgmkJc",
      "consent_purpose_name": "E-Mandate",
      "consent_purpose_version": 1,
      "data_integrity": {
        "hash": "7vbzrz+6uwzou8pmopw3jh2r/z4o90vmljxb5tz7paq="
      },
      "data_principal_id": "67cc4ede-d933-47c0-90f8-7a500354ea43",
      "language": "en",
      "minor_data_principal_id": null,
      "performed_at": "2025-07-22T12:59:23.129307Z",
      "performed_by": "self",
      "processing_purpose_code": "autopay_setup",
      "processing_purpose_name": "Autopay Setup",
      "reference_id": "7a500354ea43",
      "user_attributes": ["Bank Account number"]
    }
  ]
}
```

Webhook: Consent Expired

Summary

Description
This webhook is triggered when a previously granted consent reaches its expiration, indicating that the user's permission to process a specific data attribute (e.g., Aadhar) is no longer valid. It includes identifiers for the consent, notice, business process, and business unit involved, along with the exact timestamp of expiration.

Webhook Body Parameters

Field Name	Data Type	Length	Optional/Mandatory	Description	Example Values
reference_id	String	min: 3, max: 255		External reference associated with the consent, typically provided by the Data Fiduciary at grant time.	3bfe3972-8203-4bd4-99f2-63e2bae5b8a6
data_fiduciary_id	String	min: 3, max: 255		Identifier of the Data Fiduciary (DF) managing the consent.	72c53aa1642b
data_principal_id	String	min: 3, max: 255		Identifier for the Data Principal (individual who granted the consent).	GrantbyAPI-ConsentExpiry26feb
business_process_code	String			Code representing the business process tied to the consent.	v3iJJqEF3G
business_process_version	Integer			Version of the business process.	2
consent_id	String	min: 3, max: 255		Unique identifier of the expired consent.	ed35429c-9a25-4f39-b970-d61525d81758
consent_purpose_code	String			Code representing the purpose for which the consent was originally granted.	WR9L0olGh0
consent_purpose_version	Integer			Version of the consent purpose definition.	2
processing_purpose_code	String			Code representing the specific processing activity for which the consent was used.	fAbulxDHzo
business_unit_code	String			Code for the business unit that initiated or used the consent.	L3r6ohQCrg
business_unit_version	Integer			Version of the business unit's configuration.	1
user_attribute_name	String			Specifies which data attribute the consent was tied to.	Aadhar
status	String			Current state of the consent record.	consent_expired
selected_language	String			Language preference selected by the Data Principal.	mr
notice_id	String	min: 3, max: 255		ID of the grant notice associated with this consent.	9646db9c-e736-40a2-a53e-3c1b62c921be

parent_consent_id	Integer			If this consent was derived from another (e.g. reconsent), the parent's ID is populated. Otherwise null.	null
inserted_at	String			Timestamp when the consent record was created.	2025-03-04T05:50:31.326811Z
updated_at	String			Timestamp of the most recent update to this consent.	2025-03-04T05:50:31.326811Z
expired_at	String			Timestamp when the consent officially expired.	2025-03-04T05:50:31.326811Z

Sample Webhook Response


```
{
  "reference_id": "3bfe3972-8203-4bd4-99f2-63e2bae5b8a6",
  "data_fiduciary_id": "72c53aa1642b",
  "data_principal_id": "GrantbyAPI-ConsentExpiry26feb",
  "business_process_code": "v3iJJqEF3G",
  "business_process_version": 2,
  "consent_id": "ed35429c-9a25-4f39-b970-d61525d81758",
  "consent_purpose_code": "WR9L0olGh0",
  "consent_purpose_version": 2,
  "processing_purpose_code": "fAbulxDHzo",
  "business_unit_code": "L3r6ohQCrg",
  "business_unit_version": 1,
  "user_attribute_name": "Aadhar",
  "status": "consent_expired",
  "selected_language": "mr",
  "notice_id": "9646db9c-e736-40a2-a53e-3c1b62c921be",
  "parent_consent_id": null,
  "inserted_at": "2025-03-04T05:50:31.326811Z",
  "updated_at": "2025-03-04T05:50:31.326811Z",
  "expired_at": "2025-03-04T05:50:31.326811Z"
}
```

Privy error codes

S.No	Error Code	Error description	Response body

1	400	Client error responses	{
			"error": {
			"details": {
			"key": "Invalid input"
			}
			}
			}

2	401	Unauthorized	{
			"error": {
			"details": {
			"key": "Unauthorized access"
			}
			}
			}

3	403	Forbidden	{
			"message": "Invalid authentication credentials"
			}

4	404	Notice not found	{
			"error": {
			"details": {
			"key": "Not found"
			}
			}
			}

5	429	Rate Limit Reached	{
			"errors": "Rate Limit Reached"
			}

6	422	Client error responses	{
			"errors": {
			"details": {
			"business_process": "Notices should not share business processes between different types"
			}
			}
			}

7	500	Internal Server Error	{
			"error": {
			"details": {
			"key": "Internal Server Error"
			}
			}
			}

Whitelisting

User Access in Client Environment

These are the relevant connection whitelists needed for a User to be able to log in and use the Privy Platform on the Web.

1. Application IPs
    a. 35.244.243.72
    b. 34.120.54.183
2. Application Domains
    a. Authentication & Sign In -
        i. https://auth.shared.idfy.com
        ii. https://idp2.idfy.com
        iii. privy.idfy.com
    b. Application Fonts
        i. https://fonts.googleapis.com
    c. Application Performance Monitoring
        i. https://o4507496702869504.ingest.us.sentry.io
    d. Analytics
        i. https://insights.shared.idfy.com/ - (34.120.54.183)
        ii. https://metabase.idfy.com/ - (34.120.54.183)
3. Application Ports:
    a. 443
4. Network Protocols:
    a. HTTPS
    b. WSS - WebSockets

Application Integration in Client Environment

These are the relevant connection whitelists needed for an Application to be able to make requests and integrate with the Privy Platform.

1. Application IPs
    a. 35.244.243.72
    b. 34.120.54.183
2. Application Domains
    a. privy.idfy.com
3. Application NAT IPs - Clients have to whitelist to receive callbacks from IDfy
    a. 35.244.32.83
    b. 34.93.185.58
4. Application Ports:
    a. 443
5. Network Protocols:
    a. HTTPS

Privy™
by IDfy