The "System.IO.Directory" class

System.IO.Directory class

- The "Directory" is a class in "System.IO" namespace.
- The "Directory" class is a static class, which provides a set of static methods to manipulate folders.

Steps for development of "Directory" class:

- Import the namespace:
  - using System.IO;
- Call any static method:
  - Directory.*method* ();

Methods of "Directory" class:

Sl. No	Method	Description
1	Exists()	Checks whether the folder exists or not. **True:** The folder exists. **False:** The folder not exists **Syntax:** Directory.Exists(string FolderPath)
2	CreateDirectory()	Create the specified folder and returns corresponding DirectoryInfo's object. **Syntax:** Directory.CreateDirectory(string FolderPath)

3	Delete()	Deletes the specified folder permanently, including all of its sub folders and files in it. **Syntax:** Directory.Delete(string FolderPath, true) **Warning:** This action is permanent. It is impossible to undo this action. Check the folder path before running the program.
4	Move()	Moves the specified source folder into the specified destination location. **Rule:** Both source and destination location should be in the same drive. **Ex:** C: drive **Syntax:** Directory.Move(string SourceFolderPath, string DestinationFolderPath)

HARSHA

The "System.IO.Directory" class - Example

Creating Project

- Create the following folders:
  - C:\CSharp
    - Sample (folder)

- Open Visual Studio 2015.
- Go to "File" – "New" – "Project".
- Select ".NET Framework 4.6".
- Select "Visual C#".
- Select "Console Application".
- Type the project name as "DirectoryExample".
- Type the location as "C:\CSharp".
- Type the solution name as "DirectoryExample".
- Click on OK.

Program.cs

```
using System;
using System.IO;

namespace DirectoryExample
{
  class Program
  {
    static void Main()
```

```
    {
      if (Directory.Exists(@"c:\folder1") == true)
      {
        Directory.Delete(@"C:\folder1", true);
      }
      if (Directory.Exists(@"c:\folder2") == true)
      {
        Directory.Delete(@"C:\folder2", true);
      }

      Directory.CreateDirectory(@"C:\folder1");
      Console.WriteLine("folder1 created");
      Console.WriteLine("folder1 exists: " +
Directory.Exists(@"C:\folder1")); //Output: True

      Directory.Delete(@"C:\folder1");
      Console.WriteLine("folder1 deleted");
      Console.WriteLine("folder1 exists: " +
Directory.Exists(@"C:\folder1")); //Output: False

      Directory.CreateDirectory(@"C:\folder1");
      Console.WriteLine("folder1 created");

      Directory.Move(@"C:\folder1", @"C:\folder2");
      Console.WriteLine("folder1 moved as folder2");

      Console.ReadKey();
    }
  }
}
```

HARSHA

Running the Project

- Go to “Debug” menu and click on “Start Debugging”.

Output