

Detector–Plane Imaging (DPI): A Quantum to Classical Measurement – Plane Framework

Abstract

Detector–Plane Imaging (DPI) establishes that interference is encoded in a pre–detection coherence imprint and that detector–plane processing determines whether this structure is preserved or irreversibly lost. Integrating the Imprint Hypothesis with the Quantum Measurement Stack (QMS), this framework treats quantum measurement as a hardware–defined selection process.

1. Introduction

Quantum interference experiments are often interpreted through wave–particle duality, leading to ambiguity about when and how interference arises. DPI resolves this by separating:

- **Pre–detection coherence (imprint domain)**
- **Post–detection measurement outcomes**

Particles remain primary excitations of quantum fields, while wave–like behavior emerges as a contextual imprint of propagation.

2. Causality: Quantum Measurement Stack (QMS)

Quantum processes follow a strict causal order:

Field excitation → Imprint propagation → Detector plane → Readout → Analysis


The **detector plane** defines the measurement boundary where:

- Correlations may be preserved or discarded
- Information loss becomes **irreversible**

Once lost, correlations cannot be recovered by downstream processing.

Figure 1: Quantum Measurement Stack (QMS). The detector plane defines the measurement boundary where irreversible information loss occurs.

Quantum Measurement Stack



3. Mechanism: Detector–Plane Selection (DPI)

A single coherence imprint arrives at the detector as a continuous, phase–encoded structure. The detector determines whether this structure becomes observable.

Two regimes emerge:

Intensity–Only Detection

- Measures amplitude only
- Phase correlations discarded
- Output: **No stable interference**


Correlation–Preserving Detection

- Retains phase correlations
- Preserves coherence structure
- Output: **High–contrast interference**

Thus, interference is not created at detection but conditionally revealed.

Figure 2: A single coherence imprint leads to different outcomes depending on detector–plane coherence preservation.

Figure 2: Mechanism (DPI)
Detector Plane with **Sensor Layer**



4. Validation: QMCTB-01 Benchmark

The QMCTB-01 benchmark isolates detector-plane behavior by keeping all other conditions identical:

- Excitation
- Propagation
- Photon statistics

Only detector architecture changes.

Results:

- Intensity-only detection → no interference
- Correlation-preserving detection → stable interference

This demonstrates that:

Interference visibility is determined by detector–plane coherence preservation, not photon accumulation.

Crucially, under identical physical conditions, the detector alone determines which correlations are preserved, leading to different observed outcomes.

Same input → different detector → different observed reality.

5. Key Insight

Interference is encoded prior to detection; the detector determines its observability.


This removes ambiguity in wave–particle duality by distinguishing:

- **Physical reality:** particle–based field excitations
- **Measurement outcome:** detector–dependent imprint selection

Figure 3: Identical input conditions produce different observed outcomes due solely to detector architecture. Interference visibility is determined by detector–plane processing.

Figure 3: Validation (QMCTB-01)

Same Input → Different Detector Architectures



cture → *Different Observed Reality*

plane cannot be recovered)



Laser / Source



Readout Electronics



Data Processing

6. Conclusion

Detector–Plane Imaging (DPI) establishes quantum measurement as a detector–defined, physically localized process. The coherence imprint exists prior to detection as a continuous, phase–encoded field structure, while the detector plane determines which correlations are preserved or irreversibly lost.

The QMCTB–01 benchmark demonstrates that, even under identical excitation, propagation, and photon statistics, measurement outcomes diverge solely due to detector architecture.

This shifts the interpretation of interference from a phenomenon of accumulation or observation to a consequence of detector–plane coherence fidelity.

Same input → different detector → different observed reality

Irreversible information loss at the detector plane prevents recovery of discarded correlations, establishing measurement as a hardware–constrained selection process.

This framework remains fully compatible with quantum field theory while providing a clear, testable, and instrumentation–grounded understanding of quantum measurement.