# SIMATS ENGINEERING

## TECHNICAL PRESENTATION

### Machine Learning - ITA06

Topic: Project Significance, Pre-processing, Performance Analysis, Future Scope and Learning Problems

*Short Answer Test – Complete Model Solutions*

**NAME:** SRIKESH .G

**REG NO:** 192521084

**Machine Learning -** ITA0602

**Slot:** C

## Question 1: Practical Significance, Dataset and Literature Review

*Note: Questions 1–4 use the illustrative project "Early Prediction of Diabetes using Machine Learning". Replace it with your own topic, dataset and results.*

### Practical significance

Diabetes is a chronic disease that is often detected late. An ML-based screening model can flag high-risk patients from routine clinical measurements, so that doctors can start treatment early. The topic is practically significant because:

- **Healthcare impact:** Early detection reduces complications such as kidney failure, heart disease and blindness.
- **Low cost and accessibility:** Screening with simple measurements (glucose, BMI, age, blood pressure) is cheap and can support clinics with few specialists.
- **Intelligent automation:** The model works as a decision-support tool; it assists, not replaces, the doctor.
- **Reusability:** The same pipeline can be reused for other disease-prediction problems.

### Dataset

The Pima Indians Diabetes dataset (UCI / Kaggle) has 768 records and 8 numeric input attributes (Pregnancies, Glucose, BloodPressure, SkinThickness, Insulin, BMI, DiabetesPedigreeFunction, Age) with a binary target (diabetic / non-diabetic). About 268 records are positive and 500 negative.

| Dataset criterion | How the chosen data meets it |
|---|---|
| Relevance | Attributes are standard clinical risk factors for diabetes. |

| | |
|---|---|
| Diversity | Covers a range of ages, BMI and glucose levels; can be extended with other public datasets to include more populations. |
| Size | 768 records are enough for classical ML; for better generalisation a larger dataset should be added or data augmentation (e.g. SMOTE) used. |
| Quality | Contains invalid zero values and class imbalance, which are handled in pre-processing (Question 2). |

### Literature review

A good literature review covers recent papers (preferably the last 5 years), their methods, datasets, results and limitations. The comparison below shows the expected structure; add 6–8 citations from IEEE, Springer, Elsevier or PubMed in your own review.

| Approach | Typical methods | Strength | Gap / limitation |
|---|---|---|---|
| Classical ML | Logistic regression, SVM, KNN, Naive Bayes | Simple, fast, interpretable | Sensitive to noise and missing values |
| Tree-based ensembles | Decision tree, Random Forest, XGBoost | Good accuracy, feature importance | Risk of overfitting on small data |
| Deep learning | ANN, CNN, LSTM | Learns complex patterns | Needs large data; low interpretability |
| Hybrid / optimised models | Feature selection + ensemble, GA/PSO tuning | Higher accuracy | Costly; weak validation across datasets |

**Research gap and justification:** Many existing studies use only accuracy, ignore

invalid values in the data, do not tune the decision threshold for sensitivity, and are not validated on a second dataset. The proposed approach addresses these gaps with careful pre-processing, feature selection, ensemble learning, recall-oriented threshold tuning and cross-validation, so that the work is grounded in prior research and adds a meaningful improvement.

## Question 2: Pre-processing, Post-processing and Evaluation

### Pre-processing

- **Data cleaning:** Remove duplicates and inconsistent records; check data types.
- **Handling missing values:** In this dataset zero values of Glucose, BloodPressure, SkinThickness, Insulin and BMI are physiologically impossible, so they are treated as missing and imputed using the median (or KNN imputation).
- **Outlier treatment:** Detect outliers by the IQR rule and cap or remove them.
- **Normalisation:** Min-Max scaling or standardisation (z-score) so that attributes with large ranges (Insulin) do not dominate distance- or gradient-based models.
- **Feature selection:** Correlation analysis, information gain, Recursive Feature Elimination (RFE) and Random-Forest importance keep only the most informative attributes (Glucose, BMI, Age, etc.).
- **Class imbalance:** Class weights or SMOTE applied on the training set only, to avoid data leakage.

### Post-processing

- **Threshold tuning:** The default threshold of 0.5 is adjusted using the precision–recall or ROC curve to increase recall, because missing a diabetic patient is costlier than a false alarm.
- **Result refinement:** Probability calibration (Platt scaling) gives reliable risk scores.
- **Visualisation and interpretation:** Confusion matrix, ROC curve, feature-importance bars and SHAP plots make the output understandable to doctors.

### Evaluation

| Metric | Formula | Meaning |
|---|---|---|
| Accuracy | (TP + TN) / (TP + TN + FP + FN) | Overall correct predictions |
| Precision | TP / (TP + FP) | Correctness of positive predictions |
| Recall (Sensitivity) | TP / (TP + FN) | Share of real patients detected |
| F1-score | 2 × Precision × Recall / (Precision + Recall) | Balance of precision and recall |
| ROC-AUC | Area under TPR vs FPR curve | Ability to separate classes |

**Validation:** Stratified 10-fold cross-validation is used on the training data for model selection and hyper-parameter tuning (grid search), and a separate hold-out test set (about 20%) gives the final unbiased result. Reporting the mean and standard deviation across folds shows robustness and generalisability.

## Question 3: Performance Analysis and Merit of the System

Performance is demonstrated by (i) quantitative metrics on the test set, (ii) comparison with baseline and existing methods under identical conditions, and (iii) visual evidence. The table shows the format of the comparison; fill it with your own measured values (xx.x).

| Model | Accuracy | Precision | Recall | F1-score | ROC-AU C |
|---|---|---|---|---|---|
| Logistic Regression (baseline) | xx.x | xx.x | xx.x | xx.x | xx.x |
| Decision Tree | xx.x | xx.x | xx.x | xx.x | xx.x |
| SVM | xx.x | xx.x | xx.x | xx.x | xx.x |
| Existing method from literature | xx.x | xx.x | xx.x | xx.x | xx.x |
| Proposed system (tuned ensemble) | xx.x | xx.x | xx.x | xx.x | xx.x |

### Supporting visual evidence

- **Confusion matrix:** Shows TP, TN, FP and FN counts; fewer false negatives means improved sensitivity.
- **ROC curve:** Curves closer to the top-left corner and higher AUC show better class separation than the baselines.
- **Performance graphs:** Bar graphs of metrics for all models, and learning curves, show that the model is not overfitting.

### Merit of the system

- **Effectiveness:** Higher accuracy, F1-score and sensitivity with reduced

error rate than baseline models.

- **Efficiency:** Low training and prediction time; the pipeline runs on an ordinary computer.
- **Reliability:** Stable results across cross-validation folds (low standard deviation).

- **Scalability:** The pipeline can handle larger datasets and can be deployed as a web service or mobile app.

Overall, the results show that the proposed system outperforms traditional and baseline approaches, which justifies its use as a practical decision-support tool.

## Question 4: Future Scope and Publication Potential

### Future scope

- **Larger datasets:** Train and validate on larger, multi-hospital datasets to improve generalisation.
- **Real-time data processing:** Connect with wearable devices and electronic health records for continuous monitoring.
- **Advanced techniques:** Apply deep learning, stacking and hybrid models with optimisation techniques.
- **Interpretability:** Use SHAP / LIME so that doctors can trust the predictions.
- **Deployment and privacy:** Deploy as a web or mobile application with a secure API, and address privacy using federated learning.

### Conversion into a research paper

| Section | Content |
|---|---|
| Title and Abstract | Problem, method, key results and conclusion in 150–250 words, plus keywords. |
| Introduction | Motivation, problem statement, research gap and contributions. |
| Literature Review | Comparison of related work and limitations. |
| Methodology | Dataset, pre-processing, feature selection, models and evaluation set-up. |
| Results and Discussion | Tables, graphs, comparison with existing work, limitations. |
| Conclusion and Future Work | Summary of findings and next steps. |

| | |
|---|---|
| References | Properly cited sources in the journal/conference style (IEEE, APA, etc.). |

Before submission: select a suitable conference or journal, follow its template and page limit, check plagiarism, proofread, and make the code and dataset details available for reproducibility.

## Question 5: Learning Problems and Perspectives

### Types of learning problems

| Type | Description | Tasks | Example |
|---|---|---|---|
| Supervised | Learns from labelled data (input with known output) to predict outputs for new inputs | Classification, regression | Diabetes prediction, spam detection |
| Unsupervised | Finds structure in unlabelled data | Clustering, association, dimensionality reduction | Customer segmentation |
| Reinforcement | An agent interacts with an environment and learns a policy that maximises cumulative reward by trial and error | Control, decision-making | Game playing, robot navigation |

Semi-supervised learning, which combines a few labelled and many unlabelled examples, is also used when labelling is expensive.

### Perspectives: symbolic vs. statistical

| Aspect | Symbolic approach | Statistical approach |
|---|---|---|

| | | |
|---|---|---|
| Basis | Logic, rules and explicit knowledge representation | Probability, optimisation and numeric patterns in data |
| Examples | Decision trees, rule learning, concept learning (Find-S, Candidate Elimination) | Naive Bayes, SVM, regression, neural networks |
| Strengths | Interpretable; can use prior knowledge; works with small data | Handles noise and uncertainty; scales to large data |
| Weaknesses | Brittle with noisy or incomplete data | Often a black box; needs more data |

Modern systems often combine both perspectives (hybrid / neuro-symbolic systems).

## Key issues and their influence on design and performance

- **Data quality:** Noisy, missing, biased or mislabelled data lowers accuracy ("garbage in, garbage out"). Hence data cleaning, balanced sampling and sufficient data are designed into the system.
- **Overfitting and underfitting:** A model that fits the training data too well fails on new data (high variance), while a too simple model underfits (high bias). Remedies are cross-validation, regularisation, pruning, early stopping, dropout and more data. This is the bias–variance trade-off, and the inductive bias of the chosen algorithm affects how well it generalises.
- **Computational complexity:** Training time and memory grow with the

number of examples, features and model size. Systems therefore use dimensionality reduction, efficient algorithms, sampling and hardware acceleration, trading some accuracy for speed.

These factors guide the choice of algorithm, amount of pre-processing, evaluation strategy and hardware, and together determine the reliability and performance of a learning system.