		DATE: LCL
	And the second	DATE: 16/10/24
I-A.B03		
01.	Objective. To create a network	
25.0	To creete a make	C. F. C.
	CONCIONA	and all the second
	contex for each end devices.	to all the latest to a
		100 males 17 m 20 m 1
	Topology:	11
	10.0.0.2 Sezjo	20000
		\$13/0 20.630.2
	The second secon	RoderR2
	model de la companya del companya de la companya del companya de la companya de l	Parket Realine
	the state to the same about	
	The state of the s	all and the last trans
	PCI	PC2
710	10.0.0.1	20.0.0.1
	Del gaterony 10002	Del gateway 20.0.0.2
	the same of the 12	
200	Phonedical	
	Procedure:	and and and a second
205	- Select a generic norter RI	Pender for
	- connect an and denice PCI to	RI through parallel
	connection fact Ethernet 0/0.	
	- Configure Pal with IP address	
		Jan
	10,0.0.2	
	-> Rimilarly select another gener	nic Hoster R2 and connect
	an end dence PCZ fastEther	net 1/0.
	-> configure PCS with 19 addres	
		The USA
	2000.2	
	Note, select mater El igo +	o of and execute the
	following:	ment all all to

PAGE NO :	~
DATE:	

	CINIAL CANA	DATE:
200,11	Router > enable 40 AM	
	Router # configure terminal	
	Ronter (contia) # interlace Jast 6th	ernet olo
- Marinet	Ronter (config-if) # ip coldress 10.	0.0.2 355 0
7 6	The section of	10/130 /0 0 0 0
	-> Anterior fact (thernet 0/0, change	ed state to bo
	server Poster RZ, go to	cul and execute.
		Torologica
	Router# config terminal	
	Router(config) # interface fact (+1) Router(config) # interface fact (+1)	vernet 1/0
De la	Router (config-if) # up address 20 Router (config-if) # no chatdown	D.0.2 255.0.0.b
	- Anterface fact othernet yo, change	d state 1
	The state of the s	
	The connections between the route	is and end device
	I established	
	Connect RI with R2 using serial	cable. To setup
	connection between touters again	i go
	Select router RI and go to CH	
	Roster (config) # interface ser	200
Inli	Router (config if ) It in address	30.0.0) 255.0.0.0
	- select router R2 and go to Ch	and phable
2000	similar commande	Carpina
	- Anterface send 210 changed of	ate to sp.
- Bunaris	3/0	hali 30 cm
	CH Manager of the state	
	Observations Aller all	
1	- After softing up the mentioned to	pology, an
	- 4 n the command promot of PCI	200 1000 NO.001
100	-> 4 n the command prompt of PCI, of  Destination host unreachable.	gre pro
	Packets sent: 4 received to lost: 4	loss: 100 %.

PAGE NO: 07 -) 4t is also observed that the end system PCI was only pinged with the following 1Ps Ping 30.0.0.1 ping 10.0.0.2 - ping 30: sucressful Packets sent 4 received: 4 lost:0 loss = 0.0% - Hence , although the muters were connected socially, the end devices were unable to ping each other