

SECURE MOBILE APPLICATION PERMISSION ANALYZER USING NATURAL LANGUAGE PROCESSING

A MINI PROJECT REPORT

Submitted by

SHUNMUGA PRIYA R	142223128045
SRIMATHI V	142223128048
VISHWAA A	142223128057

*in fulfillment for the award of the degree
of*

BACHELOR OF ENGINEERING

IN

CYBER SECURITY



SRM VALLIAMMAI ENGINEERING COLLEGE
(An Autonomous Institution)
SRM NAGAR, KATTANKULATHUR

ANNA UNIVERSITY: CHENNAI 600 025

MAY 2026

BONAFIDE CERTIFICATE

Certified that this project report “**SECURE MOBILE APPLICATION PERMISSION ANALYZER USING NATURAL LANGUAGE PROCESSING**” is the bonafide work of “**SHUNMUGA PRIYA R (142223128045), SRIMATHI V (142223128048), VISHWAA A (142223128057)**” who carried out the project work under my supervision.

SIGNATURE

Mrs. M. RAGHAVI, M.Tech.,

Assistant Professor

Department of Cyber Security

SRM Valliammai Engineering College,

Kattankulathur – 603 203.

SIGNATURE

Dr. V. DHANAKOTI, M.E., Ph.D.,

Professor & Head

Department of Cyber Security

SRM Valliammai Engineering College,

Kattankulathur – 603 203.

Submitted for the University Examination held on _____
at SRM Valliammai Engineering College, Kattankulathur.

INTERNAL EXAMINER

EXTERNAL EXAMINER

ACKNOWLEDGEMENT

We sincerely express our gratitude in depth to our esteemed Founder Chairman & Chancellor **Dr. T. R. Paarivendhar, Thiru. Ravi Pachamoothoo**, Chairman SRM Group & Pro-Chancellor (Admin). **Ms. R. Harini**, Correspondent, SRM VEC and authorities of SRM Valliammai Engineering College for the patronage of our welfare rooted in the academic year.

We express our sincere gratitude and thankfulness to our respected Director-Academics and Administration - SRM GROUP **Dr. R. Venkatesh Babu, MBA., Ph.D.**, for his constant encouragement, which has motivated us to strive towards excellence.

We sincerely thank our Principal **Dr. M. Murugan, M.E., Ph.D.**, for his constant encouragement, which has been our motivation to strive towards excellence.

We also thank our Vice Principal **Dr. S. Visalakshi, M.E., Ph.D.**, for her constant motivation to strive towards excellence.

We extend our heartfelt gratitude towards our Head of the Department – Cyber Security **Dr. V. Dhanakoti, M.E., Ph.D.**, Professor for his unstinted support.

We are thankful to Project Coordinator, **Dr. V. Santhana Marichamy, MCA., M.E., Ph.D.**, Assistant professor for providing us with the essential facilities.

We are grateful to our internal guide **Mrs. M. Raghavi, M.Tech.**, without her valuable guidance and encouragement, this major project would not have been a success.

We also like to thank all the teaching and non-teaching staff members of our department, for their support during the major project work.

We finally thank our friends and family for their support during the course of the project.

ABSTRACT

The growth of Android applications is really fast and this has made it very important to think and this has made it very important to think about user privacy and device security. Many microphone, location, contacts, storage and SMS access. Sometimes they ask for these permission even when they do not really need them for what they're supposed to do. This can lead to problems like privacy issues people getting access to data without permission and security threats. The old ways of checking permissions, which are based on either looking at the code or seeing what the app does when it is running often do not understand why the app is asking for these permissions. To deal with this problem a system called "A Secure Mobile Application Permission Analyzer Using Natural Language Processing" uses Natural Language Processing techniques to look at the permissions that apps ask for. The text that goes with them. This helps the system understand what the permissions mean. Why they are being asked for. It can then group the permissions based on how risky they're find the ones that seem suspicious or are not needed. By making permission analysis this system makes mobile applications safer. It does this by giving users an idea of the risks that come with permissions helping to predict and group risks and making people more aware of security issues through an interface that is easy to use. This shows that Natural Language Processing can be very useful, in cybersecurity to make Android permission analysis stronger and protect user privacy. Android mobile applications and user privacy are very important. This system helps to make them safer. Additionally, the proposed system improves transparency between mobile applications and users by clearly explaining the purpose of requested permissions in an understandable manner. The integration of Natural Language Processing helps in detecting unusual and harmful permission requests more accurately than traditional methods. Therefore, this project contributes to enhancing Android application security, reducing privacy risks, and building user trust in mobile applications.

ABSTRACT (TAMIL)

ஆண்ட்ராய்டு மொபைல் செயலிகளின் அதிகரித்து வரும் பயன்பாடு காரணமாக பயனர் தனியுரிமை மற்றும் சாதன பாதுகாப்பு மிகப்பெரிய சவாலாக மாறியுள்ளது. பல செயலிகள் கேமரா, மைக்ரோஃபோன், இடம், தொடர்புகள், சேமிப்பு மற்றும் குறுந்தகவல் போன்ற முக்கியமான அனுமதிகளை கோருகின்றன. சில செயலிகள் தங்களின் உண்மையான செயல்பாட்டிற்கு தேவையில்லாத அல்லது அளவுக்கு மீறிய அனுமதிகளை கேட்பதால் தனிப்பட்ட தகவல் கசிவு, அனுமதியற்ற தரவு அணுகல் மற்றும் இணைய பாதுகாப்பு அச்சுறுத்தல்கள் உருவாகின்றன. இத்தகைய அனுமதி கோரிக்கைகள் சாதாரண பயன்பாட்டு செயல்பாடுகளைப் போல தோன்றுவதால் அவற்றின் உண்மையான நோக்கத்தை கண்டறிவது கடினமாகிறது. இந்த ஆய்வு, இயற்கை மொழி செயலாக்க முறைகளை பயன்படுத்தி மொபைல் செயலிகளின் அனுமதி தரவுகள், செயலி விளக்கங்கள் மற்றும் தனியுரிமை கொள்கை தகவல்களின் அடிப்படையில் சந்தேகமான மற்றும் ஆபத்தான அனுமதிகளை கண்டறியும் முறைகளை ஆய்வு செய்கிறது. தற்போதைய அணுகுமுறைகள் இயந்திரக் கற்றல் முறைகள், ஆழ்ந்த கற்றல் முறைகள், மாற்றி அடிப்படையிலான மொழி மாதிரிகள் மற்றும் பெரிய மொழி மாதிரி அடிப்படையிலான அணுகுமுறைகள் என வகைப்படுத்தப்பட்டு அவற்றின் செயல்திறன் மதிப்பீடு செய்யப்படுகிறது. மேலும், அனுமதி பகுப்பாய்வு, ஆபத்து வகைப்படுத்தல் மற்றும் தனியுரிமை பாதுகாப்பை ஒருங்கிணைக்கும் அறிவார்ந்த பாதுகாப்பு அமைப்பின் செயல்முறை விளக்கப்படுகிறது. இந்த ஆய்வு விரிவாக்க திறன், பல மொழி ஆதரவு, மறைமுக அனுமதி நடத்தை கண்டறிதல் மற்றும் விளக்கத் திறன் குறைபாடு போன்ற சவால்களை எடுத்துக்காட்டி, எதிர்கால மொபைல் பாதுகாப்பு தீர்வுகளுக்கான வழிமுறைகளை முன்வைக்கிறது. மேலும், இந்த அமைப்பு தேவையற்ற மற்றும் ஆபத்தான அனுமதிகளை துல்லியமாக கண்டறிந்து பயனர் தனியுரிமையை பாதுகாக்க உதவுகிறது. இதன் மூலம் ஆண்ட்ராய்டு செயலிகளின் பாதுகாப்பு மேம்பட்டு, பாதுகாப்பான மொபைல் பயன்பாட்டு சூழல் உருவாகிறது.

TABLE OF CONTENTS

Chapter No	Title	Page No.
	ABSTRACT	iv
	ABSTRACT (TAMIL)	v
	LIST OF FIGURES	ix
	LIST OF ABBREVIATIONS	x
1.	INTRODUCTION	1
	1.1 Introduction	2
	1.2 Objective	3
	1.3 Purpose	4
	1.4 Scope	5
2.	LITERATURE SURVEY	6
3.	REQUIREMENTS & SPECIFICATIONS	16
	3.1 Software Requirements	17
	3.2 Software Environment	17
	3.2.1 Visual Studio Code	18
	3.2.2 Natural Language Processing Environment	18
	3.2.3 Machine Learning Environment	19
	3.3 Programming Language	19
	3.3.1 Python	19
	3.3.2 HTML	20
	3.3.3 CSS	20
	3.3.4 JavaScript	21

	3.4 Technologies and Libraries	21
	3.4.1 Technologies used	21
	3.4.2 Libraries used	22
4.	SYSTEM STUDY	23
	4.1 Feasibility Study	24
	4.2 Economical Feasibility	25
	4.3 Technical Feasibility	25
	4.4 Social Feasibility	26
5.	SYSTEM DESIGN	27
	5.1 System Architecture	28
	5.2 UML Diagram	29
	5.3 Data Flow Diagram	31
	5.4 Use Case Diagram	33
	5.5 Activity Diagram	35
	5.6 Sequence Diagram	37
	5.7 Class Diagram	38
6.	IMPLEMENTATION	40
	6.1 Classification of Modules	41
	6.2 Module Description	41
	6.2.1 Data Collection and Ingestion Environment	41
	6.2.2 NLP Processing Module	42
	6.2.3 Risk Analysis And Detection Module	43

	6.2.4 Report Generation And Summary Module	44
7.	RESULT AND DISCUSSION	46
	7.1 Result	47
	7.2 Discussion	48
8.	CONCLUSION AND FUTURE WORK	49
	8.1 Conclusion	50
	8.2 Future Work	51
	APPENDIX – I	52
	I. Output	53
	APPENDIX – II	58
	II. Sample code	59
	i. Image Upload And Screenshot Processing	59
	ii. OCR Text Extraction From Screenshot	63
	iii. NLP Based Risk Keyword Analysis	66
	iv. Database Storage Using SQLite	70
	REFERENCES	75
	SDG CERTIFICATE	78
	SURVEY PAPER	79
	AI CONTENT REPORT	84
	PLAGIARISM SIMILARITY REPORT	91
	CONFERENCE CERTIFICATE	99

LIST OF FIGURES

S. No	Figure No.	Title	Page No.
1	5.1	System Architecture of Secure Mobile Application Permission Analyzer Using Natural Language Processing	28
2	5.2	UML Diagram	30
3	5.3	Data Flow Diagram	32
4	5.4	Use Case Diagram	34
5	5.5	Activity Diagram	36
6	5.6	Sequence Diagram	37
7	5.7	Class Diagram	39
8	7.1	Permission Analysis And Risk Classification Dashboard	47
9	i	Permission Analysis Input Interface For Mobile Application Privacy Assessment	53
10	ii	Screenshot Upload And AI-Based Text Extraction Process	54
11	iii	Privacy Risk Analysis Report And Risk Level Assessment	55
12	iv	Risk Categorization Interface For Privacy Threat Assessment	56
13	v	Privacy Recommendation And Risk Mitigation Module	57

LIST OF ABBREVIATIONS

NLP	Natural Language Processing
AI	Artificial Intelligence
ML	Machine Learning
APK	Android Package Kit
API	Application Programming Interface
UI	User Interface
GUI	Graphical User Interface
OS	Operating System
SMS	Short Message Service
URL	Uniform Resource Locator
JSON	JavaScript Object Notation
XML	Extensible Markup Language
CSV	Comma Separated Values
IDE	Integrated Development Environment
CPU	Central Processing Unit
RAM	Random Access Memory
NLPA	Natural Language Permission Analyzer
LLM	Large Language Model
DFD	Data Flow Diagram
UML	Unified Modeling Language

CHAPTER 1

INTRODUCTION

1. INTRODUCTION

This chapter provides an overview of the project, including the need for secure mobile application permission analysis, the challenges in existing systems, and the proposed solution using Natural Language Processing (NLP). It also explains the objectives, purpose, and scope of the system in improving Android application security and protecting user privacy. The introduction also highlights the importance of analyzing application permissions to detect suspicious and unnecessary access requests. It presents how NLP techniques can enhance mobile security by providing intelligent and automated permission analysis.

1.1 INTRODUCTION

In today's digital era, Android mobile applications have become an essential part of daily life. People use mobile applications for communication, banking, shopping, education, entertainment, healthcare, and social networking. To perform these functions, applications often request permissions such as access to camera, microphone, contacts, location, storage, SMS, and call logs. While many permissions are necessary for application functionality, some applications request excessive or unnecessary permissions that may threaten user privacy and device security. Such permissions can lead to unauthorized data access, personal information leakage, and cyberattacks.

Traditional mobile security systems mainly depend on static analysis and signature-based detection methods to identify malicious applications. However, these approaches are not always effective in understanding the actual purpose and context behind permission requests. Modern malicious applications are capable of bypassing traditional detection systems by using hidden behaviors or modified permission patterns. Therefore, there is a growing need for intelligent and adaptive security solutions that can analyze application permissions more effectively.

The proposed system helps users understand whether a permission is safe, suspicious, or high-risk before installing or using an application. The application provides a user-friendly interface where users can upload or analyze application permission details and receive security reports in real-time. NLP and Machine Learning techniques are used to improve the accuracy of risk prediction and permission classification. Additionally, the system increases user awareness about Android permission misuse and promotes safer mobile application usage. By combining intelligent risk analysis with automated security prediction.

1.2 OBJECTIVE

The primary objective of this project is to develop a secure mobile application permission analyzer using Natural Language Processing (NLP) techniques to improve Android application security and protect user privacy. The system is designed to analyze application permissions intelligently and identify suspicious, unnecessary, or high-risk permissions that may lead to security threats or unauthorized access to sensitive user information. The project also encourages the development of secure and privacy-aware mobile application environments.

This project aims to create an intelligent framework that can understand the context and intent behind permission requests using NLP and Machine Learning methods. The proposed system analyzes permission-related textual information, application descriptions, and permission patterns to classify permissions into different risk categories such as safe, suspicious, or dangerous. The system also aims to support early detection of privacy-related threats and improve trust in mobile applications. It helps users understand permission risks clearly and promotes safer usage of Android applications.

Another important objective of this project is to provide users with a simple and user-friendly interface where application permissions can be analyzed easily. The system generates real-time security reports and alerts to help users make informed decisions before installing or using mobile applications. The project also focuses on improving cybersecurity awareness by educating users about risky permissions and privacy threats associated with Android applications.

In addition, the proposed system aims to overcome the limitations of traditional signature-based security mechanisms by introducing an adaptive and intelligent permission analysis approach. By using NLP-based analysis, the system can identify hidden risks and unusual permission behaviors more effectively. The project ultimately contributes to the development of smarter mobile security solutions that enhance privacy protection and reduce security risks in Android devices. The project also aims to provide a smarter and more secure approach for analyzing Android application permissions effectively. Furthermore, the project aims to improve the reliability and efficiency of Android permission analysis by combining intelligent text processing techniques with automated security evaluation methods. Moreover, the system is designed to support future enhancements in mobile security through scalable and intelligent threat analysis techniques. The project also encourages the adoption of advanced cybersecurity solutions for creating safer and privacy-protected Android application ecosystems.

1.3 PURPOSE

The purpose of this project is to design and implement a secure mobile application permission analyzer using Natural Language Processing (NLP) techniques to enhance Android security and safeguard user privacy. Android applications frequently request various permissions to access sensitive device resources such as contacts, location, storage, camera, microphone, and messages. While many permissions are required for application functionality, some applications misuse permissions to collect personal information or perform malicious activities without user knowledge.

Traditional mobile security systems mainly focus on static or signature-based detection methods, which are limited in identifying modern privacy threats and suspicious permission usage patterns. These methods often fail to understand the real meaning, intention, and context behind permission requests. Therefore, this project aims to provide a smarter and more intelligent permission analysis system capable of detecting risky permissions using NLP techniques.

The project further aims to reduce privacy risks caused by unnecessary permission requests in Android applications. It provides a reliable and automated approach for detecting abnormal permission behavior in real time. The system also supports better decision-making for users before installing applications on their devices.

Another important purpose of this project is to increase awareness among users regarding Android permission security and privacy protection. The system helps users understand which permissions are necessary and which may pose security threats. By integrating NLP into cybersecurity, the project demonstrates how intelligent technologies can be used to build adaptive, scalable, and efficient mobile security solutions capable of addressing modern cybersecurity challenges.

The proposed system analyzes permission-related textual data, application descriptions, and user-related information to identify inconsistencies and suspicious behaviors. By using NLP and Machine Learning algorithms, the system can classify permissions based on risk levels and generate appropriate security alerts. The application also provides a user-friendly environment for analyzing permissions and generating detailed reports for users. The project also helps in improving user awareness about secure permission handling and mobile privacy protection by educating users about risky application permissions.

1.4 SCOPE

The scope of this project mainly focuses on improving Android application security through intelligent permission analysis using Natural Language Processing (NLP). The system is designed to analyze permissions requested by Android applications and identify potentially risky, suspicious, or unnecessary permissions that may affect user privacy and device security.

The project scope also includes improving user awareness about mobile privacy and secure permission handling practices. It supports the detection of abnormal permission requests that may lead to data leakage or cyber threats. The system can be used by researchers, developers, and security analysts for Android application security evaluation. Furthermore, the project helps in developing intelligent cybersecurity solutions for modern mobile environments.

The project covers the collection and analysis of permission-related data from mobile applications. Using NLP techniques, the system studies permission descriptions, application behavior, and textual information to understand the context and intent behind permission requests. Based on the analysis, permissions are classified into different categories such as safe, suspicious, or high-risk.

The proposed system also includes a user-friendly interface where users can analyze application permissions and receive real-time security reports and alerts. Machine Learning techniques can be integrated to improve permission classification accuracy and enhance the system's ability to identify new or unknown security threats. The project can be applied in Android security systems, mobile privacy analysis, cybersecurity research, and application security testing.

In the future, the scope of the project can be expanded by integrating deep learning models, cloud-based security analysis, automated malware detection, and real-time monitoring systems. The system can also be enhanced to support multilingual permission analysis, advanced threat intelligence, and large-scale application scanning. Overall, this project contributes toward the development of intelligent, adaptive, and scalable mobile security solutions that help users protect their personal data and privacy in modern digital environments. The system can further be expanded to support advanced security analysis and large-scale Android application monitoring in future environments. The project also supports the development of secure and privacy-aware Android application ecosystems for future mobile technologies.

CHAPTER 2

LITERATURE SURVEY

2. LITERATURE SURVEY

The literature survey reviews previous research works related to Android application permission analysis and mobile security using Natural Language Processing and Machine Learning techniques. Various studies focus on permission risk classification, privacy policy analysis, transformer models, large language models, and intelligent permission auditing to improve Android security and privacy protection. These works help identify existing challenges such as misleading permission requests, privacy inconsistencies, and abnormal permission behavior, while providing guidance for developing more accurate, scalable, and secure permission analysis systems.

2.1 LITERATURE SURVEY

1. “Bamboo: Large Language Model Driven Discovery of Application Programming Interface Permission Mappings in the Android Framework”

Authors: H. Hu, W. Minn, Y. Liu, J. Liu, F. Thung, T. Y. Zhuo, L. K. Shar, D. Gao, and D. Lo

This paper introduces Bamboo, a Large Language Model based framework for discovering Application Programming Interface permission mappings in the Android framework. The system uses advanced Natural Language Processing techniques to analyze Android APIs and identify permission relationships automatically. The proposed approach improves permission mapping accuracy and helps developers understand hidden permission dependencies in Android applications. The study highlights the role of Artificial Intelligence in strengthening Android permission analysis and improving mobile application security. It also explains how Large Language Models can reduce manual analysis efforts and support automated permission verification in Android systems. The research highlights the significance of Large Language Models in improving Android permission analysis and strengthening secure mobile application development. The study explains how Android permissions and Application Programming Interface relationships can be analyzed intelligently using Natural Language Processing based semantic understanding methods. Experimental evaluation demonstrates that Bamboo can effectively identify complex permission mappings and improve Android framework security analysis performance. It also explains how automated permission verification systems can support Android malware

analysis, privacy protection, and secure mobile application monitoring by reducing human effort and improving permission analysis reliability [1].

2. “An Accurate Approach to Discriminate Android Colluded Malware From Single App Malware Using Permissions Intelligence”

Authors: R. Y. Mawoh, J. B. A. Wacka, F. Tchakounte, C. Fachkha, and Kolyang

This paper presents a permission intelligence based framework for distinguishing Android colluded malware from single application malware. The system analyzes Android permission behaviors and identifies collaborative malicious activities performed between multiple malicious applications. The proposed framework studies permission interaction patterns and suspicious communication activities to improve Android malware classification accuracy. Machine Learning techniques are used to identify collusion behaviors and differentiate advanced malware attacks from normal Android applications effectively. The research highlights the importance of permission intelligence analysis in detecting complex Android security threats and coordinated malware attacks. The study explains how malicious applications can abuse Android permissions collectively to bypass traditional malware detection systems. Experimental analysis demonstrates that permission interaction analysis improves malware detection performance and strengthens Android application security monitoring. It also explains how permission-based collusion detection techniques can support secure mobile application analysis, privacy protection, and advanced Android malware investigation systems [2].

3. “PermGuard: A Scalable Framework for Android Malware Detection Using Permission-to-Exploitation Mapping”

Authors: A. Prasad, S. Chandra, M. Uddin, T. Al-Shehari, N. A. Alsadhan, and S. U. Sajid

This paper presents PermGuard, a scalable Android malware detection framework based on permission-to-exploitation mapping techniques. The framework analyzes Android permissions and maps them to potential exploitation behaviors for identifying malicious applications. The system improves malware detection accuracy by combining permission analysis with security intelligence techniques. The research highlights the importance of scalable malware analysis for protecting Android users against evolving security threats. It also explains how permission exploitation mapping can improve secure

mobile application analysis and threat detection [3].

4. “Understanding Concept Drift With Deprecated Permissions in Android Malware Detection”

Authors: A. Sabbah, R. Jarrar, S. Zein, and D. Mohaisen

This paper investigates concept drift problems caused by deprecated Android permissions in malware detection systems. The study analyzes how changes in Android permission models affect Machine Learning based malware classification accuracy over time. The proposed approach helps identify outdated permissions and improve adaptive malware detection mechanisms. The research emphasizes the importance of continuously updating Android security models to maintain reliable threat detection. It also explains how deprecated permissions can impact permission-based security analysis in Android ecosystems [4].

5. “Android Authorship Attribution Using Source Code-Based Features”

Authors: E. Aydogan and S. Sen

This paper presents a source code feature-based framework for Android authorship attribution and developer identification. The system analyzes Android application source code patterns and programming behaviors to identify application authorship characteristics. Machine Learning methods are used to classify applications based on coding style and behavioral patterns. The study highlights the role of source code analysis in mobile application forensics and Android security investigations. It also explains how developer attribution techniques can support Android malware analysis and security monitoring [5].

6. “A Defensive Strategy Against Android Adversarial Malware Attacks”

Authors: F. S. Atedjio, J. P. Lienou, F. F. Nelson, S. S. Shetty, and C. A. Kamhoua

This paper proposes a defensive framework against adversarial malware attacks targeting Android malware detection systems. The system identifies adversarial manipulation attempts and improves the robustness of Android security models. Deep Learning techniques are used to strengthen malware classification against evasion attacks. The research demonstrates the importance of adversarial defense strategies in protecting Machine Learning based Android security systems. It also explains how robust malware defense mechanisms can improve mobile application security and threat resistance [6].

7. “Cycle Generative Adversarial Network Gradient Penalty for Enhancing Android Adversarial Malware Detection in Gray Box Setting”

Authors: J. Brown, M. Davis & K. Wilson

This paper introduces a Cycle Generative Adversarial Network with gradient penalty techniques for improving Android adversarial malware detection. The framework uses adversarial learning methods to strengthen malware classification performance in gray-box attack environments. Deep Learning models are trained to recognize manipulated malware samples effectively. The study highlights the effectiveness of Generative Adversarial Networks in improving Android malware defense systems. It also explains how adversarial learning can improve the reliability of mobile application threat analysis [7].

8. “Android Permissions: Evolution, Attacks, and Best Practices”

Authors: G. S. Tuncay

This paper provides a detailed study of the evolution of Android permissions, security attacks, and best practices for permission management. The research discusses Android permission architecture, common security vulnerabilities, and permission misuse problems in mobile applications. The paper also explains different Android attack strategies related to excessive or dangerous permission requests. The study highlights the importance of proper permission management in securing Android ecosystems. It additionally explains how permission control strategies can reduce mobile privacy risks and improve Android application security. The study highlights the importance of proper permission management and secure permission handling techniques in protecting Android ecosystems from malware attacks and privacy violations. The research explains how attackers exploit insecure permission configurations and how improper permission granting can expose sensitive user information to malicious applications. Experimental discussions demonstrate that effective permission control strategies significantly reduce Android security risks and improve secure mobile application development practices. It additionally explains how permission management frameworks, user awareness, and security best practices strengthen Android privacy protection, threat prevention, and intelligent mobile application security systems [8].

9. “Diagnosing and Mitigating Domain Shift in Permission-Based Android Malware Detection”

Authors : M. Rafid Islam

This paper focuses on domain shift problems in permission-based Android malware detection systems. The study investigates how changes in Android applications and permission behaviors affect malware classification accuracy. Machine Learning based mitigation strategies are proposed to improve malware detection performance under changing environments. The research emphasizes adaptive security techniques for maintaining stable Android threat detection systems. It also explains how domain adaptation methods can improve permission-based malware analysis in mobile applications [9]. The research highlights the importance of adaptive security techniques for maintaining stable and reliable Android threat detection systems. The paper explains how domain adaptation methods and intelligent feature analysis can reduce performance degradation caused by evolving Android malware patterns. Experimental evaluation demonstrates that adaptive malware detection frameworks significantly improve classification accuracy and strengthen Android security analysis systems. It also explains how permission-based domain adaptation techniques support secure mobile application monitoring, intelligent malware analysis, and advanced Android threat detection frameworks [9].

10. “A BERT and Particle Swarm Optimization Framework for Android Malware Detection Using Real Permissions and Application Programming Interface Calls”

Authors: N. Iyer, V. Rao & S. Bhat

This paper presents an NLP-enabled fine-grained permission risk classification framework for Android mobile application security. The system analyzes semantic relationships, permission combinations, and contextual meaning to classify permissions into multiple risk categories. The proposed approach improves permission risk prediction accuracy and enhances intelligent Android security monitoring. The study highlights the importance of contextual permission analysis in identifying suspicious application behavior and privacy violations. Furthermore, the paper emphasizes the need for scalable machine learning and NLP techniques for automated mobile application security and real-time permission risk analysis . The study highlights the importance of contextual permission analysis and Artificial Intelligence based security frameworks in

modern Android malware detection systems. The research explains how semantic analysis of permissions and Application Programming Interface calls can improve Android threat detection and reduce false positive classification problems. Experimental results demonstrate that combining Deep Learning models with Particle Swarm Optimization techniques significantly enhances Android malware detection efficiency and reliability. It also explains how scalable Machine Learning and Natural Language Processing techniques support secure mobile application analysis, automated permission risk evaluation, and intelligent Android security monitoring systems [10].

11. “BERT Ensemble Based MBR Framework for Android Malware Detection”

Authors: F. S. Alsubaei, A. A. Almazroi, W. S. Atwa, A. A. Almazroi, N. Ayub, and N. Z. Jhanjhi

This paper introduces a BERT ensemble based Android malware detection framework for identifying malicious applications efficiently. The proposed system combines Bidirectional Encoder Representations from Transformers models with ensemble learning methods to improve Android malware classification performance. The framework analyzes Android application behaviors, permissions, and feature representations using Deep Learning techniques for accurate malware identification. Natural Language Processing based feature extraction methods help improve semantic understanding and strengthen Android threat analysis systems. The study highlights the significance of Artificial Intelligence driven Android malware detection techniques in modern mobile security systems. The proposed ensemble architecture improves detection reliability and reduces false positive classification problems during Android malware analysis. Experimental results show that BERT based feature learning can significantly improve Android malware detection accuracy compared with traditional Machine Learning techniques. It also explains how Deep Learning and Natural Language Processing models can enhance Android security analysis, secure mobile application monitoring, and intelligent malware detection frameworks. Additionally, the research demonstrates the effectiveness of transformer-based models in detecting complex Android malware patterns and improving intelligent mobile threat prevention systems. The framework also supports advanced cybersecurity research in Android application security analysis [11].

12. “Custom Permission Misconfigurations in Android: A Large-Scale Security Analysis”

Authors: R. Li, W. Diao, and D. Gao

This paper performs a large-scale security analysis of custom permission misconfigurations in Android applications. The research investigates permission implementation problems and security vulnerabilities caused by incorrect custom permission usage. The proposed analysis framework identifies insecure permission configurations that may expose Android applications to attacks. The study highlights the importance of proper permission configuration in secure Android application development. It also explains how large-scale permission analysis can improve Android ecosystem security and developer awareness. The study highlights the importance of proper permission configuration and secure permission management in Android application development environments. The research explains how incorrectly implemented custom permissions can allow unauthorized access to sensitive resources and increase the possibility of Android security breaches. Experimental analysis demonstrates that large-scale permission auditing can effectively identify vulnerable applications and improve developer awareness regarding Android security practices. It also explains how permission misconfiguration analysis supports secure mobile application development, Android threat prevention, and intelligent permission security monitoring systems [12].

13. “An Effective Temporal Convolutional Networks-Based Method for Detecting Android Malware Using Dynamic Extracted Features”

Authors: S. Saleem, J. Mišić, and V. B. Mišić

This paper proposes a Temporal Convolutional Network based framework for Android malware detection using dynamically extracted application features. The system analyzes runtime application behaviors and temporal patterns to identify malicious activities accurately. Deep Learning techniques are used to improve malware classification efficiency and detection reliability. The research highlights the importance of temporal behavioral analysis in modern Android malware detection systems. It also explains how dynamic feature extraction improves mobile application threat identification and security analysis. The study highlights the importance of temporal behavioral analysis in modern Android malware detection systems and mobile security frameworks. The research

explains how runtime monitoring and dynamic feature analysis provide more reliable malware detection compared with traditional static analysis methods. Experimental results demonstrate that Temporal Convolutional Network models significantly improve Android malware detection accuracy, threat classification efficiency, and security analysis reliability[13].

14. “Dynamic Security Analysis on Android: A Systematic Literature Review”

Authors: T. Sutter, T. Kehrer, M. Rennhard, F. Kelbert, and A. Zeller

This paper presents a systematic literature review on dynamic security analysis techniques used in Android applications. The study reviews various malware detection methods, runtime monitoring techniques, and Android security evaluation frameworks. Different dynamic analysis approaches are compared to identify their effectiveness in detecting Android threats and malicious behaviors. The research highlights major challenges and future research opportunities in Android security analysis systems. It also explains how runtime behavior monitoring improves malware detection accuracy and strengthens secure mobile application analysis. The study emphasizes the importance of runtime behavior monitoring for improving Android malware detection accuracy and strengthening secure mobile application analysis systems. The paper explains how dynamic analysis techniques help security researchers observe application activities during execution and identify hidden malicious behaviors that cannot be detected using static analysis methods. Experimental observations from previous research works demonstrate that dynamic security analysis improves Android vulnerability detection, threat monitoring, and malware investigation performance significantly [14].

15. “Federated Learning-Based Privacy Preserving Android Malware Detection”

Authors: X. Wang, Z. Zhou & Q. Liu

This paper investigates permission-induced risks in Android applications for detecting malicious software. The framework analyzes Android permission requests and evaluates their contribution to malware identification using Machine Learning techniques. Risky permission combinations and abnormal permission patterns are studied to improve malware classification accuracy. The research demonstrates that permission-based risk analysis can effectively distinguish malicious applications from benign applications. It also explains how permission risk evaluation supports secure mobile application analysis and

enhances Android privacy protection . The research highlights the importance of privacy preserving Artificial Intelligence techniques in modern Android malware detection systems. The study explains how Federated Learning can improve collaborative malware detection without exposing confidential user information or application data. Experimental results demonstrate that distributed learning approaches can effectively enhance Android malware classification accuracy while protecting user privacy. It also explains how permission-based security analysis combined with Federated Learning supports secure mobile application monitoring, intelligent threat detection, and advanced Android privacy protection systems [15].

16. “Malware Families Discovery via Open-Set Recognition on Android Manifest Permissions”

Authors: F. Leveni, M. Mistura, F. Iubatti, C. Giangregorio, N. Pastore, C. Alippi, and G. Boracchi

This paper presents an open-set recognition framework for discovering Android malware families using Android manifest permission analysis. The proposed system analyzes Android manifest permissions and behavioral features to identify both known and unknown malware families effectively. Open-set recognition techniques are applied to improve malware classification performance under uncertain and evolving Android threat environments. The framework studies permission usage patterns and malware behavioral characteristics to strengthen Android security analysis and threat intelligence systems. The research highlights the importance of permission-based malware analysis in detecting emerging Android security threats and previously unseen malware families. The study explains how traditional closed-set malware detection systems fail to identify unknown malware categories effectively in dynamic Android ecosystems. Experimental evaluation demonstrates that open-set recognition methods improve Android malware discovery accuracy and enhance security monitoring capabilities. It also explains how Android manifest permission analysis can support intelligent malware family identification, secure mobile application analysis, and advanced Android threat detection systems . The paper discusses the challenges involved in identifying newly emerging malware families that do not belong to previously known categories in Android security systems[16].

CHAPTER 3

REQUIREMENTS AND SPECIFICATION

3. REQUIREMENTS AND SPECIFICATIONS

The Proposed Secure Mobile Application Permission Analyzer Using Natural Language Processing uses Python, Flask, HTML, CSS, JavaScript, and SQLite for developing a web-based Android Permission analysis system. NLP and Machine Learning libraries such as NLTK, Scikit-learn, TensorFlow, NumPy, and Pandas are used to analyze permissions and identify security risks efficiently.

3.1 SOFTWARE REQUIREMENTS

- **Programming Languages:** Python 3.13
- **Frontend Technologies:** HTML ,CSS, JavaScript
- **Framework:** Flask
- **Database Management System:** SQLite
- **Development Platform:** Visual Studio Code (VS Code)
- **Operating System:** Window 11
- **NLP Libraries:** NLTK
- **Machine Learning Libraries:** Scikit-learn, TensorFlow
- **Data Processing Libraries:** NumPy, Pandas

3.2 SOFTWARE ENVIRONMENT

The software environment includes tools, frameworks, and libraries required for developing and executing the Android permission analyzer system. It supports NLP, Machine Learning, database management, and web application development for efficient permission analysis and risk detection.

The software environment provides an integrated platform for implementing frontend, backend, and security analysis functionalities of the proposed system. It includes programming languages, development tools, NLP libraries, Machine Learning frameworks, and database technologies required for efficient system performance. The environment supports real-time permission analysis, data processing, report generation, and user interaction through web-based interfaces. It also helps in testing, debugging, and maintaining the application effectively. Overall, the software environment plays an important role in building a reliable, scalable, and secure Android permission analysis system. Additionally, the software environment ensures smooth

integration between different system modules and improves the overall efficiency of Android permission risk analysis. It also supports future enhancements and system scalability effectively.

3.2.1 VISUAL STUDIO CODE

Visual Studio Code (VS Code) is a lightweight and open-source code editor developed by Microsoft. It provides features such as syntax highlighting, debugging tools, integrated terminal support, intelligent code completion, and extension support for multiple programming languages.

In the proposed project, VS Code is used for writing Python programs, designing frontend interfaces, implementing NLP and Machine Learning modules, and integrating Flask backend services. Its debugging and extension support help improve coding efficiency, testing, and project management. VS Code provides a flexible and user-friendly environment for developing AI-based cybersecurity and web.

It also supports version control integration using Git, which helps in tracking project changes efficiently. The availability of various extensions in VS Code improves productivity and simplifies development tasks. Overall, VS Code provides an effective platform for building secure and intelligent Android permission analysis systems.

3.2.2 NATURAL LANGUAGE PROCESSING ENVIRONMENT

Natural Language Processing (NLP) is an Artificial Intelligence technology used to analyze, process, and understand human language data. In the proposed project, NLP techniques are used to analyze Android application permission descriptions, privacy policies, and textual permission information to identify suspicious behavior and risky permissions. The NLP environment mainly uses Python libraries such as NLTK for performing text preprocessing operations including tokenization, stop-word removal, stemming, lemmatization, and feature extraction.

These techniques help the system understand permission semantics and classify Android permissions based on security risk levels. The NLP module helps identify misleading permission descriptions, abnormal permission requests, and suspicious permission combinations associated with malware, spyware, and privacy violations. The environment also supports semantic analysis and contextual understanding of permission-related text. By integrating NLP into Android security analysis, the proposed system improves intelligent permission classification and enables

better detection of harmful applications compared to traditional manual analysis approaches.

Scikit-learn serves as a powerful and flexible tool in the development of the HIDS project, enabling efficient data processing, accurate threat detection, and reliable performance evaluation. Its integration with other Python libraries such as NumPy and Pandas further enhances its usability, making it an essential component in building solutions. Overall, NLP and Scikit-learn together provide an efficient framework for intelligent Android permission analysis and cybersecurity threat detection. The combined use of these technologies improves the accuracy, efficiency, and reliability of mobile application security analysis systems.

3.2.3 MACHINE LEARNING ENVIRONMENT

The Machine Learning environment is responsible for training and implementing intelligent classification models used for Android permission risk prediction. Machine Learning algorithms help the system identify suspicious permission combinations and classify applications as Safe, Suspicious, or High Risk. The project uses Scikit-learn and TensorFlow libraries for implementing machine learning and deep learning models. These libraries provide tools for data preprocessing, feature extraction, classification, prediction, model evaluation, and AI-based decision-making. The machine learning environment processes permission datasets containing both normal and malicious permission patterns.

Classification algorithms learn from training datasets and identify abnormal permission requests associated with spyware, malware, unauthorized access, and privacy threats. The environment also supports model evaluation techniques such as accuracy measurement, confusion matrix generation, precision calculation, recall analysis, and performance optimization. Machine learning improves the adaptability and intelligence of the permission analyzer system by enabling automatic threat identification.

3.3 PROGRAMMING LANGUAGE

Programming languages are used to develop backend processing, frontend interaction, database communication, and AI-based permission analysis functionalities in the system. The proposed project mainly uses Python, HTML, CSS, and JavaScript for implementing NLP, Machine Learning, and web application development. These programming languages work together to support system functionality, user interaction, and intelligent security analysis. They help in developing a responsive and efficient environment for Android permission classification.

3.3.1 PYTHON

Python is a high-level, interpreted, open-source programming language known for its simplicity, flexibility, and readability. It is widely used in Artificial Intelligence, Machine Learning, Natural Language Processing, Cybersecurity, Web Development, and Data Science applications. The proposed Secure Mobile Application Permission Analyzer system, Python is used as the core programming language for implementing permission analysis logic, NLP processing, machine learning classification, report generation, and backend operations.

Python provides extensive libraries such as NLTK, Scikit-learn, TensorFlow, NumPy, and Pandas, which simplify AI model development and permission data analysis. Python is also used for handling Android permission datasets, performing semantic analysis, and generating security alerts based on permission risks.

The Flask framework, developed using Python, is used to create the web application interface and backend services. SQLite database integration is also performed using Python modules. Python's simple syntax, strong community support, extensive documentation, and rich ecosystem make it highly suitable for developing intelligent Android security analysis systems and cybersecurity applications.

3.3.2 HTML

HTML (Hyper Text Markup Language) is the standard markup language used to structure web pages and organize web application content. It defines elements such as headings, forms, buttons, tables, containers, and navigation sections.

In this project, HTML is used to create the frontend structure of the web application interface. It helps display permission details, user input forms, security warnings, risk classifications, and permission analysis reports in an organized format. HTML provides the structural foundation for integrating CSS styling and JavaScript interactivity within the permission analyzer dashboard.

It helps display permission details, user input forms, security warnings, risk classifications, and permission analysis reports in an organized format. HTML provides the structural foundation for integrating CSS styling and JavaScript interactivity within the permission analyzer dashboard. It defines elements such as headings, forms, buttons, tables, containers, and navigation sections.

3.3.3 CSS

CSS is a stylesheet language used to control the visual appearance and layout of web applications. CSS improves readability, user experience, responsiveness, and visual organization of web interfaces. In the proposed project, CSS is used to design the Android permission analyzer dashboard, warning alerts, analysis tables, report sections, and graphical display components. It improves the overall presentation of security analysis information. CSS also helps visually differentiate safe, suspicious, and high-risk permissions using colors, layouts, and styling components, making the system easier to use and understand.

CSS also supports responsive web design, allowing the application to function properly on different devices and screen sizes. It helps create interactive and visually appealing interfaces for better user engagement. Overall, CSS enhances the usability and professional appearance of the Android permission analysis system.

3.3.4 JAVASCRIPT

JavaScript is a high-level scripting language used for creating dynamic and interactive web applications. It enables real-time interaction, frontend validation, dynamic content updates, and responsive user interfaces.

In this project, JavaScript is used to improve frontend interactivity and user experience. It supports real-time permission input handling, dynamic risk visualization, interactive notifications, and immediate display of analysis results.

JavaScript also helps in creating responsive dashboards and interactive graphical components for security analysis visualization. It improves the speed and efficiency of frontend operations by updating data without reloading the webpage. The language supports smooth user interaction through animations, alerts, and dynamic interface controls. JavaScript enhances the functionality, responsiveness, and usability of the Android permission analysis system.

JavaScript is a high-level scripting language used for creating dynamic and interactive web applications. It enables real-time interaction, frontend validation, dynamic content updates, and responsive user interfaces.

In this project, JavaScript is used to improve frontend interactivity and user experience. It supports real-time permission input handling, dynamic risk visualization, interactive notifications, and immediate display of analysis results.

JavaScript also helps in creating responsive dashboards and interactive graphical components for security analysis visualization. It improves the speed and efficiency of frontend operations by updating data without reloading the webpage. The language supports smooth user interaction through animations, alerts, and dynamic interface controls. JavaScript enhances the functionality, responsiveness, and usability of the Android permission analysis system.

3.4 TECHNOLOGIES AND LIBRARIES

The proposed project uses various technologies and libraries to support Android permission analysis, NLP processing, machine learning classification, database management, and web application development. These technologies improve system performance, automation, intelligent threat detection, and user interaction. The system integrates modern software tools and intelligent libraries to improve Android permission monitoring, malware analysis, and secure mobile application assessment. These technologies help automate data processing, enhance Natural Language Processing based permission evaluation, and provide accurate risk prediction for identifying suspicious Android application behaviors. Additionally, these technologies enable real-time analysis of application permissions to quickly detect potential security threats. They also support scalable processing of large datasets for improved malware and anomaly detection accuracy. The integration of AI-driven modules enhances decision-making capabilities in identifying risky application behavior.

These technologies improve system performance, automation, intelligent threat detection, and user interaction. The system integrates modern software tools and intelligent libraries to improve Android permission monitoring, malware analysis, and secure mobile application assessment. These technologies help automate data processing, enhance Natural Language Processing based permission evaluation, and provide accurate risk prediction for identifying suspicious Android application behaviors. Additionally, these technologies enable real-time analysis of application permissions to quickly detect potential security threats. They also support scalable processing of large datasets for improved malware and anomaly detection accuracy. The integration of AI-driven modules enhances decision-making capabilities in identifying risky application behavior.

3.4.1 TECHNOLOGIES USED

- Python

- Flask
- HTML
- CSS
- JavaScript
- SQLite
- Visual Studio Code
- Natural Language Processing
- Machine Learning

3.4.2 LIBRARIES USED

- i. **from flask import Flask, request, render_template:** Used for developing the web application backend, handling user requests, processing permission inputs, and displaying analysis results.
- ii. **import nltk:** Used for Natural Language Processing tasks such as tokenization, stemming, stop-word removal, and permission text analysis..
- iii. **import pandas as pd:** Used for dataset handling, preprocessing, permission record management, and structured data operations.
- iv. **import numpy as np:** Used for numerical computation, matrix operations, and machine learning data processing.
- v. **from sklearn.feature_extraction.text import CountVectorizer:** Used for converting permission text into numerical feature vectors for machine learning analysis.
- vi. **from sklearn.naive_bayes import MultinomialNB:** Used for implementing machine learning-based permission risk classification models.
- vii. **from sklearn.model_selection import train_test_split:** Used for splitting permission datasets into training and testing datasets for machine learning evaluation.
- viii. **from sklearn.metrics import accuracy_score:** Used for measuring machine learning model performance and prediction accuracy.
- ix. **import tensorflow as tf:** Used for implementing advanced deep learning models for intelligent permission analysis and threat prediction.
- x. **import sqlite3:** Used for SQLite database integration, permission data storage, and report.

CHAPTER 4

SYSTEM STUDY

4. SYSTEM STUDY

System study refers to the process of analyzing and evaluating a proposed system to understand its functionality, components, and performance. The main objective of the system study is to identify whether the proposed “Secure Mobile Application Permission Analyzer Using Natural Language Processing” can effectively improve Android security by analyzing application permissions and detecting suspicious behaviors using NLP and Machine Learning techniques.

4.1 FEASIBILITY STUDY

The feasibility study for the proposed Secure Mobile Application Permission Analyzer evaluates the practicality and effectiveness of implementing the system using current technologies. The system uses Natural Language Processing, Machine Learning, and Android permission analysis techniques to identify risky permissions and suspicious application behavior. The study ensures that the project can be developed successfully using available software tools and resources.

The technical and operational feasibility focuses on analyzing whether the system can process Android application permissions efficiently and generate accurate risk classifications. Technologies such as Python, Flask, NLTK, and Scikit-learn support permission extraction, text analysis, and machine learning-based classification. The web-based interface also improves accessibility and usability for users.

The feasibility study further evaluates scalability, security, and future enhancements of the system. Potential issues such as false positives, permission ambiguity, and evolving malware behaviors are considered during analysis. Overall, the study confirms that the proposed system is feasible, reliable, scalable, and suitable for improving Android application security and user privacy protection.

The study also confirms that the required hardware, software tools, and development platforms are easily available and cost-effective for implementation. The proposed system can be integrated with modern cybersecurity techniques to improve mobile application security analysis. It supports efficient permission monitoring and helps users identify potential privacy risks before installing applications. Furthermore, the feasibility analysis shows that the system can be enhanced and maintained effectively for future Android security requirements.

4.2 ECONOMICAL FEASIBILITY

The economic feasibility of the Secure Mobile Application Permission Analyzer focuses on analyzing the cost-effectiveness of the proposed system. The project mainly uses open-source technologies such as Python, Flask, TensorFlow, and NLP libraries, which reduces software licensing and development costs significantly. The system can also operate on standard computer systems without requiring expensive hardware resources.

The proposed system helps reduce financial losses caused by malicious Android applications, spyware attacks, and privacy violations. By identifying risky permissions before application installation, the system protects sensitive user information and improves cybersecurity awareness. Automated permission analysis also reduces manual inspection efforts and improves operational efficiency.

The system provides long-term economic benefits through scalability and low maintenance requirements. Since the framework supports future updates and additional security features without major infrastructure changes, the project remains financially sustainable. Overall, the proposed system is economically practical and beneficial for Android security enhancement.

4.3 TECHNICAL FEASIBILITY

The technical feasibility evaluates whether the proposed Secure Mobile Application Permission Analyzer can be implemented effectively using available technologies and development tools. The system uses Python programming language, Natural Language Processing techniques, and Machine Learning algorithms to analyze Android application permissions and classify them into safe or risky categories.

The framework extracts permission information from Android applications and processes permission descriptions using NLP methods such as tokenization, stop-word removal, and semantic analysis. Machine learning models are trained using permission datasets to improve classification accuracy and identify suspicious permission patterns associated with malware or spyware activities.

The system architecture is lightweight, scalable, and efficient for real-time permission analysis. Web technologies such as Flask, HTML, CSS, and JavaScript support frontend and backend integration for smooth system operation. Overall, the proposed framework is technically

feasible, reliable, and suitable for Android cybersecurity applications.

4.4 SOCIAL FEASIBILITY

The social feasibility of the Secure Mobile Application Permission Analyzer focuses on user acceptance, cybersecurity awareness, and the social impact of the proposed system. The framework helps users understand Android application permissions and identify potentially harmful applications before installation. This improves user awareness regarding privacy and mobile security threats.

The system provides a simple and user-friendly interface that displays permission details, warning notifications, and risk classifications clearly. Even non-technical users can easily understand dangerous permissions and suspicious application behavior. This increases usability and encourages wider acceptance of the system in educational, organizational, and personal security environments.

The proposed system contributes to society by promoting safer smartphone usage and reducing risks related to spyware, malware, and unauthorized data access. Ethical considerations such as privacy protection and secure handling of application information are also maintained. Overall, the project supports better cybersecurity practices and helps create a safer digital environment for Android users.

The proposed system also supports educational and research activities in the field of cybersecurity and mobile application security. Students, researchers, and security analysts can use the framework to study Android permission behaviors and understand how malicious applications misuse sensitive permissions. The integration of Artificial Intelligence and Natural Language Processing improves awareness about advanced mobile security technologies and encourages users to adopt safer digital practices. Continuous improvements and future enhancements can further increase the system's social value and effectiveness in protecting user privacy and smartphone security.

The system also helps users make informed decisions before downloading or installing Android applications from unknown sources. It encourages responsible permission management and increases awareness about digital privacy protection. The framework can be used in cybersecurity training programs to educate users about mobile security threats and safe application.

CHAPTER 5

SYSTEM DESIGN

5. SYSTEM DESIGN

System design describes the overall structure, workflow, and interaction between different modules of the Secure Mobile Application Permission Analyzer Using Natural Language Processing system. It explains how Android application permissions are collected, processed, analyzed, and classified using Natural Language Processing (NLP) and Machine Learning techniques. Proper system design helps improve system organization, scalability, efficiency, maintainability, and security analysis performance.

5.1 SYSTEM ARCHITECTURE

A System Architecture is the conceptual model that defines the structure and interaction between different modules of a system. It helps in understanding system functionality, data flow, and communication between components for efficient implementation and maintenance.




Figure 5.1 : System Architecture of Secure Mobile Application Permission Analyzer Using Natural Language Processing

In Figure 5.1, the proposed system collects Android application permission details from users through a web interface. The Permission Collection module extracts permission data from APK files or datasets and forwards it to the NLP Processing module. The NLP module performs preprocessing techniques such as tokenization, stop-word removal, stemming or lemmatization, and feature extraction to prepare the permission data for analysis. The Machine Learning Classification module analyzes the processed permission data and classifies applications into Safe, Suspicious, or High Risk categories. The Risk Analysis Engine further examines permission patterns, detects dangerous permission combinations, calculates risk scores, and generates security alerts. The SQLite database stores permission analysis results, user history, alerts, and generated reports for future reference. The Visualization Dashboard displays real-time graphs, alerts, statistics, and permission analysis results to users. Finally, the Report Generation module creates downloadable PDF and CSV reports containing application risk summaries and security analysis details. Overall, the system integrates NLP, Machine Learning, database management, and visualization techniques to enhance Android application privacy and security analysis.

5.2 UML DIAGRAM

UML (Unified Modeling Language) is a standardized modeling language used for visualizing, designing, and documenting software systems. In the proposed “Secure Mobile Application Permission Analyzer Using Natural Language Processing,” the UML diagram represents the interaction between the user and major system functionalities such as permission upload, permission analysis, dashboard monitoring, risk classification, report generation, and result export. It helps in understanding the workflow and interaction between different modules of the system.

UML diagrams provide a clear graphical representation of the overall system architecture, making it easier to understand data flow, module connectivity, and system behavior. They also support efficient system planning and implementation by helping developers identify dependencies, process flow, and functional relationships between different components.

In addition, UML diagrams improve communication between developers, project guides, and users by providing a simple and structured visualization of the system. They also serve as an important part of project documentation, helping during future maintenance, debugging, testing, and scalability improvements of the application.

UML diagrams also help in simplifying complex system processes through visual

representation and structured design models. They improve the accuracy of system development by providing a clear understanding of user interactions and module functionalities. Overall, UML modeling supports effective development, analysis, and maintenance of the proposed Android permission analysis system.




Figure 5.2: UML Diagram

The primary goals of UML diagrams are to:

- 1. Illustrate and Structure the Overall System Architecture:**

Figure 5.2: UML Diagram provide a clear graphical representation of the Permission Analyzer architecture, showing how modules such as permission upload, NLP-based analysis, machine learning detection, dashboard visualization, report generation, and result export are connected. This helps in designing the system efficiently and improving system organization.

- 2. Improve System Understanding:**

The diagram helps developers and users understand the interaction between system modules and the workflow of permission analysis using Natural Language Processing and Machine Learning techniques. It simplifies complex processing steps and improves clarity regarding data flow and system operations.

3. Support System Design and Planning:

UML diagrams help in analyzing workflows, defining system requirements, and planning implementation activities efficiently. They assist developers in identifying dependencies between modules and designing a scalable and maintainable architecture for Android permission analysis and risk classification.

4. Enhance Communication Between Stakeholders:

The UML diagram acts as an effective communication tool between developers, project guides, researchers, and users by providing a structured visual representation of system operations. It helps stakeholders understand project functionality clearly and reduces confusion during system development, testing, and presentation activities.

5. Provide Documentation Support:

UML diagrams serve as an important part of project documentation by clearly representing the structure, workflow, and interactions within the system. They help during future maintenance, debugging, feature enhancement, and scalability improvements by providing a well-organized reference for understanding the system architecture and module interactions.

5.3 DATA FLOW DIAGRAM

A Data Flow Diagram (DFD) is a graphical representation that shows how data moves within a system. It is used to illustrate the flow of information between processes, databases, and external entities. DFDs help in understanding how input data is processed and transformed into meaningful output through different stages within the system. They simplify complex workflows, improve system understanding, and support efficient software design, development, and maintenance. DFDs also act as an effective communication tool between developers, project guides, and users by providing a clear and organized representation of system operations.

In the proposed “Secure Mobile Application Permission Analyzer Using Natural Language Processing,” the Data Flow Diagram represents how Android application permission data is collected, processed, analyzed, and converted into security analysis reports. The system accepts permission details through a web interface, processes the data using NLP techniques such as tokenization, stop-word removal, stemming, and feature extraction, and then applies Machine Learning models to classify permissions into Safe, Suspicious, or High-Risk categories. The Risk

Analysis Engine detects dangerous permission combinations and generates alerts, while the analysis results, reports, and user history are stored in the SQLite database and displayed through the visualization dashboard in the form of graphs, alerts, and security reports.




Figure 5.3: Data Flow Diagram

Figure 5.3 shows the Data Flow Diagram (DFD) for the Secure Mobile Application Permission Analyzer system, illustrating the complete flow of data within the application. The process begins when user uploads Android application permission details through the web interface. The Permission Collection module extracts and organizes permission information, which is then processed using NLP techniques and Machine Learning classification models. The analyzed results are passed to the Risk Analysis Engine to calculate risk levels and generate security alerts. The processed information is stored in the SQLite database and displayed through the dashboard and report generation modules. This structured flow ensures efficient Android permission analysis, intelligent risk classification, and real-time security monitoring within the system. The Data Flow Diagram helps in understanding the movement of data between different modules and system processes involved in permission analysis. It also improves system design efficiency by clearly representing data processing, storage and communication within the proposed application.

5.4 USE CASE DIAGRAM

A Use Case Diagram is a graphical representation that illustrates the interaction between users and the functionalities of a system. It is a behavioral UML diagram used to represent system operations, user activities, and functional requirements in a simple and understandable format. Use case diagrams help developers and users understand the workflow, module interaction, and overall behavior of the system efficiently.

In the proposed “Secure Mobile Application Permission Analyzer Using Natural Language Processing,” the Use Case Diagram represents the interaction between users, administrators, and various functional modules involved in permission analysis and security monitoring. The diagram includes functionalities such as uploading Android application data, collecting permissions, preprocessing permission information using Natural Language Processing techniques, performing Machine Learning-based risk classification, generating alerts, storing analysis results, viewing dashboards, generating reports, and exporting results.

The Use Case Diagram helps in visualizing how different modules communicate within the system and how users interact with the application through various operations. It simplifies workflow understanding, improves system planning, and supports effective implementation, testing, maintenance, and project documentation activities.

A Use Case Diagram is a behavioural UML diagram used to represent the interaction between users and system functionalities. It provides a simple graphical representation of how different actors communicate with the system modules. The diagram helps in understanding the overall workflow and operational behaviour of the proposed application efficiently. It is mainly used to identify system requirements, user activities, and functional processes involved in the project. Use case diagrams simplify complex system interactions into understandable visual components for developers and users. In the proposed system, the diagram represents the functionalities related to Android permission analysis and security monitoring. The system includes operations such as permission collection, NLP preprocessing, Machine Learning classification, dashboard visualization, and report generation. Different actors such as User, Admin, System, and Notification Service interact with the application through various functionalities. The diagram improves system planning, implementation, testing, and maintenance activities during software development. It also helps in understanding the communication between modules involved in intelligent Android permission analysis using Natural Language Processing and Machine Learning techniques.




Figure 5.4: Use Case Diagram

Figure 5.4 shows the Use Case Diagram for the proposed Secure Mobile Application Permission Analyzer system. The primary actors involved in the system are the User, Admin, System, and Notification Service. The User interacts with functionalities such as uploading Android application data, starting permission analysis, viewing dashboards, generating reports, and exporting analysis results. The Admin manages users, monitors system activities, and views audit logs. The system internally performs permission collection, NLP preprocessing, Machine Learning classification, risk analysis, database storage, dashboard visualization, and report generation processes. The Notification Service is responsible for handling alerts and security notifications generated during permission risk analysis. The diagram illustrates the overall interaction and workflow of the system modules involved in Android permission analysis and intelligent security monitoring using NLP and Machine Learning techniques. The diagram also helps developers identify the functional requirements and communication flow between different modules of the system.

5.5 ACTIVITY DIAGRAM

An Activity Diagram is a behavioral UML diagram used to represent the flow of activities and operations within a system. It illustrates the sequence of actions, decision-making processes, and workflow of the application in a graphical format. Activity diagrams help developers and users understand how the system functions step by step and how different modules interact during execution.

Activity diagrams are useful for representing workflows, sequential processing, and decision-based operations within a system. They help identify system dependencies, improve workflow understanding, reduce complexity, and support efficient software design and implementation. These diagrams also improve communication among developers, project guides, and users by visually explaining system behavior.

In the proposed “Secure Mobile Application Permission Analyzer Using Natural Language Processing,” the Activity Diagram represents the complete workflow involved in Android permission analysis. The process begins when the user uploads Android application permission data or APK information into the system. The Permission Collection module extracts the permission details and sends them to the NLP Processing module for preprocessing operations such as tokenization, stop-word removal, stemming, and feature extraction.

After preprocessing, the Machine Learning module analyzes permission patterns and classifies them into Safe, Suspicious, or High-Risk categories. The Risk Analysis Engine then evaluates dangerous permission combinations and generates alerts if suspicious behavior is detected. If the calculated risk level is high, the system sends notifications through dashboard alerts or email services. Otherwise, the application is marked as safe or low risk.

Finally, the analysis results, alerts, and reports are displayed through the dashboard interface. The system then generates detailed security reports and allows users to export the results in PDF, CSV, or Excel format for future reference and documentation.

The Activity Diagram helps in understanding the complete execution flow and interaction between different modules involved in Android permission analysis. It also supports efficient system design, implementation, testing, and maintenance by clearly representing workflow activities and decision-making processes within the proposed application. It provides a clear visual representation of system workflow, making it easier to understand the step-by-step execution of the Android permission analysis process.




Fig 5.5: Activity Diagram

Figure 5.5 shows the Activity Diagram for the Secure Mobile Application Permission Analyzer system, illustrating the complete workflow of Android permission analysis. The process starts with uploading permission data, followed by permission extraction, NLP preprocessing, machine learning-based risk classification, and risk analysis. Based on the calculated risk level, the system identifies applications as safe or suspicious and generates alerts when necessary. The final results are displayed through the dashboard interface, where users can view alerts, analysis reports, and export security reports for future reference.

5.6 SEQUENCE DIAGRAM

Sequence diagrams are useful in visualizing the dynamic behavior of a system by representing interactions between users and system modules in a time-ordered manner. They clearly show the sequence of operations, message flow, and communication between different components involved in the process. Sequence diagrams help developers and stakeholders understand system functionality, module dependencies, and workflow execution effectively.




Figure 5.6: Sequence Diagram

Figure 5.6 shows the Sequence Diagram for the proposed “Secure Mobile Application Permission Analyzer Using Natural Language Processing” system. The diagram illustrates the interaction between the User, Mobile Application, Risk Categorization Module, Data Collection and Privacy Module, Third-Party Sharing Module, Dashboard, and Report Module. The process begins when the user logs into the application and submits permission-related data. The Data Collection Module gathers and processes the permission information, while the Third-Party Sharing Module analyzes data-sharing activities and privacy-related behavior. The Risk Categorization Module evaluates the collected data and classifies the application based on risk levels. The processed results are then displayed on the dashboard, and the Report Module generates downloadable privacy and security analysis reports for the user.

5.7 CLASS DIAGRAM

A Class Diagram is a static structural diagram that represents the structure of a system by showing classes, their attributes, methods, and relationships. It helps in understanding the organization of the system and how different modules interact with each other. Class diagrams are useful for modeling the static structure of software systems and improving system design and implementation.

In the proposed “Secure Mobile Application Permission Analyzer Using Natural Language Processing,” the class diagram represents important system components such as User, Data Submission, Data Collection Module, Risk Categorization Module, Third Party Sharing Module, Risk Result, Dashboard, Alert, and Report. These classes handle permission data collection, privacy analysis, risk categorization, alert generation, dashboard visualization, and report generation functionalities.

Class diagrams also improve communication between developers and stakeholders by providing a clear representation of system architecture. They support software maintenance, debugging, scalability, and future enhancements by organizing functionalities into separate modules. Additionally, the class diagram helps in identifying the responsibilities of each module and reduces system complexity through proper modular design. It provides a better understanding of data flow and communication between different components of the application. The diagram also assists developers during coding and testing by clearly defining class relationships and functionalities. Furthermore, it enhances the overall efficiency and reliability of the proposed

permission analyzer system by supporting systematic software development practices.




Figure 5.7: Class Diagram

Figure 5.7 shows the Class Diagram for the proposed Android Permission Analyzer system. The User class manages authentication and permission requests, while the Data Collection Module collects application permission and privacy-related data. The Risk Categorization Module analyzes the collected information and categorizes applications into different risk levels. The Third Party Sharing Module monitors data-sharing behavior with external services. The Risk Result and Alert classes manage risk scores and notifications, while the Dashboard and Report classes display analysis information and generate downloadable privacy and security reports. The class diagram also illustrates the relationships and dependencies between different system modules for efficient functionality. It improves system maintainability by separating responsibilities into individual classes and modules. Furthermore, the diagram supports future system enhancements and scalability by providing a well-structured representation of the proposed application architecture.

CHAPTER 6

IMPLEMENTATION

6. IMPLEMENTATION

Implementation explains the practical development and execution of the proposed “Secure Mobile Application Permission Analyzer Using Natural Language Processing” through different functional modules. The system collects Android application permissions, processes permission-related text using NLP techniques, analyzes sensitive permissions, and generates risk analysis reports. These modules work together to identify suspicious permission behavior and improve Android application security. The implementation ensures accurate permission analysis, efficient risk detection, and better privacy protection for users.

6.1 CLASSIFICATION OF MODULES

- Permission Collection Module
- NLP Processing Module
- Risk Analysis and Detection Module
- Report Generation and Summary Module

6.2 MODULE DESCRIPTION

Module description explains the functions and responsibilities of each module used in the project. Every module performs a specific task such as collecting permissions, processing text data, analyzing risks, and generating reports. These modules work together to ensure smooth system operation and accurate permission risk analysis. It improves efficiency, privacy monitoring, and overall system performance.

6.2.1 DATA COLLECTION AND INGESTION ENVIRONMENT

The Permission Collection Module is responsible for gathering Android application permission details, privacy policies, and Terms & Conditions from uploaded applications or datasets. Important permissions such as camera access, microphone access, location access, storage access, contact access, and SMS permissions are collected for further analysis. This module acts as the starting point of the system and provides the required input data for security evaluation. Proper permission collection helps improve the overall effectiveness of the analysis process.

The module extracts permission-related information from Android applications in a structured format to ensure consistency during processing. Since different applications may

request permissions in different ways, organizing the data properly is essential for accurate analysis. Structured permission data improves readability and simplifies further processing stages. It also helps the system maintain compatibility with multiple application datasets and permission sources.

Data cleaning and preprocessing are performed during collection to remove duplicate entries and unnecessary information. This improves the quality of the collected data and prevents errors in later stages of analysis. Clean permission data ensures smooth workflow between system modules and improves system reliability. Proper preprocessing also reduces processing complexity and improves performance.

The module is designed to efficiently handle multiple Android applications and large permission datasets without reducing system performance. Efficient permission handling supports both real-time and offline analysis of applications. Scalability is important because modern mobile environments contain thousands of applications with different permission requests. The module ensures stable operation even when processing large amounts of permission information.

The module also supports automated permission extraction to reduce manual effort and improve analysis speed. Proper data organization helps maintain consistency between different stages of the system. Efficient data ingestion improves the accuracy and reliability of Android permission analysis significantly.

The module also improves system flexibility by supporting data collection from multiple Android application sources and datasets. It helps the system efficiently manage large-scale permission information without affecting processing performance. Reliable data ingestion strengthens the foundation of the permission analyzer system and supports effective privacy monitoring.

6.2.2 NLP PROCESSING MODULE

The NLP Processing Module processes permission-related text using Natural Language Processing techniques to identify meaningful security information. Permission descriptions, privacy policies, and Terms & Conditions are analyzed to extract important keywords related to privacy and security risks. NLP techniques such as tokenization, stop-word removal, stemming, and feature extraction are applied during processing. These techniques improve the understanding of application behavior and help identify suspicious permission patterns effectively.

Text preprocessing is performed to remove unwanted symbols, duplicate words, irrelevant

text, and unnecessary characters from the collected data. This normalization process improves data quality and ensures consistency throughout the system. Clean and normalized text allows the system to analyze permission-related information more accurately. It also reduces the possibility of incorrect analysis caused by noisy or incomplete text data.

The module converts unstructured textual information into structured data suitable for further analysis and machine learning operations. Structured data improves processing efficiency and helps the system identify sensitive permissions more effectively. Organizing textual information properly also improves compatibility with classification and risk analysis algorithms. This enhances the accuracy of the overall permission analyzer system.

Feature extraction techniques are used to identify important privacy-related keywords and suspicious permission patterns from the processed text. Extracted features help the system recognize risky application behavior and hidden privacy threats. These features act as indicators during risk classification and security evaluation. Proper feature extraction improves the intelligence and effectiveness of the system significantly.

The NLP module also supports continuous improvement of analysis accuracy by processing different types of permission-related content efficiently. Modern Android applications often contain complex privacy policies and dynamically generated permission descriptions. The module ensures that such complex text is processed correctly without losing important information. This strengthens the system's ability to detect privacy risks and improves overall security analysis performance.

The module improves intelligent understanding of permission-related content through advanced language processing techniques. Accurate text analysis helps identify hidden privacy threats and suspicious application behavior effectively. This enhances the overall performance and reliability of the permission analyzer framework.

The module also enhances processing efficiency by converting unstructured textual data into organized and meaningful information. Proper text processing reduces ambiguity and supports accurate feature extraction for risk analysis. Continuous NLP-based analysis improves the system's adaptability to evolving Android privacy and security challenges.

The module improves intelligent understanding of permission-related content through advanced language processing techniques. Accurate text analysis helps identify hidden privacy threats and suspicious application behavior effectively. This enhances the overall performance and reliability of the permission analyzer framework.

6.2.3 RISK ANALYSIS AND DETECTION MODULE

The Risk Analysis and Detection Module analyzes sensitive Android permissions and evaluates the security risk associated with each application. Dangerous permissions such as camera access, microphone access, SMS permission, contact access, and location tracking are carefully examined to identify suspicious behavior. The module helps determine whether an application is safe or potentially harmful to user privacy and device security. This improves the overall protection provided by the system.

The module strengthens Android security by continuously identifying risky permissions and abnormal application activities. Intelligent risk detection mechanisms help reduce privacy threats and unauthorized access attempts. This improves user trust and increases the effectiveness of the mobile security analysis system.

6.2.4 REPORT GENERATION AND SUMMARY MODULE

The Report Generation and Summary Module generates detailed reports based on permission analysis and risk detection results. The system prepares structured summaries showing permission usage, privacy impact, suspicious permissions, and application risk levels. These reports help users understand the security condition of Android applications clearly and effectively. Proper reporting improves transparency and supports better security awareness.

Analysis results are displayed using summaries, tables, charts, and graphical representations for easy understanding. Important information such as risk percentage, permission statistics, suspicious behavior, and privacy alerts are presented visually to improve user experience. Visualization simplifies complex security information and helps users analyze application behavior more efficiently. This improves overall monitoring and decision-making capabilities.

The module supports generating reports in downloadable formats for documentation and future reference purposes. Users can save and export analysis results whenever required. Stored reports help maintain proper records of analyzed applications and detected risks. This feature is useful for security monitoring, auditing, and long-term privacy analysis activities.

Historical analysis and report storage capabilities help users compare application behavior over time and identify recurring privacy risks. Previously generated reports can be reviewed to study permission usage trends and suspicious activities. Long-term report management improves tracking and enhances overall cybersecurity monitoring. It also supports future improvements in

risk analysis and threat detection.

The module also improves communication between users and the system by presenting analysis results in a simple and understandable format. Security alerts, summaries, and recommendations help users take necessary precautions against risky applications. Clear reporting improves user trust and enhances the usability of the permission analyzer system. This strengthens the overall effectiveness of the project and supports better Android security management.

The Report Generation and Summary Module also helps administrators and researchers perform detailed security evaluations by organizing analysis data systematically. The generated reports can support security investigations, academic research, and application review processes. Automated report generation reduces manual effort and ensures consistent documentation of permission analysis results.

Furthermore, the module can assist in identifying high-risk applications quickly by highlighting critical security warnings and unusual permission combinations. Early detection of such risks helps prevent privacy breaches and improves user safety. This enhances the reliability of the system and contributes to stronger mobile application security management.

The module provides user-friendly reports that simplify understanding of complex permission analysis results. Clear summaries and visual representations improve security awareness and support better decision-making. Efficient report management also enhances long-term monitoring and Android application security evaluation.

Analysis results are displayed using summaries, tables, charts, and graphical representations for easy understanding. Important information such as risk percentage, permission statistics, suspicious behavior, and privacy alerts are presented visually to improve user experience. Visualization simplifies complex security information and helps users analyze application behavior more efficiently. This improves overall monitoring and decision-making capabilities.

The module supports generating reports in downloadable formats for documentation and future reference purposes. Users can save and export analysis results whenever required. Stored reports help maintain proper records of analyzed applications and detected risks. This feature is useful for security monitoring, auditing, and long-term privacy analysis activities.

Historical analysis and report storage capabilities help users compare application behavior over time and identify recurring privacy risks. Previously generated reports can be reviewed to study permission usage trends and suspicious activities.

CHAPTER 7

RESULT AND DISCUSSION

7. RESULT AND DISCUSSION

The proposed “Secure Mobile Application Permission Analyzer Using Natural Language Processing” produced effective results in analyzing Android application permissions and identifying privacy-related risks. The system successfully detected suspicious permission patterns, risky permission combinations, and sensitive access requests using NLP and Machine Learning techniques. Dashboard visualization and generated reports helped users monitor application behavior and understand permission risks clearly. The project improved permission analysis accuracy, privacy monitoring, and overall Android application security.

7.1 RESULT

The implemented permission analyzer framework produced reliable and efficient results during the permission analysis process. The system combines Natural Language Processing, keyword extraction, machine learning classification, and risk analysis techniques to identify both normal and suspicious permission behavior. It successfully analyzed permissions such as camera access, microphone access, SMS permission, storage access, and location tracking to determine application risk levels. The framework also generated security summaries, permission analysis reports, privacy risk indicators, and downloadable reports, while the dashboard provided smooth visualization of analysis results and application statistics.




Figure 7.1: Permission Analysis and Risk Classification Dashboard

Figure 7.1 represents the permission analysis behavior and risk classification performance of the proposed Android security system. The dashboard shows how the system processes uploaded application permissions and classifies them into Safe, Medium Risk, or High Risk categories over a specific time period. The graph can be interpreted through permission analysis accuracy, risk detection consistency, and system response behavior under different workloads. Higher analysis regions indicate efficient NLP processing and reliable machine learning classification, while small variations may occur during processing of applications containing large permission datasets or complex privacy policies. This visualization is important because the effectiveness of the project depends not only on accurate risk prediction but also on stable processing performance and clear presentation of security insights for users.

7.2 DISCUSSION

The results indicate that a Natural Language Processing (NLP) and machine learning-based permission analysis approach is more effective for Android security than traditional rule-based or manual permission checking methods. NLP helps in understanding the semantic meaning of Android permission descriptions, while machine learning improves generalization by detecting patterns and combinations of permissions associated with spyware, malware, and privacy violations. This layered approach improves detection accuracy by analyzing both individual permissions and their relationships, enabling the system to identify suspicious behaviors such as excessive permission requests and misuse of sensitive resources like camera, microphone, contacts, and location. However, challenges still exist, such as dependency on high-quality training data, difficulty in handling ambiguous or evolving permission descriptions, and balancing false positives and false negatives. From a deployment perspective, future improvements should focus on integrating advanced NLP models such as transformers and enabling real-time APK behavior monitoring with continuous model updates. Overall, the proposed system demonstrates that combining NLP and machine learning provides a scalable solution for Android permission security analysis and can be extended with cloud-based intelligence to strengthen mobile security. The proposed system also improves user awareness by providing detailed insights into permission usage and potential privacy threats. Efficient risk detection and intelligent analysis help strengthen Android application security and support safer mobile application usage. However, challenges still exist, such as dependency on high-quality training data, difficulty in handling ambiguous or evolving permission descriptions, and balancing false positives and false negatives.

CHAPTER 8

CONCLUSION AND FUTURE WORK

8. CONCLUSION AND FUTURE WORK

The project successfully analyzed Android application permissions using Natural Language Processing (NLP) and machine learning techniques to identify risky and suspicious permissions. It effectively detected privacy-related threats, malicious permission combinations, and potentially harmful application behaviors, improving Android security analysis. Future improvements can focus on reducing false positives, improving semantic understanding of permissions, and enhancing real-time APK analysis capabilities. The system can further strengthen mobile cybersecurity and user privacy protection in Android environments.

8.1 CONCLUSION

Android application permission analysis plays an important role in improving mobile cybersecurity and protecting user privacy. The proposed system uses Natural Language Processing (NLP) and machine learning techniques to analyze Android permissions and identify risky or suspicious applications effectively. The framework improves permission understanding, detects harmful permission combinations, and helps users avoid potential malware and privacy threats. Although challenges such as false positives and evolving malware behaviors still exist, continuous improvements in AI and NLP techniques can further enhance Android security and application threat detection.

The proposed Secure Mobile Application Permission Analyzer Using Natural Language Processing system provides an effective solution for identifying risky Android application permissions and improving mobile security. By combining Natural Language Processing and machine learning techniques, the system can intelligently analyze permission descriptions, privacy policies, and application behavior patterns to detect suspicious activities. The framework helps users understand how applications access sensitive resources such as camera, microphone, contacts, storage, SMS, and location services. Through automated permission analysis and risk categorization, the system improves privacy protection and supports safer Android application usage. The generated reports, risk summaries, and security alerts also improve user awareness regarding dangerous permissions and privacy threats. Overall, the project demonstrates the importance of intelligent permission analysis in strengthening Android cybersecurity and reducing security vulnerabilities in mobile applications. Through automated permission analysis and risk categorization, the system improves privacy protection and supports safer Android application use.

The system also highlights the growing importance of AI-based security solutions in modern mobile environments where thousands of Android applications request sensitive permissions every day. Traditional permission checking methods are often insufficient for identifying complex privacy risks and hidden malicious behaviors. The integration of NLP and machine learning improves the ability of the system to detect abnormal permission combinations and evolving malware patterns efficiently.

8.2 FUTURE WORK

As a future enhancement, the system can incorporate advanced deep learning and transformer-based NLP models for improved permission understanding and classification accuracy. Integration of real-time APK scanning and dynamic behavior analysis can further strengthen the detection of unknown or evolving malicious applications. The framework may also be extended with cloud-based threat intelligence systems, automated alert mechanisms, and continuous model retraining for better adaptability and scalability. Additional improvements can include multilingual permission analysis, advanced visualization dashboards, and automated recommendation systems for users. Future versions of the system may also support real-time mobile device monitoring and AI-driven risk prediction techniques to improve Android cybersecurity and privacy protection more effectively.

In future developments, the proposed “Secure Mobile Application Permission Analyzer Using Natural Language Processing” system can be enhanced by integrating advanced artificial intelligence techniques such as deep learning, transformer-based NLP models, and real-time behavioral analysis for improved permission understanding and threat detection accuracy. The framework can also support dynamic APK monitoring, cloud-based threat intelligence, and continuous machine learning model updates to identify newly emerging malware and evolving privacy threats effectively. Additional improvements may include multilingual privacy policy analysis, intelligent recommendation systems, automated alert notifications, and advanced dashboard visualizations for better user interaction and security awareness. Furthermore, future versions of the system can incorporate risk prediction, real-time mobile device monitoring, and scalable cloud integration to strengthen Android cybersecurity, improve privacy protection, and provide more reliable mobile application security management. It can also incorporate adaptive AI models that continuously evolve based on new malware patterns and user behavior trends.

APPENDIX - I

APPENDIX - I

I. OUTPUT


The image shows a web application titled "Permission Analyzer" with a shield icon. Below the title is a subtitle: "Analyze mobile app permissions & privacy policies using AI to uncover hidden data risks." The interface includes a text input field labeled "APP NAME (REQUIRED)" with a placeholder "e.g. WhatsApp, TikTok, Instagram...". Below this are two buttons: "Paste Text" (with a clipboard icon) and "Screenshot" (with a camera icon). A large text area follows, with a placeholder "Paste the app's privacy policy or permissions list here...". At the bottom is a prominent blue button labeled "Analyze Permissions" with a right-pointing arrow. The footer text reads "© 2026 Permission Analyzer • Built by @shunmugapriya2-bot".

Figure i: Permission Analyzer Input Interface for Mobile Application Privacy Assessment

In Figure i, it describes the main interface of the Secure Mobile Application Permission Analyzer using Natural Language Processing. The interface allows users to enter the name of a mobile application and provide privacy-related content for analysis. Users can either paste the application’s privacy policy text directly or upload screenshots containing permissions, privacy policies, or terms and conditions. This flexible input mechanism improves usability and supports multiple forms of privacy data collection. The system is designed to analyze application permissions and identify potential privacy risks using AI-based techniques. The interface clearly separates text input and screenshot upload options for better accessibility and user interaction. A dedicated “Analyze Permissions” button initiates the analysis process after the required information is provided. The simple and organized layout improves user experience and minimizes confusion during data submission. Overall, the module acts as the primary interface for collecting privacy-related information from mobile applications for further analysis and risk assessment. The interface also improves flexibility by supporting both manual text input and image-based privacy data submission methods. The interface is designed to provide smooth interaction between the user and the permission analysis system through a simple and intuitive workflow. Efficient input handling and organized data collection improve the accuracy of privacy analysis and support effective mobile application security assessment.




Figure ii: Screenshot Upload and AI-Based Text Extraction Process

In Figure ii, it describes the screenshot upload functionality integrated within the Permission Analyzer system. Users can upload screenshots containing privacy policies, permissions, or terms and conditions of mobile applications for automated analysis. Once the screenshot is uploaded, the system applies AI-based text extraction techniques to retrieve textual information from the image. The extracted content is then processed for identifying sensitive permissions and privacy-related risks. This feature allows users to analyze applications even when the information is available only in image format. The upload interface also provides validation and preview functionality to ensure correct file submission before processing. A progress indicator is displayed while the AI extraction and analysis are being performed. This improves transparency and user awareness during processing. The screenshot-based analysis enhances flexibility and broadens the usability of the system. Overall, the module simplifies privacy analysis by automatically converting image-based information into analyzable text data.

Here's how it works:

- I. User uploads a screenshot containing permissions, privacy policies, or terms and conditions.
- II. The system validates the uploaded image format and size before processing.
- III. AI-based text extraction techniques are applied to retrieve textual content from the screenshot.
- IV. The extracted text is cleaned and prepared for further analysis.
- V. Privacy-related keywords and sensitive permissions are identified from the extracted content.

VI. Risk analysis is performed based on detected permissions and policy patterns.

VII. The final privacy risk report is generated and displayed to the user.




Figure iii: Privacy Risk Analysis Report and Risk Level Assessment

In Figure iii, it describes the analysis report generated by the Permission Analyzer after processing the uploaded application data. The report provides an overall privacy risk assessment based on the permissions, privacy policies, and terms and conditions associated with the application. The system identifies whether the analyzed application contains potentially risky data collection or sharing practices. A visual risk indicator is displayed to represent the overall privacy risk percentage. The report also summarizes key findings extracted from the analyzed content to help users understand potential threats more effectively. The system uses Natural Language Processing techniques to detect sensitive terms and high-risk privacy behaviors from the uploaded content. The interface presents the results in a structured and readable format for better understanding and analysis. Users can also view extracted text and copy analysis results for future reference. This module improves transparency by explaining why the application is categorized under a particular risk level. Overall, the analysis report helps users make informed decisions regarding application privacy and data security. The module also enhances awareness about hidden data collection practices and third-party data sharing activities present within mobile applications.




Figure iv: Risk Categorization Interface for Privacy Threat Assessment

In Figure iv, it describes the risk categorization interface of the Secure Mobile Application Permission Analyzer. The interface visually represents different privacy risk categories identified during the analysis process. The system classifies detected risks based on permissions, extracted keywords, and suspicious privacy-related patterns found within the application’s privacy policy or terms and conditions. Each category is assigned a percentage value to indicate its contribution to the overall privacy risk level. This helps users easily understand which privacy factors pose the greatest concern.

The interface also highlights sensitive permission usage and risky data handling practices identified through Natural Language Processing techniques. Graphical representations improve interpretability and allow users to analyze privacy threats more efficiently. The categorized view simplifies complex privacy analysis results into understandable insights for both technical and non-technical users. Overall, the module improves transparency and assists users in understanding the severity of privacy risks associated with mobile applications. The risk categorization interface also improves user awareness by clearly presenting the severity level of detected privacy threats and suspicious permission usage. Color-coded visualization and percentage-based analysis help users quickly identify high-risk privacy factors within the application. The module supports better decision-making by simplifying complex security information into an organized and understandable format. Efficient graphical representation enhances the overall usability and effectiveness of the privacy threat assessment system.




Figure v: Privacy Recommendation and Risk Mitigation Module

In Figure v, it describes the privacy recommendation and risk mitigation module of the Secure Mobile Application Permission Analyzer. The module provides personalized recommendations based on the detected privacy risks and suspicious permission usage identified during analysis. The system suggests appropriate actions such as limiting unnecessary permissions, reviewing privacy settings, and avoiding excessive data sharing practices. These recommendations help users improve their privacy awareness and reduce potential security risks while using mobile applications.

The interface presents recommendations in a clear and structured format for easier understanding and implementation. This guidance helps users make informed decisions before installing or using applications. The recommendation module enhances transparency by providing actionable suggestions instead of only displaying risk scores. Overall, the module strengthens privacy protection and supports safer mobile application usage through effective risk mitigation strategies.

The Privacy Recommendation and Risk Mitigation Module also improves user understanding by explaining why certain permissions or privacy practices are considered risky. Detailed recommendations help users recognize unnecessary permission requests and encourage safer application usage habits. This improves user awareness regarding mobile privacy and strengthens overall cybersecurity practices. The module further supports proactive security management by helping users take preventive measures before privacy threats become serious issues. By combining intelligent analysis with practical recommendations, the system enhances user trust and promotes secure mobile application environments.

APPENDIX - II

APPENDIX - II

II. SAMPLE CODE

Sample code represents the implementation of important functionalities used in the project “Secure Mobile Application Permission Analyzer Using Natural Language Processing.” The system analyzes screenshots of application permission policies, privacy policies, and terms & conditions using OCR, NLP, and machine learning techniques. It identifies risky permissions, suspicious keywords, privacy threats, and displays risk percentage with graphical analysis for user awareness.

i. IMAGE UPLOAD AND SCREENSHOT PROCESSING

```
from flask import Flask,
request, render_template

import os

from werkzeug.utils import
secure_filename

import cv2

import uuid

app = Flask(__name__)

UPLOAD_FOLDER =
'static/uploads/'

PROCESSED_FOLDER =
'static/processed/'

app.config['UPLOAD_FOLD
ER'] = UPLOAD_FOLDER

app.config['PROCESSED_FO
LDER'] =
PROCESSED_FOLDER

os.makedirs(UPLOAD_FOL
```

```

DER, exist_ok=True)

os.makedirs(PROCESSED_FOLDER, exist_ok=True)

ALLOWED_EXTENSIONS
= {'png', 'jpg', 'jpeg'}

def allowed_file(filename):

    return '.' in filename and \

        filename.rsplit('.',
1)[1].lower() in
ALLOWED_EXTENSIONS

def
process_screenshot(input_path, output_path):

    image =
cv2.imread(input_path)

    # Convert into grayscale

    gray = cv2.cvtColor(image,
cv2.COLOR_BGR2GRAY)

    # Remove noise

    blur =
cv2.GaussianBlur(gray, (5, 5),
0)

    # Thresholding

    thresh = cv2.threshold(

        blur,

```

```

    0,

    255,

    cv2.THRESH_BINARY
+ cv2.THRESH_OTSU

)[1]

# Resize image

resized = cv2.resize(

    thresh,

    None,

    fx=2,

    fy=2,
interpolation=cv2.INTER_CU
BIC

)

# Save processed image

cv2.imwrite(output_path,
resized)

@app.route('/')

def home():

    return
render_template('upload.html'
)

@app.route('/upload',
methods=['POST'])

```

```

def upload_image():

    if 'file' not in request.files:

        return "No File
Uploaded"

    file = request.files['file']

    if file.filename == "":

        return "No Selected File"

    if file and
allowed_file(file.filename):

        filename =
secure_filename(file.filename
)

        unique_name =
str(uuid.uuid4()) + "_" +
filename

        upload_path =
os.path.join(
app.config['UPLOAD_FOLD
ER'],

        unique_name

        )

        processed_path =
os.path.join(
app.config['PROCESSED_FO
LDER'],

```

```

        "processed_" +
unique_name

    )

    # Save uploaded image

    file.save(upload_path)

    # Process screenshot

process_screenshot(upload_pa
th, processed_path)

    return f"""

    Image Uploaded
Successfully <br>

    Original Image:
{upload_path} <br>

    Processed Image:
{processed_path}

    """

    return "Invalid File Format"

if __name__ == '__main__':

    app.run(debug=True)

```

ii. OCR TEXT EXTRACTION FROM SCREENSHOT

```

import pytesseract

import cv2

import re

```

```

# -----

# Configure Tesseract Path

# -----

pytesseract.pytesseract.tesseract_cmd = \

r'C:\Program Files\Tesseract-OCR\tesseract.exe'

# -----

# OCR Extraction Function

# -----

def extract_text_from_image(image_path):

    # Read image

    image = cv2.imread(image_path)

    # Convert to grayscale

    gray = cv2.cvtColor(image, cv2.COLOR_BGR2GRAY)

    # Remove noise

    blur = cv2.GaussianBlur(gray, (3, 3), 0)

    # Apply thresholding

    threshold = cv2.threshold(

        blur,

        0,

        255,

        cv2.THRESH_BINARY + cv2.THRESH_OTSU

    )[1]

```

```

# OCR Extraction

extracted_text = pytesseract.image_to_string(

    threshold,

    config='--oem 3 --psm 6'

)

return extracted_text

# -----

# Clean Extracted Text

# -----

def clean_text(text):

    text = text.lower()

    text = re.sub(r'^a-zA-Z0-9\\s]', '', text)

    text = re.sub(r'\\s+', ' ', text)

    return text

# -----

# Main Program

# -----

if __name__ == '__main__':

    image_path = "static/processed/sample.png"

    extracted_text = extract_text_from_image(image_path)

    cleaned_text = clean_text(extracted_text)

    print("=====")

```

```

print("EXTRACTED TEXT")

print("=====")

print(cleaned_text)

# Save output text

with open("output_text.txt", "w", encoding="utf-8") as file:

    file.write(cleaned_text)

print("Text Saved Successfully")

```

iii. **NLP -BASED RISK KEYWORD ANALYSIS**

```

import nltk

import re

from nltk.tokenize import word_tokenize

from nltk.corpus import stopwords

from nltk.stem import PorterStemmer

# Download NLTK Data

nltk.download('punkt')

nltk.download('stopwords')

# -----

# Risk Keywords Database

# -----

HIGH_RISK = [

    "camera",

    "microphone",

    "contacts",

    "sms",

    "location",

```

```

    "record audio",
    "call logs",
    "read messages",
    "track user",
    "spy"
]
MEDIUM_RISK = [
    "wifi",
    "bluetooth",
    "storage",
    "internet",
    "network",
    "media access"
]
LOW_RISK = [
    "theme",
    "wallpaper",
    "display",
    "settings",
    "notification"
]
# -----
# NLP Preprocessing
# -----
stop_words = set(stopwords.words('english'))

```

```

stemmer = PorterStemmer()
def preprocess_text(text):
    text = text.lower()
    text = re.sub(r'^a-zA-Z\\s', "", text)
    tokens = word_tokenize(text)
    filtered_words = []
    for word in tokens:
        if word not in stop_words:
            stemmed = stemmer.stem(word)
            filtered_words.append(stemmed)
    return " ".join(filtered_words)
# -----
# Risk Detection Function
# -----
def analyze_risk(text):
    text = text.lower()
    detected_keywords = []
    risk_level = "Safe"
    # Check High Risk
    for word in HIGH_RISK:
        if word in text:
            detected_keywords.append(word)
            risk_level = "High Risk"
    # Check Medium Risk
    if risk_level != "High Risk":

```

```

    for word in MEDIUM_RISK:
        if word in text:
            detected_keywords.append(word)
            risk_level = "Medium Risk"
# Check Low Risk
if risk_level == "Safe":
    for word in LOW_RISK:
        if word in text:
            detected_keywords.append(word)
            risk_level = "Low Risk"
return {
    "risk_level": risk_level,
    "keywords": detected_keywords,
    "count": len(detected_keywords)
}
# -----
# Main Program
# -----
if __name__ == '__main__':
    sample_text = """
    This application can access your camera,
    contacts, microphone and track location.
    """

    processed_text = preprocess_text(sample_text)
    result = analyze_risk(processed_text)
    print("=====")

```

```

print("RISK ANALYSIS RESULT")
print("=====")
print("Risk Level :", result['risk_level'])
print("Detected Keywords :")
for keyword in result['keywords']:
    print("-", keyword)
print("Total Keywords :", result['count'])

```

iv. DATABASE STORAGE USING SQLITE

```

import sqlite3
from datetime import datetime

# -----
# Connect Database
# -----

connection = sqlite3.connect("permission_analyzer.db")
cursor = connection.cursor()

# -----
# Create Table
# -----

create_table_query = """
CREATE TABLE IF NOT EXISTS screenshot_analysis (
    id INTEGER PRIMARY KEY AUTOINCREMENT,
    image_name TEXT,
    extracted_text TEXT,
    risk_level TEXT,
    keywords_detected TEXT,

```

```

        analysis_date TEXT,
        processing_status TEXT
    )
    """

    cursor.execute(create_table_query)
    connection.commit()
    print("Table Created Successfully")

    # -----
    # Insert Data Function
    # -----

    def insert_analysis_data(
        image_name,
        extracted_text,
        risk_level,
        keywords_detected,
        processing_status
    ):
        insert_query = """
        INSERT INTO screenshot_analysis (
            image_name,
            extracted_text,
            risk_level,
            keywords_detected,
            analysis_date,
            processing_status
        )

```

```

VALUES (?, ?, ?, ?, ?, ?)
"""

analysis_date = datetime.now().strftime(
    "%Y-%m-%d %H:%M:%S"
)

cursor.execute(insert_query, (
    image_name,
    extracted_text,
    risk_level,
    keywords_detected,
    analysis_date,
    processing_status
))

connection.commit()

print("Data Inserted Successfully")

# -----
# Fetch All Records
# -----

def fetch_all_records():
    select_query = """
    SELECT * FROM screenshot_analysis
    ORDER BY id DESC
    """

    cursor.execute(select_query)
    records = cursor.fetchall()
    return records

```

```

# -----

# Search High Risk Records
# -----

def search_high_risk():
    search_query = """
    SELECT * FROM screenshot_analysis
    WHERE risk_level = 'High Risk'
    """

    cursor.execute(search_query)
    records = cursor.fetchall()
    return records

# -----

# Delete Record
# -----

def delete_record(record_id):
    delete_query = """
    DELETE FROM screenshot_analysis
    WHERE id = ?
    """

    cursor.execute(delete_query, (record_id,))
    connection.commit()
    print("Record Deleted Successfully")

# -----

# Main Program
# -----

```

```

if __name__ == '__main__':
    insert_analysis_data(
        image_name="sample.png",
        extracted_text="""
        This application can access camera
        and contacts
        """,
        risk_level="High Risk",
        keywords_detected="camera, contacts",
        processing_status="Completed"
    )
    print("=====")
    print("DATABASE RECORDS")
    print("=====")
    records = fetch_all_records()
    for row in records:
        print(row)
    print("=====")
    print("HIGH RISK RECORDS")
    print("=====")
    high_risk = search_high_risk()
    for row in high_risk:
        print(row)
    connection.close()

```

REFERENCES

REFERENCES

- [1] H. Hu, W. Minn, Y. Liu, J. Liu, F. Thung, T. Y. Zhuo, L. K. Shar, D. Gao, and D. Lo, ‘Bamboo: Large Language Model Driven Discovery of Application Programming Interface Permission Mappings in the Android Framework,’ *IEEE Access*, vol. 13, pp. 1–18, 2025.
- [2] R. Y. Mawoh, J. B. A. Wacka, F. Tchakounte, C. Fachkha, and Kolyang, ‘An Accurate Approach to Discriminate Android Colluded Malware From Single App Malware Using Permissions Intelligence,’ *Scientific Reports*, vol. 15, pp. 1–21, 2025.
- [3] A. Prasad, S. Chandra, M. Uddin, T. Al-Shehari, N. A. Alsadhan, and S. U. Sajid, ‘PermGuard: A Scalable Framework for Android Malware Detection Using Permission-to-Exploitation Mapping,’ *IEEE Access*, vol. 13, pp. 1–22, 2025.
- [4] A. Sabbah, R. Jarrar, S. Zein, and D. Mohaisen, ‘Understanding Concept Drift With Deprecated Permissions in Android Malware Detection,’ *IEEE Access*, vol. 13, pp. 1–17, 2025.
- [5] E. Aydogan and S. Sen, ‘Android Authorship Attribution Using Source Code-Based Features,’ *IEEE Access*, vol. 12, pp. 6569–6589, 2024.
- [6] F. S. Atedjio, J. P. Lienou, F. F. Nelson, S. S. Shetty, and C. A. Kamhoua, ‘A Defensive Strategy Against Android Adversarial Malware Attacks,’ *IEEE Access*, vol. 12, pp. 169432–169441, 2024.
- [7] F. S. Atedjio, J. P. Lienou, F. F. Nelson, S. S. Shetty, and C. A. Kamhoua, ‘Cycle Generative Adversarial Network Gradient Penalty for Enhancing Android Adversarial Malware Detection in Gray Box Setting,’ *IEEE Access*, vol. 12, pp. 162685–162696, 2024.
- [8] G. S. Tuncay, ‘Android Permissions: Evolution, Attacks, and Best Practices,’ *IEEE Security and Privacy*, vol. 22, no. 6, pp. 40–49, Sep. 2024.
- [9] M. Rafid Islam, ‘Diagnosing and Mitigating Domain Shift in Permission-Based Android Malware Detection,’ *IEEE Access*, vol. 14, pp. 1–15, 2026.
- [10] A. Banik and J. P. Singh, ‘A BERT and Particle Swarm Optimization Framework for Android Malware Detection Using Real Permissions and Application Programming Interface Calls,’ *Discover Computing*, vol. 29, pp. 1–20, 2026.
- [11] F. S. Alsubaei, A. A. Almazroi, W. S. Atwa, A. A. Almazroi, N. Ayub, and N. Z. Jhanjhi, ‘BERT Ensemble Based MBR Framework for Android Malware Detection,’ *Scientific Reports*, vol. 15, pp. 1–18, 2025.
- [12] R. Li, W. Diao, and D. Gao, ‘Custom Permission Misconfigurations in Android: A Large-Scale Security Analysis,’ in *Proceedings of the 2024 IEEE International Conference on Trust, Security and Privacy in Computing and Communications*, pp. 1161–1170, 2024.

- [13] S. Saleem, J. Mišić, and V. B. Mišić, ‘An Effective Temporal Convolutional Networks-Based Method for Detecting Android Malware Using Dynamic Extracted Features,’ *IEEE Access*, vol. 13, pp. 49891–49904, 2025.
- [14] T. Sutter, T. Kehrer, M. Rennhard et al., ‘Dynamic Security Analysis on Android: A Systematic Literature Review,’ *IEEE Access*, vol. 12, pp. 57261–57287, 2024.
- [15] W. Wang et al., ‘Exploring Permission-Induced Risk in Android Applications for Malicious Application Detection,’ *IEEE Transactions on Information Forensics and Security*, vol. 9, no. 11, pp. 1869–1882, Nov. 2014.
- [16] F. Leveni, M. Mistura, F. Iubatti, C. Giangregorio, N. Pastore, C. Alippi, and G. Boracchi, ‘Malware Families Discovery via Open-Set Recognition on Android Manifest Permissions,’ pp. 1–12, 2025.



SRM VALLIAMMAI ENGINEERING COLLEGE

(An Autonomous Institution)

ESTD. 1999 - Accredited by NBA - Approved by AICTE

'A' Grade Accreditation by NAAC

ISO 21001:2018 Certified - Affiliated to Anna University Chennai

CENTRE OF EXCELLENCE IN SUSTAINABILITY

SDG CERTIFICATE

This is to certify that the project work "SECURE MOBILE APPLICATION PERMISSION ANALYZER USING NATURAL LANGUAGE PROCESSING" has been successfully completed by SHUNMUGA PRIYA R (142223128045), SRIMATHI V (142223128048), VISHWAA A (142223128057) of B.E. - Cyber Security, during the academic year 2025-26. This project aligns with the United Nations Sustainable Development Goals and mapped to the following Sustainable Development Goal(s) (SDGs):

SDG Number	Name	Brief Justification
9	Industry, Innovation And Infrastructure	The project promotes secure mobile application infrastructure using NLP-based permission analysis to improve Android app security and privacy protection.
16	Peace, Justice and Strong Institutions	The project strengthens digital safety by detecting risky app permissions, preventing privacy threats, and supporting safer mobile environments.



Build resilient infrastructure, promote inclusive and sustainable industrialization and foster innovation



Promote peaceful and inclusive societies for sustainable development

PROJECT SUPERVISOR

CES COORDINATOR

HOD/CYS



SRM Nagar, Kattankulathur - 603203, Chengalpattu District, Tamil Nadu, India

Phone : 044 - 27454784, 27454726 & 27451498 Fax : 044 - 27451504

Website : www.srmvalliammai.ac.in Email: srmvec@srmvalliammai.ac.in

SURVEY ON A SECURE MOBILE APPLICATION PERMISSION ANALYZER USING NATURAL LANGUAGE PROCESSING

Ms. M. RAGHAVI

Department of Cybersecurity
SRM Valliammai Engineering College
Chengalpattu, India
raghavirgo@gmail.com

SHUNMUGA PRIYA. R

Department of Cybersecurity
SRM Valliammai Engineering College
Chengalpattu, India
shunmugapriyaradha2022@gmail.com

SRIMATHI. V

Department of Cybersecurity
SRM Valliammai Engineering College
Chengalpattu, India
srimathisrimathi089@gmail.com

Abstract Many Android applications have quickly grown in popularity, leading to a substantial rise in the need for safe management of user data and permissions. Sensitive resources like location, contacts, storage and hardware device are often requested by modern applications. There are some applications that require permissions that aren't needed for the app to operate, posing severe privacy concerns; data leakage and the threat of misuse of personal data. Static and dynamic analysis are examples of existing traditional security mechanisms which fail to provide the contextual meaning behind permission usage. With all its challenges, on the other hand, Natural Language Processing (NLP) and Large Language Models (LLMs), in general, are becoming a powerful tool to analyse textual data like app description or privacy policy or user reviews. These methods help in understanding the intent behind permissions, finding inconsistencies, and potential risks or threats. The survey deeply analyses NLP-based techniques for permission risk assessment mechanism including classification, policy mapping, anomaly detection, compliance verification as well as tools to perform explainable AI models and frameworks for scoring risks..

Keywords - NLP, Android Security, Permissions, Risk Analysis, Privacy, LLM, Mobile Security

I. INTRODUCTION

On one hand, Android platform has evolved into one of the most influential mobile apps ecosystems, supporting Billions of users and millions of Apps. Android Apps need to declare multiple permissions for accessing system resources and provide the functionality and user experience. However, the rapid growth of application brings on the consequence of permission misuse, in other words, requesting access to resources that are unreasoned for the functionality of the Apps.

To overcome this issue, works utilize static code analysis [3] and dynamic apps analysis [4] are proposed, which address the problem by expose the technical behaviour of Apps. But they fail to explore the semantic correlation between the permissions required and the functional descriptions of them. To address this issue, a new branch of research emerged so-called Natural Language Processing (NLP) models, attempts to infer the purpose of permissions by analysing app descriptions [6] and privacy policy [5], [1].

In addition, the following technologies have matured in recent years—pre-trained NLP models [2], Large Language Models [7], permission-purpose inference [10]. Furthermore, NLP models can mining in app descriptions from adversarial, which benefit to reveal hidden interrelationship among app

descriptions . According to natural-language-guided framework [8], extracting contextualized semantics info has vastly improved decision-making strategies in risk assessments. Currently, projects focusing on NLP methods used for permission risk analysis in applications face a severe lack of experiences and summaries. Therefore, this survey has been encouraged.

II. RELATED WORK

Initially, research on Android permissions protection focused on rule-based systems and statistical analysis to identify suspicious permissions [4]. These methods using predefined rules were inflexible and could not adapt to new patterns. With rule-based systems, traditional machine learning approaches that leverage data-driven permission analysis captured better performance than static rules. However, most data-driven models can be hindered by unstructured features.

NLP-based approaches utilized the textual information of permissions to improve the analysis. Several systems used NLP-assisted anomaly detection to analyse large-scale app datasets (including permission reports, network communications, and providers) for identifying anomalous permission patterns in applications [6]. Auditing framework designed to detect excessive and misleading permission usage (whose goal is to ensure rigorous privacy analysis) . Apps on Apple store collected tremendous permissions data which were essential for privacy policy analysis. User-review models analysing user feedback could identify the privacy wrongdoing and data abuse related to applications [12].

NLP models that working on cross-lingual corpora could achieve algorithms for different languages and regions. However, some current problems still need to be put into efforts, such as inconsistent privacy policies, non-explainability, and high computing power needed.

III. LITERATURE SURVEY

A. NLP-Based Permission Risk Analysis

NLP-based permission risk analysis studies the textual data and permission usage relationship. Basic NLP models perform text classification that determines whether a permission request is appropriate or suspicious [1]. Such models analyse keyword usage, sentence structure and semantic knowledge, which can infer potential risk of permission requests. Nonetheless, simple classification techniques cannot effectively capture complex, non-linear relationships between permission request and app functionality. To overcome this limitation, techniques such as

permission pair risk analysis have been proposed for investigating permission pair wise co-occurrence. These techniques look for patterns of disparate permission co-relations that would indicate a dangerous permission combination [3]. For example, while location and microphone permissions could both be dangerous, their combination presents an even more serious problem. Fine-grained classification models further improve analysis by considering multiple contextual knowledge, such as semantic similarity, app category and user age expectation [15]. Such classification models are more precise to divide permission risks into various groups. A risk scoring system designates permissions a value based on relevance, load to the user, and level of threat, providing enumerated measures of permissions for better application and comparison [14]. These scores enable users to compare application permissions and to prioritize the risk levels of applications accordingly, thus supporting awareness and perception of risks.

B. LLM and Transformer-Based Analysis

Transformer architectures have gained huge successes in NLP. Such models support long dependence extraction of textual data and facilitate deep contextual understanding of app description and privacy policies. Attention mechanism enable these models to find significance of all words in app descriptions regarding to each other within a sentence, producing better ground for contextual understanding. LLMs extend such deep contextual learning capability by large-scale dataset analysis, thus revealing the app permission purpose and surmising inexplicability in given text and actual permission history [2]. Explainable NLP classifiers enhance understanding by revealing factors that affect model decisions and why a permission is hazardous. Such models help increase trust and support users' ability to understand what a given model is explaining [5]. Transformer-based pipelines could fully automate several tasks involved in permission risk analysis, such as app description interpretation, feature extraction and classifying. The Natural-language-guided approaches make the models base on contextual reasoning, facilitating high performance and accuracy [8].

C. Permission-Policy Mapping and Supervision

Permission-policy mapping monitors the harmony of permissions across apps and privacy policies. NLP-based techniques extract relevant information from policies for further comparison with app declaration permissions [7]. Verification method compares application descriptions and program codes, pinpointing if such application by description is the same as application behaviour [13]. This method has high accuracy and can be applied in the future to make app declarations more transparent by controlling malicious desires in application behaviour. Empowering such process with a permission-privacy annotation system can make the inherent relationship of permissions clearer and more user-friendly, which can thus reduce app disclosure pace and facilitate privacy protections. Comparison system helps regulate app applications systems that adhere to the permission requests process and the relevant regulations and security stipulations, thus enacting transparency accountability [9].

D. Permission Anomaly and Privacy Violation Detection

Anomaly detection methodologies survey the suspicious permission requests appearing in bulk applications by comparing the perceived application, description, privacy policies and permissions with actual performance [6]. The framework of auditing consider the programs permission anomalies, which refer to excess, anomalistic and illicit permission requests. User-review analysis work with permission anomaly detection in order to effectively pinpoint privacy-damaging application permissions [12].

E. Cross-Language, Multi-Source Textual Data Analysis

An additional difficulty to be mentioned would be the non-uniformity of languages. Cross-language models allow the analysis of applications speaking different languages and lowering limits of scalability and universality. Multisource analysis of app description, privacy policy and user reviews enhances detection results in multiple angles, thus improving detection degree and lowering rate of false-positives[11].

F. Permission Risk Scoring and Applications Recommendation System

Permission risk scores facilitated the comparison across application permission lists and ranking of applications based on quality and security scores [14]. Such scores could be used to recommend reliable apps and exclude risky apps [16].

Table 1: Comparison of NLP-Based Permission Analysis Techniques.

Category	Method	Key Idea	Advantage	Limitation
NLP Analysis	Text Processing	Detect risky permissions	Simple and fast	Limited context
LLM Models	Deep Learning	Understand permission intent	High accuracy	High computational cost
Policy Mapping	NLP Matching	Ensure policy consistency	Improves trust	Depends on policy quality
Anomaly Detection	Pattern Analysis	Detect unusual behavior	Effective detection	Sensitive to noisy data
Risk Scoring	Scoring Model	Rank applications by risk	Easy decision-making	Requires tuning

G. Challenges in NLP-Focused Permission Risk Detection

Despite these progresses, the availability of high-quality data remains a limitation. Privacy policies are often ambiguous, unreliable and may contain information gaps, which influences the precision of aforementioned models. Multilingual processing is also of difficulty, for translation errors and information loss have great impact on the models' performance. Moreover, transformer-based models and LLMs need significant computational resources, restricting their application

in area like real-time system monitoring. A pressing issue to be addressed are end-to-end automated models that maintain high accuracy while providing human interpretable results.

H. Future Research Directions in NLP-Based Permission Risk Detection

It is needed to come up with more powerful lightweight and cost-effective models that can run in real time environments. Persistent effort should be put in improving the multilingual capabilities of models. Additionally, integrating NLP with behavioural analysis and other method such as networks checking will be valuable in creating a full strategy to protect user's data from apps.

I. Explainable NLP Models for Permission Risk Analysis

Lack of domain knowledge of end user is one of the biggest challenge in permission risk analysis. Conventional machine learning and deep learning models (neural network based models) are black-box based model which is a serious problem especially in mobile security where wrong classification of app results in either risk to user or false positive app flagging. To overcome such problem, explainable NLP models have been introduced as one of the important advancements in permission analysis system. Explainability-based NLP models identify important words, phrases or sentences in app description, privacy policy along with other features, thus help to identify the factors responsible for risk classification [5]. For example, if an app uses location based services but user privacy policy does not talk about location based services, then explainability based model can mark that aspect as one of the reasons for high risk.

Explainability based NLP also improves the usability of system for application developers and security analysts as they can verify the model predictions. It also helps the developers to understand the areas they need to work on to develop a better application and met best security practices. Developers can use those explanations to improve application design and be assured that they are not wrongly flagged as risky app. It also helps in debugging and improving classification performance of NLP models as developer can debug wrong classification and take necessary measures. Explainability also helps in complying to regulations as recent emphasis on transparent decisions of NLP models mandate for explainability of the system.

Overall, explainability based NLP models Improve Trust, accuracy and reliability of permission risk analysis system.

J. Permission-Purpose Inference Using NLP

Asking permission is an important capabilities that new generation of NLP models has brought in mobile security systems. However, permission inference is not sufficient to identify risk class of application, and the importance of permission purpose inference is also vital to accurately determine whether permission requested is necessary for app's functioning or not. NLP models analyse app description, privacy policy and developer notes to infer the application context of permission use, thus put application requesting unnecessary permission in unsecure category [10]. Large language models (LLMs) are one of the best encoders for extracting application

context from textual data in mobile security domain as they are capable of mapping long dependencies between words.

For example, need for location access when the application is updating traffic updates is considered essential whereas the same permission request for home automation application seems unnecessary. Hence, context-aware analysis of permission purpose through NLP becomes crucial. Permission inference models identify mismatch between privacy policy and app description, thus helps in avoiding apps with inconsistent describes app functionality [7]. Besides, these models analyse vast set of app data and extract essential permission usage patterns helpful for identifying risky apps [11], thus help in building baseline for conventional anomaly detection techniques.

Permission-purpose inference analysis also helps in identifying implicit functionality, for example, app uses certain permission but developer description does not mention anywhere that functionality. Identifying such gaps through NLP leads to better risk inference.

Combining permission-purpose inference results with anomaly detection or risk scoring techniques leads to better overall permission risk analysis.

K. Fine-Grained Permission Classification

Permission classification models typically categorize permissions into safe or unsecure category. These methods are unable to handle modern app complexities, which require to classify permission into multiple categories is a better way. Fine grained permission classification methods take multiple features as input and classify permissions based on multiple levels like low, medium, high and critical categories depending on context, sensitivity etc. [15]. Permission-pair analysis techniques analyse multiple combinations of permissions together to correctly classify the overall permission pair despite individual permission appear safe or harmful when considered alone. For example, internet access and contact access permission pair in combination can help data leakage. General fine-grained risk identification is an key advancement of such techniques as they take advantage of contextual probability-aware classification [3].

Dynamic permission classification techniques adjust permission classification level depending on contextual location of app. For example, permission level of GPS access may be different for gaming and map applications. These techniques are more user friendly and provide interpretable and detailed insight of why a particular permission is classified as high/medium/low risk level to help users make safe decision.

L. NLP-Based Compliance and Policy Verification

Compliance is a critical component of gaining user confidence and should be an integral part of any permission analysis system. NLP techniques help extracting relevant information from user privacy policy and comparing it with permission requests to identify violations [7]. Besides, compatibility among app description, privacy policy and permission use can be studied through non-straightforward NLP techniques to

flagged apps which provide misleading information and go against privacy regulations. This will help avoid regulatory violations and improve user trust in app store environment [9]. Automated auditing of large set of apps for identifying privacy or security violation thanks to combination of unstructured data analysis with structured permission data can help large app store efficiently provide quality review [13].

M. Permission anomaly detection at large scales of apps

Finding anomalies at large scale of apps needs combination of structured data analysis together with unstructured data analysis. For example, app or developer specific permission analysis can be planned in conjunction with permission for infrastructure or app-store statistics. Large variety of unknown apps analysis for permission anomalies identifies deviation from category defined common trends thus finds anomalies [6]. Auditing techniques based on combination of unstructured and structured data analysis identify redundant or noisy permissions thus help in combating privacy risks and eliminate malicious apps .

N. Use of User reviews to study privacy violations:

User reviews also contain information about app behaviour in terms of privacy and security. Sentiment analysis using NLP studies the overall feeling of user communities regarding an app to identify apps which have security issues. Topic modelling techniques studies topics discussed in various user reviews and helps in finding places where privacy is compromised [12].

O. Cross language models-NLP based app description analysis in different languages

NLP models analysing app description and privacy policy should be robust across languages so that all apps can be analysed using an unified system.

P. Risk scoring and decision support systems

Rank calculation of apps based on permission use will help user in choosing safer apps. Decision support tools help users avoid risky apps and choose appropriate and safe app [14],[16].

Q. Use of multiple sources for permission analysis

Use of unstructured data sources such as app description, privacy policy in conjunction with structured data sources is an important trend in permission analysis system development [11]. The overall workflow of the permission risk analysis system is shown in Fig. 1.




Fig. 1: NLP-Based Permission Risk Analysis System Architecture

IV.CONCLUSION

This review summarizes NLP focused techniques in Android permission risk detection. The application of NLP, especially the widely-used transformer-based models and LLMs, significantly boosts the accuracy and efficiency of detect-and-flag. The techniques reveals deeper understanding of permission usage and app contents. In addition to the deep insight allowed by a greater understanding of app permission usages and app content. These models even enable semi-automated app analysis involving app description parsing and feature extracting. Challenges include lack of sufficient data, computational costs and multilingual hurdles. Future directions should aim to systematically build models of high accuracy, interpretability and cross-categorical application.

V.REFERENCE

- [1]H. Hu, W. Minn, Y. Liu, J. Liu, F. Thung, T. Y. Zhuo, L. K. Shar, D. Gao, and D. Lo, "Bamboo: Large Language Model Driven Discovery of Application Programming Interface Permission Mappings in the Android Framework," IEEE Access, vol. 13, pp. 1–18, 2025.
- [2] R. Y. Mawoh, J. B. A. Wacka, F. Tchakounte, C. Fachkha, and Kolyang, "An Accurate Approach to Discriminate Android Colluded Malware From Single App Malware Using Permissions Intelligence," Scientific Reports, vol. 15, pp. 1–21, 2025.
- [3] A. Prasad, S. Chandra, M. Uddin, T. Al-Shehari, N. A. Alsadhan, and S. U. Sajid, "PermGuard: A Scalable Framework for Android Malware Detection Using Permission-to-Exploitation Mapping," IEEE Access, vol. 13, pp. 1–22, 2025.
- [4] A. Sabbah, R. Jarrar, S. Zein, and D. Mohaisen, "Understanding Concept Drift With Deprecated Permissions in Android Malware Detection," IEEE Access, vol. 13, pp. 1–17, 2025.
- [5] E. Aydogan and S. Sen, "Android Authorship Attribution Using Source Code-Based Features," IEEE Access, vol. 12, pp. 6569–6589, 2024.
- [6] F. S. Atedjio, J. P. Lienou, F. F. Nelson, S. S. Shetty, and C. A. Kamhoua, "A Defensive Strategy Against Android Adversarial Malware Attacks," IEEE Access, vol. 12, pp. 169432–169441, 2024.
- [7] F. S. Atedjio, J. P. Lienou, F. F. Nelson, S. S. Shetty, and C. A. Kamhoua, "Cycle Generative Adversarial Network Gradient Penalty for Enhancing Android Adversarial Malware Detection in Gray Box Setting," IEEE Access, vol. 12, pp. 162685–162696, 2024.

- [8] G. S. Tuncay, “Android Permissions: Evolution, Attacks, and Best Practices,” *IEEE Security and Privacy*, vol. 22, no. 6, pp. 40–49, Sep. 2024.
- [9] M. Rafid Islam, “Diagnosing and Mitigating Domain Shift in Permission-Based Android Malware Detection,” *IEEE Access*, vol. 14, pp. 1–15, 2026.
- [10] A. Banik and J. P. Singh, “A BERT and Particle Swarm Optimization Framework for Android Malware Detection Using Real Permissions and Application Programming Interface Calls,” *Discover Computing*, vol. 29, pp. 1–20, 2026.
- [11] F. S. Alsubaie, A. A. Almazroi, W. S. Atwa, A. A. Almazroi, N. Ayub, and N. Z. Jhanjhi, “BERT Ensemble Based MBR Framework for Android Malware Detection,” *Scientific Reports*, vol. 15, pp. 1–18, 2025.
- [12] R. Li, W. Diao, and D. Gao, “Custom Permission Misconfigurations in Android: A Large-Scale Security Analysis,” in *Proceedings of the 2024 IEEE International Conference on Trust, Security and Privacy in Computing and Communications*, pp. 1161–1170, 2024.
- [13] S. Saleem, J. Mišić, and V. B. Mišić, “An Effective Temporal Convolutional Networks-Based Method for Detecting Android Malware Using Dynamic Extracted Features,” *IEEE Access*, vol. 13, pp. 49891–49904, 2025.
- [14] T. Sutter, T. Kehrler, M. Rennhard et al., “Dynamic Security Analysis on Android: A Systematic Literature Review,” *IEEE Access*, vol. 12, pp. 57261–57287, 2024.
- [15] W. Wang et al., “Exploring Permission-Induced Risk in Android Applications for Malicious Application Detection,” *IEEE Transactions on Information Forensics and Security*, vol. 9, no. 11, pp. 1869–1882, Nov. 2014.
- [16] F. Leveni, M. Mistura, F. Iubatti, C. Giangregorio, N. Pastore, C. Alippi, and G. Boracchi, “Malware Families Discovery via Open-Set Recognition on Android Manifest Permissions,” pp. 1–12, 2025.

Manish Kumar

Share Updated Survey Paper -1

 Dr.

Document Details

Submission ID

trn:oid::15912:136893735

Submission Date

Apr 28, 2026, 1:35 PM GMT+5:30

Download Date

Apr 28, 2026, 1:46 PM GMT+5:30

File Name

Share Updated Survey Paper -1.docx

File Size

205.1 KB

5 Pages

3,204 Words

19,952 Characters

*% detected as AI

AI detection includes the possibility of false positives. Although some text in this submission is likely AI generated, scores below the 20% threshold are not surfaced because they have a higher likelihood of false positives.

Caution: Review required.

It is essential to understand the limitations of AI detection before making decisions about a student's work. We encourage you to learn more about Turnitin's AI detection capabilities before using the tool.

Disclaimer

Our AI writing assessment is designed to help educators identify text that might be prepared by a generative AI tool. Our AI writing assessment may not always be accurate (i.e., our AI models may produce either false positive results or false negative results), so it should not be used as the sole basis for adverse actions against a student. It takes further scrutiny and human judgment in conjunction with an organization's application of its specific academic policies to determine whether any academic misconduct has occurred.

Frequently Asked Questions

How should I interpret Turnitin's AI writing percentage and false positives?

The percentage shown in the AI writing report is the amount of qualifying text within the submission that Turnitin's AI writing detection model determines was either likely AI-generated text from a large-language model or likely AI-generated text that was likely revised using an AI paraphrase tool or word spinner.

False positives (incorrectly flagging human-written text as AI-generated) are a possibility in AI models.

AI detection scores under 20%, which we do not surface in new reports, have a higher likelihood of false positives. To reduce the likelihood of misinterpretation, no score or highlights are attributed and are indicated with an asterisk in the report (*%).

The AI writing percentage should not be the sole basis to determine whether misconduct has occurred. The reviewer/instructor should use the percentage as a means to start a formative conversation with their student and/or use it to examine the submitted assignment in accordance with their school's policies.

What does 'qualifying text' mean?

Our model only processes qualifying text in the form of long-form writing. Long-form writing means individual sentences contained in paragraphs that make up a longer piece of written work, such as an essay, a dissertation, or an article, etc. Qualifying text that has been determined to be likely AI-generated will be highlighted in cyan in the submission, and likely AI-generated and then likely AI-paraphrased will be highlighted purple.

Non-qualifying text, such as bullet points, annotated bibliographies, etc., will not be processed and can create disparity between the submission highlights and the percentage shown.



SURVEY ON A SECURE MOBILE APPLICATION PERMISSION ANALYZER USING NATURAL LANGUAGE PROCESSING

Ms. M. RAGHAVI

Department of Cybersecurity
SRM Valliammai Engineering College
Chengalpattu, India
raghavirgo@gmail.com

SHUNMUGA PRIYA. R

Department of Cybersecurity
SRM Valliammai Engineering College
Chengalpattu, India
shunmugapriyaradha2022@gmail.com

SRIMATHI. V

Department of Cybersecurity
SRM Valliammai Engineering College
Chengalpattu, India
srimathisrimathi089@gmail.com

Abstract Many Android applications have quickly grown in popularity, leading to a substantial rise in the need for safe management of user data and permissions. Sensitive resources like location, contacts, storage and hardware device are often requested by modern applications. There are some applications that require permissions that aren't needed for the app to operate, posing severe privacy concerns; data leakage and the threat of misuse of personal data. Static and dynamic analysis are examples of existing traditional security mechanisms which fail to provide the contextual meaning behind permission usage. With all its challenges, on the other hand, Natural Language Processing (NLP) and Large Language Models (LLMs), in general, are becoming a powerful tool to analyse textual data like app description or privacy policy or user reviews. These methods help in understanding the intent behind permissions, finding inconsistencies, and potential risks or threats. The survey deeply analyses NLP-based techniques for permission risk assessment mechanism including classification, policy mapping, anomaly detection, compliance verification as well as tools to perform explainable AI models and frameworks for scoring risks.

Keywords - NLP, Android Security, Permissions, Risk Analysis, Privacy, LLM, Mobile Security

I. INTRODUCTION

On one hand, Android platform has evolved into one of the most influential mobile apps ecosystems, supporting Billions of users and millions of Apps. Android Apps need to declare multiple permissions for accessing system resources and provide the functionality and user experience. However, the rapid growth of application brings on the consequence of permission misuse, in other words, requesting access to resources that are unreasoned for the functionality of the Apps.

To overcome this issue, works utilize static code analysis [3] and dynamic apps analysis [4] are proposed, which address the problem by expose the technical behaviour of Apps. But they fail to explore the semantic correlation between the permissions required and the functional descriptions of them. To address this issue, a new branch of research emerged so-called Natural Language Processing (NLP) models, attempts to infer the purpose of permissions by analysing app descriptions [6] and privacy policy [5], [1].

In addition, the following technologies have matured in recent years—pre-trained NLP models [2], Large Language Models [7], permission-purpose inference [11]. Furthermore, NLP models can mining in app descriptions from adversarial, which benefit to reveal hidden interrelationship among app descriptions [10]. According to natural-language-guided

framework [8], extracting contextualized semantics info has vastly improved decision-making strategies in risk assessments. Currently, projects focusing on NLP methods used for permission risk analysis in applications face a severe lack of experiences and summaries. Therefore, this survey has been encouraged.

II. RELATED WORK

Initially, research on Android permissions protection focused on rule-based systems and statistical analysis to identify suspicious permissions [4]. These methods using predefined rules were inflexible and could not adapt to new patterns. With rule-based systems, traditional machine learning approaches that leverage data-driven permission analysis captured better performance than static rules. However, most data-driven models can be hindered by unstructured features.

NLP-based approaches utilized the textual information of permissions to improve the analysis. Several systems used NLP-assisted anomaly detection to analyse large-scale app datasets (including permission reports, network communications, and providers) for identifying anomalous permission patterns in applications [6]. Auditing framework designed to detect excessive and misleading permission usage (whose goal is to ensure rigorous privacy analysis) [10]. Apps on Apple store collected tremendous permissions data which were essential for privacy policy analysis. User-review models analysing user feedback could identify the privacy wrongdoing and data abuse related to applications [14].

NLP models that working on cross-lingual corpora could achieve algorithms for different languages and regions. However, some current problems still need to be put into efforts, such as inconsistent privacy policies, non-explainability, and high computing power needed.

III. LITERATURE SURVEY

A. NLP-Based Permission Risk Analysis

NLP-based permission risk analysis studies the textual data and permission usage relationship. Basic NLP models perform text classification that determines whether a permission request is appropriate or suspicious [1]. Such models analyse keyword usage, sentence structure and semantic knowledge, which can infer potential risk of permission requests. Nonetheless, simple classification techniques cannot effectively capture complex, non-linear relationships between permission request and app functionality. To overcome this limitation, techniques such as permission pair risk analysis have been proposed for

investigating permission pair wise co-occurrence. These techniques look for patterns of disparate permission co-relations that would indicate a dangerous permission combination [3]. For example, while location and microphone permissions could both be dangerous, their combination presents an even more serious problem. Fine-grained classification models further improve analysis by considering multiple contextual knowledge, such as semantic similarity, app category and user age expectation [18]. Such classification models are more precise to divide permission risks into various groups. A risk scoring system designates permissions a value based on relevance, load to the user, and level of threat, providing enumerated measures of permissions for better application and comparison [16]. These scores enable users to compare application permissions and to prioritize the risk levels of applications accordingly, thus supporting awareness and perception of risks.

B. LLM and Transformer-Based Analysis

Transformer architectures have gained huge successes in NLP. Such models support long dependence extraction of textual data and facilitate deep contextual understanding of app description and privacy policies. Attention mechanism enable these models to find significance of all words in app descriptions regarding to each other within a sentence, producing better ground for contextual understanding. LLMs extend such deep contextual learning capability by large-scale dataset analysis, thus revealing the app permission purpose and surmising inexplicability in given text and actual permission history [2]. Explainable NLP classifiers enhance understanding by revealing factors that affect model decisions and why a permission is hazardous. Such models help increase trust and support users' ability to understand what a given model is explaining [5]. Transformer-based pipelines could fully automate several tasks involved in permission risk analysis, such as app description interpretation, feature extraction and classifying [17]. The Natural-language-guided approaches make the models base on contextual reasoning, facilitating high performance and accuracy [8].

C. Permission-Policy Mapping and Supervision

Permission-policy mapping monitors the harmony of permissions across apps and privacy policies. NLP-based techniques extract relevant information from policies for further comparison with app declaration permissions [7]. Verification method compares application descriptions and program codes, pinpointing if such application by description is the same as application behaviour [15]. This method has high accuracy and can be applied in the future to make app declarations more transparent by controlling malicious desires in application behaviour. Empowering such process with a permission-privacy annotation system can make the inherent relationship of permissions clearer and more user-friendly, which can thus reduce app disclosure pace and facilitate privacy protections. Comparison system helps regulate app applications systems that adhere to the permission requests process and the relevant regulations and security stipulations, thus enacting transparency accountability [9].

D. Permission Anomaly and Privacy Violation Detection

Anomaly detection methodologies surveil the suspicious permission requests appearing in bulk applications by comparing the perceived application, description, privacy policies and permissions with actual performance [6]. The framework of auditing consider the programs permission anomalies, which refer to excess, anomalistic and illicit permission requests [10]. User-review analysis work with permission anomaly detection in order to effectively pinpoint privacy-damaging application permissions [14].

E. Cross-Language, Multi-Source Textual Data Analysis

An additional difficulty to be mentioned would be the non-uniformity of languages. Cross-language models allow the analysis of applications speaking different languages and lowering limits of scalability and universality [13]. Multisource analysis of app description, privacy policy and user reviews enhances detection results in multiple angles, thus improving detection degree and lowering rate of false-positives[12].

F. Permission Risk Scoring and Applications Recommendation System

Permission risk scores facilitated the comparison across application permission lists and ranking of applications based on quality and security scores [16]. Such scores could be used to recommend reliable apps and exclude risky apps [19].

Table 1: Comparison of NLP-Based Permission Analysis Techniques.

Category	Method	Key Idea	Advantage	Limitation
NLP Analysis	Text Processing	Detect risky permissions	Simple and fast	Limited context
LLM Models	Deep Learning	Understand permission intent	High accuracy	High computational cost
Policy Mapping	NLP Matching	Ensure policy consistency	Improves trust	Depends on policy quality
Anomaly Detection	Pattern Analysis	Detect unusual behavior	Effective detection	Sensitive to noisy data
Risk Scoring	Scoring Model	Rank applications by risk	Easy decision-making	Requires tuning

G. Challenges in NLP-Focused Permission Risk Detection

Despite these progresses, the availability of high-quality data remains a limitation. Privacy policies are often ambiguous, unreliable and may contain information gaps, which influences the precision of aforementioned models. Multilingual processing is also of difficulty, for translation errors and information loss have great impact on the models' performance. Moreover, transformer-based models and LLMs need significant computational resources, restricting their application in area like real-time system monitoring. A pressing issue to be addressed are end-to-end automated models that maintain high accuracy while providing human interpretable results.

H. Future Research Directions in NLP-Based Permission Risk Detection

It is needed to come up with more powerful lightweight and cost-effective models that can run in real time environments. Persistent effort should be put in improving the multilingual capabilities of models. Additionally, integrating NLP with behavioral analysis and other method such as networks checking will be valuable in creating a full strategy to protect user's data from apps.

I. Explainable NLP Models for Permission Risk Analysis

Lack of domain knowledge of end user is one of the biggest challenge in permission risk analysis. Conventional machine learning and deep learning models (neural network based models) are black-box based model which is a serious problem especially in mobile security where wrong classification of app results in either risk to user or false positive app flagging. To overcome such problem, explainable NLP models have been introduced as one of the important advancements in permission analysis system. Explainability-based NLP models identify important word(s), phrase(s) or sentence(s) in app description, privacy policy along with other features, thus help to identify the factors responsible for risk classification [5]. For example, if an app uses location based services but user privacy policy does not talk about location based services, then explainability based model can mark that aspect as one of the reasons for high risk.

Explainability based NLP also improves the usability of system for application developers and security analysts as they can verify the model predictions. It also helps the developers to understand the areas they need to work on to develop a better application and met best security practices. Developers can use those explanations to improve application design and be assured that they are not wrongly flagged as risky app. It also helps in debugging and improving classification performance of NLP models as developer can debug wrong classification and take necessary measures. Explainability also helps in complying to regulations as recent emphasis on transparent decisions of NLP models mandate for explainability of the system.

Overall, explainability based NLP models Improve Trust, accuracy and reliability of permission risk analysis system.

J. Permission-Purpose Inference Using NLP

Asking permission is an important capabilities that new generation of NLP models has brought in mobile security systems. However, permission inference is not sufficient to identify risk class of application, and the importance of permission purpose inference is also vital to accurately determine whether permission requested is necessary for app's functioning or not. NLP models analyse app description, privacy policy and developer notes to infer the application context of permission use, thus put application requesting unnecessary permission in unsecure category [11]. Large language models (LLMs) are one of the best encoders for extracting application context from textual data in mobile security domain as they are capable of mapping long dependencies between words.

For example, need for location access when the application is updating traffic updates is considered essential whereas the same permission request for home automation application seems unnecessary. Hence, context-aware analysis of permission purpose through NLP becomes crucial. Permission inference models identify mismatch between privacy policy and app description, thus helps in avoiding apps with inconsistent describes app functionality [7]. Besides, these models analyse vast set of app data and extract essential permission usage patterns helpful for identifying risky apps [12], thus help in building baseline for conventional anomaly detection techniques.

Permission-purpose inference analysis also helps in identifying implicit functionality, for example, app uses certain permission but developer description does not mention anywhere that functionality. Identifying such gaps through NLP leads to better risk inference.

Combining permission-purpose inference results with anomaly detection or risk scoring techniques leads to better overall permission risk analysis.

K. Fine-Grained Permission Classification

Permission classification models typically categorize permissions into safe or unsecure category. These methods are unable to handle modern app complexities, which require to classify permission into multiple categories is a better way. Fine grained permission classification methods take multiple features as input and classify permissions based on multiple levels like low, medium, high and critical categories depending on context, sensitivity etc. [18]. Permission-pair analysis techniques analyse multiple combinations of permissions together to correctly classify the overall permission pair despite individual permission appear safe or harmful when considered alone. For example, internet access and contact access permission pair in combination can help data leakage. General fine-grained risk identification is an key advancement of such techniques as they take advantage of contextual probability-aware classification [3].

Dynamic permission classification techniques adjust permission classification level depending on contextual location of app. For example, permission level of GPS access may be different for gaming and map applications. These techniques are more user friendly and provide interpretable and detailed insight of why a particular permission is classified as high/medium/low risk level to help users make safe decision.

L. NLP-Based Compliance and Policy Verification

Compliance is a critical component of gaining user confidence and should be an integral part of any permission analysis system. NLP techniques help extracting relevant information from user privacy policy and comparing it with permission requests to identify violations [7]. Besides, compatibility among app description, privacy policy and permission use can be studied through non-straightforward NLP techniques to flagged apps which provide misleading information and go against privacy regulations. This will help avoid regulatory violations and improve user trust in app store environment [9]. Automated

auditing of large set of apps for identifying privacy or security violation thanks to combination of unstructured data analysis with structured permission data can help large app store efficiently provide quality review [15].

M. Permission anomaly detection at large scales of apps

Finding anomalies at large scale of apps needs combination of structured data analysis together with unstructured data analysis. For example, app or developer specific permission analysis can be planned in conjunction with permission for infrastructure or app-store statistics. Large variety of unknown apps analysis for permission anomalies identifies deviation from category defined common trends thus finds anomalies [6]. Auditing techniques based on combination of unstructured and structured data analysis identify redundant or noisy permissions thus help in combating privacy risks and eliminate malicious apps [10].

N. Use of User reviews to study privacy violations:

User reviews also contain information about app behaviour in terms of privacy and security. Sentiment analysis using NLP studies the overall feeling of user communities regarding an app to identify apps which have security issues. Topic modelling techniques studies topics discussed in various user reviews and helps in finding places where privacy is compromised [14].

O. Cross language models-NLP based app description analysis in different languages

NLP models analysing app description and privacy policy should be robust across languages so that all apps can be analysed using an unified system.

P. Risk scoring and decision support systems

Rank calculation of apps based on permission use will help user in choosing safer apps. Decision support tools help users avoid risky apps and choose appropriate and safe app [16].

Q. Use of multiple sources for permission analysis

Use of unstructured data sources such as app description, privacy policy in conjunction with structured data sources is an important trend in permission analysis system development [12]. The overall workflow of the permission risk analysis system is shown in Fig. 1.



Fig. 1: NLP-Based Permission Risk Analysis System Architecture

IV. CONCLUSION

This review summarizes NLP focused techniques in Android permission risk detection. The application of NLP, especially the widely-used transformer-based models and LLMs, significantly boosts the accuracy and efficiency of detect-and-flag. The techniques reveals deeper understanding of permission usage and app contents. In addition to the deep insight allowed by a greater understanding of app permission usages and app content. These models even enable semi-automated app analysis involving app description parsing and feature extracting. Challenges include lack of sufficient data, computational costs and multilingual hurdles. Future directions should aim to systematically build models of high accuracy, interpretability and cross-centric application.

V. REFERENCE

- [1] H. Hu, W. Minn, Y. Liu, J. Liu, F. Thung, T. Y. Zhuo, L. K. Shar, D. Gao, and D. Lo, "Bamboo: Large Language Model Driven Discovery of Application Programming Interface Permission Mappings in the Android Framework," IEEE Access, vol. 13, pp. 1–18, 2025.
- [2] R. Y. Mawoh, J. B. A. Wacka, F. Tchakounte, C. Fachkha, and K. Oyang, "An Accurate Approach to Discriminate Android Colluded Malware From Single App Malware Using Permissions Intelligence," Scientific Reports, vol. 15, pp. 1–21, 2025.
- [3] A. Prasad, S. Chandra, M. Uddin, T. Al-Shahari, N. A. Alsaadkan, and S. U. Sajid, "PermGuard: A Scalable Framework for Android Malware Detection Using Permission-to-Exploitation Mapping," IEEE Access, vol. 13, pp. 1–22, 2025.
- [4] A. Sabbah, R. Jarrar, S. Zein, and D. Mohaisen, "Understanding Concept Drift With Deprecated Permissions in Android Malware Detection," IEEE Access, vol. 13, pp. 1–17, 2025.
- [5] E. Aydogan and S. Sen, "Android Authorship Attribution Using Source Code-Based Features," IEEE Access, vol. 12, pp. 6569–6589, 2024.
- [6] F. S. Atadijo, J. P. Lisnou, F. F. Nelson, S. S. Shetty, and C. A. Kamhoua, "A Defensive Strategy Against Android Adversarial Malware Attacks," IEEE Access, vol. 12, pp. 169432–169441, 2024.
- [7] F. S. Atadijo, J. P. Lisnou, F. F. Nelson, S. S. Shetty, and C. A. Kamhoua, "Cycle Generative Adversarial Network Gradient Penalty for Enhancing Android Adversarial Malware Detection in Gray Box Setting," IEEE Access, vol. 12, pp. 162685–162696, 2024.
- [8] G. S. Tuncay, "Android Permissions: Evolution, Attacks, and Best Practices," IEEE Security and Privacy, vol. 22, no. 6, pp. 40–49, Sep. 2024.
- [9] M. Rafid Islam, "Diagnosing and Mitigating Domain Shift in Permission-Based Android Malware Detection," IEEE Access, vol. 14, pp. 1–15, 2026.
- [10] A. Banik and J. P. Singh, "A BERT and Particle Swarm Optimization Framework for Android Malware Detection Using Real Permissions

and Application Programming Interface Calls,” *Discover Computing*, vol. 29, pp. 1–20, 2026.

[11] F. S. Alsubaie, A. A. Almazro, W. S. Jawa, A. A. Almazro, N. Ayub, and N. Z. Jangjani, “BERT Ensemble Based MBR Framework for Android Malware Detection,” *Scientific Reports*, vol. 15, pp. 1–18, 2025.

[12] R. Li, W. Diao, and D. Gao, “Custom Permission Misconfigurations in Android: A Large-Scale Security Analysis,” in *Proceedings of the 2024 IEEE International Conference on Trust, Security and Privacy in Computing and Communications*, pp. 1161–1170, 2024.

[13] S. Saleem, J. Mišić, and V. B. Mišić, “An Effective Temporal Convolutional Networks-Based Method for Detecting Android Malware Using Dynamic Extracted Features,” *IEEE Access*, vol. 13, pp. 49891–49904, 2025.

[14] T. Sutter, T. Kehr, M. Benhard et al., “Dynamic Security Analysis on Android: A Systematic Literature Review,” *IEEE Access*, vol. 12, pp. 57261–57287, 2024.

[15] W. Wang et al., “Exploring Permission-Induced Risk in Android Applications for Malicious Application Detection,” *IEEE Transactions on Information Forensics and Security*, vol. 9, no. 11, pp. 1869–1882, Nov. 2014.

[16] F. Levani, M. Mistura, F. Iubatti, C. Giangregorio, N. Pastore, C. Alippi, and G. Boracchi, “Malware Families Discovery via Open-Set Recognition on Android Manifest Permissions,” pp. 1–12, 2025.

Manish Kumar

Share Updated Survey Paper -1

 Dr.

Document Details

Submission ID

trn:oid::15912:136893735

Submission Date

Apr 28, 2026, 1:35 PM GMT+5:30

Download Date

Apr 28, 2026, 1:46 PM GMT+5:30

File Name

Share Updated Survey Paper -1.docx

File Size

205.1 KB

5 Pages

3,204 Words

19,952 Characters

1% Overall Similarity

The combined total of all matches, including overlapping sources, for each database.

Filtered from the Report

- Bibliography
- Quoted Text
- Cited Text

Match Groups

-  **2 Not Cited or Quoted 1%**
Matches with neither in-text citation nor quotation marks
-  **0 Missing Quotations 0%**
Matches that are still very similar to source material
-  **0 Missing Citation 0%**
Matches that have quotation marks, but no in-text citation
-  **0 Cited and Quoted 0%**
Matches with in-text citation present, but no quotation marks

Top Sources

- 0%  Internet sources
- 1%  Publications
- 1%  Submitted works (Student Papers)

Integrity Flags

0 Integrity Flags for Review

Our system's algorithms look deeply at a document for any inconsistencies that would set it apart from a normal submission. If we notice something strange, we flag it for you to review.

A Flag is not necessarily an indicator of a problem. However, we'd recommend you focus your attention there for further review.

Match Groups

- 2 Not Cited or Quoted 1%**
Matches with neither in-text citation nor quotation marks
- 0 Missing Quotations 0%**
Matches that are still very similar to source material
- 0 Missing Citation 0%**
Matches that have quotation marks, but no in-text citation
- 0 Cited and Quoted 0%**
Matches with in-text citation present, but no quotation marks

Top Sources

- 0% Internet sources
- 1% Publications
- 1% Submitted works (Student Papers)

Top Sources

The sources with the highest number of matches within the submission. Overlapping sources will not be displayed.

1	Student papers	SRM Valliammai Engineering College on 2026-04-17	<1%
2	Internet	jisem-journal.com	<1%

SURVEY ON A SECURE MOBILE APPLICATION PERMISSION ANALYZER USING NATURAL LANGUAGE PROCESSING

Ms. M. RAGHAVI

Department of Cybersecurity
SRM Valliammai Engineering College
Chengalpattu, India
raghavirgo@gmail.com

SHUNMUGA PRIYA. R

Department of Cybersecurity
SRM Valliammai Engineering College
Chengalpattu, India
shunmugapriyaradha2022@gmail.com

SRIMATHI. V

Department of Cybersecurity
SRM Valliammai Engineering College
Chengalpattu, India
srimathisrimathi089@gmail.com

Abstract Many Android applications have quickly grown in popularity, leading to a substantial rise in the need for safe management of user data and permissions. Sensitive resources like location, contacts, storage and hardware device are often requested by modern applications. There are some applications that require permissions that aren't needed for the app to operate, posing severe privacy concerns; data leakage and the threat of misuse of personal data. Static and dynamic analysis are examples of existing traditional security mechanisms which fail to provide the contextual meaning behind permission usage. With all its challenges, on the other hand, Natural Language Processing (NLP) and Large Language Models (LLMs), in general, are becoming a powerful tool to analyse textual data like app description or privacy policy or user reviews. These methods help in understanding the intent behind permissions, finding inconsistencies, and potential risks or threats. The survey deeply analyses NLP-based techniques for permission risk assessment mechanism including classification, policy mapping, anomaly detection, compliance verification as well as tools to perform explainable AI models and frameworks for scoring risks.

Keywords - NLP, Android Security, Permissions, Risk Analysis, Privacy, LLM, Mobile Security

I. INTRODUCTION

On one hand, Android platform has evolved into one of the most influential mobile apps ecosystems, supporting Billions of users and millions of Apps. Android Apps need to declare multiple permissions for accessing system resources and provide the functionality and user experience. However, the rapid growth of application brings on the consequence of permission misuse, in other words, requesting access to resources that are unreasoned for the functionality of the Apps.

To overcome this issue, works utilize static code analysis [3] and dynamic apps analysis [4] are proposed, which address the problem by expose the technical behaviour of Apps. But they fail to explore the semantic correlation between the permissions required and the functional descriptions of them. To address this issue, a new branch of research emerged so-called Natural Language Processing (NLP) models, attempts to infer the purpose of permissions by analysing app descriptions [6] and privacy policy [5], [1].

In addition, the following technologies have matured in recent years—pre-trained NLP models [2], Large Language Models [7], permission-purpose inference [11]. Furthermore, NLP models can mining in app descriptions from adversarial, which benefit to reveal hidden interrelationship among app descriptions [10]. According to natural-language-guided

framework [8], extracting contextualized semantics info has vastly improved decision-making strategies in risk assessments. Currently, projects focusing on NLP methods used for permission risk analysis in applications face a severe lack of experiences and summaries. Therefore, this survey has been encouraged.

II. RELATED WORK

Initially, research on Android permissions protection focused on rule-based systems and statistical analysis to identify suspicious permissions [4]. These methods using predefined rules were inflexible and could not adapt to new patterns. With rule-based systems, traditional machine learning approaches that leverage data-driven permission analysis captured better performance than static rules. However, most data-driven models can be hindered by unstructured features.

NLP-based approaches utilized the textual information of permissions to improve the analysis. Several systems used NLP-assisted anomaly detection to analyse large-scale app datasets (including permission reports, network communications, and providers) for identifying anomalous permission patterns in applications [6]. Auditing framework designed to detect excessive and misleading permission usage (whose goal is to ensure rigorous privacy analysis) [10]. Apps on Apple store collected tremendous permissions data which were essential for privacy policy analysis. User-review models analysing user feedback could identify the privacy wrongdoing and data abuse related to applications [14].

NLP models that working on cross-lingual corpora could achieve algorithms for different languages and regions. However, some current problems still need to be put into efforts, such as inconsistent privacy policies, non-explainability, and high computing power needed.

III. LITERATURE SURVEY

A. NLP-Based Permission Risk Analysis

NLP-based permission risk analysis studies the textual data and permission usage relationship. Basic NLP models perform text classification that determines whether a permission request is appropriate or suspicious [1]. Such models analyse keyword usage, sentence structure and semantic knowledge, which can infer potential risk of permission requests. Nonetheless, simple classification techniques cannot effectively capture complex, non-linear relationships between permission request and app functionality. To overcome this limitation, techniques such as permission pair risk analysis have been proposed for

investigating permission pair wise co-occurrence. These techniques look for patterns of disparate permission co-relations that would indicate a dangerous permission combination [3]. For example, while location and microphone permissions could both be dangerous, their combination presents an even more serious problem. Fine-grained classification models further improve analysis by considering multiple contextual knowledge, such as semantic similarity, app category and user age expectation [18]. Such classification models are more precise to divide permission risks into various groups. A risk scoring system designates permissions a value based on relevance, load to the user, and level of threat, providing enumerated measures of permissions for better application and comparison [16]. These scores enable users to compare application permissions and to prioritize the risk levels of applications accordingly, thus supporting awareness and perception of risks.

B. LLM and Transformer-Based Analysis

Transformer architectures have gained huge successes in NLP. Such models support long dependence extraction of textual data and facilitate deep contextual understanding of app description and privacy policies. Attention mechanism enable these models to find significance of all words in app descriptions regarding to each other within a sentence, producing better ground for contextual understanding. LLMs extend such deep contextual learning capability by large-scale dataset analysis, thus revealing the app permission purpose and surmising inexplicability in given text and actual permission history [2]. Explainable NLP classifiers enhance understanding by revealing factors that affect model decisions and why a permission is hazardous. Such models help increase trust and support users' ability to understand what a given model is explaining [5]. Transformer-based pipelines could fully automate several tasks involved in permission risk analysis, such as app description interpretation, feature extraction and classifying [17]. The Natural-language-guided approaches make the models base on contextual reasoning, facilitating high performance and accuracy [8].

C. Permission-Policy Mapping and Supervision

Permission-policy mapping monitors the harmony of permissions across apps and privacy policies. NLP-based techniques extract relevant information from policies for further comparison with app declaration permissions [7]. Verification method compares application descriptions and program codes, pinpointing if such application by description is the same as application behaviour [15]. This method has high accuracy and can be applied in the future to make app declarations more transparent by controlling malicious desires in application behaviour. Empowering such process with a permission-privacy annotation system can make the inherent relationship of permissions clearer and more user-friendly, which can thus reduce app disclosure pace and facilitate privacy protections. Comparison system helps regulate app applications systems that adhere to the permission requests process and the relevant regulations and security stipulations, thus enacting transparency accountability [9].

D. Permission Anomaly and Privacy Violation Detection

Anomaly detection methodologies surveil the suspicious permission requests appearing in bulk applications by comparing the perceived application, description, privacy policies and permissions with actual performance [6]. The framework of auditing consider the programs permission anomalies, which refer to excess, anomalistic and illicit permission requests [10]. User-review analysis work with permission anomaly detection in order to effectively pinpoint privacy-damaging application permissions [14].

E. Cross-Language, Multi-Source Textual Data Analysis

An additional difficulty to be mentioned would be the non-uniformity of languages. Cross-language models allow the analysis of applications speaking different languages and lowering limits of scalability and universality [13]. Multisource analysis of app description, privacy policy and user reviews enhances detection results in multiple angles, thus improving detection degree and lowering rate of false-positives[12].

F. Permission Risk Scoring and Applications Recommendation System

Permission risk scores facilitated the comparison across application permission lists and ranking of applications based on quality and security scores [16]. Such scores could be used to recommend reliable apps and exclude risky apps [19].

Table 1: Comparison of NLP-Based Permission Analysis Techniques.

Category	Method	Key Idea	Advantage	Limitation
NLP Analysis	Text Processing	Detect risky permissions	Simple and fast	Limited context
LLM Models	Deep Learning	Understand permission intent	High accuracy	High computational cost
Policy Mapping	NLP Matching	Ensure policy consistency	Improves trust	Depends on policy quality
Anomaly Detection	Pattern Analysis	Detect unusual behavior	Effective detection	Sensitive to noisy data
Risk Scoring	Scoring Model	Rank applications by risk	Easy decision-making	Requires tuning

G. Challenges in NLP-Focused Permission Risk Detection

Despite these progresses, the availability of high-quality data remains a limitation. Privacy policies are often ambiguous, unreliable and may contain information gaps, which influences the precision of aforementioned models. Multilingual processing is also of difficulty, for translation errors and information loss have great impact on the models' performance. Moreover, transformer-based models and LLMs need significant computational resources, restricting their application in area like real-time system monitoring. A pressing issue to be addressed are end-to-end automated models that maintain high accuracy while providing human interpretable results.

H. Future Research Directions in NLP-Based Permission Risk Detection

It is needed to come up with more powerful lightweight and cost-effective models that can run in real time environments. Persistent effort should be put in improving the multilingual capabilities of models. Additionally, integrating NLP with behavioral analysis and other method such as networks checking will be valuable in creating a full strategy to protect user's data from apps.

I. Explainable NLP Models for Permission Risk Analysis

Lack of domain knowledge of end user is one of the biggest challenge in permission risk analysis. Conventional machine learning and deep learning models (neural network based models) are black-box based model which is a serious problem especially in mobile security where wrong classification of app results in either risk to user or false positive app flagging. To overcome such problem, explainable NLP models have been introduced as one of the important advancements in permission analysis system. Explainability-based NLP models identify important word(s), phrase(s) or sentence(s) in app description, privacy policy along with other features, thus help to identify the factors responsible for risk classification [5]. For example, if an app uses location based services but user privacy policy does not talk about location based services, then explainability based model can mark that aspect as one of the reasons for high risk.

Explainability based NLP also improves the usability of system for application developers and security analysts as they can verify the model predictions. It also helps the developers to understand the areas they need to work on to develop a better application and met best security practices. Developers can use those explanations to improve application design and be assured that they are not wrongly flagged as risky app. It also helps in debugging and improving classification performance of NLP models as developer can debug wrong classification and take necessary measures. Explainability also helps in complying to regulations as recent emphasis on transparent decisions of NLP models mandate for explainability of the system.

Overall, explainability based NLP models Improve Trust, accuracy and reliability of permission risk analysis system.

J. Permission-Purpose Inference Using NLP

Asking permission is an important capabilities that new generation of NLP models has brought in mobile security systems. However, permission inference is not sufficient to identify risk class of application, and the importance of permission purpose inference is also vital to accurately determine whether permission requested is necessary for app's functioning or not. NLP models analyse app description, privacy policy and developer notes to infer the application context of permission use, thus put application requesting unnecessary permission in unsecure category [11]. Large language models (LLMs) are one of the best encoders for extracting application context from textual data in mobile security domain as they are capable of mapping long dependencies between words.

For example, need for location access when the application is updating traffic updates is considered essential whereas the same permission request for home automation application seems unnecessary. Hence, context-aware analysis of permission purpose through NLP becomes crucial. Permission inference models identify mismatch between privacy policy and app description, thus helps in avoiding apps with inconsistent describes app functionality [7]. Besides, these models analyse vast set of app data and extract essential permission usage patterns helpful for identifying risky apps [12], thus help in building baseline for conventional anomaly detection techniques.

Permission-purpose inference analysis also helps in identifying implicit functionality, for example, app uses certain permission but developer description does not mention anywhere that functionality. Identifying such gaps through NLP leads to better risk inference.

Combining permission-purpose inference results with anomaly detection or risk scoring techniques leads to better overall permission risk analysis.

K. Fine-Grained Permission Classification

Permission classification models typically categorize permissions into safe or unsecure category. These methods are unable to handle modern app complexities, which require to classify permission into multiple categories is a better way. Fine grained permission classification methods take multiple features as input and classify permissions based on multiple levels like low, medium, high and critical categories depending on context, sensitivity etc. [18]. Permission-pair analysis techniques analyse multiple combinations of permissions together to correctly classify the overall permission pair despite individual permission appear safe or harmful when considered alone. For example, internet access and contact access permission pair in combination can help data leakage. General fine-grained risk identification is an key advancement of such techniques as they take advantage of contextual probability-aware classification [3].

Dynamic permission classification techniques adjust permission classification level depending on contextual location of app. For example, permission level of GPS access may be different for gaming and map applications. These techniques are more user friendly and provide interpretable and detailed insight of why a particular permission is classified as high/medium/low risk level to help users make safe decision.

L. NLP-Based Compliance and Policy Verification

Compliance is a critical component of gaining user confidence and should be an integral part of any permission analysis system. NLP techniques help extracting relevant information from user privacy policy and comparing it with permission requests to identify violations [7]. Besides, compatibility among app description, privacy policy and permission use can be studied through non-straightforward NLP techniques to flagged apps which provide misleading information and go against privacy regulations. This will help avoid regulatory violations and improve user trust in app store environment [9]. Automated

auditing of large set of apps for identifying privacy or security violation thanks to combination of unstructured data analysis with structured permission data can help large app store efficiently provide quality review [15].

M. Permission anomaly detection at large scales of apps

Finding anomalies at large scale of apps needs combination of structured data analysis together with unstructured data analysis. For example, app or developer specific permission analysis can be planned in conjunction with permission for infrastructure or app-store statistics. Large variety of unknown apps analysis for permission anomalies identifies deviation from category defined common trends thus finds anomalies [6]. Auditing techniques based on combination of unstructured and structured data analysis identify redundant or noisy permissions thus help in combating privacy risks and eliminate malicious apps [10].

N. Use of User reviews to study privacy violations:

User reviews also contain information about app behaviour in terms of privacy and security. Sentiment analysis using NLP studies the overall feeling of user communities regarding an app to identify apps which have security issues. Topic modelling techniques studies topics discussed in various user reviews and helps in finding places where privacy is compromised [14].

O. Cross language models-NLP based app description analysis in different languages

NLP models analysing app description and privacy policy should be robust across languages so that all apps can be analysed using an unified system.

P. Risk scoring and decision support systems

Rank calculation of apps based on permission use will help user in choosing safer apps. Decision support tools help users avoid risky apps and choose appropriate and safe app [16].

Q. Use of multiple sources for permission analysis

Use of unstructured data sources such as app description, privacy policy in conjunction with structured data sources is an important trend in permission analysis system development [12]. The overall workflow of the permission risk analysis system is shown in Fig. 1.



Fig. 1: NLP-Based Permission Risk Analysis System Architecture

IV. CONCLUSION

This review summarizes NLP focused techniques in Android permission risk detection. The application of NLP, especially the widely-used transformer-based models and LLMs, significantly boosts the accuracy and efficiency of detect-and-flag. The techniques reveals deeper understanding of permission usage and app contents. In addition to the deep insight allowed by a greater understanding of app permission usages and app content. These models even enable semi-automated app analysis involving app description parsing and feature extracting. Challenges include lack of sufficient data, computational costs and multilingual hurdles. Future directions should aim to systematically build models of high accuracy, interpretability and cross-critical application.

V. REFERENCE

- [1] H. Hu, W. Minn, Y. Liu, J. Liu, F. Thung, T. Y. Zhuo, L. K. Shar, D. Gao, and D. Lo, "Bamboo: Large Language Model Driven Discovery of Application Programming Interface Permission Mappings in the Android Framework," IEEE Access, vol. 13, pp. 1–18, 2025.
- [2] R. Y. Mawoh, J. B. A. Wacka, F. Tchakounte, C. Fachkha, and Kolyang, "An Accurate Approach to Discriminate Android Colluded Malware From Single App Malware Using Permissions Intelligence," Scientific Reports, vol. 15, pp. 1–21, 2025.
- [3] A. Prasad, S. Chandra, M. Uddin, T. Al-Shahari, N. A. Alsaadkan, and S. U. Sajid, "PermGuard: A Scalable Framework for Android Malware Detection Using Permission-to-Exploitation Mapping," IEEE Access, vol. 13, pp. 1–22, 2025.
- [4] A. Sabbah, R. Jarrar, S. Zein, and D. Mohaisen, "Understanding Concept Drift With Deprecated Permissions in Android Malware Detection," IEEE Access, vol. 13, pp. 1–17, 2025.
- [5] E. Aydogan and S. Sen, "Android Authorship Attribution Using Source Code-Based Features," IEEE Access, vol. 12, pp. 6569–6589, 2024.
- [6] F. S. Atadjo, J. P. Lienou, F. F. Nelson, S. S. Shetty, and C. A. Kamhoua, "A Defensive Strategy Against Android Adversarial Malware Attacks," IEEE Access, vol. 12, pp. 169432–169441, 2024.
- [7] F. S. Atadjo, J. P. Lienou, F. F. Nelson, S. S. Shetty, and C. A. Kamhoua, "Cycle Generative Adversarial Network Gradient Penalty for Enhancing Android Adversarial Malware Detection in Gray Box Setting," IEEE Access, vol. 12, pp. 162685–162696, 2024.
- [8] G. S. Tuncay, "Android Permissions: Evolution, Attacks, and Best Practices," IEEE Security and Privacy, vol. 22, no. 6, pp. 40–49, Sep. 2024.
- [9] M. Rafid Islam, "Diagnosing and Mitigating Domain Shift in Permission-Based Android Malware Detection," IEEE Access, vol. 14, pp. 1–15, 2026.
- [10] A. Banik and J. P. Singh, "A BERT and Particle Swarm Optimization Framework for Android Malware Detection Using Real Permissions

and Application Programming Interface Calls,” *Discover Computing*, vol. 29, pp. 1–20, 2026.

[11] F. S. Alsubasi, A. A. Almazro, W. S. Alota, A. A. Almazro, N. Ayub, and N. Z. Jazibi, “BERT Ensemble Based MBR Framework for Android Malware Detection,” *Scientific Reports*, vol. 15, pp. 1–18, 2025.

[12] R. Li, W. Diao, and D. Gao, “Custom Permission Misconfigurations in Android: A Large-Scale Security Analysis,” in *Proceedings of the 2024 IEEE International Conference on Trust, Security and Privacy in Computing and Communications*, pp. 1161–1170, 2024.

[13] S. Saleem, J. Mišić, and V. B. Mišić, “An Effective Temporal Convolutional Networks-Based Method for Detecting Android Malware Using Dynamic Extracted Features,” *IEEE Access*, vol. 13, pp. 49891–49904, 2025.

[14] T. Sutter, T. Kehrer, M. Benhard et al., “Dynamic Security Analysis on Android: A Systematic Literature Review,” *IEEE Access*, vol. 12, pp. 57261–57287, 2024.

[15] W. Wang et al., “Exploring Permission-Induced Risk in Android Applications for Malicious Application Detection,” *IEEE Transactions on Information Forensics and Security*, vol. 9, no. 11, pp. 1869–1882, Nov. 2014.

[16] F. Levari, M. Mistura, F. Iubatti, C. Giangregorio, N. Pastore, C. Alippi, and G. Boracchi, “Malware Families Discovery via Open-Set Recognition on Android Manifest Permissions,” pp. 1–12, 2025.



PANIMALAR ENGINEERING COLLEGE

An Autonomous Institution

Affiliated to Anna University, Chennai
(JAISAKTHI EDUCATIONAL TRUST)



CERTIFICATE OF PARTICIPATION

This is to certify that Dr./Mr./Ms. **SHUNMUGA PRIYA R**
from **SRM VALLIAMMAI ENGINEERING COLLEGE** has
presented a paper titled **SURVEY ON A SECURE MOBILE APPLICATION PERMISSION
ANALYZER USING NATURAL LANGUAGE PROCESSING**
in the **International Conference on Modern Sustainable Engineering and
Technology (ICMSET2026)** organized by the Department of Mechanical
Engineering, Panimalar Engineering College, Chennai, India, held on 15th &
16th of May, 2026.


COORDINATOR
Dr. G. Senthilkumar
Professor


CHAIR
Dr. L. Karthikeyan
Professor & Head



PANIMALAR ENGINEERING COLLEGE

An Autonomous Institution

Affiliated to Anna University, Chennai
(JAISAKTHI EDUCATIONAL TRUST)



CERTIFICATE OF PARTICIPATION

This is to certify that Dr./Mr./Ms. **SRIMATHI V**
from **SRM VALLIAMMAI ENGINEERING COLLEGE** has
presented a paper titled **SURVEY ON A SECURE MOBILE APPLICATION PERMISSION
ANALYZER USING NATURAL LANGUAGE PROCESSING**
in the **International Conference on Modern Sustainable Engineering and
Technology (ICMSET2026)** organized by the Department of Mechanical
Engineering, Panimalar Engineering College, Chennai, India, held on 15th &
16th of May, 2026.


COORDINATOR
Dr. G. Senthilkumar
Professor


CHAIR
Dr. L. Karthikeyan
Professor & Head