

SECURE MOBILE APPLICATION PERMISSION ANALYZER USING NATURAL LANGUAGE PROCESSING

A MINI PROJECT REPORT

Submitted by

SHUNMUGA PRIYA R	142223128045
SRIMATHI V	142223128048
VISHWA A	142223128057

*in fulfillment for the award of the degree
of*

BACHELOR OF ENGINEERING

IN

CYBER SECURITY



SRM VALLIAMMAI ENGINEERING COLLEGE
(An Autonomous Institution)
SRM NAGAR, KATTANKULATHUR

ANNA UNIVERSITY: CHENNAI 600 025

MAY 2026

BONAFIDE CERTIFICATE

Certified that this project report “**SECURE MOBILE APPLICATION PERMISSION ANALYZER USING NATURAL LANGUAGE PROCESSING**” is the bonafide work of “**SHUNMUGA PRIYA R (142223128045), SRIMATHI V (142223128048), VISHWA A (142223128057)**” who carried out the project work under my supervision.

SIGNATURE

Mr. M. RAGHAVI, M.E.,

Assistant Professor

Department of Cyber Security

SRM Valliammai Engineering College,

Kattankulathur – 603 203.

SIGNATURE

Dr. V. DHANAKOTI, M.E., Ph.D.,

Professor & Head

Department of Cyber Security

SRM Valliammai Engineering College,

Kattankulathur – 603 203.

Submitted for the University Examination held on _____
at SRM Valliammai Engineering College, Kattankulathur.

INTERNAL EXAMINER

EXTERNAL EXAMINER

ACKNOWLEDGEMENT

We sincerely express our gratitude in depth to our esteemed Founder Chairman & Chancellor **Dr. T. R. Paarivendhar, Thiru. Ravi Pachamoothoo**, Chairman SRM Group & Pro-Chancellor (Admin). **Ms. R. Harini**, Correspondent, SRM VEC and authorities of SRM Valliammai Engineering College for the patronage of our welfare rooted in the academic year.

We express our sincere gratitude and thankfulness to our respected Director-Academics and Administration - SRM GROUP **Dr. R. Venkatesh Babu, MBA., Ph.D.**, for his constant encouragement, which has motivated us to strive towards excellence.

We sincerely thank our Principal **Dr. M. Murugan, M.E., Ph.D.**, for his constant encouragement, which has been our motivation to strive towards excellence.

We also thank our Vice Principal **Dr. S. Visalakshi, M.E., Ph.D.**, for her constant motivation to strive towards excellence.

We extend our heartfelt gratitude towards our Head of the Department – Cyber Security **Dr. V. Dhanakoti, M.E., Ph.D.**, Professor for his unstinted support.

We are thankful to Project Coordinator, **Dr. V. Santhana Marichamy, MCA., M.E., Ph.D.**, Assistant professor for providing us with the essential facilities.

We are grateful to our internal guide **Mr. M. Raghavi, M.E.**, without his valuable guidance and encouragement, this major project would not have been a success.

We also like to thank all the teaching and non-teaching staff members of our department, for their support during the major project work.

We finally thank our friends and family for their support during the course of the project.

ABSTRACT

The growth of Android applications is really fast and this has made it very important to think and this has made it very important to think about user privacy and device security. Many microphone, location, contacts, storage and SMS access. Sometimes they ask for these permissions even when they do not really need them for what they're supposed to do. This can lead to problems like privacy issues people getting access to data without permission and security threats. The old ways of checking permissions, which are based on either looking at the code or seeing what the app does when it is running often do not understand why the app is asking for these permissions. To deal with this problem a system called "A Secure Mobile Application Permission Analyzer Using Natural Language Processing" uses Natural Language Processing techniques to look at the permissions that apps ask for. The text that goes with them. This helps the system understand what the permissions mean. Why they are being asked for. It can then group the permissions based on how risky they're find the ones that seem suspicious or are not needed. By making permission analysis this system makes mobile applications safer. It does this by giving users an idea of the risks that come with permissions helping to predict and group risks and making people more aware of security issues through an interface that is easy to use. This shows that Natural Language Processing can be very useful, in cybersecurity to make Android permission analysis stronger and protect user privacy. Android mobile applications and user privacy are very important. This system helps to make them safer.

ABSTRACT (TAMIL)

ஆண்ட்ராய்டு மொபைல் செயலிகளின் அதிகரித்து வரும் பயன்பாடு காரணமாக பயனர் தனியுரிமை மற்றும் சாதன பாதுகாப்பு மிகப்பெரிய சவாலாக மாறியுள்ளது. பல செயலிகள் கேமரா, மைக்ரோஃபோன், இடம், தொடர்புகள், சேமிப்பு மற்றும் குறுந்தகவல் போன்ற முக்கியமான அனுமதிகளை கோருகின்றன. சில செயலிகள் தங்களின் உண்மையான செயல்பாட்டிற்கு தேவையில்லாத அல்லது அளவுக்கு மீறிய அனுமதிகளை கேட்பதால் தனிப்பட்ட தகவல் கசிவு, அனுமதியற்ற தரவு அணுகல் மற்றும் இணைய பாதுகாப்பு அச்சுறுத்தல்கள் உருவாகின்றன. இத்தகைய அனுமதி கோரிக்கைகள் சாதாரண பயன்பாட்டு செயல்பாடுகளைப் போல தோன்றுவதால் அவற்றின் உண்மையான நோக்கத்தை கண்டறிவது கடினமாகிறது. இந்த ஆய்வு, இயற்கை மொழி செயலாக்க முறைகளை பயன்படுத்தி மொபைல் செயலிகளின் அனுமதி தரவுகள், செயலி விளக்கங்கள் மற்றும் தனியுரிமை கொள்கை தகவல்களின் அடிப்படையில் சந்தேகமான மற்றும் ஆபத்தான அனுமதிகளை கண்டறியும் முறைகளை ஆய்வு செய்கிறது. தற்போதைய அணுகுமுறைகள் இயந்திரக் கற்றல் முறைகள், ஆழ்ந்த கற்றல் முறைகள், மாற்றி அடிப்படையிலான மொழி மாதிரிகள் மற்றும் பெரிய மொழி மாதிரி அடிப்படையிலான அணுகுமுறைகள் என வகைப்படுத்தப்பட்டு அவற்றின் செயல்திறன் மதிப்பீடு செய்யப்படுகிறது. மேலும், அனுமதி பகுப்பாய்வு, ஆபத்து வகைப்படுத்தல் மற்றும் தனியுரிமை பாதுகாப்பை ஒருங்கிணைக்கும் அறிவார்ந்த பாதுகாப்பு அமைப்பின் செயல்முறை விளக்கப்படுகிறது. இந்த ஆய்வு விரிவாக்க திறன், பல மொழி ஆதரவு, மறைமுக அனுமதி நடத்தை கண்டறிதல் மற்றும் விளக்கத் திறன் குறைபாடு போன்ற சவால்களை எடுத்துக்காட்டி, எதிர்கால மொபைல் பாதுகாப்பு தீர்வுகளுக்கான வழிமுறைகளை முன்வைக்கிறது.

TABLE OF CONTENTS

Chapter No	Title	Page No.
	ABSTRACT	Iv
	ABSTRACT (TAMIL)	V
	LIST OF FIGURES	Ix
	LIST OF ABBREVIATIONS	X
1.	INTRODUCTION	1
	1.1 Introduction	2
	1.2 Objective	3
	1.3 Purpose	4
	1.4 Scope	5
2.	LITERATURE SURVEY	6
3.	REQUIREMENTS & SPECIFICATIONS	13
	3.1 Software Requirements	14
	3.2 Software Environment	14
	3.2.1 Visual Studio Code	14
	3.2.2 Natural Language Processing Environment	15
	3.2.3 Machine Learning Environment	15
	3.3 Programming Language	16
	3.3.1 Python	16
	3.3.2 HTML	17
	3.3.3 CSS	17
	3.3.4 JavaScript	17

	3.4 Technologies and Libraries	18
	3.4.1 Technologies used	18
	3.4.2 Libraries used	18
4.	SYSTEM STUDY	20
	4.1 Feasibility Study	21
	4.2 Economical Feasibility	21
	4.3 Technical Feasibility	22
	4.4 Social Feasibility	23
5.	SYSTEM DESIGN	24
	5.1 System Architecture	25
	5.2 UML Diagram	26
	5.3 Data Flow Diagram	28
	5.4 Use Case Diagram	30
	5.5 Activity Diagram	32
	5.6 Sequence Diagram	34
	5.7 Class Diagram	35
6.	IMPLEMENTATION	37
	6.1 Classification of Modules	38
	6.2 Module Description	38
	6.2.1 Data Collection and Ingestion Environment	38

	6.2.2 NLP Processing Module	39
	6.2.3 Risk Analysis And Detection Module	40
	6.2.4 Report Generation And Summary Module	41
7.	RESULT AND DISCUSSION	43
	7.1 Result	44
	7.2 Discussion	45
8.	CONCLUSION AND FUTURE WORK	46
	8.1 Conclusion	47
	8.2 Future Work	47
	APPENDIX – I	48
	I. Output	59
	APPENDIX – II	54
	II. Sample code	55
	i. Image Upload And Screenshot Processing	55
	ii. OCR Text Extraction From Screenshot	56
	iii. NLP Based Risk Keyword Analysis	56
	iv. Database Storage Using SQLite	57
	REFERENCES	58
	SDG CERTIFICATE	61

SURVEY PAPER	62
AI CONTENT REPORT	67
PLAGIARISM SIMILARITY REPORT	74
CONFERENCE CERTIFICATE	82

LIST OF FIGURES

S. No	Figure No.	Title	Page No.
1	5.1	System Architecture of Secure Mobile Application Permission Analyzer Using Natural Language Processing	25
2	5.2	UML Diagram	27
3	5.3	Data Flow Diagram	29
4	5.4	Use Case Diagram	31
5	5.5	Activity Diagram	33
6	5.6	Sequence Diagram	34
7	5.7	Class Diagram	36
8	7.1	Permission Analysis And Risk Classification Dashboard	44
9	I	Permission Analysis Input Interface For Mobile Application Privacy Assessment	49
10	II	Screenshot Upload And AI-Based Text Extraction Process	50
11	III	Privacy Risk Analysis Report And Risk Level Assessment	51
12	IV	Risk Categorization Interface For Privacy Threat Assessment	52
13	V	Privacy Recommendation And Risk Mitigation Module	53

LIST OF ABBREVIATIONS

NLP	Natural Language Processing
AI	Artificial Intelligence
ML	Machine Learning
APK	Android Package Kit
API	Application Programming Interface
UI	User Interface
GUI	Graphical User Interface
OS	Operating System
SMS	Short Message Service
URL	Uniform Resource Locator
JSON	JavaScript Object Notation
XML	Extensible Markup Language
CSV	Comma Separated Values
IDE	Integrated Development Environment
CPU	Central Processing Unit
RAM	Random Access Memory
NLPA	Natural Language Permission Analyzer
LLM	Large Language Model
DFD	Data Flow Diagram
UML	Unified Modeling Language

CHAPTER 1

INTRODUCTION

1. INTRODUCTION

This chapter provides an overview of the project, including the need for secure mobile application permission analysis, the challenges in existing systems, and the proposed solution using Natural Language Processing (NLP). It also explains the objectives, purpose, and scope of the system in improving Android application security and protecting user privacy.

1.1 INTRODUCTION

In today's digital era, Android mobile applications have become an essential part of daily life. People use mobile applications for communication, banking, shopping, education, entertainment, healthcare, and social networking. To perform these functions, applications often request permissions such as access to camera, microphone, contacts, location, storage, SMS, and call logs. While many permissions are necessary for application functionality, some applications request excessive or unnecessary permissions that may threaten user privacy and device security. Such permissions can lead to unauthorized data access, personal information leakage, and cyberattacks.

Traditional mobile security systems mainly depend on static analysis and signature-based detection methods to identify malicious applications. However, these approaches are not always effective in understanding the actual purpose and context behind permission requests. Modern malicious applications are capable of bypassing traditional detection systems by using hidden behaviors or modified permission patterns. Therefore, there is a growing need for intelligent and adaptive security solutions that can analyze application permissions more effectively.

The proposed system helps users understand whether a permission is safe, suspicious, or high-risk before installing or using an application. The application provides a user-friendly interface where users can upload or analyze application permission details and receive security reports in real-time. NLP and Machine Learning techniques are used to improve the accuracy of risk prediction and permission classification.

1.2 OBJECTIVE

The primary objective of this project is to develop a secure mobile application permission analyzer using Natural Language Processing (NLP) techniques to improve Android application security and protect user privacy. The system is designed to analyze application permissions intelligently and identify suspicious, unnecessary, or high-risk permissions that may lead to security threats or unauthorized access to sensitive user information.

This project aims to create an intelligent framework that can understand the context and intent behind permission requests using NLP and Machine Learning methods. The proposed system analyzes permission-related textual information, application descriptions, and permission patterns to classify permissions into different risk categories such as safe, suspicious, or dangerous.

Another important objective of this project is to provide users with a simple and user-friendly interface where application permissions can be analyzed easily. The system generates real-time security reports and alerts to help users make informed decisions before installing or using mobile applications. The project also focuses on improving cybersecurity awareness by educating users about risky permissions and privacy threats associated with Android applications.

In addition, the proposed system aims to overcome the limitations of traditional signature-based security mechanisms by introducing an adaptive and intelligent permission analysis approach. By using NLP-based analysis, the system can identify hidden risks and unusual permission behaviors more effectively. The project ultimately contributes to the development of smarter mobile security solutions that enhance privacy protection and reduce security risks in Android devices. The project also aims to provide a smarter and more secure approach for analyzing Android application permissions effectively. Furthermore, the project aims to improve the reliability and efficiency of Android permission analysis by combining intelligent text processing techniques with automated security evaluation methods.

1.3 PURPOSE

The purpose of this project is to design and implement a secure mobile application permission analyzer using Natural Language Processing (NLP) techniques to enhance Android security and safeguard user privacy. Android applications frequently request various permissions to access sensitive device resources such as contacts, location, storage, camera, microphone, and messages. While many permissions are required for application functionality, some applications misuse permissions to collect personal information or perform malicious activities without user knowledge.

Traditional mobile security systems mainly focus on static or signature-based detection methods, which are limited in identifying modern privacy threats and suspicious permission usage patterns. These methods often fail to understand the real meaning, intention, and context behind permission requests. Therefore, this project aims to provide a smarter and more intelligent permission analysis system capable of detecting risky permissions using NLP techniques.

Another important purpose of this project is to increase awareness among users regarding Android permission security and privacy protection. The system helps users understand which permissions are necessary and which may pose security threats. By integrating NLP into cybersecurity, the project demonstrates how intelligent technologies can be used to build adaptive, scalable, and efficient mobile security solutions capable of addressing modern cybersecurity challenges.

The proposed system analyzes permission-related textual data, application descriptions, and user-related information to identify inconsistencies and suspicious behaviors. By using NLP and Machine Learning algorithms, the system can classify permissions based on risk levels and generate appropriate security alerts. The application also provides a user-friendly environment for analyzing permissions and generating detailed reports for users. The project also helps in improving user awareness about secure permission handling and mobile privacy protection by educating users about risky application permissions.

1.4 SCOPE

The scope of this project mainly focuses on improving Android application security through intelligent permission analysis using Natural Language Processing (NLP). The system is designed to analyze permissions requested by Android applications and identify potentially risky, suspicious, or unnecessary permissions that may affect user privacy and device security.

The project covers the collection and analysis of permission-related data from mobile applications. Using NLP techniques, the system studies permission descriptions, application behavior, and textual information to understand the context and intent behind permission requests. Based on the analysis, permissions are classified into different categories such as safe, suspicious, or high-risk.

The proposed system also includes a user-friendly interface where users can analyze application permissions and receive real-time security reports and alerts. Machine Learning techniques can be integrated to improve permission classification accuracy and enhance the system's ability to identify new or unknown security threats. The project can be applied in Android security systems, mobile privacy analysis, cybersecurity research, and application security testing.

In the future, the scope of the project can be expanded by integrating deep learning models, cloud-based security analysis, automated malware detection, and real-time monitoring systems. The system can also be enhanced to support multilingual permission analysis, advanced threat intelligence, and large-scale application scanning. Overall, this project contributes toward the development of intelligent, adaptive, and scalable mobile security solutions that help users protect their personal data and privacy in modern digital environments. The system can further be expanded to support advanced security analysis and large-scale Android application monitoring in future environments.

CHAPTER 2

LITERATURE SURVEY

2. LITERATURE SURVEY

The literature survey reviews previous research works related to Android application permission analysis and mobile security using Natural Language Processing and Machine Learning techniques. Various studies focus on permission risk classification, privacy policy analysis, transformer models, large language models, and intelligent permission auditing to improve Android security and privacy protection. These works help identify existing challenges such as misleading permission requests, privacy inconsistencies, and abnormal permission behavior, while providing guidance for developing more accurate, scalable, and secure permission analysis systems.

2.1 LITERATURE SURVEY

1. “NLP Based Permission Usage Auditing in Android App Descriptions and Privacy Policies

Authors: A. Kumar, R. Patel & S. Sharma

This paper presents an NLP-based framework for auditing Android application permissions using app descriptions and privacy policies. The system compares textual information with requested permissions to identify suspicious or misleading permission usage. Natural Language Processing techniques help improve semantic understanding and detect privacy inconsistencies in Android applications. The study highlights the importance of automated permission auditing in improving mobile privacy and reducing security risks. It also explains how NLP can strengthen Android security by identifying excessive or abnormal permission requests [1].

2. “NLP-Based Verification of Permission Consistency Between App Descriptions and Code Level Behaviour”

Authors: B. Zhao, L. Zhang & Y. Wang

This paper proposes an NLP-based verification approach for analyzing consistency between Android application descriptions and actual code-level permission behavior. The

framework compares textual permission explanations with application actions to identify mismatched or suspicious permissions. Machine learning and NLP techniques improve the detection of hidden permission misuse and abnormal application behavior. The study highlights the importance of permission transparency in protecting user privacy and strengthening Android security. It also emphasizes the need for automated and scalable verification systems for large-scale Android application analysis [2].

3. “Transformer-Based NLP Pipeline for Secure Mobile App Permission Policy Analysis”

Authors: C. Lopez, J. Garcia & M. Sanchez

This paper introduces a transformer-based NLP pipeline for analyzing Android application permission policies and detecting privacy risks. The system uses transformer models to identify suspicious permission requests and security inconsistencies from permission descriptions and privacy policies. The study shows that transformer-based models improve semantic understanding and classification accuracy compared to traditional NLP methods. It also highlights the importance of deep contextual analysis in Android permission security monitoring. Furthermore, the authors suggest integrating transformer models with real-time Android security systems to improve mobile application protection [3].

4. “NLP-Driven User Review Analysis for Detecting Permission-Related Privacy Concerns”

Authors: E. Kim, J. Park & S. Lee

This paper focuses on analyzing user reviews using NLP techniques to detect permission-related privacy concerns in Android applications. The framework extracts security-related keywords and identifies suspicious permission behavior based on user feedback. The study highlights the importance of user-generated content in improving Android privacy analysis and identifying risky applications. Experimental results show better detection of permission-related security issues and improved application trust evaluation. Furthermore, the paper emphasizes integrating user review analysis with

automated permission monitoring systems for enhanced Android security [4].

5. “Cross-Language NLP Models for Android App Permission Meaning Analysis”

Authors: F. Garcia, M. Rodriguez & C. Martinez

This paper proposes cross-language NLP models for analyzing Android application permission meanings across multiple languages. The framework processes multilingual permission descriptions to identify semantic relationships between permissions and application behavior. The study shows that cross-language analysis improves Android security monitoring and permission understanding in diverse language environments. It also discusses challenges such as language variations and semantic ambiguity in permission descriptions. Experimental results demonstrate improved permission classification accuracy and better analysis of privacy-related permission requests across different languages [5].

6. “NLP-Enabled Privacy Policy-to-Permission Mapping Framework for Secure Mobile Apps”

Authors: H. Liu, X. Wu & Y. Yang

This paper presents an NLP-enabled framework for mapping Android privacy policies to requested permissions for secure mobile application analysis. The system compares policy statements with application permissions to identify inconsistencies and suspicious access requests. Natural Language Processing techniques improve semantic mapping between privacy policies and permission behavior. The study highlights the importance of privacy transparency and automated permission verification in Android security. Furthermore, the paper emphasizes the need for intelligent policy analysis systems to improve user trust and detect hidden privacy risks in mobile applications [6].

7. “NLP-Assisted Auditing of Excessive and Misleading Mobile App Permissions”

Authors: J. Brown, M. Davis & K. Wilson

This paper proposes an NLP-assisted auditing system for detecting excessive and misleading permissions in Android applications. The framework analyzes application descriptions and permission requests to identify unnecessary or suspicious permissions. The study shows that Natural Language Processing improves permission auditing efficiency and helps users identify potentially harmful applications. It also highlights the importance of automated permission analysis in reducing privacy risks and improving Android security monitoring. Experimental results demonstrate improved detection of misleading permission requests and better mobile application privacy analysis [7].

8. “Harnessing Large Language Models to Analyse Android App Permission Declarations”

Authors: L. Chen, H. Wang & M. Liu

This paper introduces a large language model-based framework for analyzing Android application permission declarations and identifying risky permission behavior. The system uses advanced NLP and language modeling techniques to improve permission understanding and risk prediction accuracy. The study demonstrates that large language models can effectively identify hidden permission patterns and enhance automated Android security analysis. It also discusses challenges such as computational resource requirements and model optimization for real-time applications. Experimental results show significant improvements in permission analysis accuracy and intelligent risk classification performance [8].

9. “Explainable NLP Classifier for Android App Permission Risk Labelling”

Authors: M. Singh, A. Verma & P. Rao

This paper proposes an explainable NLP-based classifier for Android permission risk labeling. The framework classifies permissions into safe, suspicious, or high-risk

categories while providing understandable explanations for predictions. The study highlights the importance of explainable AI in improving user trust and transparency in Android security systems. It also discusses challenges in balancing classification accuracy and model interpretability. Experimental results show improved permission classification performance and better user understanding of Android permission risks [9].

10. “NLP-Enabled Fine-Grained Permission Risk Classification for Mobile App Security”

Authors: N. Iyer, V. Rao & S. Bhat

This paper presents an NLP-enabled fine-grained permission risk classification framework for Android mobile application security. The system analyzes semantic relationships, permission combinations, and contextual meaning to classify permissions into multiple risk categories. The proposed approach improves permission risk prediction accuracy and enhances intelligent Android security monitoring. The study highlights the importance of contextual permission analysis in identifying suspicious application behavior and privacy violations. Furthermore, the paper emphasizes the need for scalable machine learning and NLP techniques for automated mobile application security and real-time permission risk analysis [10].

11. “Natural Language-Guided Permission Risk Assessment for Mobile App Security”

Authors: P. Das, S. Nath & A. Ghosh

This paper presents a natural language-guided framework for assessing permission risks in mobile applications. The system analyzes permission-related textual information to identify risky and suspicious permission behavior. The study highlights the importance of NLP techniques in improving Android security and enhancing automated permission risk analysis. Furthermore, the paper emphasizes intelligent permission assessment for protecting user privacy and secure mobile application usage. It also discusses the need for scalable security models capable of handling large numbers of Android applications efficiently [11].

12. “NLP-Driven Permission Pair Interaction Risk Analysis For Secure Mobile Application Recommendation”

Authors: R. Patel, V. Kumar & S. Desai

This paper proposes an NLP-driven framework for analyzing risky interactions between Android permission pairs. The system identifies suspicious permission combinations that may lead to privacy and security threats in mobile applications. The study highlights the importance of permission interaction analysis in improving secure application recommendation systems. Experimental results show improved detection of risky permission combinations and better mobile security evaluation. Furthermore, the paper emphasizes automated risk analysis for enhancing Android application trust and privacy protection [12].

13. “Natural Language Processing for Secure Mobile App Permission Risk Assessment”

Authors: S. Sharma, N. Gupta & A. Mishra

This paper presents an NLP-based approach for secure mobile app permission risk assessment. The framework analyzes permission descriptions and application behavior to classify risky permissions and detect privacy threats. The study highlights the role of Natural Language Processing in improving Android security and automated permission analysis. Furthermore, the paper emphasizes intelligent risk assessment systems for enhancing user privacy protection. It also discusses the importance of accurate semantic analysis in identifying hidden permission misuse [13].

14. “NLP-Assisted Permission Anomaly Detection in Android App Stores”

Authors: T. Nguyen, L. Tran & H. Hoang

This paper introduces an NLP-assisted system for detecting permission anomalies in Android app stores. The framework analyzes application descriptions and permission requests to identify abnormal or suspicious permission behavior. The study highlights the importance of automated anomaly detection in reducing privacy risks and improving Android security monitoring. Experimental results demonstrate improved detection

accuracy for suspicious applications. Furthermore, the paper emphasizes scalable NLP techniques for continuous Android app store security analysis [14].

15. Large Language Model Assisted Android Permission Purpose Inference From App Descriptions and Policies

Authors: X. Wang, Z. Zhou & Q. Liu

This paper proposes a large language model-assisted framework for inferring Android permission purposes from app descriptions and privacy policies. The system uses advanced NLP techniques to understand permission semantics and identify hidden privacy risks. The study demonstrates that large language models improve permission purpose analysis and Android security evaluation. Furthermore, the paper highlights the importance of intelligent language models in enhancing mobile privacy protection. It also discusses challenges related to computational complexity and real-time security analysis [15].

16. Fine-Grained Permission Policy Alignment Verification Using Transformer-Based NLP

Authors: Y. Zhang, J. Li & W. Chen

This paper presents a transformer-based NLP framework for verifying alignment between Android permission policies and application behavior. The system performs fine-grained analysis to detect inconsistencies and suspicious permission usage. The study highlights the effectiveness of transformer models in improving semantic understanding and permission verification accuracy. Furthermore, the paper emphasizes the importance of automated policy alignment verification for enhancing Android security and user privacy protection. Experimental results show improved accuracy in detecting mismatched permission policies and application activities [16].

CHAPTER 3

REQUIREMENTS AND SPECIFICATION

3. REQUIREMENTS AND SPECIFICATIONS

The Proposed “Secure Mobile Application Permission Analyzer Using Natural Language Processing “ uses Python, Flask, HTML, CSS, JavaScript, and SQLite for developing a web-based Android Permission analysis system. NLP and Machine Learning libraries such as NLTK, Scikit-learn, TensorFlow, NumPy, and Pandas are used to analyze permissions and identify security risks efficiently.

3.1 SOFTWARE REQUIREMENTS

- **Programming Languages:** Python 3.13
- **Frontend Technologies:** HTML ,CSS, JavaScript
- **Framework:** Flask
- **Database Management System:** SQLite
- **Development Platform:** Visual Studio Code (VS Code)
- **Operating System:** Window 11
- **NLP Libraries:** NLTK
- **Machine Learning Libraries:** Scikit-learn, TensorFlow
- **Data Processing Libraries:** NumPy, Pandas

3.2 SOFTWARE ENVIRONMENT

The software environment includes tools, frameworks, and libraries required for developing and executing the Android permission analyzer system. It supports NLP, Machine Learning, database management, and web application development for efficient permission analysis and risk detection.

3.2.1 VISUAL STUDIO CODE

Visual Studio Code (VS Code) is a lightweight and open-source code editor developed by Microsoft. It provides features such as syntax highlighting, debugging tools, integrated terminal support, intelligent code completion, and extension support for multiple programming languages.

In the proposed project, VS Code is used for writing Python programs, designing frontend interfaces, implementing NLP and Machine Learning modules, and integrating Flask backend

services. Its debugging and extension support help improve coding efficiency, testing, and project management.

VS Code provides a flexible and user-friendly environment for developing AI-based cybersecurity and web.

3.2.2 NATURAL LANGUAGE PROCESSING ENVIRONMENT

Natural Language Processing (NLP) is an Artificial Intelligence technology used to analyze, process, and understand human language data. In the proposed project, NLP techniques are used to analyze Android application permission descriptions, privacy policies, and textual permission information to identify suspicious behavior and risky permissions. The NLP environment mainly uses Python libraries such as NLTK for performing text preprocessing operations including tokenization, stop-word removal, stemming, lemmatization, and feature extraction.

These techniques help the system understand permission semantics and classify Android permissions based on security risk levels. The NLP module helps identify misleading permission descriptions, abnormal permission requests, and suspicious permission combinations associated with malware, spyware, and privacy violations. The environment also supports semantic analysis and contextual understanding of permission-related text. By integrating NLP into Android security analysis, the proposed system improves intelligent permission classification and enables better detection of harmful applications compared to traditional manual analysis approaches.

Scikit-learn serves as a powerful and flexible tool in the development of the HIDS project, enabling efficient data processing, accurate threat detection, and reliable performance evaluation. Its integration with other Python libraries such as NumPy and Pandas further enhances its usability, making it an essential component in building solutions.

3.2.3 MACHINE LEARNING ENVIRONMENT

The Machine Learning environment is responsible for training and implementing intelligent classification models used for Android permission risk prediction. Machine Learning algorithms help the system identify suspicious permission combinations and classify applications as Safe, Suspicious, or High Risk. The project uses Scikit-learn and TensorFlow libraries for implementing machine learning

and deep learning models. These libraries provide tools for data preprocessing, feature extraction, classification, prediction, model evaluation, and AI-based decision-making. The machine learning environment processes permission datasets containing both normal and malicious permission patterns.

Classification algorithms learn from training datasets and identify abnormal permission requests associated with spyware, malware, unauthorized access, and privacy threats. The environment also supports model evaluation techniques such as accuracy measurement, confusion matrix generation, precision calculation, recall analysis, and performance optimization. Machine learning improves the adaptability and intelligence of the permission analyzer system by enabling automatic threat identification.

3.3 PROGRAMMING LANGUAGE

Programming languages are used to develop backend processing, frontend interaction, database communication, and AI-based permission analysis functionalities in the system. The proposed project mainly uses Python, HTML, CSS, and JavaScript for implementing NLP, Machine Learning, and web application development.

3.3.1 PYTHON

Python is a high-level, interpreted, open-source programming language known for its simplicity, flexibility, and readability. It is widely used in Artificial Intelligence, Machine Learning, Natural Language Processing, Cybersecurity, Web Development, and Data Science applications.

In the proposed Secure Mobile Application Permission Analyzer system, Python is used as the core programming language for implementing permission analysis logic, NLP processing, machine learning classification, report generation, and backend operations.

Python provides extensive libraries such as NLTK, Scikit-learn, TensorFlow, NumPy, and Pandas, which simplify AI model development and permission data analysis. Python is also used for handling Android permission datasets, performing semantic analysis, and generating security alerts based on permission risks.

The Flask framework, developed using Python, is used to create the web application interface and backend services. SQLite database integration is also performed using Python

modules.

Python's simple syntax, strong community support, extensive documentation, and rich ecosystem make it highly suitable for developing intelligent Android security analysis systems and cybersecurity applications.

3.3.2 HTML

HTML (Hyper Text Markup Language) is the standard markup language used to structure web pages and organize web application content. It defines elements such as headings, forms, buttons, tables, containers, and navigation sections.

In this project, HTML is used to create the frontend structure of the web application interface. It helps display permission details, user input forms, security warnings, risk classifications, and permission analysis reports in an organized format.

HTML provides the structural foundation for integrating CSS styling and JavaScript interactivity within the permission analyzer dashboard.

3.3.3 CSS

CSS is a stylesheet language used to control the visual appearance and layout of web applications. CSS improves readability, user experience, responsiveness, and visual organization of web interfaces.

In the proposed project, CSS is used to design the Android permission analyzer dashboard, warning alerts, analysis tables, report sections, and graphical display components. It improves the overall presentation of security analysis information.

CSS also helps visually differentiate safe, suspicious, and high-risk permissions using colors, layouts, and styling components, making the system easier to use and understand.

3.3.4 JAVASCRIPT

JavaScript is a high-level scripting language used for creating dynamic and interactive web applications. It enables real-time interaction, frontend validation, dynamic content updates, and responsive user interfaces.

In this project, JavaScript is used to improve frontend interactivity and user experience. It supports real-time permission input handling, dynamic risk visualization, interactive notifications, and immediate display of analysis results.

JavaScript also enables communication between the frontend interface and Flask backend services, helping users receive instant Android permission analysis reports and warning notifications.

3.4 TECHNOLOGIES AND LIBRARIES

The proposed project uses various technologies and libraries to support Android permission analysis, NLP processing, machine learning classification, database management, and web application development.

These technologies improve system performance, automation, intelligent threat detection, and user interaction.

3.4.1 TECHNOLOGIES USED

- Python
- Flask
- HTML
- CSS
- JavaScript
- SQLite
- Visual Studio Code
- Natural Language Processing
- Machine Learning

3.4.2 LIBRARIES USED

- i. **from flask import Flask, request, render_template:** Used for developing the web application backend, handling user requests, processing permission inputs, and displaying analysis results.
- ii. **import nltk:** Used for Natural Language Processing tasks such as tokenization, stemming,

stop-word removal, and permission text analysis..

- iii. **import pandas as pd:** Used for dataset handling, preprocessing, permission record management, and structured data operations.
- iv. **import numpy as np:** Used for numerical computation, matrix operations, and machine learning data processing.
- v. **from sklearn.feature_extraction.text import CountVectorizer:** Used for converting permission text into numerical feature vectors for machine learning analysis.
- vi. **from sklearn.naive_bayes import MultinomialNB:** Used for implementing machine learning-based permission risk classification models.
- vii. **from sklearn.model_selection import train_test_split:** Used for splitting permission datasets into training and testing datasets for machine learning evaluation.
- viii. **from sklearn.metrics import accuracy_score:** Used for measuring machine learning model performance and prediction accuracy.
- ix. **import tensorflow as tf:** Used for implementing advanced deep learning models for intelligent permission analysis and threat prediction.
- x. **import sqlite3:** Used for SQLite database integration, permission data storage, and report management.

CHAPTER 4

SYSTEM STUDY

4. SYSTEM STUDY

System study refers to the process of analyzing and evaluating a proposed system to understand its functionality, components, and performance. The main objective of the system study is to identify whether the proposed “Secure Mobile Application Permission Analyzer Using Natural Language Processing” can effectively improve Android security by analyzing application permissions and detecting suspicious behaviors using NLP and Machine Learning techniques.

4.1 FEASIBILITY STUDY

The feasibility study for the proposed Secure Mobile Application Permission Analyzer evaluates the practicality and effectiveness of implementing the system using current technologies. The system uses Natural Language Processing, Machine Learning, and Android permission analysis techniques to identify risky permissions and suspicious application behavior. The study ensures that the project can be developed successfully using available software tools and resources.

The technical and operational feasibility focuses on analyzing whether the system can process Android application permissions efficiently and generate accurate risk classifications. Technologies such as Python, Flask, NLTK, and Scikit-learn support permission extraction, text analysis, and machine learning-based classification. The web-based interface also improves accessibility and usability for users.

The feasibility study further evaluates scalability, security, and future enhancements of the system. Potential issues such as false positives, permission ambiguity, and evolving malware behaviors are considered during analysis. Overall, the study confirms that the proposed system is feasible, reliable, scalable, and suitable for improving Android application security and user privacy protection.

4.2 ECONOMICAL FEASIBILITY

The economic feasibility of the Secure Mobile Application Permission Analyzer focuses on analyzing the cost-effectiveness of the proposed system. The project mainly uses open-source technologies such as Python, Flask, TensorFlow, and NLP libraries, which reduces software licensing and development costs significantly. The system can also operate on standard computer

systems without requiring expensive hardware resources.

The proposed system helps reduce financial losses caused by malicious Android applications, spyware attacks, and privacy violations. By identifying risky permissions before application installation, the system protects sensitive user information and improves cybersecurity awareness. Automated permission analysis also reduces manual inspection efforts and improves operational efficiency.

The system provides long-term economic benefits through scalability and low maintenance requirements. Since the framework supports future updates and additional security features without major infrastructure changes, the project remains financially sustainable. Overall, the proposed system is economically practical and beneficial for Android security enhancement.

4.3 TECHNICAL FEASIBILITY

The technical feasibility evaluates whether the proposed Secure Mobile Application Permission Analyzer can be implemented effectively using available technologies and development tools. The system uses Python programming language, Natural Language Processing techniques, and Machine Learning algorithms to analyze Android application permissions and classify them into safe or risky categories.

The framework extracts permission information from Android applications and processes permission descriptions using NLP methods such as tokenization, stop-word removal, and semantic analysis. Machine learning models are trained using permission datasets to improve classification accuracy and identify suspicious permission patterns associated with malware or spyware activities.

The system architecture is lightweight, scalable, and efficient for real-time permission analysis. Web technologies such as Flask, HTML, CSS, and JavaScript support frontend and backend integration for smooth system operation. Overall, the proposed framework is technically feasible, reliable, and suitable for Android cybersecurity applications.

4.4 SOCIAL FEASIBILITY

The social feasibility of the Secure Mobile Application Permission Analyzer focuses on user acceptance, cybersecurity awareness, and the social impact of the proposed system. The framework helps users understand Android application permissions and identify potentially harmful applications before installation. This improves user awareness regarding privacy and mobile security threats.

The system provides a simple and user-friendly interface that displays permission details, warning notifications, and risk classifications clearly. Even non-technical users can easily understand dangerous permissions and suspicious application behavior. This increases usability and encourages wider acceptance of the system in educational, organizational, and personal security environments.

The proposed system contributes to society by promoting safer smartphone usage and reducing risks related to spyware, malware, and unauthorized data access. Ethical considerations such as privacy protection and secure handling of application information are also maintained. Overall, the project supports better cybersecurity practices and helps create a safer digital environment for Android users.

The proposed system also supports educational and research activities in the field of cybersecurity and mobile application security. Students, researchers, and security analysts can use the framework to study Android permission behaviors and understand how malicious applications misuse sensitive permissions. The integration of Artificial Intelligence and Natural Language Processing improves awareness about advanced mobile security technologies and encourages users to adopt safer digital practices. Continuous improvements and future enhancements can further increase the system's social value and effectiveness in protecting user privacy and smartphone security.

CHAPTER 5

SYSTEM DESIGN

5. SYSTEM DESIGN

System design describes the overall structure , workflow, and interaction between different modules of the “Secure Mobile Application Permission Analyzer Using Natural Language Processing” system. It explains how Android application permissions are collected, processed, analyzed, and classified using Natural Language Processing (NLP) and Machine Learning techniques. Proper system design helps improve system organization, scalability, efficiency, maintainability, and security analysis performance.

5.1 SYSTEM ARCHITECTURE

A System Architecture is the conceptual model that defines the structure and interaction between different modules of a system. It helps in understanding system functionality, data flow, and communication between components for efficient implementation and maintenance.




Figure 5.1: System Architecture of Secure Mobile Application Permission Analyzer Using Natural Language Processing

In Figure 5.1, the proposed system collects Android application permission details from users through a web interface. The Permission Collection module extracts permission data from

APK files or datasets and forwards it to the NLP Processing module. The NLP module performs preprocessing techniques such as tokenization, stop-word removal, stemming or lemmatization, and feature extraction to prepare the permission data for analysis. The Machine Learning Classification module analyzes the processed permission data and classifies applications into Safe, Suspicious, or High Risk categories. The Risk Analysis Engine further examines permission patterns, detects dangerous permission combinations, calculates risk scores, and generates security alerts. The SQLite database stores permission analysis results, user history, alerts, and generated reports for future reference. The Visualization Dashboard displays real-time graphs, alerts, statistics, and permission analysis results to users. Finally, the Report Generation module creates downloadable PDF and CSV reports containing application risk summaries and security analysis details. Overall, the system integrates NLP, Machine Learning, database management, and visualization techniques to enhance Android application privacy and security analysis.

5.2 UML DIAGRAM

UML (Unified Modeling Language) is a standardized modeling language used for visualizing, designing, and documenting software systems. In the proposed “Secure Mobile Application Permission Analyzer Using Natural Language Processing,” the UML diagram represents the interaction between the user and major system functionalities such as permission upload, permission analysis, dashboard monitoring, risk classification, report generation, and result export. It helps in understanding the workflow and interaction between different modules of the system. UML diagrams provide a clear graphical representation of the overall system architecture, making it easier to understand data flow, module connectivity, and system behavior. They also support efficient system planning and implementation by helping developers identify dependencies, process flow, and functional relationships between different components. In addition, UML diagrams improve communication between developers, project guides, and users by providing a simple and structured visualization of the system. They also serve as an important part of project documentation, helping during future maintenance, debugging, testing, and scalability improvements of the application.




Figure 5.2: UML Diagram

The primary goals of UML diagrams are to:

1. Illustrate and Structure the Overall System Architecture:

UML diagrams provide a clear graphical representation of the Permission Analyzer architecture, showing how modules such as permission upload, NLP-based analysis, machine learning detection, dashboard visualization, report generation, and result export are connected. This helps in designing the system efficiently and improving system organization.

2. Improve System Understanding:

The diagram helps developers and users understand the interaction between system modules and the workflow of permission analysis using Natural Language Processing and Machine Learning techniques. It simplifies complex processing steps and improves clarity regarding data flow and system operations.

3. Support System Design and Planning::

UML diagrams help in analyzing workflows, defining system requirements, and planning implementation activities efficiently. They assist developers in identifying dependencies between modules and designing a scalable and maintainable architecture for Android permission analysis and risk classification.

4. Enhance Communication Between Stakeholders:

The UML diagram acts as an effective communication tool between developers, project guides, researchers, and users by providing a structured visual representation of system operations. It helps stakeholders understand project functionality clearly and reduces confusion during system development, testing, and presentation activities.

5. Provide Documentation Support:

UML diagrams serve as an important part of project documentation by clearly representing the structure, workflow, and interactions within the system. They help during future maintenance, debugging, feature enhancement, and scalability improvements by providing a well-organized reference for understanding the system architecture and module interactions.

5.3 DATA FLOW DIAGRAM

A Data Flow Diagram (DFD) is a graphical representation that shows how data moves within a system. It is used to illustrate the flow of information between processes, databases, and external entities. DFDs help in understanding how input data is processed and transformed into meaningful output through different stages within the system. They simplify complex workflows, improve system understanding, and support efficient software design, development, and maintenance. DFDs also act as an effective communication tool between developers, project guides, and users by providing a clear and organized representation of system operations.

In the proposed “Secure Mobile Application Permission Analyzer Using Natural Language Processing,” the Data Flow Diagram represents how Android application permission data is collected, processed, analyzed, and converted into security analysis reports. The system accepts permission details through a web interface, processes the data using NLP techniques such as tokenization, stop-word removal, stemming, and feature extraction, and then applies Machine Learning models to classify permissions into Safe, Suspicious, or High-Risk categories. The Risk Analysis Engine detects dangerous permission combinations and generates alerts, while the analysis results, reports, and user history are stored in the SQLite database and displayed through the visualization dashboard in the form of graphs, alerts, and security reports.




Figure 5.3: Data Flow Diagram

Figure 5.3 shows the Data Flow Diagram (DFD) for the Secure Mobile Application Permission Analyzer system, illustrating the complete flow of data within the application. The

process begins when the user uploads Android application permission details through the web interface. The Permission Collection module extracts and organizes permission information, which is then processed using NLP techniques and Machine Learning classification models. The analyzed results are passed to the Risk Analysis Engine to calculate risk levels and generate security alerts. Finally, the processed information is stored in the SQLite database and displayed through the dashboard and report generation modules. This structured flow ensures efficient Android permission analysis, intelligent risk classification, and real-time security monitoring within the system.

5.4 USE CASE DIAGRAM

A Use Case Diagram is a graphical representation that illustrates the interaction between users and the functionalities of a system. It is a behavioral UML diagram used to represent system operations, user activities, and functional requirements in a simple and understandable format. Use case diagrams help developers and users understand the workflow, module interaction, and overall behavior of the system efficiently.

In the proposed “Secure Mobile Application Permission Analyzer Using Natural Language Processing,” the Use Case Diagram represents the interaction between users, administrators, and various functional modules involved in permission analysis and security monitoring. The diagram includes functionalities such as uploading Android application data, collecting permissions, preprocessing permission information using Natural Language Processing techniques, performing Machine Learning-based risk classification, generating alerts, storing analysis results, viewing dashboards, generating reports, and exporting results.

The Use Case Diagram helps in visualizing how different modules communicate within the system and how users interact with the application through various operations. It simplifies workflow understanding, improves system planning, and supports effective implementation, testing, maintenance, and project documentation activities.




Figure 5.4: Use Case Diagram

Figure 5.4 shows the Use Case Diagram for the proposed Secure Mobile Application Permission Analyzer system. The primary actors involved in the system are the User, Admin, System, and Notification Service. The User interacts with functionalities such as uploading Android application data, starting permission analysis, viewing dashboards, generating reports, and exporting analysis results. The Admin manages users, monitors system activities, and views audit logs. The system internally performs permission collection, NLP preprocessing, Machine Learning classification, risk analysis, database storage, dashboard visualization, and report generation processes. The Notification Service is responsible for handling alerts and security notifications generated during permission risk analysis. The diagram illustrates the overall interaction and workflow of the system modules involved in Android permission analysis and intelligent security monitoring using NLP and Machine Learning techniques.

5.5 ACTIVITY DIAGRAM

An Activity Diagram is a behavioral UML diagram used to represent the flow of activities and operations within a system. It illustrates the sequence of actions, decision-making processes, and workflow of the application in a graphical format. Activity diagrams help developers and users understand how the system functions step by step and how different modules interact during execution.

Activity diagrams are useful for representing workflows, sequential processing, and decision-based operations within a system. They help identify system dependencies, improve workflow understanding, reduce complexity, and support efficient software design and implementation. These diagrams also improve communication among developers, project guides, and users by visually explaining system behavior.

In the proposed “Secure Mobile Application Permission Analyzer Using Natural Language Processing,” the Activity Diagram represents the complete workflow involved in Android permission analysis. The process begins when the user uploads Android application permission data or APK information into the system. The Permission Collection module extracts the permission details and sends them to the NLP Processing module for preprocessing operations such as tokenization, stop-word removal, stemming, and feature extraction.

After preprocessing, the Machine Learning module analyzes permission patterns and classifies them into Safe, Suspicious, or High-Risk categories. The Risk Analysis Engine then evaluates dangerous permission combinations and generates alerts if suspicious behavior is detected. If the calculated risk level is high, the system sends notifications through dashboard alerts or email services. Otherwise, the application is marked as safe or low risk.

Finally, the analysis results, alerts, and reports are displayed through the dashboard interface. The system then generates detailed security reports and allows users to export the results in PDF, CSV, or Excel format for future reference and documentation.




Fig 5.5: Activity Diagram

Figure 5.5 shows the Activity Diagram for the Secure Mobile Application Permission

Analyzer system, illustrating the complete workflow of Android permission analysis. The process starts with uploading permission data, followed by permission extraction, NLP preprocessing, machine learning-based risk classification, and risk analysis. Based on the calculated risk level, the system identifies applications as safe or suspicious and generates alerts when necessary. The final results are displayed through the dashboard interface, where users can view alerts, analysis reports, and export security reports for future reference.

5.6 SEQUENCE DIAGRAM

Sequence diagrams are useful in visualizing the dynamic behavior of a system by representing interactions between users and system modules in a time-ordered manner. They clearly show the sequence of operations, message flow, and communication between different components involved in the process. Sequence diagrams help developers and stakeholders understand system functionality, module dependencies, and workflow execution effectively.




Figure 5.6: Sequence Diagram

Figure 5.6 shows the Sequence Diagram for the proposed “Secure Mobile Application Permission

Analyzer Using Natural Language Processing” system. The diagram illustrates the interaction between the User, Mobile Application, Risk Categorization Module, Data Collection and Privacy Module, Third-Party Sharing Module, Dashboard, and Report Module. The process begins when the user logs into the application and submits permission-related data. The Data Collection Module gathers and processes the permission information, while the Third-Party Sharing Module analyzes data-sharing activities and privacy-related behavior. The Risk Categorization Module evaluates the collected data and classifies the application based on risk levels. The processed results are then displayed on the dashboard, and the Report Module generates downloadable privacy and security analysis reports for the user.

5.7 CLASS DIAGRAM

A Class Diagram is a static structural diagram that represents the structure of a system by showing classes, their attributes, methods, and relationships. It helps in understanding the organization of the system and how different modules interact with each other. Class diagrams are useful for modeling the static structure of software systems and improving system design and implementation.

In the proposed “Secure Mobile Application Permission Analyzer Using Natural Language Processing,” the class diagram represents important system components such as User, DataSubmission, DataCollectionModule, RiskCategorizationModule, ThirdPartySharingModule, RiskResult, Dashboard, Alert, and Report. These classes handle permission data collection, privacy analysis, risk categorization, alert generation, dashboard visualization, and report generation functionalities.

Class diagrams also improve communication between developers and stakeholders by providing a clear representation of system architecture. They support software maintenance, debugging, scalability, and future enhancements by organizing functionalities into separate modules.




Figure 5.7: Class Diagram

Figure 5.7 shows the Class Diagram for the proposed Android Permission Analyzer system. The User class manages authentication and permission requests, while the DataCollectionModule collects application permission and privacy-related data. The RiskCategorizationModule analyzes the collected information and categorizes applications into different risk levels. The ThirdPartySharingModule monitors data-sharing behavior with external services. The RiskResult and Alert classes manage risk scores and notifications, while the Dashboard and Report classes display analysis information and generate downloadable privacy and security reports.

CHAPTER 6

IMPLEMENTATION

6. IMPLEMENTATION

Implementation explains the practical development and execution of the proposed “Secure Mobile Application Permission Analyzer Using Natural Language Processing” through different functional modules. The system collects Android application permissions, processes permission-related text using NLP techniques, analyzes sensitive permissions, and generates risk analysis reports. These modules work together to identify suspicious permission behavior and improve Android application security. The implementation ensures accurate permission analysis, efficient risk detection, and better privacy protection for users.

6.1 CLASSIFICATION OF MODULES

- Permission Collection Module
- NLP Processing Module
- Risk Analysis and Detection Module
- Report Generation and Summary Module

6.2 MODULE DESCRIPTION

Module description explains the functions and responsibilities of each module used in the project. Every module performs a specific task such as collecting permissions, processing text data, analyzing risks, and generating reports. These modules work together to ensure smooth system operation and accurate permission risk analysis. It improves efficiency, privacy monitoring, and overall system performance.

6.2.1 Data Collection and Ingestion Environment

The Permission Collection Module is responsible for gathering Android application permission details, privacy policies, and Terms & Conditions from uploaded applications or datasets. Important permissions such as camera access, microphone access, location access, storage access, contact access, and SMS permissions are collected for further analysis. This module acts as the starting point of the system and provides the required input data for security evaluation. Proper permission collection helps improve the overall effectiveness of the analysis process.

The module extracts permission-related information from Android applications in a structured format to ensure consistency during processing. Since different applications may request permissions in different ways, organizing the data properly is essential for accurate analysis. Structured permission data improves readability and simplifies further processing stages. It also helps the system maintain compatibility with multiple application datasets and permission sources..

Data cleaning and preprocessing are performed during collection to remove duplicate entries and unnecessary information. This improves the quality of the collected data and prevents errors in later stages of analysis. Clean permission data ensures smooth workflow between system modules and improves system reliability. Proper preprocessing also reduces processing complexity and improves performance.

The module is designed to efficiently handle multiple Android applications and large permission datasets without reducing system performance. Efficient permission handling supports both real-time and offline analysis of applications. Scalability is important because modern mobile environments contain thousands of applications with different permission requests. The module ensures stable operation even when processing large amounts of permission information.

6.2.2 NLP Processing Module

The NLP Processing Module processes permission-related text using Natural Language Processing techniques to identify meaningful security information. Permission descriptions, privacy policies, and Terms & Conditions are analyzed to extract important keywords related to privacy and security risks. NLP techniques such as tokenization, stop-word removal, stemming, and feature extraction are applied during processing. These techniques improve the understanding of application behavior and help identify suspicious permission patterns effectively.

Text preprocessing is performed to remove unwanted symbols, duplicate words, irrelevant text, and unnecessary characters from the collected data. This normalization process improves data quality and ensures consistency throughout the system. Clean and normalized text allows the system to analyze permission-related information more accurately. It also reduces the possibility of incorrect analysis caused by noisy or incomplete text data.

The module converts unstructured textual information into structured data suitable for

further analysis and machine learning operations. Structured data improves processing efficiency and helps the system identify sensitive permissions more effectively. Organizing textual information properly also improves compatibility with classification and risk analysis algorithms. This enhances the accuracy of the overall permission analyzer system.

Feature extraction techniques are used to identify important privacy-related keywords and suspicious permission patterns from the processed text. Extracted features help the system recognize risky application behavior and hidden privacy threats. These features act as indicators during risk classification and security evaluation. Proper feature extraction improves the intelligence and effectiveness of the system significantly.

The NLP module also supports continuous improvement of analysis accuracy by processing different types of permission-related content efficiently. Modern Android applications often contain complex privacy policies and dynamically generated permission descriptions. The module ensures that such complex text is processed correctly without losing important information. This strengthens the system's ability to detect privacy risks and improves overall security analysis performance.

6.2.3 Risk Analysis and Detection Module

The Risk Analysis and Detection Module analyzes sensitive Android permissions and evaluates the security risk associated with each application. Dangerous permissions such as camera access, microphone access, SMS permission, contact access, and location tracking are carefully examined to identify suspicious behavior. The module helps determine whether an application is safe or potentially harmful to user privacy and device security. This improves the overall protection provided by the system.

Machine Learning techniques and pattern analysis are used to classify applications into different risk levels such as Safe, Medium Risk, and High Risk. The system compares permission patterns with predefined security rules and trained detection models to identify unusual activities. Combining intelligent analysis techniques improves detection accuracy and reduces the chances of missing hidden threats. This creates a more reliable and efficient risk detection system.

The module identifies dangerous permission combinations that may lead to privacy leakage, unauthorized access, or malicious activities. Applications requesting unnecessary or excessive permissions are marked as suspicious for further analysis. This layered approach helps detect both

known and unknown threats effectively. It improves the system's ability to monitor Android application behavior continuously, making in real-time systems. It is a critical step for improving system efficiency.

Risk scoring and prioritization mechanisms are implemented to classify applications based on the severity of their permission requests. Each application is assigned a risk level according to its permission usage and detected behavior patterns. This helps users quickly identify high-risk applications that require immediate attention. Prioritized analysis also improves decision-making and enhances security management efficiency.

Continuous monitoring and analysis improve the adaptability of the system against evolving Android security threats. As new permission abuse techniques and malicious applications appear, the detection module can adapt its analysis process accordingly. Regular updates to machine learning models and risk evaluation techniques improve long-term system effectiveness. This strengthens the reliability and performance of the permission analyzer framework.

6.2.4 Report Generation and Summary Module

The Report Generation and Summary Module generates detailed reports based on permission analysis and risk detection results. The system prepares structured summaries showing permission usage, privacy impact, suspicious permissions, and application risk levels. These reports help users understand the security condition of Android applications clearly and effectively. Proper reporting improves transparency and supports better security awareness.

Analysis results are displayed using summaries, tables, charts, and graphical representations for easy understanding. Important information such as risk percentage, permission statistics, suspicious behavior, and privacy alerts are presented visually to improve user experience. Visualization simplifies complex security information and helps users analyze application behavior more efficiently. This improves overall monitoring and decision-making capabilities.

The module supports generating reports in downloadable formats for documentation and future reference purposes. Users can save and export analysis results whenever required. Stored reports help maintain proper records of analyzed applications and detected risks. This feature is

useful for security monitoring, auditing, and long-term privacy analysis activities.

Historical analysis and report storage capabilities help users compare application behavior over time and identify recurring privacy risks. Previously generated reports can be reviewed to study permission usage trends and suspicious activities. Long-term report management improves tracking and enhances overall cybersecurity monitoring. It also supports future improvements in risk analysis and threat detection..

The module also improves communication between users and the system by presenting analysis results in a simple and understandable format. Security alerts, summaries, and recommendations help users take necessary precautions against risky applications. Clear reporting improves user trust and enhances the usability of the permission analyzer system. This strengthens the overall effectiveness of the project and supports better Android security management.

The Report Generation and Summary Module also helps administrators and researchers perform detailed security evaluations by organizing analysis data systematically. The generated reports can support security investigations, academic research, and application review processes. Automated report generation reduces manual effort and ensures consistent documentation of permission analysis results.

Furthermore, the module can assist in identifying high-risk applications quickly by highlighting critical security warnings and unusual permission combinations. Early detection of such risks helps prevent privacy breaches and improves user safety. This enhances the reliability of the system and contributes to stronger mobile application security management.

CHAPTER 7

RESULT AND DISCUSSION

7. RESULT AND DISCUSSION

The proposed “Secure Mobile Application Permission Analyzer Using Natural Language Processing” produced effective results in analyzing Android application permissions and identifying privacy-related risks. The system successfully detected suspicious permission patterns, risky permission combinations, and sensitive access requests using NLP and Machine Learning techniques. Dashboard visualization and generated reports helped users monitor application behavior and understand permission risks clearly. The project improved permission analysis accuracy, privacy monitoring, and overall Android application security.

7.1 RESULT

The implemented permission analyzer framework produced reliable and efficient results during the permission analysis process. The system combines Natural Language Processing, keyword extraction, machine learning classification, and risk analysis techniques to identify both normal and suspicious permission behavior. It successfully analyzed permissions such as camera access, microphone access, SMS permission, storage access, and location tracking to determine application risk levels. The framework also generated security summaries, permission analysis reports, privacy risk indicators, and downloadable reports, while the dashboard provided smooth visualization of analysis results and application statistics.




Figure 7.1: Permission Analysis and Risk Classification Dashboard

Figure 7.1 represents the permission analysis behavior and risk classification performance of the proposed Android security system. The dashboard shows how the system processes uploaded application permissions and classifies them into Safe, Medium Risk, or High Risk categories over a specific time period. The graph can be interpreted through permission analysis accuracy, risk detection consistency, and system response behavior under different workloads. Higher analysis regions indicate efficient NLP processing and reliable machine learning classification, while small variations may occur during processing of applications containing large permission datasets or complex privacy policies. This visualization is important because the effectiveness of the project depends not only on accurate risk prediction but also on stable processing performance and clear presentation of security insights for users.

7.2 DISCUSSION

The results indicate that a Natural Language Processing (NLP) and machine learning-based permission analysis approach is more effective for Android security than traditional rule-based or manual permission checking methods. NLP helps in understanding the semantic meaning of Android permission descriptions, while machine learning improves generalization by detecting patterns and combinations of permissions associated with spyware, malware, and privacy violations. This layered approach improves detection accuracy by analyzing both individual permissions and their relationships, enabling the system to identify suspicious behaviors such as excessive permission requests and misuse of sensitive resources like camera, microphone, contacts, and location. However, challenges still exist, such as dependency on high-quality training data, difficulty in handling ambiguous or evolving permission descriptions, and balancing false positives and false negatives. From a deployment perspective, future improvements should focus on integrating advanced NLP models such as transformers and enabling real-time APK behavior monitoring with continuous model updates. Overall, the proposed system demonstrates that combining NLP and machine learning provides a scalable solution for Android permission security analysis and can be extended with cloud-based intelligence to strengthen mobile security.

CHAPTER 8

CONCLUSION AND FUTURE WORK

8. CONCLUSION AND FUTURE WORK

The project successfully analyzed Android application permissions using Natural Language Processing (NLP) and machine learning techniques to identify risky and suspicious permissions. It effectively detected privacy-related threats, malicious permission combinations, and potentially harmful application behaviors, improving Android security analysis. Future improvements can focus on reducing false positives, improving semantic understanding of permissions, and enhancing real-time APK analysis capabilities. The system can further strengthen mobile cybersecurity and user privacy protection in Android environments.

8.1 CONCLUSION

Android application permission analysis plays an important role in improving mobile cybersecurity and protecting user privacy. The proposed system uses Natural Language Processing (NLP) and machine learning techniques to analyze Android permissions and identify risky or suspicious applications effectively. The framework improves permission understanding, detects harmful permission combinations, and helps users avoid potential malware and privacy threats. Although challenges such as false positives and evolving malware behaviors still exist, continuous improvements in AI and NLP techniques can further enhance Android security and application threat detection.


8.2 FUTURE WORK

As a future enhancement, the system can incorporate advanced deep learning and transformer-based NLP models for improved permission understanding and classification accuracy. Integration of real-time APK scanning and dynamic behavior analysis can further strengthen the detection of unknown or evolving malicious applications. The framework may also be extended with cloud-based threat intelligence systems, automated alert mechanisms, and continuous model retraining for better adaptability and scalability. Additional improvements can include multilingual permission analysis, advanced visualization dashboards, and automated recommendation systems for users. Future versions of the system may also support real-time mobile device monitoring and AI-driven risk prediction techniques to improve Android cybersecurity and privacy protection more effectively.

APPENDIX - I

APPENDIX - I

I. OUTPUT



The image shows a web-based interface for a tool called "Permission Analyzer". At the top, there is a blue shield icon and the title "Permission Analyzer" in a large, bold, black font. Below the title, a subtitle reads: "Analyze mobile app permissions & privacy policies using AI to uncover hidden data risks." The interface is set against a light gray grid background. Below the subtitle, there is a section labeled "APP NAME (REQUIRED)" in blue. It contains a text input field with the placeholder text "e.g. WhatsApp, TikTok, Instagram...". Below this input field are two buttons: "Paste Text" (with a document icon) and "Screenshot" (with a camera icon). Below these buttons is a large text area with the placeholder text "Paste the app's privacy policy or permissions list here...". At the bottom of the form is a large blue button labeled "Analyze Permissions" with a right-pointing arrow icon. At the very bottom of the interface, there is a small footer that reads: "© 2026 Permission Analyzer • Built by @shunmugapriya2-bot".

Figure i: Permission Analyzer Input Interface for Mobile Application Privacy Assessment

In Figure i, it describes the main interface of the Secure Mobile Application Permission Analyzer using Natural Language Processing. The interface allows users to enter the name of a mobile application and provide privacy-related content for analysis. Users can either paste the application's privacy policy text directly or upload screenshots containing permissions, privacy policies, or terms and conditions. This flexible input mechanism improves usability and supports multiple forms of privacy data collection. The system is designed to analyze application permissions and identify potential privacy risks using AI-based techniques. The interface clearly separates text input and screenshot upload options for better accessibility and user interaction. A dedicated "Analyze Permissions" button initiates the analysis process after the required information is provided. The simple and organized layout improves user experience and minimizes confusion during data submission. Overall, the module acts as the primary interface for collecting privacy-related information from mobile applications for further analysis and risk assessment.




Figure ii: Screenshot Upload and AI-Based Text Extraction Process

In Figure ii, it describes the screenshot upload functionality integrated within the Permission Analyzer system. Users can upload screenshots containing privacy policies, permissions, or terms and conditions of mobile applications for automated analysis. Once the screenshot is uploaded, the system applies AI-based text extraction techniques to retrieve textual information from the image. The extracted content is then processed for identifying sensitive permissions and privacy-related risks. This feature allows users to analyze applications even when the information is available only in image format. The upload interface also provides validation and preview functionality to ensure correct file submission before processing. A progress indicator is displayed while the AI extraction and analysis are being performed. This improves transparency and user awareness during processing. The screenshot-based analysis enhances flexibility and broadens the usability of the system. Overall, the module simplifies privacy analysis by automatically converting image-based information into analyzable text data.

Here's how it works:

- I. User uploads a screenshot containing permissions, privacy policies, or terms and conditions.
- II. The system validates the uploaded image format and size before processing.

III. AI-based text extraction techniques are applied to retrieve textual content from the screenshot.

IV. The extracted text is cleaned and prepared for further analysis.

V. Privacy-related keywords and sensitive permissions are identified from the extracted content.

VI. Risk analysis is performed based on detected permissions and policy patterns.

VII. The final privacy risk report is generated and displayed to the user.




Figure iii: Privacy Risk Analysis Report and Risk Level Assessment

In Figure iii, it describes the analysis report generated by the Permission Analyzer after processing the uploaded application data. The report provides an overall privacy risk assessment based on the permissions, privacy policies, and terms and conditions associated with the application. The system identifies whether the analyzed application contains potentially risky data collection or sharing practices. A visual risk indicator is displayed to represent the overall privacy

risk percentage. The report also summarizes key findings extracted from the analyzed content to help users understand potential threats more effectively. The system uses Natural Language Processing techniques to detect sensitive terms and high-risk privacy behaviors from the uploaded content. The interface presents the results in a structured and readable format for better understanding and analysis. Users can also view extracted text and copy analysis results for future reference. This module improves transparency by explaining why the application is categorized under a particular risk level. Overall, the analysis report helps users make informed decisions regarding application privacy and data security. The module also enhances awareness about hidden data collection practices and third-party data sharing activities present within mobile applications.




Figure iv: Risk Categorization Interface for Privacy Threat Assessment

In Figure iv, it describes the risk categorization interface of the Secure Mobile Application Permission Analyzer. The interface visually represents different privacy risk categories identified during the analysis process. The system classifies detected risks based on permissions, extracted keywords, and suspicious privacy-related patterns found within the application’s privacy policy or terms and conditions. Each category is assigned a percentage value to indicate its contribution to the overall privacy risk level. This helps users easily understand which privacy factors pose the greatest concern.

The interface also highlights sensitive permission usage and risky data handling

practices identified through Natural Language Processing techniques. Graphical representations improve interpretability and allow users to analyze privacy threats more efficiently. The categorized view simplifies complex privacy analysis results into understandable insights for both technical and non-technical users. Overall, the module improves transparency and assists users in understanding the severity of privacy risks associated with mobile applications.




Figure v: Privacy Recommendation and Risk Mitigation Module

In Figure v, it describes the privacy recommendation and risk mitigation module of the Secure Mobile Application Permission Analyzer. The module provides personalized recommendations based on the detected privacy risks and suspicious permission usage identified during analysis. The system suggests appropriate actions such as limiting unnecessary permissions, reviewing privacy settings, and avoiding excessive data sharing practices. These recommendations help users improve their privacy awareness and reduce potential security risks while using mobile applications.

The interface presents recommendations in a clear and structured format for easier understanding and implementation. This guidance helps users make informed decisions before installing or using applications. The recommendation module enhances transparency by providing actionable suggestions instead of only displaying risk scores. Overall, the module strengthens privacy protection and supports safer mobile application usage through effective risk mitigation strategies.

APPENDIX - II

APPENDIX - II

II. SAMPLE CODE

Sample code represents the implementation of important functionalities used in the project “Secure Mobile Application Permission Analyzer Using Natural Language Processing.” The system analyzes screenshots of application permission policies, privacy policies, and terms & conditions using OCR, NLP, and machine learning techniques. It identifies risky permissions, suspicious keywords, privacy threats, and displays risk percentage with graphical analysis for user awareness.

i. IMAGE UPLOAD AND SCREENSHOT PROCESSING

```
from flask import Flask,
request
import os

app = Flask(__name__)

UPLOAD_FOLDER =
"uploads"

app.config['UPLOAD_FOLD
ER'] = UPLOAD_FOLDER

@app.route('/upload',
methods=['POST'])
def upload_image():
    file = request.files['image']

    if file:
        filepath =
os.path.join(app.config['UPL
OAD_FOLDER'],
file.filename)
```

```

        file.save(filepath)

    return "Screenshot
Uploaded Successfully"

if __name__ == "__main__":
    app.run(debug=True)

```

ii. OCR TEXT EXTRACTION FROM SCREENSHOT

```

import pytesseract
from PIL import Image

image = Image.open("policy_screenshot.png")

extracted_text = pytesseract.image_to_string(image)

print("Extracted Text:")
print(extracted_text)

```

iii. NLP-BASED RISK KEYWORD ANALYSIS

```

risky_keywords = [
    "location",
    "contacts",
    "microphone",
    "camera",
    "sms",
    "storage"
]

text = """
This app can access your location,
contacts, camera, and storage.
"""

```

```

detected = []

for word in risky_keywords:
    if word.lower() in text.lower():
        detected.append(word)

print("Risky Keywords Found:")
print(detected)

```

iv. DATABASE STORAGE USING SQLITE

```

import sqlite3

connection = sqlite3.connect("permission_analyzer.db")

cursor = connection.cursor()

cursor.execute("""
CREATE TABLE IF NOT EXISTS app_analysis (
    id INTEGER PRIMARY KEY AUTOINCREMENT,
    app_name TEXT,
    risky_permission TEXT,
    risk_level TEXT
)
""")

cursor.execute("""
INSERT INTO app_analysis (app_name, risky_permission, risk_level)
VALUES (?, ?, ?)
""", ("Sample App", "READ_SMS", "High Risk"))

connection.commit()

print("Data Stored Successfully")

connection.close()

```

REFERENCES

REFERENCES

- [1] A. Kumar, R. Patel, and S. Sharma, "NLP based permission usage auditing in Android app descriptions and privacy policies", *Computers & Security*, vol. 140, pp. 113–128, 2024.
- [2] B. Zhao, L. Zhang, and Y. Wang, "NLP-based verification of permission consistency between app descriptions and code level behavior", *Computers & Security*, vol. 142, pp. 103945–103965, 2025.
- [3] C. Lopez, J. Garcia, and M. Sanchez, "Transformer-based NLP pipeline for secure mobile app permission policy analysis", *Inf. Sci.*, vol. 630, pp. 245–265, 2025.
- [4] E. Kim, J. Park, and S. Lee, "NLP-driven user review analysis for detecting permission-related privacy concerns", *IEEE Trans. Consumer. Electron.*, vol. 70, no. 2, pp. 2341–2358, 2024.
- [5] F. Garcia, M. Rodriguez, and C. Martinez, "Cross-language NLP models for Android app permission meaning analysis", *Inf. Process. Manage.*, vol. 59, no. 4, pp. 102960–102980, 2024.
- [6] H. Liu, X. Wu, and Y. Yang, "NLP-enabled privacy policy to-permission mapping framework for secure mobile apps", *Future Gener. Computer. Syst.*, vol. 155, pp. 412–429, 2025.
- [7] J. Brown, M. Davis, and K. Wilson, "NLP-assisted auditing of excessive and misleading mobile app permissions", *Inf. Process. Manage.*, vol. 59, no. 3, pp. 102908–102925, 2024.
- [8] L. Chen, H. Wang, and M. Liu, "Harnessing large language models to analyse Android app permission declarations", *IEEE Trans. Inf. Forensics Security*, vol. 19, no. 6, pp. 4521–4538, 2024.
- [9] M. Singh, A. Verma, and P. Rao, "Explainable NLP classifier for Android app permission risk labelling", *IEEE Trans. Neural Networks. Learn. Syst.*, vol. 36, no. 3, pp. 1823–1840, 2025.
- [10] N. Iyer, V. Rao, and S. Bhat, "NLP-enabled fine-grained permission risk classification for mobile app security", *Knowledge-Based Syst.*, vol. 278, pp. 110912–110930, 2025.
- [11] P. Das, S. Nath, and A. Ghosh, "Natural language-guided permission risk assessment for mobile app security", *Knowledge-Based Syst.*, vol. 274, pp. 110645–110665, 2025.

- [12] R. Patel, V. Kumar, and S. Desai, "NLP-driven permission pair interaction risk analysis for secure mobile application recommendation", *Expert Syst. Appl.*, vol. 230, pp. 120589–120605, 2024.
- [13] S. Sharma, N. Gupta, and A. Mishra, "Natural language processing for secure mobile app permission risk assessment", *IEEE Trans. Dependable Secure Computer.*, vol. 21, no. 4, pp. 2156–2171, 2024.
- [14] T. Nguyen, L. Tran, and H. Hoang, "NLP-assisted permission anomaly detection in Android app stores", *J. Inf. Security Appl.*, vol. 78, pp. 103501–103520, 2024.
- [15] X. Wang, Z. Zhou, and Q. Liu, "Large language model assisted Android permission purpose inference from app descriptions and policies", *IEEE Access*, vol. 12, pp. 78521–78540, 2024.
- [16] Y. Zhang, J. Li, and W. Chen, "Fine-grained permission policy alignment verification using transformer-based NLP", *Inf. Sci.*, vol. 620, 10.1016/j.ins.2025.876895, pp. 876–895, 2025.



SRM VALLIAMMAI ENGINEERING COLLEGE

(An Autonomous Institution)

ESTD. 1999 - Accredited by NBA - Approved by AICTE

'A' Grade Accreditation by NAAC

ISO 21001:2018 Certified - Affiliated to Anna University Chennai

CENTRE OF EXCELLENCE IN SUSTAINABILITY

SDG CERTIFICATE

This is to certify that the project work "**SECURE MOBILE APPLICATION PERMISSION ANALYZER USING NATURAL LANGUAGE PROCESSING**" has been successfully completed by **SHUNMUGA PRIYA R (142223128045)**, **SRIMATHI V (142223128048)**, **VISHWA A (142223128057)** of B.E. - Cyber Security, during the academic year 2025-26. This project aligns with the United Nations Sustainable Development Goals and mapped to the following Sustainable Development Goal(s) (SDGs):

SDG Number	Name	Brief Justification
9	Industry, Innovation And Infrastructure	The project promotes secure mobile application infrastructure using NLP-based permission analysis to improve Android app security and privacy protection.
16	Peace, Justice and Strong Institutions	The project strengthens digital safety by detecting risky app permissions, preventing privacy threats, and supporting safer mobile environments.



Build resilient infrastructure, promote inclusive and sustainable industrialization and foster innovation



Promote peaceful and inclusive societies for sustainable development

PROJECT SUPERVISOR

CES COORDINATOR

HOD/CYS



SRM Nagar, Kattankulathur - 603203, Chengalpattu District, Tamil Nadu, India
Phone : 044 - 27454784, 27454726 & 27451498 Fax : 044 - 27451504

Website : www.srmvalliammai.ac.in Email: srmvec@srmvalliammai.ac.in

SURVEY ON A SECURE MOBILE APPLICATION PERMISSION ANALYZER USING NATURAL LANGUAGE PROCESSING

Ms. M. RAGHAVI

Department of Cybersecurity
SRM Valliammai Engineering College
Chengalpattu, India
raghavirgo@gmail.com

SHUNMUGA PRIYA. R

Department of Cybersecurity
SRM Valliammai Engineering College
Chengalpattu, India
shunmugapriyaradha2022@gmail.com

SRIMATHI. V

Department of Cybersecurity
SRM Valliammai Engineering College
Chengalpattu, India
srimathisrimathi089@gmail.com

Abstract Many Android applications have quickly grown in popularity, leading to a substantial rise in the need for safe management of user data and permissions. Sensitive resources like location, contacts, storage and hardware device are often requested by modern applications. There are some applications that require permissions that aren't needed for the app to operate, posing severe privacy concerns; data leakage and the threat of misuse of personal data. Static and dynamic analysis are examples of existing traditional security mechanisms which fail to provide the contextual meaning behind permission usage. With all its challenges, on the other hand, Natural Language Processing (NLP) and Large Language Models (LLMs), in general, are becoming a powerful tool to analyse textual data like app description or privacy policy or user reviews. These methods help in understanding the intent behind permissions, finding inconsistencies, and potential risks or threats. The survey deeply analyses NLP-based techniques for permission risk assessment mechanism including classification, policy mapping, anomaly detection, compliance verification as well as tools to perform explainable AI models and frameworks for scoring risks..

Keywords - NLP, Android Security, Permissions, Risk Analysis, Privacy, LLM, Mobile Security

I. INTRODUCTION

On one hand, Android platform has evolved into one of the most influential mobile apps ecosystems, supporting Billions of users and millions of Apps. Android Apps need to declare multiple permissions for accessing system resources and provide the functionality and user experience. However, the rapid growth of application brings on the consequence of permission misuse, in other words, requesting access to resources that are unreasoned for the functionality of the Apps.

To overcome this issue, works utilize static code analysis [3] and dynamic apps analysis [4] are proposed, which address the problem by expose the technical behaviour of Apps. But they fail to explore the semantic correlation between the permissions required and the functional descriptions of them. To address this issue, a new branch of research emerged so-called Natural Language Processing (NLP) models, attempts to infer the purpose of permissions by analysing app descriptions [6] and privacy policy [5], [1].

In addition, the following technologies have matured in recent years—pre-trained NLP models [2], Large Language Models [7], permission-purpose inference [10]. Furthermore, NLP models can mining in app descriptions from adversarial, which benefit to reveal hidden interrelationship among app

descriptions . According to natural-language-guided framework [8], extracting contextualized semantics info has vastly improved decision-making strategies in risk assessments. Currently, projects focusing on NLP methods used for permission risk analysis in applications face a severe lack of experiences and summaries. Therefore, this survey has been encouraged.

II. RELATED WORK

Initially, research on Android permissions protection focused on rule-based systems and statistical analysis to identify suspicious permissions [4]. These methods using predefined rules were inflexible and could not adapt to new patterns. With rule-based systems, traditional machine learning approaches that leverage data-driven permission analysis captured better performance than static rules. However, most data-driven models can be hindered by unstructured features.

NLP-based approaches utilized the textual information of permissions to improve the analysis. Several systems used NLP-assisted anomaly detection to analyse large-scale app datasets (including permission reports, network communications, and providers) for identifying anomalous permission patterns in applications [6]. Auditing framework designed to detect excessive and misleading permission usage (whose goal is to ensure rigorous privacy analysis) . Apps on Apple store collected tremendous permissions data which were essential for privacy policy analysis. User-review models analysing user feedback could identify the privacy wrongdoing and data abuse related to applications [12].

NLP models that working on cross-lingual corpora could achieve algorithms for different languages and regions. However, some current problems still need to be put into efforts, such as inconsistent privacy policies, non-explainability, and high computing power needed.

III. LITERATURE SURVEY

A. NLP-Based Permission Risk Analysis

NLP-based permission risk analysis studies the textual data and permission usage relationship. Basic NLP models perform text classification that determines whether a permission request is appropriate or suspicious [1]. Such models analyse keyword usage, sentence structure and semantic knowledge, which can infer potential risk of permission requests. Nonetheless, simple classification techniques cannot effectively capture complex, non-linear relationships between permission request and app functionality. To overcome this limitation, techniques such as

permission pair risk analysis have been proposed for investigating permission pair wise co-occurrence. These techniques look for patterns of disparate permission co-relations that would indicate a dangerous permission combination [3]. For example, while location and microphone permissions could both be dangerous, their combination presents an even more serious problem. Fine-grained classification models further improve analysis by considering multiple contextual knowledge, such as semantic similarity, app category and user age expectation [15]. Such classification models are more precise to divide permission risks into various groups. A risk scoring system designates permissions a value based on relevance, load to the user, and level of threat, providing enumerated measures of permissions for better application and comparison [14]. These scores enable users to compare application permissions and to prioritize the risk levels of applications accordingly, thus supporting awareness and perception of risks.

B. LLM and Transformer-Based Analysis

Transformer architectures have gained huge successes in NLP. Such models support long dependence extraction of textual data and facilitate deep contextual understanding of app description and privacy policies. Attention mechanism enable these models to find significance of all words in app descriptions regarding to each other within a sentence, producing better ground for contextual understanding. LLMs extend such deep contextual learning capability by large-scale dataset analysis, thus revealing the app permission purpose and surmising inexplicability in given text and actual permission history [2]. Explainable NLP classifiers enhance understanding by revealing factors that affect model decisions and why a permission is hazardous. Such models help increase trust and support users' ability to understand what a given model is explaining [5]. Transformer-based pipelines could fully automate several tasks involved in permission risk analysis, such as app description interpretation, feature extraction and classifying. The Natural-language-guided approaches make the models base on contextual reasoning, facilitating high performance and accuracy [8].

C. Permission-Policy Mapping and Supervision

Permission-policy mapping monitors the harmony of permissions across apps and privacy policies. NLP-based techniques extract relevant information from policies for further comparison with app declaration permissions [7]. Verification method compares application descriptions and program codes, pinpointing if such application by description is the same as application behaviour [13]. This method has high accuracy and can be applied in the future to make app declarations more transparent by controlling malicious desires in application behaviour. Empowering such process with a permission-privacy annotation system can make the inherent relationship of permissions clearer and more user-friendly, which can thus reduce app disclosure pace and facilitate privacy protections. Comparison system helps regulate app applications systems that adhere to the permission requests process and the relevant regulations and security stipulations, thus enacting transparency accountability [9].

D. Permission Anomaly and Privacy Violation Detection

Anomaly detection methodologies survey the suspicious permission requests appearing in bulk applications by comparing the perceived application, description, privacy policies and permissions with actual performance [6]. The framework of auditing consider the programs permission anomalies, which refer to excess, anomalous and illicit permission requests. User-review analysis work with permission anomaly detection in order to effectively pinpoint privacy-damaging application permissions [12].

E. Cross-Language, Multi-Source Textual Data Analysis

An additional difficulty to be mentioned would be the non-uniformity of languages. Cross-language models allow the analysis of applications speaking different languages and lowering limits of scalability and universality. Multisource analysis of app description, privacy policy and user reviews enhances detection results in multiple angles, thus improving detection degree and lowering rate of false-positives[11].

F. Permission Risk Scoring and Applications Recommendation System

Permission risk scores facilitated the comparison across application permission lists and ranking of applications based on quality and security scores [14]. Such scores could be used to recommend reliable apps and exclude risky apps [16].

Table 1: Comparison of NLP-Based Permission Analysis Techniques.

Category	Method	Key Idea	Advantage	Limitation
NLP Analysis	Text Processing	Detect risky permissions	Simple and fast	Limited context
LLM Models	Deep Learning	Understand permission intent	High accuracy	High computational cost
Policy Mapping	NLP Matching	Ensure policy consistency	Improves trust	Depends on policy quality
Anomaly Detection	Pattern Analysis	Detect unusual behavior	Effective detection	Sensitive to noisy data
Risk Scoring	Scoring Model	Rank applications by risk	Easy decision-making	Requires tuning

G. Challenges in NLP-Focused Permission Risk Detection

Despite these progresses, the availability of high-quality data remains a limitation. Privacy policies are often ambiguous, unreliable and may contain information gaps, which influences the precision of aforementioned models. Multilingual processing is also of difficulty, for translation errors and information loss have great impact on the models' performance. Moreover, transformer-based models and LLMs need significant computational resources, restricting their application

in area like real-time system monitoring. A pressing issue to be addressed are end-to-end automated models that maintain high accuracy while providing human interpretable results.

H. Future Research Directions in NLP-Based Permission Risk Detection

It is needed to come up with more powerful lightweight and cost-effective models that can run in real time environments. Persistent effort should be put in improving the multilingual capabilities of models. Additionally, integrating NLP with behavioural analysis and other method such as networks checking will be valuable in creating a full strategy to protect user's data from apps.

I. Explainable NLP Models for Permission Risk Analysis

Lack of domain knowledge of end user is one of the biggest challenge in permission risk analysis. Conventional machine learning and deep learning models (neural network based models) are black-box based model which is a serious problem especially in mobile security where wrong classification of app results in either risk to user or false positive app flagging. To overcome such problem, explainable NLP models have been introduced as one of the important advancements in permission analysis system. Explainability-based NLP models identify important words, phrases or sentences in app description, privacy policy along with other features, thus help to identify the factors responsible for risk classification [5]. For example, if an app uses location based services but user privacy policy does not talk about location based services, then explainability based model can mark that aspect as one of the reasons for high risk.

Explainability based NLP also improves the usability of system for application developers and security analysts as they can verify the model predictions. It also helps the developers to understand the areas they need to work on to develop a better application and met best security practices. Developers can use those explanations to improve application design and be assured that they are not wrongly flagged as risky app. It also helps in debugging and improving classification performance of NLP models as developer can debug wrong classification and take necessary measures. Explainability also helps in complying to regulations as recent emphasis on transparent decisions of NLP models mandate for explainability of the system.

Overall, explainability based NLP models Improve Trust, accuracy and reliability of permission risk analysis system.

J. Permission-Purpose Inference Using NLP

Asking permission is an important capabilities that new generation of NLP models has brought in mobile security systems. However, permission inference is not sufficient to identify risk class of application, and the importance of permission purpose inference is also vital to accurately determine whether permission requested is necessary for app's functioning or not. NLP models analyse app description, privacy policy and developer notes to infer the application context of permission use, thus put application requesting unnecessary permission in unsecure category [10]. Large language models (LLMs) are one of the best encoders for extracting application

context from textual data in mobile security domain as they are capable of mapping long dependencies between words.

For example, need for location access when the application is updating traffic updates is considered essential whereas the same permission request for home automation application seems unnecessary. Hence, context-aware analysis of permission purpose through NLP becomes crucial. Permission inference models identify mismatch between privacy policy and app description, thus helps in avoiding apps with inconsistent describes app functionality [7]. Besides, these models analyse vast set of app data and extract essential permission usage patterns helpful for identifying risky apps [11], thus help in building baseline for conventional anomaly detection techniques.

Permission-purpose inference analysis also helps in identifying implicit functionality, for example, app uses certain permission but developer description does not mention anywhere that functionality. Identifying such gaps through NLP leads to better risk inference.

Combining permission-purpose inference results with anomaly detection or risk scoring techniques leads to better overall permission risk analysis.

K. Fine-Grained Permission Classification

Permission classification models typically categorize permissions into safe or unsecure category. These methods are unable to handle modern app complexities, which require to classify permission into multiple categories is a better way. Fine grained permission classification methods take multiple features as input and classify permissions based on multiple levels like low, medium, high and critical categories depending on context, sensitivity etc. [15]. Permission-pair analysis techniques analyse multiple combinations of permissions together to correctly classify the overall permission pair despite individual permission appear safe or harmful when considered alone. For example, internet access and contact access permission pair in combination can help data leakage. General fine-grained risk identification is an key advancement of such techniques as they take advantage of contextual probability-aware classification [3].

Dynamic permission classification techniques adjust permission classification level depending on contextual location of app. For example, permission level of GPS access may be different for gaming and map applications. These techniques are more user friendly and provide interpretable and detailed insight of why a particular permission is classified as high/medium/low risk level to help users make safe decision.

L. NLP-Based Compliance and Policy Verification

Compliance is a critical component of gaining user confidence and should be an integral part of any permission analysis system. NLP techniques help extracting relevant information from user privacy policy and comparing it with permission requests to identify violations [7]. Besides, compatibility among app description, privacy policy and permission use can be studied through non-straightforward NLP techniques to

to flagged apps which provide misleading information and go against privacy regulations. This will help avoid regulatory violations and improve user trust in app store environment [9]. Automated auditing of large set of apps for identifying privacy or security violation thanks to combination of unstructured data analysis with structured permission data can help large app store efficiently provide quality review [13].

M. Permission anomaly detection at large scales of apps

Finding anomalies at large scale of apps needs combination of structured data analysis together with unstructured data analysis. For example, app or developer specific permission analysis can be planned in conjunction with permission for infrastructure or app-store statistics. Large variety of unknown apps analysis for permission anomalies identifies deviation from category defined common trends thus finds anomalies [6]. Auditing techniques based on combination of unstructured and structured data analysis identify redundant or noisy permissions thus help in combating privacy risks and eliminate malicious apps .

N. Use of User reviews to study privacy violations:

User reviews also contain information about app behaviour in terms of privacy and security. Sentiment analysis using NLP studies the overall feeling of user communities regarding an app to identify apps which have security issues. Topic modelling techniques studies topics discussed in various user reviews and helps in finding places where privacy is compromised [12].

O. Cross language models-NLP based app description analysis in different languages

NLP models analysing app description and privacy policy should be robust across languages so that all apps can be analysed using an unified system.

P. Risk scoring and decision support systems

Rank calculation of apps based on permission use will help user in choosing safer apps. Decision support tools help users avoid risky apps and choose appropriate and safe app [14],[16].

Q. Use of multiple sources for permission analysis

Use of unstructured data sources such as app description, privacy policy in conjunction with structured data sources is an important trend in permission analysis system development [11]. The overall workflow of the permission risk analysis system is shown in Fig. 1.




Fig. 1: NLP-Based Permission Risk Analysis System Architecture

IV.CONCLUSION

This review summarizes NLP focused techniques in Android permission risk detection. The application of NLP, especially the widely-used transformer-based models and LLMs, significantly boosts the accuracy and efficiency of detect-and-flag. The techniques reveals deeper understanding of permission usage and app contents. In addition to the deep insight allowed by a greater understanding of app permission usages and app content. These models even enable semi-automated app analysis involving app description parsing and feature extracting. Challenges include lack of sufficient data, computational costs and multilingual hurdles. Future directions should aim to systematically build models of high accuracy, interpretability and cross-categorical application.

V.REFERENCE

- [1] A. Kumar, R. Patel, and S. Sharma, "NLP based permission usage auditing in Android app descriptions and privacy policies," *Computers & Security*, vol. 140, pp. 113–128, 2024.
- [2] S. Sharma, N. Gupta, and A. Mishra, "Natural language processing for secure mobile app permission risk assessment," *IEEE Trans. Dependable Secure Computer.*, vol. 21, no. 4, pp. 2156–2171, 2024.
- [3] L. Chen, H. Wang, and M. Liu, "Harnessing large language models to analyse Android app permission declarations," *IEEE Trans. Inf. Forensics Security*, vol. 19, no. 6, pp. 4521–4538, 2024.
- [4] R. Patel, V. Kumar, and S. Desai, "NLP-driven permission pair interaction risk analysis for secure mobile application recommendation," *Expert Syst. Appl.*, vol. 230, pp. 120589–120605, 2024.
- [5] Y. Zhang, J. Li, and W. Chen, "Fine-grained permission policy alignment verification using transformer-based NLP," *Inf. Sci.*, vol. 620, pp. 876–895, 2025, DOI: 10.1016/j.ins.2025.876895.
- [6] M. Singh, A. Verma, and P. Rao, "Explainable NLP classifier for Android app permission risk labelling " *IEEE Trans. Neural Networks. Learn. Syst.*, vol. 36, no. 3, pp. 1823–1840, 2025.
- [7] T. Nguyen, L. Tran, and H. Hoang, "NLP-assisted permission anomaly detection in Android app stores," *J. Inf. Security Appl.*, vol. 78, pp. 103501–103520, 2024.
- [8] H. Liu, X. Wu, and Y. Yang, "NLP-enabled privacy policy-to-permission mapping framework for secure mobile apps," *Future Gener. Computer. Syst.*, vol. 155, pp. 412–429, 2025.

m

[9] P. Das, S. Nath, and A. Ghosh, "Natural language-guided permission risk assessment for mobile app security," *Knowledge-Based Syst.*, vol. 274, pp. 110645–110665, 2025.

[10] J. Brown, M. Davis, and K. Wilson, "NLP-assisted auditing of excessive and misleading mobile app permissions," *Inf. Process. Manage.*, vol. 59, no. 3, pp. 102908–102925, 2024.

[11] X. Wang, Z. Zhou, and Q. Liu, "Large language model-assisted Android permission purpose inference from app descriptions and policies," *IEEE Access*, vol. 12, pp. 78521–78540, 2024.

[12] F. Garcia, M. Rodriguez, and C. Martinez, "Cross-language NLP models for Android app permission meaning analysis," *Inf. Process. Manage.*, vol. 59, no. 4, pp. 102960–102980, 2024.

[13] E. Kim, J. Park, and S. Lee, "NLP-driven user review analysis for detecting permission-related privacy concerns," *IEEE Trans. Consumer. Electron.*, vol. 70, no. 2, pp. 2341–2358, 2024.

[14] B. Zhao, L. Zhang, and Y. Wang, "NLP-based verification of permission consistency between app descriptions and code-level behaviour," *Computers & Security*, vol. 142, pp. 103945–103965, 2025.

[15] C. Lopez, J. Garcia, and M. Sanchez, "Transformer-based NLP pipeline for secure mobile app permission policy analysis," *Inf. Sci.*, vol. 630, pp. 245–265, 2025.

[16] N. Iyer, V. Rao, and S. Bhat, "NLP-enabled fine-grained permission risk classification for mobile app security," *Knowledge-Based Syst.*, vol. 278, pp. 110912–110930, 2025.

Manish Kumar

Share Updated Survey Paper -1

 Dr.

Document Details

Submission ID

trn:oid::15912:136893735

Submission Date

Apr 28, 2026, 1:35 PM GMT+5:30

Download Date

Apr 28, 2026, 1:46 PM GMT+5:30

File Name

Share Updated Survey Paper -1.docx

File Size

205.1 KB

5 Pages

3,204 Words

19,952 Characters

*% detected as AI

AI detection includes the possibility of false positives. Although some text in this submission is likely AI generated, scores below the 20% threshold are not surfaced because they have a higher likelihood of false positives.

Caution: Review required.

It is essential to understand the limitations of AI detection before making decisions about a student's work. We encourage you to learn more about Turnitin's AI detection capabilities before using the tool.

Disclaimer

Our AI writing assessment is designed to help educators identify text that might be prepared by a generative AI tool. Our AI writing assessment may not always be accurate (i.e., our AI models may produce either false positive results or false negative results), so it should not be used as the sole basis for adverse actions against a student. It takes further scrutiny and human judgment in conjunction with an organization's application of its specific academic policies to determine whether any academic misconduct has occurred.

Frequently Asked Questions

How should I interpret Turnitin's AI writing percentage and false positives?

The percentage shown in the AI writing report is the amount of qualifying text within the submission that Turnitin's AI writing detection model determines was either likely AI-generated text from a large-language model or likely AI-generated text that was likely revised using an AI paraphrase tool or word spinner.

False positives (incorrectly flagging human-written text as AI-generated) are a possibility in AI models.


AI detection scores under 20%, which we do not surface in new reports, have a higher likelihood of false positives. To reduce the likelihood of misinterpretation, no score or highlights are attributed and are indicated with an asterisk in the report (*%).

The AI writing percentage should not be the sole basis to determine whether misconduct has occurred. The reviewer/instructor should use the percentage as a means to start a formative conversation with their student and/or use it to examine the submitted assignment in accordance with their school's policies.

What does 'qualifying text' mean?

Our model only processes qualifying text in the form of long-form writing. Long-form writing means individual sentences contained in paragraphs that make up a longer piece of written work, such as an essay, a dissertation, or an article, etc. Qualifying text that has been determined to be likely AI-generated will be highlighted in cyan in the submission, and likely AI-generated and then likely AI-paraphrased will be highlighted purple.

Non-qualifying text, such as bullet points, annotated bibliographies, etc., will not be processed and can create disparity between the submission highlights and the percentage shown.



SURVEY ON A SECURE MOBILE APPLICATION PERMISSION ANALYZER USING NATURAL LANGUAGE PROCESSING

Ms. M. RAGHAVI

Department of Cybersecurity
SRM Valliammai Engineering College
Chengalpattu, India
raghavirgo@gmail.com

SHUNMUGA PRIYA. R

Department of Cybersecurity
SRM Valliammai Engineering College
Chengalpattu, India
shunmugapriyaradha2022@gmail.com

SRIMATHI. V

Department of Cybersecurity
SRM Valliammai Engineering College
Chengalpattu, India
srimathisrimathi089@gmail.com

Abstract Many Android applications have quickly grown in popularity, leading to a substantial rise in the need for safe management of user data and permissions. Sensitive resources like location, contacts, storage and hardware device are often requested by modern applications. There are some applications that require permissions that aren't needed for the app to operate, posing severe privacy concerns; data leakage and the threat of misuse of personal data. Static and dynamic analysis are examples of existing traditional security mechanisms which fail to provide the contextual meaning behind permission usage. With all its challenges, on the other hand, Natural Language Processing (NLP) and Large Language Models (LLMs), in general, are becoming a powerful tool to analyse textual data like app description or privacy policy or user reviews. These methods help in understanding the intent behind permissions, finding inconsistencies, and potential risks or threats. The survey deeply analyses NLP-based techniques for permission risk assessment mechanism including classification, policy mapping, anomaly detection, compliance verification as well as tools to perform explainable AI models and frameworks for scoring risks.

Keywords - NLP, Android Security, Permissions, Risk Analysis, Privacy, LLM, Mobile Security

I. INTRODUCTION

On one hand, Android platform has evolved into one of the most influential mobile apps ecosystems, supporting Billions of users and millions of Apps. Android Apps need to declare multiple permissions for accessing system resources and provide the functionality and user experience. However, the rapid growth of application brings on the consequence of permission misuse, in other words, requesting access to resources that are unreasoned for the functionality of the Apps.

To overcome this issue, works utilize static code analysis [3] and dynamic apps analysis [4] are proposed, which address the problem by expose the technical behaviour of Apps. But they fail to explore the semantic correlation between the permissions required and the functional descriptions of them. To address this issue, a new branch of research emerged so-called Natural Language Processing (NLP) models, attempts to infer the purpose of permissions by analysing app descriptions [6] and privacy policy [5], [1].

In addition, the following technologies have matured in recent years—pre-trained NLP models [2], Large Language Models [7], permission-purpose inference [11]. Furthermore, NLP models can mining in app descriptions from adversarial, which benefit to reveal hidden interrelationship among app descriptions [10]. According to natural-language-guided

framework [8], extracting contextualized semantics info has vastly improved decision-making strategies in risk assessments. Currently, projects focusing on NLP methods used for permission risk analysis in applications face a severe lack of experiences and summaries. Therefore, this survey has been encouraged.

II. RELATED WORK

Initially, research on Android permissions protection focused on rule-based systems and statistical analysis to identify suspicious permissions [4]. These methods using predefined rules were inflexible and could not adapt to new patterns. With rule-based systems, traditional machine learning approaches that leverage data-driven permission analysis captured better performance than static rules. However, most data-driven models can be hindered by unstructured features.

NLP-based approaches utilized the textual information of permissions to improve the analysis. Several systems used NLP-assisted anomaly detection to analyse large-scale app datasets (including permission reports, network communications, and providers) for identifying anomalous permission patterns in applications [6]. Auditing framework designed to detect excessive and misleading permission usage (whose goal is to ensure rigorous privacy analysis) [10]. Apps on Apple store collected tremendous permissions data which were essential for privacy policy analysis. User-review models analysing user feedback could identify the privacy wrongdoing and data abuse related to applications [14].

NLP models that working on cross-lingual corpora could achieve algorithms for different languages and regions. However, some current problems still need to be put into efforts, such as inconsistent privacy policies, non-explainability, and high computing power needed.

III. LITERATURE SURVEY

A. NLP-Based Permission Risk Analysis

NLP-based permission risk analysis studies the textual data and permission usage relationship. Basic NLP models perform text classification that determines whether a permission request is appropriate or suspicious [1]. Such models analyse keyword usage, sentence structure and semantic knowledge, which can infer potential risk of permission requests. Nonetheless, simple classification techniques cannot effectively capture complex, non-linear relationships between permission request and app functionality. To overcome this limitation, techniques such as permission pair risk analysis have been proposed for

investigating permission pair wise co-occurrence. These techniques look for patterns of disparate permission co-relations that would indicate a dangerous permission combination [3]. For example, while location and microphone permissions could both be dangerous, their combination presents an even more serious problem. Fine-grained classification models further improve analysis by considering multiple contextual knowledge, such as semantic similarity, app category and user age expectation [18]. Such classification models are more precise to divide permission risks into various groups. A risk scoring system designates permissions a value based on relevance, load to the user, and level of threat, providing enumerated measures of permissions for better application and comparison [16]. These scores enable users to compare application permissions and to prioritize the risk levels of applications accordingly, thus supporting awareness and perception of risks.

B. LLM and Transformer-Based Analysis

Transformer architectures have gained huge successes in NLP. Such models support long dependence extraction of textual data and facilitate deep contextual understanding of app description and privacy policies. Attention mechanism enable these models to find significance of all words in app descriptions regarding to each other within a sentence, producing better ground for contextual understanding. LLMs extend such deep contextual learning capability by large-scale dataset analysis, thus revealing the app permission purpose and surmising inexplicability in given text and actual permission history [2]. Explainable NLP classifiers enhance understanding by revealing factors that affect model decisions and why a permission is hazardous. Such models help increase trust and support users' ability to understand what a given model is explaining [5]. Transformer-based pipelines could fully automate several tasks involved in permission risk analysis, such as app description interpretation, feature extraction and classifying [17]. The Natural-language-guided approaches make the models base on contextual reasoning, facilitating high performance and accuracy [8].

C. Permission-Policy Mapping and Supervision

Permission-policy mapping monitors the harmony of permissions across apps and privacy policies. NLP-based techniques extract relevant information from policies for further comparison with app declaration permissions [7]. Verification method compares application descriptions and program codes, pinpointing if such application by description is the same as application behaviour [15]. This method has high accuracy and can be applied in the future to make app declarations more transparent by controlling malicious desires in application behaviour. Empowering such process with a permission-privacy annotation system can make the inherent relationship of permissions clearer and more user-friendly, which can thus reduce app disclosure pace and facilitate privacy protections. Comparison system helps regulate app applications systems that adhere to the permission requests process and the relevant regulations and security stipulations, thus enacting transparency accountability [9].

D. Permission Anomaly and Privacy Violation Detection

Anomaly detection methodologies surveil the suspicious permission requests appearing in bulk applications by comparing the perceived application, description, privacy policies and permissions with actual performance [6]. The framework of auditing consider the programs permission anomalies, which refer to excess, anomalistic and illicit permission requests [10]. User-review analysis work with permission anomaly detection in order to effectively pinpoint privacy-damaging application permissions [14].

E. Cross-Language, Multi-Source Textual Data Analysis

An additional difficulty to be mentioned would be the non-uniformity of languages. Cross-language models allow the analysis of applications speaking different languages and lowering limits of scalability and universality [13]. Multisource analysis of app description, privacy policy and user reviews enhances detection results in multiple angles, thus improving detection degree and lowering rate of false-positives[12].

F. Permission Risk Scoring and Applications Recommendation System

Permission risk scores facilitated the comparison across application permission lists and ranking of applications based on quality and security scores [16]. Such scores could be used to recommend reliable apps and exclude risky apps [19].

Table 1: Comparison of NLP-Based Permission Analysis Techniques.

Category	Method	Key Idea	Advantage	Limitation
NLP Analysis	Text Processing	Detect risky permissions	Simple and fast	Limited context
LLM Models	Deep Learning	Understand permission intent	High accuracy	High computational cost
Policy Mapping	NLP Matching	Ensure policy consistency	Improves trust	Depends on policy quality
Anomaly Detection	Pattern Analysis	Detect unusual behavior	Effective detection	Sensitive to noisy data
Risk Scoring	Scoring Model	Rank applications by risk	Easy decision-making	Requires tuning

G. Challenges in NLP-Focused Permission Risk Detection

Despite these progresses, the availability of high-quality data remains a limitation. Privacy policies are often ambiguous, unreliable and may contain information gaps, which influences the precision of aforementioned models. Multilingual processing is also of difficulty, for translation errors and information loss have great impact on the models' performance. Moreover, transformer-based models and LLMs need significant computational resources, restricting their application in area like real-time system monitoring. A pressing issue to be addressed are end-to-end automated models that maintain high accuracy while providing human interpretable results.

H. Future Research Directions in NLP-Based Permission Risk Detection

It is needed to come up with more powerful lightweight and cost-effective models that can run in real time environments. Persistent effort should be put in improving the multilingual capabilities of models. Additionally, integrating NLP with behavioral analysis and other method such as networks checking will be valuable in creating a full strategy to protect user's data from apps.

I. Explainable NLP Models for Permission Risk Analysis

Lack of domain knowledge of end user is one of the biggest challenge in permission risk analysis. Conventional machine learning and deep learning models (neural network based models) are black-box based model which is a serious problem especially in mobile security where wrong classification of app results in either risk to user or false positive app flagging. To overcome such problem, explainable NLP models have been introduced as one of the important advancements in permission analysis system. Explainability-based NLP models identify important word(s), phrase(s) or sentence(s) in app description, privacy policy along with other features, thus help to identify the factors responsible for risk classification [5]. For example, if an app uses location based services but user privacy policy does not talk about location based services, then explainability based model can mark that aspect as one of the reasons for high risk.

Explainability based NLP also improves the usability of system for application developers and security analysts as they can verify the model predictions. It also helps the developers to understand the areas they need to work on to develop a better application and met best security practices. Developers can use those explanations to improve application design and be assured that they are not wrongly flagged as risky app. It also helps in debugging and improving classification performance of NLP models as developer can debug wrong classification and take necessary measures. Explainability also helps in complying to regulations as recent emphasis on transparent decisions of NLP models mandate for explainability of the system.

Overall, explainability based NLP models Improve Trust, accuracy and reliability of permission risk analysis system.

J. Permission-Purpose Inference Using NLP

Asking permission is an important capabilities that new generation of NLP models has brought in mobile security systems. However, permission inference is not sufficient to identify risk class of application, and the importance of permission purpose inference is also vital to accurately determine whether permission requested is necessary for app's functioning or not. NLP models analyse app description, privacy policy and developer notes to infer the application context of permission use, thus put application requesting unnecessary permission in unsecure category [11]. Large language models (LLMs) are one of the best encoders for extracting application context from textual data in mobile security domain as they are capable of mapping long dependencies between words.

For example, need for location access when the application is updating traffic updates is considered essential whereas the same permission request for home automation application seems unnecessary. Hence, context-aware analysis of permission purpose through NLP becomes crucial. Permission inference models identify mismatch between privacy policy and app description, thus helps in avoiding apps with inconsistent describes app functionality [7]. Besides, these models analyse vast set of app data and extract essential permission usage patterns helpful for identifying risky apps [12], thus help in building baseline for conventional anomaly detection techniques.

Permission-purpose inference analysis also helps in identifying implicit functionality, for example, app uses certain permission but developer description does not mention anywhere that functionality. Identifying such gaps through NLP leads to better risk inference.

Combining permission-purpose inference results with anomaly detection or risk scoring techniques leads to better overall permission risk analysis.

K. Fine-Grained Permission Classification

Permission classification models typically categorize permissions into safe or unsecure category. These methods are unable to handle modern app complexities, which require to classify permission into multiple categories is a better way. Fine grained permission classification methods take multiple features as input and classify permissions based on multiple levels like low, medium, high and critical categories depending on context, sensitivity etc. [18]. Permission-pair analysis techniques analyse multiple combinations of permissions together to correctly classify the overall permission pair despite individual permission appear safe or harmful when considered alone. For example, internet access and contact access permission pair in combination can help data leakage. General fine-grained risk identification is an key advancement of such techniques as they take advantage of contextual probability-aware classification [3].

Dynamic permission classification techniques adjust permission classification level depending on contextual location of app. For example, permission level of GPS access may be different for gaming and map applications. These techniques are more user friendly and provide interpretable and detailed insight of why a particular permission is classified as high/medium/low risk level to help users make safe decision.

L. NLP-Based Compliance and Policy Verification

Compliance is a critical component of gaining user confidence and should be an integral part of any permission analysis system. NLP techniques help extracting relevant information from user privacy policy and comparing it with permission requests to identify violations [7]. Besides, compatibility among app description, privacy policy and permission use can be studied through non-straightforward NLP techniques to flagged apps which provide misleading information and go against privacy regulations. This will help avoid regulatory violations and improve user trust in app store environment [9]. Automated

auditing of large set of apps for identifying privacy or security violation thanks to combination of unstructured data analysis with structured permission data can help large app store efficiently provide quality review [15].

M. Permission anomaly detection at large scales of apps

Finding anomalies at large scale of apps needs combination of structured data analysis together with unstructured data analysis. For example, app or developer specific permission analysis can be planned in conjunction with permission for infrastructure or app-store statistics. Large variety of unknown apps analysis for permission anomalies identifies deviation from category defined common trends thus finds anomalies [6]. Auditing techniques based on combination of unstructured and structured data analysis identify redundant or noisy permissions thus help in combating privacy risks and eliminate malicious apps [10].

N. Use of User reviews to study privacy violations:

User reviews also contain information about app behaviour in terms of privacy and security. Sentiment analysis using NLP studies the overall feeling of user communities regarding an app to identify apps which have security issues. Topic modelling techniques studies topics discussed in various user reviews and helps in finding places where privacy is compromised [14].

O. Cross language models-NLP based app description analysis in different languages

NLP models analysing app description and privacy policy should be robust across languages so that all apps can be analysed using an unified system.

P. Risk scoring and decision support systems

Rank calculation of apps based on permission use will help user in choosing safer apps. Decision support tools help users avoid risky apps and choose appropriate and safe app [16, 19].

Q. Use of multiple sources for permission analysis

Use of unstructured data sources such as app description, privacy policy in conjunction with structured data sources is an important trend in permission analysis system development [12]. The overall workflow of the permission risk analysis system is shown in Fig. 1.




Fig. 1: NLP-Based Permission Risk Analysis System Architecture

IV.CONCLUSION

This review summarizes NLP focused techniques in Android permission risk detection. The application of NLP, especially the widely-used transformer-based models and LLMs, significantly boosts the accuracy and efficiency of detect-and-flag. The techniques reveals deeper understanding of permission usage and app contents. In addition to the deep insight allowed by a greater understanding of app permission usages and app content. These models even enable semi-automated app analysis involving app description parsing and feature extracting. Challenges include lack of sufficient data, computational costs and multilingual hurdles. Future directions should aim to systematically build models of high accuracy, interpretability and cross-centrical application.

V.REFERENCE

- [1] A. Kumar et al., "NLP based permission use auditing in Android app descriptions and privacy policies," *Computers & Security*, vol. 140, 2024.
- [2] S. Sharma et al., "Natural language processing for secure mobile app permission risk assessment," *IEEE Transactions on Dependable and Secure Computing (TDSC)*, vol. 21, 2024.
- [3] L. Chen et al., "Harnessing large language models to analyze Android app permission declarations," *IEEE Transactions on Information Forensics and Security*, vol. 19, 2024.
- [4] R. Patel et al., "NLP driven permission pair risk analysis for secure mobile application recommendation," *Expert Systems with Applications*, vol. 230, 2024.
- [5] Y. Zhang et al., "Fine grained permission policy alignment verification using transformer based NLP," *Information Sciences*, vol. 620, 2025.
- [6] M. Singh et al., "Explainable NLP classifier for Android app permission risk labeling," *IEEE Transactions on Neural Networks and Learning Systems*, vol. 36, 2025.
- [7] T. Nguyen et al., "NLP assisted permission anomaly detection in Android app stores," *Journal of Information Security and Applications*, vol. 78, 2024.
- [8] H. Liu et al., "NLP enabled privacy policy to permission mapping framework for secure mobile apps," *Future Generation Computer Systems*, vol. 155, 2025.
- [9] P. Das et al., "Natural language guided permission risk assessment for mobile app security," *Knowledge Based Systems*, vol. 274, 2025.
- [10] K. Mehta et al., "NLP based permission compliance checker for secure mobile application stores," *Decision Support Systems*, vol. 178, 2026.

- [11] J. Brown et al., "NLP assisted auditing of excessive and misleading mobile app permissions," *Information Processing & Management*, vol. 59, no. 3, 2024.
- [12] X. Wang et al., "Large language model assisted Android permission purpose inference from app descriptions and policies," *IEEE Access*, vol. 12, 2024.
- [13] D. Roy et al., "NLP based mining of app description text to infer permission use purposes," *Expert Systems with Applications*, vol. 232, 2025.
- [14] F. Garcia et al., "Cross language NLP models for Android app permission meaning analysis," *Information Processing & Management*, vol. 59, no. 4, 2024.
- [15] E. Kim et al., "NLP driven user review analysis for detecting permission related privacy concerns," *IEEE Transactions on Consumer Electronics*, vol. 70, 2024.
- [16] B. Zhao et al., "NLP based verification of permission consistency between app descriptions and code level behavior," *Computers & Security*, vol. 142, 2025.
- [17] A. Verma et al., "NLP assisted permission risk scoring framework for Android app stores," *Future Generation Computer Systems*, vol. 160, 2025.
- [18] C. Lopez et al., "Transformer based NLP pipeline for secure mobile app permission policy analysis," *Information Sciences*, vol. 630, 2025.
- [19] N. Iyer et al., "NLP enabled fine grained permission risk classification for mobile app security," *Knowledge Based Systems*, vol. 278, 2025.
- [20] S. Reddy et al., "NLP based permission analyzer for secure mobile application recommendation," *Decision Support Systems*, vol. 180, 2026.

Manish Kumar

Share Updated Survey Paper -1

 Dr.

Document Details

Submission ID

trn:oid::15912:136893735

Submission Date

Apr 28, 2026, 1:35 PM GMT+5:30

Download Date

Apr 28, 2026, 1:46 PM GMT+5:30

File Name

Share Updated Survey Paper -1.docx

File Size

205.1 KB

5 Pages

3,204 Words

19,952 Characters

1% Overall Similarity

The combined total of all matches, including overlapping sources, for each database.

Filtered from the Report

- Bibliography
- Quoted Text
- Cited Text

Match Groups

-  **2 Not Cited or Quoted 1%**
Matches with neither in-text citation nor quotation marks
-  **0 Missing Quotations 0%**
Matches that are still very similar to source material
-  **0 Missing Citation 0%**
Matches that have quotation marks, but no in-text citation
-  **0 Cited and Quoted 0%**
Matches with in-text citation present, but no quotation marks

Top Sources

- 0%  Internet sources
- 1%  Publications
- 1%  Submitted works (Student Papers)

Integrity Flags

0 Integrity Flags for Review

Our system's algorithms look deeply at a document for any inconsistencies that would set it apart from a normal submission. If we notice something strange, we flag it for you to review.

A Flag is not necessarily an indicator of a problem. However, we'd recommend you focus your attention there for further review.

Match Groups

-  **2 Not Cited or Quoted 1%**
Matches with neither in-text citation nor quotation marks
-  **0 Missing Quotations 0%**
Matches that are still very similar to source material
-  **0 Missing Citation 0%**
Matches that have quotation marks, but no in-text citation
-  **0 Cited and Quoted 0%**
Matches with in-text citation present, but no quotation marks

Top Sources

- 0%  Internet sources
- 1%  Publications
- 1%  Submitted works (Student Papers)

Top Sources

The sources with the highest number of matches within the submission. Overlapping sources will not be displayed.

- 1

Student papers

SRM Valliammai Engineering College on 2026-04-17

<1%
- 2

Internet

jisem-journal.com

<1%

SURVEY ON A SECURE MOBILE APPLICATION PERMISSION ANALYZER USING NATURAL LANGUAGE PROCESSING

Ms. M. RAGHAVI

Department of Cybersecurity
SRM Valliammai Engineering College
Chengalpattu, India
raghavirgo@gmail.com

SHUNMUGA PRIYA. R

Department of Cybersecurity
SRM Valliammai Engineering College
Chengalpattu, India
shunmugapriyaradha2022@gmail.com

SRIMATHI. V

Department of Cybersecurity
SRM Valliammai Engineering College
Chengalpattu, India
srmathisrimathi089@gmail.com

Abstract Many Android applications have quickly grown in popularity, leading to a substantial rise in the need for safe management of user data and permissions. Sensitive resources like location, contacts, storage and hardware device are often requested by modern applications. There are some applications that require permissions that aren't needed for the app to operate, posing severe privacy concerns; data leakage and the threat of misuse of personal data. Static and dynamic analysis are examples of existing traditional security mechanisms which fail to provide the contextual meaning behind permission usage. With all its challenges, on the other hand, Natural Language Processing (NLP) and Large Language Models (LLMs), in general, are becoming a powerful tool to analyse textual data like app description or privacy policy or user reviews. These methods help in understanding the intent behind permissions, finding inconsistencies, and potential risks or threats. The survey deeply analyses NLP-based techniques for permission risk assessment mechanism including classification, policy mapping, anomaly detection, compliance verification as well as tools to perform explainable AI models and frameworks for scoring risks.

Keywords - NLP, Android Security, Permissions, Risk Analysis, Privacy, LLM, Mobile Security

I. INTRODUCTION

On one hand, Android platform has evolved into one of the most influential mobile apps ecosystems, supporting Billions of users and millions of Apps. Android Apps need to declare multiple permissions for accessing system resources and provide the functionality and user experience. However, the rapid growth of application brings on the consequence of permission misuse, in other words, requesting access to resources that are unreasoned for the functionality of the Apps.

To overcome this issue, works utilize static code analysis [3] and dynamic apps analysis [4] are proposed, which address the problem by expose the technical behaviour of Apps. But they fail to explore the semantic correlation between the permissions required and the functional descriptions of them. To address this issue, a new branch of research emerged so-called Natural Language Processing (NLP) models, attempts to infer the purpose of permissions by analysing app descriptions [6] and privacy policy [5], [1].

In addition, the following technologies have matured in recent years—pre-trained NLP models [2], Large Language Models [7], permission-purpose inference [11]. Furthermore, NLP models can mining in app descriptions from adversarial, which benefit to reveal hidden interrelationship among app descriptions [10]. According to natural-language-guided

framework [8], extracting contextualized semantics info has vastly improved decision-making strategies in risk assessments. Currently, projects focusing on NLP methods used for permission risk analysis in applications face a severe lack of experiences and summaries. Therefore, this survey has been encouraged.

II. RELATED WORK

Initially, research on Android permissions protection focused on rule-based systems and statistical analysis to identify suspicious permissions [4]. These methods using predefined rules were inflexible and could not adapt to new patterns. With rule-based systems, traditional machine learning approaches that leverage data-driven permission analysis captured better performance than static rules. However, most data-driven models can be hindered by unstructured features.

NLP-based approaches utilized the textual information of permissions to improve the analysis. Several systems used NLP-assisted anomaly detection to analyse large-scale app datasets (including permission reports, network communications, and providers) for identifying anomalous permission patterns in applications [6]. Auditing framework designed to detect excessive and misleading permission usage (whose goal is to ensure rigorous privacy analysis) [10]. Apps on Apple store collected tremendous permissions data which were essential for privacy policy analysis. User-review models analysing user feedback could identify the privacy wrongdoing and data abuse related to applications [14].

NLP models that working on cross-lingual corpora could achieve algorithms for different languages and regions. However, some current problems still need to be put into efforts, such as inconsistent privacy policies, non-explainability, and high computing power needed.

III. LITERATURE SURVEY

A. NLP-Based Permission Risk Analysis

NLP-based permission risk analysis studies the textual data and permission usage relationship. Basic NLP models perform text classification that determines whether a permission request is appropriate or suspicious [1]. Such models analyse keyword usage, sentence structure and semantic knowledge, which can infer potential risk of permission requests. Nonetheless, simple classification techniques cannot effectively capture complex, non-linear relationships between permission request and app functionality. To overcome this limitation, techniques such as permission pair risk analysis have been proposed for

investigating permission pair wise co-occurrence. These techniques look for patterns of disparate permission co-relations that would indicate a dangerous permission combination [3]. For example, while location and microphone permissions could both be dangerous, their combination presents an even more serious problem. Fine-grained classification models further improve analysis by considering multiple contextual knowledge, such as semantic similarity, app category and user age expectation [18]. Such classification models are more precise to divide permission risks into various groups. A risk scoring system designates permissions a value based on relevance, load to the user, and level of threat, providing enumerated measures of permissions for better application and comparison [16]. These scores enable users to compare application permissions and to prioritize the risk levels of applications accordingly, thus supporting awareness and perception of risks.

B. LLM and Transformer-Based Analysis

Transformer architectures have gained huge successes in NLP. Such models support long dependence extraction of textual data and facilitate deep contextual understanding of app description and privacy policies. Attention mechanism enable these models to find significance of all words in app descriptions regarding to each other within a sentence, producing better ground for contextual understanding. LLMs extend such deep contextual learning capability by large-scale dataset analysis, thus revealing the app permission purpose and surmising inexplicability in given text and actual permission history [2]. Explainable NLP classifiers enhance understanding by revealing factors that affect model decisions and why a permission is hazardous. Such models help increase trust and support users' ability to understand what a given model is explaining [5]. Transformer-based pipelines could fully automate several tasks involved in permission risk analysis, such as app description interpretation, feature extraction and classifying [17]. The Natural-language-guided approaches make the models base on contextual reasoning, facilitating high performance and accuracy [8].

C. Permission-Policy Mapping and Supervision

Permission-policy mapping monitors the harmony of permissions across apps and privacy policies. NLP-based techniques extract relevant information from policies for further comparison with app declaration permissions [7]. Verification method compares application descriptions and program codes, pinpointing if such application by description is the same as application behaviour [15]. This method has high accuracy and can be applied in the future to make app declarations more transparent by controlling malicious desires in application behaviour. Empowering such process with a permission-privacy annotation system can make the inherent relationship of permissions clearer and more user-friendly, which can thus reduce app disclosure pace and facilitate privacy protections. Comparison system helps regulate app applications systems that adhere to the permission requests process and the relevant regulations and security stipulations, thus enacting transparency accountability [9].

D. Permission Anomaly and Privacy Violation Detection

Anomaly detection methodologies surveil the suspicious permission requests appearing in bulk applications by comparing the perceived application, description, privacy policies and permissions with actual performance [6]. The framework of auditing consider the programs permission anomalies, which refer to excess, anomalistic and illicit permission requests [10]. User-review analysis work with permission anomaly detection in order to effectively pinpoint privacy-damaging application permissions [14].

E. Cross-Language, Multi-Source Textual Data Analysis

An additional difficulty to be mentioned would be the non-uniformity of languages. Cross-language models allow the analysis of applications speaking different languages and lowering limits of scalability and universality [13]. Multisource analysis of app description, privacy policy and user reviews enhances detection results in multiple angles, thus improving detection degree and lowering rate of false-positives[12].

F. Permission Risk Scoring and Applications Recommendation System

Permission risk scores facilitated the comparison across application permission lists and ranking of applications based on quality and security scores [16]. Such scores could be used to recommend reliable apps and exclude risky apps [19].

Table 1: Comparison of NLP-Based Permission Analysis Techniques.

Category	Method	Key Idea	Advantage	Limitation
NLP Analysis	Text Processing	Detect risky permissions	Simple and fast	Limited context
LLM Models	Deep Learning	Understand permission intent	High accuracy	High computational cost
Policy Mapping	NLP Matching	Ensure policy consistency	Improves trust	Depends on policy quality
Anomaly Detection	Pattern Analysis	Detect unusual behavior	Effective detection	Sensitive to noisy data
Risk Scoring	Scoring Model	Rank applications by risk	Easy decision-making	Requires tuning

G. Challenges in NLP-Focused Permission Risk Detection

Despite these progresses, the availability of high-quality data remains a limitation. Privacy policies are often ambiguous, unreliable and may contain information gaps, which influences the precision of aforementioned models. Multilingual processing is also of difficulty, for translation errors and information loss have great impact on the models' performance. Moreover, transformer-based models and LLMs need significant computational resources, restricting their application in area like real-time system monitoring. A pressing issue to be addressed are end-to-end automated models that maintain high accuracy while providing human interpretable results.

H. Future Research Directions in NLP-Based Permission Risk Detection

It is needed to come up with more powerful lightweight and cost-effective models that can run in real time environments. Persistent effort should be put in improving the multilingual capabilities of models. Additionally, integrating NLP with behavioral analysis and other method such as networks checking will be valuable in creating a full strategy to protect user's data from apps.

I. Explainable NLP Models for Permission Risk Analysis

Lack of domain knowledge of end user is one of the biggest challenge in permission risk analysis. Conventional machine learning and deep learning models (neural network based models) are black-box based model which is a serious problem especially in mobile security where wrong classification of app results in either risk to user or false positive app flagging. To overcome such problem, explainable NLP models have been introduced as one of the important advancements in permission analysis system. Explainability-based NLP models identify important word(s), phrase(s) or sentence(s) in app description, privacy policy along with other features, thus help to identify the factors responsible for risk classification [5]. For example, if an app uses location based services but user privacy policy does not talk about location based services, then explainability based model can mark that aspect as one of the reasons for high risk.

Explainability based NLP also improves the usability of system for application developers and security analysts as they can verify the model predictions. It also helps the developers to understand the areas they need to work on to develop a better application and met best security practices. Developers can use those explanations to improve application design and be assured that they are not wrongly flagged as risky app. It also helps in debugging and improving classification performance of NLP models as developer can debug wrong classification and take necessary measures. Explainability also helps in complying to regulations as recent emphasis on transparent decisions of NLP models mandate for explainability of the system.

Overall, explainability based NLP models Improve Trust, accuracy and reliability of permission risk analysis system.

J. Permission-Purpose Inference Using NLP

Asking permission is an important capabilities that new generation of NLP models has brought in mobile security systems. However, permission inference is not sufficient to identify risk class of application, and the importance of permission purpose inference is also vital to accurately determine whether permission requested is necessary for app's functioning or not. NLP models analyse app description, privacy policy and developer notes to infer the application context of permission use, thus put application requesting unnecessary permission in unsecure category [11]. Large language models (LLMs) are one of the best encoders for extracting application context from textual data in mobile security domain as they are capable of mapping long dependencies between words.

For example, need for location access when the application is updating traffic updates is considered essential whereas the same permission request for home automation application seems unnecessary. Hence, context-aware analysis of permission purpose through NLP becomes crucial. Permission inference models identify mismatch between privacy policy and app description, thus helps in avoiding apps with inconsistent describes app functionality [7]. Besides, these models analyse vast set of app data and extract essential permission usage patterns helpful for identifying risky apps [12], thus help in building baseline for conventional anomaly detection techniques.

Permission-purpose inference analysis also helps in identifying implicit functionality, for example, app uses certain permission but developer description does not mention anywhere that functionality. Identifying such gaps through NLP leads to better risk inference.

Combining permission-purpose inference results with anomaly detection or risk scoring techniques leads to better overall permission risk analysis.

K. Fine-Grained Permission Classification

Permission classification models typically categorize permissions into safe or unsecure category. These methods are unable to handle modern app complexities, which require to classify permission into multiple categories is a better way. Fine grained permission classification methods take multiple features as input and classify permissions based on multiple levels like low, medium, high and critical categories depending on context, sensitivity etc. [18]. Permission-pair analysis techniques analyse multiple combinations of permissions together to correctly classify the overall permission pair despite individual permission appear safe or harmful when considered alone. For example, internet access and contact access permission pair in combination can help data leakage. General fine-grained risk identification is an key advancement of such techniques as they take advantage of contextual probability-aware classification [3].

Dynamic permission classification techniques adjust permission classification level depending on contextual location of app. For example, permission level of GPS access may be different for gaming and map applications. These techniques are more user friendly and provide interpretable and detailed insight of why a particular permission is classified as high/medium/low risk level to help users make safe decision.

L. NLP-Based Compliance and Policy Verification

Compliance is a critical component of gaining user confidence and should be an integral part of any permission analysis system. NLP techniques help extracting relevant information from user privacy policy and comparing it with permission requests to identify violations [7]. Besides, compatibility among app description, privacy policy and permission use can be studied through non-straightforward NLP techniques to flagged apps which provide misleading information and go against privacy regulations. This will help avoid regulatory violations and improve user trust in app store environment [9]. Automated

auditing of large set of apps for identifying privacy or security violation thanks to combination of unstructured data analysis with structured permission data can help large app store efficiently provide quality review [15].

M. Permission anomaly detection at large scales of apps

Finding anomalies at large scale of apps needs combination of structured data analysis together with unstructured data analysis. For example, app or developer specific permission analysis can be planned in conjunction with permission for infrastructure or app-store statistics. Large variety of unknown apps analysis for permission anomalies identifies deviation from category defined common trends thus finds anomalies [6]. Auditing techniques based on combination of unstructured and structured data analysis identify redundant or noisy permissions thus help in combating privacy risks and eliminate malicious apps [10].

N. Use of User reviews to study privacy violations:

User reviews also contain information about app behaviour in terms of privacy and security. Sentiment analysis using NLP studies the overall feeling of user communities regarding an app to identify apps which have security issues. Topic modelling techniques studies topics discussed in various user reviews and helps in finding places where privacy is compromised [14].

O. Cross language models-NLP based app description analysis in different languages

NLP models analysing app description and privacy policy should be robust across languages so that all apps can be analysed using an unified system.

P. Risk scoring and decision support systems

Rank calculation of apps based on permission use will help user in choosing safer apps. Decision support tools help users avoid risky apps and choose appropriate and safe app [16, 19].

Q. Use of multiple sources for permission analysis

Use of unstructured data sources such as app description, privacy policy in conjunction with structured data sources is an important trend in permission analysis system development [12]. The overall workflow of the permission risk analysis system is shown in Fig. 1.




Fig. 1: NLP-Based Permission Risk Analysis System Architecture

IV.CONCLUSION

This review summarizes NLP focused techniques in Android permission risk detection. The application of NLP, especially the widely-used transformer-based models and LLMs, significantly boosts the accuracy and efficiency of detect-and-flag. The techniques reveals deeper understanding of permission usage and app contents. In addition to the deep insight allowed by a greater understanding of app permission usages and app content. These models even enable semi-automated app analysis involving app description parsing and feature extracting. Challenges include lack of sufficient data, computational costs and multilingual hurdles. Future directions should aim to systematically build models of high accuracy, interpretability and cross-centirical application.

V.REFERENCE

- [1] A. Kumar et al., "NLP based permission use auditing in Android app descriptions and privacy policies," *Computers & Security*, vol. 140, 2024.
- [2] S. Sharma et al., "Natural language processing for secure mobile app permission risk assessment," *IEEE Transactions on Dependable and Secure Computing (TDSC)*, vol. 21, 2024.
- [3] L. Chen et al., "Harnessing large language models to analyze Android app permission declarations," *IEEE Transactions on Information Forensics and Security*, vol. 19, 2024.
- [4] R. Patel et al., "NLP driven permission pair risk analysis for secure mobile application recommendation," *Expert Systems with Applications*, vol. 230, 2024.
- [5] Y. Zhang et al., "Fine grained permission policy alignment verification using transformer based NLP," *Information Sciences*, vol. 620, 2025.
- [6] M. Singh et al., "Explainable NLP classifier for Android app permission risk labeling," *IEEE Transactions on Neural Networks and Learning Systems*, vol. 36, 2025.
- [7] T. Nguyen et al., "NLP assisted permission anomaly detection in Android app stores," *Journal of Information Security and Applications*, vol. 78, 2024.
- [8] H. Liu et al., "NLP enabled privacy policy to permission mapping framework for secure mobile apps," *Future Generation Computer Systems*, vol. 155, 2025.
- [9] P. Das et al., "Natural language guided permission risk assessment for mobile app security," *Knowledge Based Systems*, vol. 274, 2025.
- [10] K. Mehta et al., "NLP based permission compliance checker for secure mobile application stores," *Decision Support Systems*, vol. 178, 2026.

- [11] J. Brown et al., "NLP assisted auditing of excessive and misleading mobile app permissions," *Information Processing & Management*, vol. 59, no. 3, 2024.
- [12] X. Wang et al., "Large language model assisted Android permission purpose inference from app descriptions and policies," *IEEE Access*, vol. 12, 2024.
- [13] D. Roy et al., "NLP based mining of app description text to infer permission use purposes," *Expert Systems with Applications*, vol. 232, 2025.
- [14] F. Garcia et al., "Cross language NLP models for Android app permission meaning analysis," *Information Processing & Management*, vol. 59, no. 4, 2024.
- [15] E. Kim et al., "NLP driven user review analysis for detecting permission related privacy concerns," *IEEE Transactions on Consumer Electronics*, vol. 70, 2024.
- [16] B. Zhao et al., "NLP based verification of permission consistency between app descriptions and code level behavior," *Computers & Security*, vol. 142, 2025.
- [17] A. Verma et al., "NLP assisted permission risk scoring framework for Android app stores," *Future Generation Computer Systems*, vol. 160, 2025.
- [18] C. Lopez et al., "Transformer based NLP pipeline for secure mobile app permission policy analysis," *Information Sciences*, vol. 630, 2025.
- [19] N. Iyer et al., "NLP enabled fine grained permission risk classification for mobile app security," *Knowledge Based Systems*, vol. 278, 2025.
- [20] S. Reddy et al., "NLP based permission analyzer for secure mobile application recommendation," *Decision Support Systems*, vol. 180, 2026.



PANIMALAR ENGINEERING COLLEGE

An Autonomous Institution

Affiliated to Anna University, Chennai
(JAISAKTHI EDUCATIONAL TRUST)



CERTIFICATE OF PARTICIPATION

This is to certify that Dr./Mr./Ms. **RAGHAVI M**
from **SRM VALLIAMMAI ENGINEERING COLLEGE** has
presented a paper titled **SURVEY ON A SECURE MOBILE APPLICATION PERMISSION
ANALYZER USING NATURAL LANGUAGE PROCESSING**
in the **International Conference on Modern Sustainable Engineering and
Technology (ICMSET2026)** organized by the Department of Mechanical
Engineering, Panimalar Engineering College, Chennai, India, held on 15th &
16th of May, 2026.


COORDINATOR
Dr. G. Senthilkumar
Professor


CHAIR
Dr. L. Karthikeyan
Professor & Head



PANIMALAR ENGINEERING COLLEGE

An Autonomous Institution

Affiliated to Anna University, Chennai
(JAISAKTHI EDUCATIONAL TRUST)



CERTIFICATE OF PARTICIPATION

This is to certify that Dr./Mr./Ms. **SHUNMUGA PRIYA R**
from **SRM VALLIAMMAI ENGINEERING COLLEGE** has
presented a paper titled **SURVEY ON A SECURE MOBILE APPLICATION PERMISSION
ANALYZER USING NATURAL LANGUAGE PROCESSING**
in the **International Conference on Modern Sustainable Engineering and
Technology (ICMSET2026)** organized by the Department of Mechanical
Engineering, Panimalar Engineering College, Chennai, India, held on 15th &
16th of May, 2026.


COORDINATOR
Dr. G. Senthilkumar
Professor


CHAIR
Dr. L. Karthikeyan
Professor & Head



PANIMALAR ENGINEERING COLLEGE


An Autonomous Institution

Affiliated to Anna University, Chennai
(JAISAKTHI EDUCATIONAL TRUST)



CERTIFICATE OF PARTICIPATION

This is to certify that Dr./Mr./Ms. **SRIMATHI V**
from **SRM VALLIAMMAI ENGINEERING COLLEGE** has
presented a paper titled **SURVEY ON A SECURE MOBILE APPLICATION PERMISSION**
ANALYZER USING NATURAL LANGUAGE PROCESSING
in the **International Conference on Modern Sustainable Engineering and Technology (ICMSET2026)** organized by the Department of Mechanical Engineering, Panimalar Engineering College, Chennai, India, held on 15th & 16th of May, 2026.


COORDINATOR
Dr. G. Senthilkumar
Professor


CHAIR
Dr. L. Karthikeyan
Professor & Head