

CS 32 Week 9

Discussion 1I

Srinath

Outline

- Hash Tables
- Worksheet 9


Hash Tables

Hash Tables :

A data structure to store key-value pairs.
Something like a dictionary.

Simplest

- may be an array of strings.
- array index is key




Hash Tables :

A data structure to store key-value pairs.
Something like a dictionary.

Simplest

- may be an array of strings.
- array index is key

What if keys are not in array index range?



Hash Tables :


A data structure to store key-value pairs.
Something like a dictionary.

Simplest

- may be an array of strings.
- array index is key

What if keys are not in array index range?

- Need a way to map them to array-index (hash function)



Hash Tables : The Hash Function

A mapping from a given key to an index

```
int hash(int x){  
    return x % 7;  
}
```

Hash Tables : The Hash Function

A mapping from a given key to an index

```
int hash(int x){  
    return x % 7;  
}
```

What if our keys are strings instead?

Hash Tables : The Hash Function

A mapping from a given key to an index

```
int hash(int x){  
    return x % 7;  
}
```

What if our keys are strings instead?

```
int hash(string s){  
    sm = 0;  
    for(int i=0; i<s.length(); i++)  
        sm += s[i]-'0';  
  
    return sm%7;  
}
```

Hash Tables : The Hash Function

A mapping from a given key to an index

```
int hash(int x){  
    return x % 7;  
}
```

What if our keys are strings instead?

- Create data structure to store Key-Value pair
- Store it in the array at index returned by hash function.

```
int hash(string s){  
    sm = 0;  
    for(int i=0; i<s.length(); i++)  
        sm += s[i]-'0';  
  
    return sm%7;  
}
```

Hash Tables : The Hash Function

A mapping from a given key to an index

```
int hash(int x){  
    return x % 7;  
}
```

What if our keys are strings instead?

- Create data structure to store Key-Value pair
- Store it in the array at index returned by hash function.

Consider integer keys 23, 65

Their hashes?? -

```
int hash(string s){  
    sm = 0;  
    for(int i=0; i<s.length(); i++)  
        sm += s[i]-'0';  
  
    return sm%7;  
}
```

Hash Tables : The Hash Function

A mapping from a given key to an index

```
int hash(int x){  
    return x % 7;  
}
```

What if our keys are strings instead?

- Create data structure to store Key-Value pair
- Store it in the array at index returned by hash function.

Consider integer keys 23, 65

Their hashes?? - 2, 2 Oh No! we have a collision

```
int hash(string s){  
    sm = 0;  
    for(int i=0; i<s.length(); i++)  
        sm += s[i]-'0';  
  
    return sm%7;  
}
```

Hash Tables : The Hash Function

Collision is when two keys map to the same index.


How to resolve a collision?

Hash Tables : The Hash Function

Collision is when two keys map to the same index.

How to resolve a collision?

- Store a list at that index instead of a single element.




Hash Tables : The Hash Function

Collision is when two keys map to the same index.

How to resolve a collision?

- Store a list at that index instead of a single element.

Assume we have 10000 buckets, only 100 items, can we have a collision?



Hash Tables : The Hash Function


Collision is when two keys map to the same index.

How to resolve a collision?

- Store a list at that index instead of a single element.

Assume we have 10000 buckets, only 100 items, can we have a collision?

- Yes, possible. Two keys can still map to same index.



Hash Tables : The Hash Function

What is a good hash function?




Image: <https://vhanda.in/blog>

Hash Tables : The Hash Function

What is a good hash function?

- Something which generates a uniform distribution over the buckets.
- Keep in mind, what input(key) distribution you have and what the corresponding output distribution that is generated.




Image: <https://vhanda.in/blog>

Hash Tables : Complexity

Load Factor = #input size(N) / #buckets

If the hash distribution is uniform, represents how many elements each bucket holds on average




Image: <https://vhanda.in/blog>

Hash Tables : Complexity

Load Factor = #input size(N) / #buckets

If the hash distribution is uniform, represents how many elements each bucket holds on average

What is the average case time complexity?




Image: <https://vhanda.in/blog>

Hash Tables : Complexity

Load Factor = #input size(N) / #buckets

If the hash distribution is uniform, represents how many elements each bucket holds on average

What is the average case time complexity?

- $O(\text{Load Factor})$

What is the worst case time complexity?




Image: <https://vhanda.in/blog>

Hash Tables : Complexity

Load Factor = #input size(N) / #buckets

If the hash distribution is uniform, represents how many elements each bucket holds on average

What is the average case time complexity?

- $O(\text{Load Factor})$

What is the worst case time complexity?

- $O(N)$, when all keys map to same hash value

If we have $\sim O(N)$ buckets, then Load Factor $\sim O(1)$, therefore average case complexity is $\sim O(1)$




Image: <https://vhanda.in/blog>

Hash Tables : Complexity

Load Factor = #input size(N) / #buckets

For fixed number of buckets, time complexity grows linearly with input size N. i.e $O(N)$




Image: <https://vhanda.in/blog>

Hash Tables : Complexity

Load Factor = #input size(N) / #buckets

For fixed number of buckets, time complexity grows linearly with input size N. i.e $O(N)$

Can we do better?




Image: <https://vhanda.in/blog>

Hash Tables : Complexity

Load Factor = #input size(N) / #buckets

For fixed number of buckets, time complexity grows linearly with input size N. i.e $O(N)$

Can we do better?

- Yes, increase number of buckets dynamically.

Dynamic hashing




Image: <https://vhanda.in/blog>

Hash Tables : Complexity

Load Factor = $\text{\#input size}(N) / \text{\#buckets}$

For fixed number of buckets, time complexity grows linearly with input size N . i.e $O(N)$

Can we do better?

- Yes, increase number of buckets dynamically.

Dynamic hashing

- When load factor reaches a limit, create a new hash table with $2x$ size, move values from old to new(**re-hashing**)




Image: <https://vhanda.in/blog>

Hash Tables : Complexity

Load Factor = $\text{\#input size}(N) / \text{\#buckets}$

For fixed number of buckets, time complexity grows linearly with input size N . i.e $O(N)$

Can we do better?

- Yes, increase number of buckets dynamically.

Dynamic hashing

- When load factor reaches a limit, create a new hash table with 2x size, move values from old to new(**re-hashing**)
- Drawbacks?




Image: <https://vhanda.in/blog>

Hash Tables : Complexity

Load Factor = $\text{\#input size}(N) / \text{\#buckets}$

For fixed number of buckets, time complexity grows linearly with input size N . i.e $O(N)$

Can we do better?

- Yes, increase number of buckets dynamically.

Dynamic hashing

- When load factor reaches a limit, create a new hash table with 2x size, move values from old to new(**re-hashing**)
- **Drawbacks?**
 - Copying takes $O(N)$ time, inconsistent performance.




Image: <https://vhanda.in/blog>

Hash Tables : Complexity

Load Factor = #input size(N) / #buckets

For fixed number of buckets, time complexity grows linearly with input size N.

Can we do better?

- Yes, increase number of buckets dynamically.

Dynamic hashing (Any better ideas?)




Image: <https://vhanda.in/blog>

Hash Tables : Complexity

Load Factor = $\text{\#input size}(N) / \text{\#buckets}$

For fixed number of buckets, time complexity grows linearly with input size N .

Can we do better?

- Yes, increase number of buckets dynamically.

Dynamic hashing (Any better ideas?)

- Create a new Hash Table with bigger size, but don't copy values from old to new.
- Handle copy along with insertion i.e distribute the copying across all new insertions possible.
- Eg: If we want to increase \#buckets by 1.5x, along with each new insertion, move 2 more key-values from the old table.




Image: <https://vhanda.in/blog>

Hash Tables : Complexity Summary

Operations on hash tables with a fixed number of buckets are $O(N)$.

Operations on a hash table with a fixed maximum load factor (so it grows the number of buckets if necessary)

- $O(1)$ on average if a full rehash is done all at once,
- $O(1)$ always if re-hashing is done incrementally. (This assumes a good hash function that produces reasonably uniformly distributed output values.)




Image: <https://vhanda.in/blog>

Hash Tables : Implementation

```
class HashTable{
public :
    HashTable();
    bool find(string key);
    int get(string key);
    bool insert(string key, int value);
    bool delete(string key);
private:
    int hash(string key);
    vector<list<Node>> m_array;
    int arr_size;
    int m_size;
};

struct Node{
    string key;
    int value;
};
```


Hash Tables : STL

`unordered_set`, `unordered_map`

- Uses hash table
- Unsorted
- No duplicates allowed
- Average case $O(1)$
- Worst case $O(N)$

Reference

https://www.cplusplus.com/reference/unordered_set/unordered_set/

https://www.cplusplus.com/reference/unordered_map/unordered_map/

Hash Tables : Examples

```
//example from geeksforgeeks.org
unordered_set <string> stringSet ;
stringSet.insert("code") ;
stringSet.insert("in") ;
stringSet.insert("c++") ;
stringSet.insert("is") ;
stringSet.insert("fast") ;
string key1 = "slow" ;
if (stringSet.find(key1) == stringSet.end())
    cout << key1 << " not found" << endl;
else
    cout << "Found " << key1 << endl ;
string key2 = "C++" ;
if (stringSet.find(key2) == stringSet.end())
    cout << key2 << " not found" << endl;
else
    cout << "Found " << key2 << endl ;
```

Hash Tables : Examples

```
//example from geeksforgeeks.org
unordered_set <string> stringSet ;
stringSet.insert("code") ;
stringSet.insert("in") ;
stringSet.insert("c++") ;
stringSet.insert("is") ;
stringSet.insert("fast") ;
string key1 = "slow" ;
if (stringSet.find(key1) == stringSet.end())
    cout << key1 << " not found" << endl;
else
    cout << "Found " << key1 << endl ;
string key2 = "C++" ;
if (stringSet.find(key2) == stringSet.end())
    cout << key2 << " not found" << endl;
else
    cout << "Found " << key2 << endl ;
```

slow not found
C++ not found

Hash Tables : Examples

```
unordered_map<string, int> umap;  
umap["GeeksforGeeks"] = 10;  
umap["Practice"] = 20;  
umap["Contribute"] = 30;  
umap["GeeksforGeeks"] = 20;  
umap.insert(pair<string, int>("Practice", 10));  
for (auto x : umap)  
    cout << x.first << " " << x.second << endl;
```

Hash Tables : Examples

```
unordered_map<string, int> umap;  
umap["GeeksforGeeks"] = 10;  
umap["Practice"] = 20;  
umap["Contribute"] = 30;  
umap["GeeksforGeeks"] = 20;  
umap.insert(pair<string, int>("Practice", 10));  
for (auto x : umap)  
    cout << x.first << " " << x.second << endl;
```

GeeksforGeeks 20
Practice 20
Contribute 30