

METOR 28

Hand-held metal detector with 3 sensitivity settings to detect all types of metal.

Unique Angled Design

Rugged Construction

Detects All Metals

Lightweight



Hand-held metal detectors are an integral part of the physical security screening process. With the Metor 28, we have designed a unit that benefits security personnel as well as the person being scanned. Our unique angled design allows you to thoroughly scan an individual, while keeping your hand away from their body.

Additional Benefits

- The circular opening assists in pinpointing metal objects
- Comfortable handle for easy control and grip
- Lightweight 260 g (9.3 oz.) with battery
- Wrist strap

Detection

Detects all metals, both ferrous and non-ferrous.

Sensitivity

Three (3) sensitivity settings

Detection performance:

Level 1: small handguns and knives

Level 2: razor blades, handcuff keys

Level 3: .22 caliber bullet, metal shanks

Operation

3-way push-button operation:

On/Off/Momentary.

Battery

NiMH rechargeable battery or 9V alkaline battery.

Low battery indicator, both visual and audible.

Alarm

Audible and visual alarm indication.

Rugged Construction

High impact resistant ABS case.

Safety

The Metor 28 is safe for people with pacemakers and will not affect magnetic recording media. The magnetic field strength of the Metor 28 meets with the limits set by international standards for human safety.

Warranty

Two (2) years, parts.




Rapiscan[®]
systems

An OSI Systems Company

METOR 28

Conformity

Safety Standards	Conforms with the applicable EU directives.
 Compliant	Yes, conforms to the applicable international standards for electrical safety and EMC.

Specifications

Ambient Operating Temperature	0°C to 50°C (32°F to 122°F)
Power Supply	Standard 9V battery or rechargeable NiMH battery.
Battery Life	Alkaline battery 120 h Rechargeable NiMH battery (170 mAh) 40 h* Recharge time for NiMH battery (170 mAh) 12 h* *The values may vary between batteries with different capacity.
Weight	260 g (9.3 oz.) with battery.
Dimensions (Body)	410 x 140mm (16.35 x 5.5 in).
Dimensions (Grip)	33 x 33mm (1.3 x 1.3 in).
Warranty	Two (2) years, parts

Options and Accessories

Charging Unit: Simple charging connection that plugs directly into the unit.

With continual development of our products Rapiscan Systems reserves the right to amend specifications without notice. Product pictures are for general reference. Please note that due to US laws and regulations, not all Rapiscan products are available for sale in all countries without restriction. Please contact your Rapiscan Systems sales representative for more information.

AMERICAS, CARIBBEAN

2805 Columbia Street
Torrance, California 90503
UNITED STATES of AMERICA
Tel: +1 310-978-1457
Fax: +1 310-349-2491

EUROPE, MIDDLE EAST, AFRICA

X-Ray House
Bonehurst Road
Salfords
Surrey RH1 5GG
UNITED KINGDOM
Tel: +44 (0) 870-7774301
Fax: +44 (0) 870-7774302

ASIA

240 Macpherson Road
#07-01 Pines Industrial Building
Singapore 348574
SINGAPORE
Tel: +65-6846-3511
Fax: +65-6743-9915

EMAIL

sales@rapiscansystems.com

WEB

www.rapiscansystems.com

Rapiscan[®]
systems

An OSI Systems Company

ONE COMPANY - TOTAL SECURITY



Rapiscan Systems is
ISO 9001:2008 Certified

www.rapiscansystems.com