Status	Finished
Started	Tuesday, 20 October 2026, 7:36 PM
Completed	Tuesday, 20 October 2026, 7:39 PM
Duration	3 mins 12 secs
Grade	**14.00** out of 15.00 (**93.33**%)

Question **1**

Correct

Mark 1.00 out of 1.00

What happens if you try to open a file in write mode ('w') and the file already exists?

a. It raises an error
b. It does nothing
c. It clears the old data and starts fresh ✓
d. It appends data to the file

The correct answer is: It clears the old data and starts fresh

Question **2**

Correct

Mark 1.00 out of 1.00

Which of the following is true about the readlines() method?

a. It reads a single line from the file
b. It reads the entire file and returns it as a string
c. It reads the entire file and returns it as a list of lines ✓
d. It reads the file and returns it as a dictionary

The correct answer is: It reads the entire file and returns it as a list of lines

Question **3**

Correct

Mark 1.00 out of 1.00

Which method is used to write a list of strings to a file?

a. write_all()
b. write()
c. writelines() ✓
d. write_list()

The correct answer is: writelines()

Question **4**

Correct

Mark 1.00 out of 1.00

Select the incorrect file access mode

a. r
b. wb+
c. rw+ ✓
d. ab+

The correct answer is: rw+

Question **5**

Correct

Mark 1.00 out of 1.00

If the file is opened in write mode and already exists, it truncates the existing content and places the filehandle at the beginning of the file.

Select one:

True ✓
False

The correct answer is 'True'.

Question **6**

Correct

Mark 1.00 out of 1.00

f.seek(5,1) means

- a. move the file pointer to beginning of the file
- b. move the file pointer five characters behind from the current position
- c. moves the file pointer to the end of a file
- d. move the file pointer five characters ahead from the current position ✓

The correct answer is:
move the file pointer five characters ahead from the current position

Question **7**

Correct

Mark 1.00 out of 1.00

What is the result of the following code?

```
with open("example.txt", "r") as f:
    data = f.read()
print(data)
```

- a. Prints the entire content of the file ✓
- b. Prints each line of the file
- c. Prints the first 10 characters of the file
- d. Prints an error message

The correct answer is: Prints the entire content of the file

Question **8**

Correct

Mark 1.00 out of 1.00

What does the buffering parameter in the open() function control?

a. The access mode of the file
b. The encoding of the file
c. The file's read/write position
d. The buffer size for the file operations ✓

The correct answer is: The buffer size for the file operations

Question **9**

Correct

Mark 1.00 out of 1.00

To open a file c:\scores.txt for appending data, we use _____

a. outfile = open("c:\\scores.txt", "rw")
b. outfile = open(file = "c:\\scores.txt", "w")
c. outfile = open("c:\\scores.txt", "a") ✓
d. outfile = open(file = "c:\scores.txt", "w")

The correct answer is:
outfile = open("c:\\scores.txt", "a")

Question **10**

Correct

Mark 1.00 out of 1.00

Which method can be used to read all lines of a file into a list?

a. readlist()
b. readline()
c. read()
d. readlines() ✓

The correct answer is: readlines()

Question **11**

Correct

Mark 1.00 out of 1.00

Which method is used to truncate a file to a specific size?

a. shrink()
b. reduce()
c. resize()
d. truncate() ✓

The correct answer is: truncate()

Question **12**

Correct

Mark 1.00 out of 1.00

Which method is used to read a specific number of characters from a file?

a. readline()
b. readlines()
c. readchar()
d. read(size) ✓

The correct answer is: read(size)

Question **13**

Correct

Mark 1.00 out of 1.00

What happens if you try to open a file in read mode ('r') that does not exist?

a. An empty file object is returned
b. An error is raised ✓
c. The operation is ignored
d. A new file is created

The correct answer is: An error is raised

Question **14**

Correct

Mark 1.00 out of 1.00

Which of the following is data file?

- a. Text file
- b. Both text and binary file ✓
- c. none of the given choices
- d. Binary file

The correct answer is: Both text and binary file

Question **15**

Incorrect

Mark 0.00 out of 1.00

What is the use of seek() method in files?

- a. sets the file's current position at the offset
- b. none of the mentioned
- c. sets the file's current position within the file ✕
- d. sets the file's previous position at the offset

The correct answer is:
sets the file's current position at the offset