

6)

A) Terminal 1

```
nithya@WIN-482M0QMA856:~$ gcc server.c
nithya@WIN-482M0QMA856:~$ ./a.out
Server waiting for client...
Client says: hello this is my os first class
```

Terminal 2

```
nithya@WIN-482M0QMA856:~$ gcc client.c
nithya@WIN-482M0QMA856:~$ ./a.out
Enter message: hello this is my os first class
Server says: Message received by server
```

B) Terminal 1

```
nithya@WIN-482M0QMA856:~$ gcc signal.c
nithya@WIN-482M0QMA856:~$ ./a.out
Process ID: 5713
Waiting for signals...
^C
SIGINT received
SIGUSR1 received
```

CTRL + C enter

```
nithya@WIN-482M0QMA856:~$ gcc signal.c
nithya@WIN-482M0QMA856:~$ ./a.out
Process ID: 5713
Waiting for signals...
^C
SIGINT received
SIGUSR1 received
```

Terminal 2

```
nithya@WIN-482M0QMA856:~$ kill -SIGUSR1 5713
```

In terminal 1

Output-

```
nithya@WIN-482M0QMA856:~$ gcc signal.c
nithya@WIN-482M0QMA856:~$ ./a.out
Process ID: 5713
Waiting for signals...
^C
SIGINT received
SIGUSR1 received
^C
SIGINT received
```