

Matroids & The Greedy Paradigm

PPT PRESENTED BY

NAME : Srinivas Rao Tammireddy

ROLL NO : 257Y1D5805

YEAR : I Year II Semester

ACADEMIC YEAR : 2025 - 2026

What is a Matroid?

A Matroid is a mathematical structure that generalizes the concept of linear independence in vector spaces. It defines a family of subsets where a simple greedy algorithm is guaranteed to find an optimal solution.

Formal Definition $M = (S, I)$

A matroid is an ordered pair (S, I) satisfying three axioms:

- 1. Finite Ground Set S :** A non-empty finite set of elements.
- 2. Hereditary Property:** I is a non-empty family of subsets of S (independent sets) such that if $B \in I$ and $A \subseteq B$, then $A \in I$. (Subsets of independent sets are independent).
- 3. Exchange Property:** If $A, B \in I$ and $|A| < |B|$, there exists some element $x \in B - A$ such that $A \cup \{x\} \in I$. (We can extend independent sets).

Vector Space Analogy

Matroid axioms match properties of vectors:

- **Ground Set S :** A set of vectors in a vector space.
- **Independent Sets I :** Subsets of vectors that are linearly independent (no vector is a linear combination of others).
- **Hereditary:** Subsets of linearly independent vectors are also linearly independent. ✓
- **Exchange:** If you have a basis of size 3 and another of size 4, you can find a vector in the larger set to extend the smaller one. ✓

The Matroid Greedy Algorithm

If we assign weights to ground elements, a greedy algorithm finds a maximum-weight independent set:

The General Greedy Algorithm

Given Matroid $M = (S, I)$ and weight function $w(x) > 0$ for $x \in S$:

1. Sort Ground elements: Sort all $x \in S$ in descending order of weights:

$$w(x_1) \geq w(x_2) \geq \dots \geq w(x_n).$$

2. Initialize Set: Set $A = \emptyset$ (empty set).

3. Greedy Loop: For $i = 1$ to n :

- If $A \cup \{x_i\} \in I$ (independent):
- Update: $A = A \cup \{x_i\}$.

4. Return A: A is guaranteed to be a maximum-weight maximal independent set (basis) of the Matroid.

Why Greedy Works (Matroid Theorem)

- **Rado-Edmonds Theorem:** A hereditary system (S, I) is a matroid if and only if the greedy algorithm finds an optimal independent set for all positive weight functions.
- **Optimization Guarantee:** The exchange property guarantees that a local greedy choice never blocks reaching the global optimum.
- **Contrast with Non-Matroids:** In non-matroid systems (e.g. Knapsack, TSP), greedy decisions can lead to sub-optimal solutions. Matroids are the boundary of greedy solvability.

Application: Kruskal's MST Algorithm

Kruskal's Minimum Spanning Tree algorithm is a direct application of the Matroid Greedy algorithm:

Graphic Matroids

We can model graphs as matroids. Given $G = (V, E)$:

- **Ground Set S:** The edge set E of G .
- **Independent Sets I:** Any subset of edges that is acyclic (contains no cycles, forming a forest).
- **Hereditary Property:** Subsets of acyclic edges are also acyclic. ✓
- **Exchange Property:** If forest A has fewer edges than forest B , we can always find an edge in B to add to A without forming a cycle. ✓

Kruskal's Code Map

Kruskal's steps map directly to the Matroid algorithm:

- 1. Sort Edges:** Sort edges by weight in ascending order (we find the minimum spanning tree, which is equivalent to maximizing negative weights).
- 2. Select Edges:** Add edges one-by-one to our MST.
- 3. Cycle Check (Independence):** Only add an edge if it does not form a cycle with already-selected edges (checking independence in the graphic matroid).

Applications of Matroids in CS

Matroid structures guarantee optimal greedy solutions across scheduling and network designs:

Kruskal's MST Networks

Graphic matroids prove the correctness of Kruskal's MST algorithm. Used to construct optimal telecommunication, power grid, and computer network wiring systems.

Task Scheduling with Deadlines

Scheduling unit-time jobs with deadlines and penalties is modeled as a matroid. The greedy algorithm yields the optimal schedule that minimizes penalties.

Network Flow & Matrix Matching

Algebraic matroids solve structural matching in matrix computations, optimizing index allocations for high-performance solvers.

Coding Theory & Cryptography

Matroid theory is utilized in error-correcting codes and secret sharing schemes to design linear bounds for secure communications.

THANK YOU

Department of Computer Science and Engineering
Marri Laxman Reddy Institute of Technology and Management